
# NOTICE: This standard has either been superseded and replaced by a new version or discontinued. Contact ASTM International (www.astm.org) for the latest information.



# Standard Specification for Labeled Length per Holder of Sewing Thread<sup>1</sup>

This standard is issued under the fixed designation D 3693; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

 $\epsilon^1$  Note—Editorial changes were made throughout in November 1996.

### 1. Scope

1.1 This specification covers requirements for the labeled lengths of sewing threads of all materials.

## 2. Referenced Documents

2.1 ASTM Standards:

D 123 Terminology Relating to Textiles<sup>2</sup>

D 204 Methods of Testing Sewing Threads<sup>2</sup>

#### 3. Terminology

3.1 Definitions:

3.1.1 *thread holder*, *n*—the support package on which sewing yarn is wound.

3.1.1.1 *Discussion*—This support package enables sewing yarn to be securely placed for subsequent transportation, storage, and utilization. These support packages may be in the form of a cone, spool, tube, or bobbin.

3.1.2 sewing thread, n—a flexible small-diameter yarn or strand, usually treated with a surface coating, lubricant, or both, intended to be used to stitch one or more pieces of material or an object to a material.

3.1.3 For definitions of other textile terms used in this 369 specification, refer to Terminology D 123.

#### 4. Requirements

4.1 The average for all holders shall equal or exceed the labeled length.

4.2 For home sewing spools, the observed length of individual holders shall equal or exceed the percent of labeled length shown in Table 1.

4.3 For ready-made bobbins, the observed length of individual holders shall equal or exceed 97 % of the labeled length.

4.4 For all other holders, when the sample size is nine or fewer, the observed length of individual holders shall equal or exceed 95 % of the labeled length. For a sample size of ten or more the observed length of one holder may be less than 95 % of the labeled length.

TABLE 1 Minimum Length for Individual Home Sewing Spools

	* *
Labeled Length, m	Minimum % Allowed
0 to 40	98.5
Over 40 to 85	98
Over 85 to 140	97.5
Over 140 to 300	97
Over 300 to 1000	96
Over 1000	95

4.5 If the initial sample consists of fewer than ten holders and the average length measured fails to conform to the requirements of 4.1 but meets those of 4.2, 4.3, or 4.4, as appropriate, take additional specimens from the lot and test until a total of ten have been measured. Reevaluate the results of these ten specimens against the requirements of 4.1, 4.2, 4.3, or 4.4, as appropriate. If the new average conforms with the requirements of 4.1 and the individual holders with the requirements of 4.2, 4.3, or 4.4, as appropriate, consider the lot acceptable.

4.5.1 If the original lot consists of fewer than ten holders, the supplementary sample will be one half of the holders remaining in the lot following the initial sampling.

## -5. Sampling-ad57-d8b07e1e564f/astm-d3693-911996e1

5.1 *Lot*—Unless otherwise agreed upon between the purchaser and supplier, a lot shall be a discrete manufacturing unit or a billed quantity of a specific color, ticket size, and length put-up of thread. A billed quantity can consist of a single unit, a carton, box, or multiple units of either, containing a number of holders of thread.

NOTE 1—An adequate specification or other agreement between the purchaser and the supplier requires taking into account variability between shipping units, between packages, or ends within shipping unit, and between specimens from a single package so as to provide a sampling plan with a meaningful producer's risk, user's risk, acceptable quality level, and limiting quality level.

5.2 *Sample*—Unless otherwise agreed upon between the purchaser and seller, and except for ready-made bobbins, the sample, chosen at random, shall be 10 % of the holders in the lot, with a minimum of one holder, up to a maximum of ten holders. The lot sample and laboratory sample are synonymous.

5.2.1 For ready-made bobbins the sample shall be as shown in Table 2.

<sup>&</sup>lt;sup>1</sup> This specification is under the jurisdiction of ASTM Committee D-13 on Textiles and is the direct responsibility of Subcommittee D13.58 on Yarn Test Methods, General.

Current edition approved July 15, 1991. Published September 1991. Originally published as D 3693 – 78. Last previous edition D 3693 – 80 (Reapproved 1985)<sup> $\epsilon$ 1</sup>.

<sup>&</sup>lt;sup>2</sup> Annual Book of ASTM Standards, Vol 07.01.

Copyright © ASTM, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959, United States.