

ETSI TS 144 160 V13.0.0 (2016-01)



TECHNICAL SPECIFICATION

**Digital cellular telecommunications system (Phase 2+);
General Packet Radio Service (GPRS);
Mobile Station (MS) - Base Station System (BSS) interface;
Radio Link Control / Medium Access Control (RLC/MAC)
protocol lu mode
(3GPP TS 44.160 version 13.0.0 Release 13)**



Reference

RTS/TSGG-0244160vd00

Keywords

GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	12
1 Scope	13
1.1 General	13
1.2 Related documents	13
1.3 Use of logical control channels	13
1.4 Use of logical traffic channels.....	14
1.4a Use of transport channels	14
1.5 Conventions.....	14
2 References	14
3 Definitions, symbols and abbreviations	16
3.1 Definitions	16
3.2 Symbols.....	16
3.3 Abbreviations	17
4 Layered overview of radio interface.....	18
4.0 Protocol architecture.....	18
4.1 Layer services.....	20
4.2 Layer functions.....	20
4.2.1 RLC function	20
4.2.2 MAC layer function	21
4.3 Service primitives.....	22
4.3.1 MAC to Physical Layer Primitives	22
4.3.2 PDCP to RLC Primitives	22
4.3.2.1 Primitives	22
4.3.2.2 Primitive parameters	23
4.3.3 RRC to RLC Primitives	23
4.3.3.1 Primitives	23
4.3.3.2 Primitive parameters	24
4.3.4 RRC to MAC Primitives.....	25
4.3.4.1 Primitives	25
4.3.4.2 Primitive Parameters	26
4.4 Services required from lower layers.....	26
5 Introduction to the Medium Access Control (MAC) procedures	27
5.1 General	27
5.2 Multiplexing principles	27
5.2.1 Temporary Block Flow	27
5.2.2 Temporary Flow Identity	28
5.2.2.1 Temporary Flow Identity for SBPSCH	28
5.2.2.2 Temporary Flow Identity for DBPSCH	28
5.2.3 Uplink State Flag	28
5.2.4 Medium Access modes	29
5.2.4.1 Medium Access modes for SBPSCH	29
5.2.4.2 Medium Access modes for DBPSCH	29
5.2.5 Multiplexing of GPRS and EGPRS TBF mode capable mobile stations.....	29
5.3 MAC States	29
5.3.1 MAC-Idle state	29
5.3.1.1 General	29
5.3.1.2 Establishment of a SBPSCH	29
5.3.1.3 Establishment of a DBPSCH.....	29
5.3.2 MAC-Shared state	29

5.3.2.1	General	29
5.3.2.2	Release of all SBPSCHs	29
5.3.2.3	Establishment of a DBPSCH	30
5.3.2.4	Radio bearer reconfiguration	30
5.3.3	MAC-DTM state	30
5.3.3.1	General	30
5.3.3.2	Release of all SBPSCHs	30
5.3.3.3	Release of all DBPSCHs	30
5.3.3.4	Release of all SBPSCHs and DBPSCHs	30
5.3.4	MAC-Dedicated state	30
5.3.4.1	General	30
5.3.4.2	Release of all DBPSCHs	30
5.3.4.3	Radio bearer reconfiguration	30
5.3.5	MAC state machine	31
5.4	General MAC procedures in MAC-Idle state and MAC-Shared state	31
5.4.1	Mobile station side	31
5.4.1.1	General	31
5.4.1.2	Cell reselection	31
5.4.1.3	Network Assisted Cell Change	32
5.4.1.4	Release of DBPSCHs	32
5.4.1.4.1	General	32
5.4.1.4.2	Continuation of PBCCH information	32
5.4.1.4.3	Receipt of PSII4 message in MAC-DTM state	33
5.4.1.5	System information on PBCCH	33
5.4.1.6	System information on BCCH	33
5.4.1.6.1	General	33
5.4.1.6.2	Establishment of PBCCH	33
5.4.1.6.3	(void)	33
5.4.1.7	(void)	33
5.4.1.8	Discontinuous reception (DRX)	33
5.4.1.9	Page mode procedures on PCCCH	34
5.4.1.10	Frequency Parameters	34
5.4.1.11	G-RNTI Management	34
5.4.2	Network side	34
5.4.2.1	System Information broadcasting	34
5.4.2.1.1	System information on PBCCH	34
5.4.2.1.2	System information on BCCH	35
5.4.2.1.3	System information on PACCH (and other logical channels)	35
5.4.2.1.4	Consistent sets of system information messages	35
5.4.2.2	Paging	36
5.4.2.3	Network Assisted Cell Change	36
5.5	Measurement reports	36
5.5.1	General	36
5.5.2	Network Control (NC) measurement reporting	36
5.5.3	(void)	37
5.5.4	Additional measurement and reporting parameters	37
5.6	Mapping of Signalling Radio Bearers (SRB) onto logical channels / transport channels	37
5.6.1	Downlink	37
5.6.2	Uplink	37
5.6.2.1	MAC-Dedicated State	37
5.6.2.2	MAC-Shared State	38
5.6.2.3	MAC-DTM State	38
5.7	Multiplexing principles with Flexible Layer One	39
5.7.1	General	39
5.7.2	Multiplexing between user-plane and control-plane	40
6	Paging procedures	40
6.1	General	40
6.2	Paging initiation in MAC-Idle state	41
6.3	Paging initiation in MAC-Shared state	41
6.4	Reception of PACKET PAGING REQUEST by an MS	41

7	Medium Access Control (MAC) procedures on PCCCH.....	41
7.1	General	41
7.2	TBF establishment initiated by the mobile station on PCCCH	42
7.2.1	General.....	42
7.2.2	Permission to access the network	42
7.2.3	Initiation of a TBF establishment	42
7.2.3.1	Initiation of the packet access procedure	42
7.2.3.1.1	General	42
7.2.3.1.2	Access persistence control on PRACH.....	43
7.2.3.2	Packet assignment procedure	43
7.2.3.2.1	On receipt of a PACKET CHANNEL REQUEST or EGPRS PACKET CHANNEL REQUEST message.....	43
7.2.3.2.1.2	Allocation of resource on SBPSCH(s).....	43
7.2.3.2.1.3	Allocation of resource on DBPSCH(s)	44
7.2.3.3	Contention resolution at one phase access	45
7.2.3.3.1	Contention resolution at one phase access on SBPSCHs	45
7.2.3.3.2	Contention resolution at one phase access on DBPSCH	46
7.2.3.4	RLC/MAC procedures during contention resolution	47
7.2.3.4.1	RLC/MAC procedures during contention resolution on SBPSCHs	47
7.2.3.4.2	RLC/MAC procedures during contention resolution on DBPSCHs.....	47
7.2.3.5	One phase packet access completion.....	48
7.2.3.5.1	One phase packet access completion on SBPSCHs.....	48
7.2.3.5.2	One phase packet access completion on DBPSCHs.....	48
7.2.3.6	Timing Advance.....	48
7.2.3.6.1	Timing advance on SBPSCHs.....	48
7.2.3.6.2	Timing advance on DBPSCHs	48
7.2.4	TBF establishment using two phase access	48
7.2.4.1	Initiation of the Packet resource request procedure	48
7.2.4.2	Packet resource assignment for uplink procedure	49
7.2.4.2.1	(void).....	49
7.2.4.2.2	On receipt of a PACKET RESOURCE REQUEST message.....	49
7.2.4.3	Contention resolution at two phase access	49
7.2.4.4	Two phase packet access completion.....	50
7.2.4.5	Timing Advance.....	50
7.2.5	Abnormal cases.....	50
7.3	TBF establishment initiated by the network on PCCCH.....	51
7.3.1	General.....	51
7.3.2	Entering the MAC-Shared state.....	51
7.3.2.1	General	51
7.3.2.2	Packet downlink assignment procedure	51
7.3.2.2.1	Packet downlink assignment procedure.....	51
7.3.2.2.2	HFN synchronization.....	51
7.3.2.3	Packet downlink assignment procedure completion	51
7.3.2.4	Packet polling procedure	52
7.3.2.5	Abnormal cases	52
7.3.3	Entering the MAC-Dedicated state	52
7.3.3.1	General	52
7.3.3.2	Packet DBPSCH assignment procedure.....	52
7.3.3.3	Packet DBPSCH assignment procedure completion.....	53
7.3.3.4	Packet polling procedure	53
7.3.3.5	Abnormal cases	53
7.4	Procedure for measurement report sending in MAC-Idle state	53
7.4.1	General.....	53
7.4.2	Measurement report sending procedure initiated on PCCCH	53
7.4.2.1	General	53
7.4.2.2	On receipt of a PACKET CHANNEL REQUEST message	53
7.4.2.3	On receipt of a PACKET UPLINK ASSIGNMENT message.....	53
7.4.2.4	On receipt of a PACKET ACCESS REJECT message.....	54
7.4.2.5	Abnormal cases	54
7.5	Cell Change Order procedures in MAC-Idle state	54
7.5.1	General.....	54
7.6	Measurement Order procedures in MAC-Idle state.....	54

7.6.1	General.....	54
7.6.2	Measurement Order procedures initiated on PCCCH.....	55
8	Medium Access Control (MAC) procedures on SBPSCH.....	55
8.1	General	55
8.1a	Resource stealing (SFACCH).....	55
8.2	Transfer of RLC data blocks	56
8.2.1	Medium access mode.....	56
8.2.2	Uplink RLC data block transfer.....	56
8.2.2.0	General	56
8.2.2.0.1	General	56
8.2.2.0.2	Establishment of additional uplink TBF(s).....	56
8.2.2.0.3	Uplink resource reallocation / reconfiguration	56
8.2.2.0.4	Establishment of downlink TBF(s).....	57
8.2.2.1	Dynamic Allocation uplink RLC data block transfer.....	57
8.2.2.1.1	PACCH operation.....	57
8.2.2.1.2	Resource Allocation / Reallocation for Uplink.....	57
8.2.2.1.2.2	On receipt of the PACKET RESOURCE REQUEST.....	57
8.2.2.1.3	Establishment of downlink TBF.....	59
8.2.2.1.3.1	General.....	59
8.2.2.1.3.2	Abnormal cases.....	60
8.2.2.2	Extended Dynamic Allocation uplink RLC data block transfer.....	60
8.2.2.2.0	General	60
8.2.2.2.1	Uplink PDCH Allocation.....	60
8.2.2.2.2	PACCH operation.....	60
8.2.2.2.3	Neighbour cell power measurements.....	61
8.2.2.2.4	Shifted USF operation.....	61
8.2.2.3	Exclusive Allocation uplink RLC data block transfer.....	61
8.2.2.3.1	(void).....	61
8.2.2.3.2	(void).....	61
8.2.2.3.3	(void).....	61
8.2.2.3.4	(void).....	61
8.2.2.3.5	(void).....	61
8.2.2.3.6	(void).....	61
8.2.2.4	Network initiated release of uplink TBF.....	61
8.2.2.5	Abnormal cases	61
8.2.3	Downlink RLC data block transfer.....	61
8.2.3.1	General	61
8.2.3.1.0	General	61
8.2.3.1.1	Downlink resource reallocation.....	62
8.2.3.1.2	(void).....	62
8.2.3.2	Downlink RLC data block transfer procedure	62
8.2.3.2.0	General	62
8.2.3.2.1	Abnormal cases	62
8.2.3.3	Polling for Packet Downlink Ack/Nack.....	64
8.2.3.4	Resource Reassignment for downlink.....	64
8.2.3.5	Establishment of uplink TBF	65
8.2.3.5.0	General	65
8.2.3.5.1	Abnormal cases	66
8.2.3.6	Network initiated abnormal release of downlink TBF.....	67
8.3	Packet PDCH Release	67
8.4	Procedure for measurement report sending in MAC-Shared state	67
8.5	Network Controlled cell reselection procedures in MAC-Shared state.....	67
8.6	Measurement Order procedures in MAC-Shared state.....	67
8.7	PACKET CONTROL ACKNOWLEDGEMENT	67
8.8	Abnormal cases	67
8.8.1	General.....	67
8.8.2	Abnormal release without retry	67
8.8.3	Abnormal release with access retry	68
8.8.4	Abnormal release with system information	68
8.8.5	Abnormal release of an Uplink TBF with access retry	68
8.8.6	Abnormal release of a Downlink TBF.....	68

8.9	Network Assisted Cell Change procedures in MAC-Shared state.....	68
9	Medium Access Control (MAC) procedures on DBPSCH.....	69
9.1	General.....	69
9.2	Transfer of RLC/MAC blocks.....	69
9.2.0	General.....	69
9.2.1	Dedicated allocation.....	70
9.2.1.1	General.....	70
9.2.1.2	Performance requirements for TCH and DCCH TBF modes.....	70
9.2.1.3	Performance requirements for UDCH and CDCH TBF modes.....	71
9.2.2	Transfer of RLC/MAC blocks on TCH.....	72
9.2.3	Transfer of RLC/MAC blocks on FACCH, SACCH and SDCCH.....	72
9.2.4	Transfer of RLC/MAC blocks on PDTCH and PACCH.....	73
9.2.4.1	General.....	73
9.2.4.1.1	Downlink transfer.....	73
9.2.4.1.1.1	General.....	73
9.2.4.1.1.2	Polling for Packet Downlink Ack/Nack.....	73
9.2.4.1.2	Uplink transfer.....	74
9.2.4.1.2.1	General.....	74
9.2.4.1.2.2	On receipt of a Packet Uplink Assignment message.....	74
9.2.4.1.2.3	Release of the USF.....	75
9.2.4.2	Scheduling an inactive TBF on a DBPSCH.....	75
9.2.4.3	Further USF handling.....	76
9.2.5	Transfer of RLC/MAC blocks on UDCH, CDCH and ADCH.....	76
9.2.5.1	General.....	76
9.2.5.2	Transport format combination (TFC) selection.....	77
9.2.5.2.1	General requirements.....	77
9.2.5.2.2	Downlink.....	77
9.2.5.2.3	Uplink.....	77
9.2.5.3	Polling for PACKET DBPSCH DOWNLINK ACK/NACK TYPE 2.....	77
9.3	PACKET CONTROL ACKNOWLEDGEMENT.....	77
9.3a	Handover Access and Physical Information.....	78
9.3a.1	Handover Access.....	78
9.3a.2	Physical Information.....	78
9.4	Abnormal cases.....	78
10	Radio Link Control (RLC) procedures on PDTCH and PACCH.....	79
10.1	General.....	79
10.2	Procedures and parameters for peer-to-peer operation.....	79
10.2.1	Send state variable V(S).....	79
10.2.2	Control send state variable V(CS).....	79
10.2.3	Acknowledge state variable V(A).....	79
10.2.4	Acknowledge state array V(B).....	79
10.2.5	Block sequence number BSN.....	79
10.2.6	Receive state variable V(R).....	79
10.2.7	Receive window state variable V(Q).....	79
10.2.8	Receive state array V(N).....	79
10.2.9	Starting sequence number (SSN) and received block bitmap (RBB).....	79
10.2.10	Window Size.....	79
10.2.10a	RLC buffer.....	79
10.2.11	Compression.....	80
10.2.12	Segmentation of upper layer PDUs into RLC data units.....	80
10.2.13	Re-assembly of upper layer PDUs from RLC data units.....	80
10.2.14	Segmentation of RLC/MAC control messages into RLC/MAC control blocks.....	80
10.2.15	Re-assembly of RLC/MAC control messages from RLC/MAC control blocks.....	80
10.3	Operation during RLC/MAC control message transfer.....	81
10.4	Operation during RLC data block transfer.....	81
10.4.1	General.....	81
10.4.2	Countdown procedure.....	81
10.4.3	Delayed release of downlink Temporary Block Flow.....	81
10.4.4	Extended uplink TBF mode.....	81
10.4.5	Acknowledged mode operation.....	81

10.4.5.1	General	81
10.4.5.2	Additional functionality in acknowledged EGPRS TBF Mode	81
10.4.5.3	Establishment of Temporary Block Flow	81
10.4.5.4	Operation of uplink Temporary Block Flow	81
10.4.5.5	Release of uplink Temporary Block Flow	82
10.4.5.6	Operation of downlink Temporary Block Flow	82
10.4.5.7	Release of downlink Temporary Block Flow	82
10.4.6	Unacknowledged mode operation	82
10.4.6.1	General	82
10.4.6.2	Establishment of Temporary Block Flow	82
10.4.6.3	Operation of uplink Temporary Block Flow	82
10.4.6.4	Release of uplink Temporary Block Flow	82
10.4.6.5	Operation of downlink Temporary Block Flow	82
10.4.6.6	Release of downlink Temporary Block Flow	82
10.5	Abnormal release cases	83
10.5.1	Abnormal release with access retry	83
10.5.2	Abnormal release with cell reselection	83
10.6	Uplink TBF release in extended uplink TBF mode	83
11	Radio Link Control (RLC) procedures on TCH, FACCH, SACCH, SDCCH and CDCH	84
11.1	General	84
11.2	Procedures and parameters for peer-to-peer operation	84
11.2.1	Send state variable V(S)	84
11.2.2	Control send state variable V(CS)	84
11.2.3	Acknowledge state variable V(A)	85
11.2.4	Acknowledge state array V(B)	85
11.2.5	Block sequence number BSN	85
11.2.5.1	Block sequence number for TCH TBF mode	85
11.2.5.2	Block sequence number for DCCH TBF mode and CDCH TBF mode	85
11.2.6	Reduced block sequence number RBSN	85
11.2.7	Receive state variable V(R)	85
11.2.8	Receive window state variable V(Q)	86
11.2.9	Receive state array V(N)	86
11.2.10	Starting sequence number (SSN) and received block bitmap (RBB)	86
11.2.11	Window Size	86
11.2.11.1	TCH	86
11.2.11.2	FACCH, SACCH, SDCCH and CDCH	87
11.2.11a	RLC buffer	87
11.2.12	Segmentation of upper layer PDUs into RLC data units	87
11.2.13	Re-assembly of upper layer PDUs from RLC data units	87
11.2.14	Segmentation of RLC/MAC control messages into RLC/MAC control blocks	87
11.2.15	Re-assembly of RLC/MAC control messages from RLC/MAC control blocks	87
11.3	Operation during RLC/MAC control message transfer	88
11.4	Operation during RLC data block transfer	88
11.4.1	General	88
11.4.2	Acknowledged mode operation	89
11.4.2.1	General	89
11.4.2.2	On TCH	89
11.4.2.2.1	General	89
11.4.2.2.2	Uplink	89
11.4.2.2.3	Downlink	89
11.4.2.3	On FACCH, SACCH, SDCCH or CDCH	90
11.4.2.3.1	General	90
11.4.2.3.2	Uplink	90
11.4.2.3.3	Downlink	90
11.4.3	Unacknowledged mode operation	91
11.4.3.1	General	91
11.4.3.2	On TCH	91
11.4.3.2.1	Uplink	91
11.4.3.2.2	(void)	91
11.4.3.3	On FACCH, SACCH, SDCCH or CDCH	91
11.4.3.3.1	Uplink	91

11.4.3.3.2	Downlink	91
11.4.4	Transparent mode operation (TCH TBF mode only)	91
11a	Radio Link Control (RLC) procedures for FLO on UDCH, ADCH	92
11a.1	General	92
11a.2	Procedures and parameters for peer-to-peer operation	92
11a.2.1	Send state variable V(S)	92
11a.2.2	Control send state variable V(CS)	92
11a.2.3	Acknowledge state variable V(A)	92
11a.2.4	Acknowledge state array V(B)	92
11a.2.5	Block sequence number BSN	92
11a.2.6	Reduced block sequence number RBSN	92
11a.2.7	Receive state variable V(R)	92
11a.2.8	Receive window state variable V(Q)	93
11a.2.9	Receive state array V(N)	93
11a.2.10	Starting sequence number (SSN) and received block bitmap (RBB)	93
11a.2.10.1	General	93
11a.2.10.2	Polling	93
11a.2.10.3	Determination of SSN and generation of the reported bitmap	93
11a.2.10.4	Interpretation of the bitmap	94
11a.2.11	Window Size	95
11a.2.11a	RLC buffer	95
11a.2.12	Segmentation of upper layer PDUs into RLC data units	95
11a.2.13	Re-assembly of upper layer PDUs from RLC data units	95
11a.2.14	Segmentation of RLC/MAC control messages into RLC/MAC control blocks	95
11a.2.15	Re-assembly of RLC/MAC control messages from RLC/MAC control blocks	95
11a.3	Operation during RLC/MAC control message transfer	96
11a.4	Operation during RLC data block transfer	96
11a.4.1	General	96
11a.4.2	Acknowledged mode operation	96
11a.4.2.1	General	96
11a.4.2.2	Uplink	97
11a.4.2.3	Downlink	97
11a.4.3	Unacknowledged mode operation	97
11a.4.3.1	General	97
11a.4.3.2	Uplink	97
11a.4.3.3.2	Downlink	98
11a.4.4	Transparent mode operation	98
12	RLC/MAC block structure	98
12.1	RLC/MAC block structure	98
12.2	RLC/MAC block format conventions	98
12.3	Spare bits	98
12.4	GPRS RLC data blocks (PDTCH)	98
12.4.1	Downlink RLC data block	98
12.4.2	Uplink RLC data block	99
12.5	RLC/MAC control blocks (PACCH)	99
12.6	EGPRS RLC data blocks and RLC/MAC headers (PDTCH)	99
12.6.1	General	99
12.6.2	EGPRS downlink RLC data block	99
12.6.3	EGPRS uplink RLC data block	99
12.6.4	EGPRS downlink RLC/MAC header	100
12.6.5	EGPRS uplink RLC/MAC header	100
12.7	RLC/MAC block formats on FACCH, SACCH, SDCCH and CDCH	100
12.7.1	RLC/MAC block	100
12.7.2	Downlink RLC/MAC block for data transfer	101
12.7.3	Uplink RLC/MAC block for data transfer	101
12.7.4	RLC/MAC block for control message transfer	101
12.8	RLC/MAC block format on TCH (NT-RLC)	102
12.8.1	RLC/MAC block	102
12.8.1.1	General	102
12.8.1.2	RLC/MAC block for E-TCH/F28.8 coding scheme	102

12.8.1.3	RLC/MAC block for E-TCH/F32.0 coding scheme.....	102
12.8.1.4	RLC/MAC block for E-TCH/F43.2 coding scheme.....	103
12.8.2	Downlink RLC/MAC block for data transfer	103
12.8.3	Uplink RLC/MAC block for data transfer	103
12.8.4	RLC/MAC block for control message transfer	103
12.8a	RLC/MAC block for control message transfer on ADCH	104
12.8a.1	Downlink RLC/MAC control block format.....	104
12.8a.2	Uplink RLC/MAC control block format.....	104
12.8b	RLC/MAC blocks for URB data transfer on UDCH.....	104
12.8b.1	Downlink RLC/MAC block for data transfer	104
12.8b.1.1	RLC unacknowledged mode	104
12.8b.1.2	RLC acknowledged mode	105
12.8b.1.3	RLC transparent mode	105
12.8b.2	Uplink RLC/MAC block for data transfer	105
12.8b.2.1	RLC unacknowledged mode	105
12.8b.2.2	RLC acknowledged mode	105
12.8b.2.3	RLC transparent mode	106
12.9	Header fields	106
12.9.1	General.....	106
12.9.2	Payload Type (PT) field.....	106
12.9.3	Polling (P) bit.....	106
12.9.4	Reduced Radio Bearer identity (RRBid) field	107
12.9.5	More (M) bit and Extension (E) bit	107
12.9.6	Extension bis (Ebis) bit.....	107
12.9.7	Stall Indicator (SI) bit	107
12.9.8	Ack Indicator (AI) field	107
12.9.9	Ack/Nack Description field	108
12.9.10	G-RNTI indicator (GI) bit.....	108
12.9.11	Segmentation (S) bit	108
12.9.12	Reduced Block Sequence Number (RBSN) bit	108
12.9.13	(void)	109
12.9.14	Radio Transaction Identifier (RTI) field	109
12.9.15	Block Sequence Number (BSN) field.....	109
12.9.16	Radio Bearer Identity (RB Id) field	109
12.9.17	Signalling Radio Bearer Identity (SRB Id) field.....	109
12.9.18	GERAN Radio Network Temporary Identity Extension (G-RNTI Extension) field	109
12.9.19	Length Indicator (LI) field.....	109
12.9.20	PFI Indicator (PI) field.....	110
12.9.21	HFN Least Significant Bit (HFN_LSB) field	110
13	Ciphering.....	111
13.1	General	111
13.2	Applicability of ciphering	111
13.3	Ciphering at RLC sublayer.....	111
13.3.1	General.....	111
13.3.2	Parameter settings.....	111
13.3.2.1	Input parameters to the ciphering algorithm	111
13.3.2.2	Handling of the HFN.....	112
13.3.3	Ciphering of RLC PDUs in non-transparent RLC mode	112
13.4	Ciphering at MAC sublayer.....	113
13.4.1	General.....	113
13.4.2	Parameter settings	113
13.4.2.1	Input parameters to the ciphering algorithm	113
13.4.2.2	Handling of the HFN.....	114
13.4.2.2.1	Ciphering in transparent RLC mode.....	114
13.4.2.2.2	Ciphering of RLC/MAC control messages.....	115
13.4.3	Ciphering of RLC/MAC control messages.....	115
13.4.4	Ciphering of RLC PDUs in transparent RLC mode.....	116
14	RLC suspension, stop and re-establishment procedures	116
14.1	General	116
14.2	Local suspend/resume function (NT-RLC)	116

14.3 Stop/continue function (NT-RLC)117
14.4 RLC re-establishment function (NT-RLC).....118
Annex A (informative): Change History119
History120

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/3ae6c49f-f746-4462-963e-f1cca8e35dcb/etsi-ts-144-160-v13.0.0-2016-01>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

ITEH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/5a266c49f-f746-4462-963e-f1cca8e35dcb/etsi-ts-144-160-v13.0.0-2016-01>