

ETSI TS 145 005 V13.0.0 (2016-01)



Digital cellular telecommunications system (Phase 2+); Radio transmission and reception (3GPP TS 45.005 version 13.0.0 Release 13)

PREVIEW
iTech Standards (standards.it-eui.com)
Full standards list: <https://standards.it-eui.com/catalogue/standards/97456415-f0dd-414c-ad56-63671e8d5fe4/etsi-ts-145-005-v13.0.0-2016-01>



Reference

RTS/TSGG-0145005vd00

Keywords

GSM**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	10
1 Scope	11
1.1 References	12
1.2 Abbreviations	13
1.3 Definitions.....	14
2 Frequency bands and channel arrangement.....	14
3 Reference configuration	17
4 Transmitter characteristics	17
4.1 Output power.....	18
4.1.1 Mobile Station	18
4.1.2 Base station.....	22
4.1.2.1 Additional requirements for PCS 1 900 and MXM 1900 Base stations.....	24
4.1.2.2 Additional requirements for GSM 850 and MXM 850 Base stations.....	24
4.1.2.3 Additional requirements for GSM 700 Base stations.....	24
4.1.2.4 Additional requirements for ER-GSM 900 Base stations.....	24
4.1.2.4.1 Uncoordinated deployment	24
4.1.2.4.2 Coordinated deployment	25
4.2 Output RF spectrum	25
4.2.1 Spectrum due to the modulation and wide band noise.....	25
4.2.1.1 General requirements for all types of Base stations and MS.....	25
4.2.1.2 Additional requirements for multicarrier BTS	26
4.2.1.3 Tables for spectrum requirements due to modulation and wideband noise.....	26
4.2.1.4 Exceptions for spectrum due to modulation and wideband noise	31
4.2.1.4.1 Mobile Stations and Base Transceiver Stations except multicarrier BTS	31
4.2.1.4.2 Multicarrier BTS	32
4.2.2 Spectrum due to switching transients	32
4.2.2.1 General requirements.....	32
a) Mobile Station:.....	33
b) Base transceiver station:.....	33
4.3 Spurious emissions	34
4.3.1 Principle of the specification	34
4.3.2 Base Transceiver Station	36
4.3.2.1 General requirements	36
4.3.2.2 Additional requirements for co-existence with GSM systems on other frequency bands.....	37
4.3.2.3 Additional requirements for co-existence with 3 G	38
4.3.3 Mobile Station	39
4.3.3.1 Mobile Station GSM 400, T-GSM 810, GSM 900, ER-GSM 900 and DCS 1 800.....	39
4.3.3.2 Mobile Station GSM 700, GSM 850 and PCS 1 900.....	40
4.4 Radio frequency tolerance.....	41
4.5 Output level dynamic operation	41
4.5.1 Base Transceiver Station	41
4.5.2 Mobile Station	41
4.6 Modulation accuracy.....	42
4.6.1 GMSK modulation.....	42
4.6.2 QPSK, AQPSK, 8-PSK, 16-QAM and 32-QAM modulations.....	42
4.6.2.1 RMS EVM	43
4.6.2.1.1 MS requirements	43
4.6.2.1.2 Requirements for BTS.....	43
4.6.2.2 Origin Offset Suppression.....	44
4.6.2.3 Peak EVM.....	44

4.6.2.4	95:th percentile.....	44
4.7	Intermodulation attenuation.....	45
4.7.1	Base transceiver station	45
4.7.2	Intra BTS intermodulation attenuation	45
4.7.2.1	GSM 400, GSM 900, ER-GSM 900, DCS 1800.....	45
4.7.2.1.1	Requirements for BTS except multicarrier BTS.....	45
4.7.2.1.2	Requirements for multicarrier BTS	45
4.7.2.2	MXM 850 and MXM 1900.....	46
4.7.2.3	GSM 700, GSM 850 and PCS 1900.....	46
a)	Requirements for BTS except multicarrier BTS.....	46
b)	Requirements for multicarrier BTS	47
c)	Additional requirements for all BTS	47
4.7.3	Void	47
4.7.4	Mobile PBX (GSM 900 only).....	47
5	Receiver characteristics.....	47
5.1	Blocking characteristics	48
5.1.1	Definitions of applicable frequency ranges	48
5.1.2	Requirements for MS.....	50
5.1.3	Requirements for BTS	51
5.1.4	Signal levels of blocking signal	53
5.1.5	Micro- and pico-BTS.....	58
5.2	AM suppression characteristics.....	58
5.2.1	Requirements for MS.....	58
5.2.2	Requirements for BTS	59
5.3	Intermodulation characteristics	60
5.3.1	Requirements for MS.....	60
5.3.2	Requirements for BTS	60
5.4	Spurious emissions.....	61
6	Transmitter/receiver performance.....	61
6.1a	MS conditions	61
6.1b	BTS conditions.....	62
6.1	Nominal Error Rates (NER).....	63
6.1.1	GMSK modulation.....	63
6.1.1.1	General performance requirements	63
6.1.1.2	Requirements for MS	63
6.1.1.3	Requirements for BTS.....	64
6.1.2	QPSK/8-PSK modulation.....	64
6.1.2.1	Requirements for MS.....	64
6.1.2.2	Requirements for BTS.....	65
6.1.3	16-QAM/32-QAM modulation.....	66
6.1.3.1	Requirements for MS	66
6.1.3.2	Requirements for BTS.....	66
6.2	Reference sensitivity level.....	67
6.2.1	Circuit-switched channels.....	67
6.2.1a	Reference performance in VAMOS mode.....	69
6.2.2	Packet-switched channels	70
6.2.3	Flexible Layer One	72
6.2.4	Repeated associated control channel performance	72
6.2.5	Enhanced MS receiver performance	72
6.2.6	Additional performance conditions.....	73
6.3	Reference interference level.....	74
6.3.1	GMSK modulated speech channels and associated control channels	74
6.3.2	Co-channel reference interference performance	74
6.3.2.1	MS requirements	74
6.3.2.2	BTS requirements	75
6.3.3	Adjacent channel reference interference performance.....	75
6.3.3.1	Normal symbol rate used	75
6.3.3.1.1	MS requirements	75
6.3.3.1.2	BTS requirements.....	76
6.3.3.2	Higher symbol rate used:	76

6.3.3.2.1	MS requirements	76
6.3.3.2.2	BTS requirements	77
6.3.4	Reference interference performance – signal levels	77
6.3.5	Additional reference interference performance requirements and conditions.....	78
6.4	Erroneous frame indication performance	80
6.5	Random access and paging performance at high input levels	81
6.6	Frequency hopping performance under interference conditions	82
6.7	Incremental Redundancy Performance for EGPRS and EGPRS2 MS	82
Annex A (informative): Spectrum characteristics (spectrum due to the modulation)		175
Annex B (normative): Transmitted power level versus time		183
Annex C (normative): Propagation conditions.....		189
C.1	Simple wideband propagation model	189
C.2	Doppler spectrum types	189
C.3	Propagation models	190
C.3.1	Typical case for rural area (RAx): (6 tap setting)	190
C.3.2	Typical case for hilly terrain (HTx): (12 tap setting).....	190
C.3.3	Typical case for urban area (TUx): (12 tap setting).....	191
C.3.4	Profile for equalization test (EQx): (6 tap setting)	191
C.3.5	Typical case for very small cells (Tix): (2 tap setting).....	191
Annex D (normative): Environmental conditions		192
D.1	General	192
D.2	Environmental requirements for the MSs.....	192
D.2.1	Temperature (GSM 400, GSM 900, ER-GSM 900 and DCS 1 800)	192
D.2.1.1	Environmental Conditions (PCS 1 900, GSM 850 and GSM 700).....	192
D.2.2	Voltage	192
D.2.3	Vibration (GSM 400, GSM 900, ER-GSM 900 and DCS 1 800).....	193
D.2.3.1	Vibration (PCS 1 900, GSM 850 and GSM 700).....	193
D.3	Environmental requirements for the BSS equipment	193
D.3.1	Environmental requirements for the BSS equipment	194
Annex E (normative): Repeater characteristics		195
E.1	Introduction	195
E.2	Spurious emissions	195
E.3	Intermodulation products	196
E.4	Out of band gain	196
E.5	Frequency error and modulation accuracy	196
E.5.1	Frequency error	196
E.5.2	Modulation accuracy at GMSK modulation.....	197
E.5.3	Modulation accuracy at 8-PSK, 16-QAM, 32-QAM, QPSK and AQPSK modulation.....	197
Annex F (normative): Antenna Feeder Loss Compensator Characteristics (GSM 400, GSM 900 and DCS 1800).....		199
F.1	Introduction	199
F.2	Transmitting path	199
F.2.1	Maximum output power	199
F.2.2	Gain	200
F.2.3	Burst transmission characteristics	200
F.2.4	Phase error	200
F.2.5	Frequency error	201
F.2.6	Group delay	201

F.2.7	Spurious emissions	201
F.2.8	VSWR	202
F.2.9	Stability	202
F.3	Receiving path.....	202
F.3.1	Gain	202
F.3.2	Noise figure	202
F.3.3	Group delay	202
F.3.4	Intermodulation performance	202
F.3.5	VSWR	202
F.3.6	Stability	202
F.4	Guidelines (informative)	202
Annex G (normative):	Calculation of Error Vector Magnitude	204
Annex H (normative):	Requirements on Location Measurement Unit	206
H.1	TOA LMU Requirements.....	206
H.1.1	Void.....	206
H.1.2	LMU characteristics	206
H.1.2.1	Blocking characteristics	206
H.1.2.2	AM suppression characteristics	206
H.1.2.3	Intermodulation characteristics.....	207
H.1.2.4	Spurious emissions	207
H.1.3	Time-of-Arrival Measurement Performance	207
H.1.3.1	Sensitivity Performance	207
H.1.3.2	Interference Performance.....	208
H.1.3.3	Multipath Performance	209
H.1.4	Radio Interface Timing Measurement Performance.....	209
H.2	E-OTD LMU Requirements	209
H.2.1	LMU Characteristics	209
H.2.1.1	Blocking characteristics	210
H.2.1.2	AM suppression characteristics	210
H.2.1.3	Intermodulation characteristics.....	210
H.2.2	Sensitivity and Interference Performance	210
H.2.2.1	Sensitivity Performance	210
H.2.2.2	Interference Performance	211
H.2.2.3	Multipath Performance	211
Annex I (normative):	E-OTD Mobile Station Requirements.....	213
I.1	Introduction	213
I.2	Sensitivity and Interference Performance	213
I.2.1	Sensitivity Performance	213
I.2.2	Interference Performance	214
I.2.3	Multipath Performance.....	214
Annex J (informative):	Guidance on the Usage of Dynamic ARFCN Mapping	215
J.1	Introduction	215
J.2	Dynamic allocation of GSM 400, GSM 800, GSM 900, ER-GSM 900, DCS 1800 and PCS 1900 ARFCNs.....	215
J.3	Controlling changes in dynamic mapping.....	215
Annex K (normative):	Reference TFCs for FLO	217
Annex L (normative):	Reference Test Scenarios for DARP	219
Annex M (normative):	Minimum Performance Requirements for Assisted Global Positioning System (A-GPS)	221

M.1	General	221
M.1.1	Abbreviations	221
M.1.2	Measurement parameters.....	221
M.1.2.1	MS based A-GPS measurement parameters	221
M.1.2.2	MS assisted A-GPS measurement parameters	221
M.1.3	Response time	221
M.1.4	Time assistance	221
M.1.4.1	Use of fine time assistance.....	222
M.1.4.2	2D position error.....	222
M.2	A-GPS minimum performance requirements.....	222
M.2.1	Sensitivity.....	222
M.2.1.1	Coarse time assistance	222
M.2.1.1.1	Minimum Requirements (Coarse time assistance).....	223
M.2.1.2	Fine time assistance	223
M.2.1.2.1	Minimum Requirements (Fine time assistance).....	223
M.2.2	Nominal Accuracy.....	223
M.2.2.1	Minimum requirements (nominal accuracy).....	224
M.2.3	Dynamic Range	224
M.2.3.1	Minimum requirements (dynamic range)	224
M.2.4	Multi-Path scenario	224
M.2.4.1	Minimum Requirements (multi-path scenario).....	225
M.2.5	Moving scenario and periodic location	225
M.2.5.1	Minimum Requirements (moving scenario and periodic location).....	226
M.3	Test conditions	226
M.3.1	General	226
M.3.1.1	Parameter values.....	226
M.3.1.2	Time assistance	227
M.3.1.3	GPS Reference Time	227
M.3.1.4	Reference and MS locations.....	227
M.3.1.5	Satellite constellation and assistance data.....	227
M.3.1.6	Atmospheric delays.....	227
M.3.1.7	GSM Frequency and frequency error.....	228
M.3.1.8	Information elements	228
M.3.1.9	GPS signals	228
M.3.1.10	RESET MS POSITIONING STORED INFORMATION Message	228
M.4	Propagation Conditions	228
M.4.1	Static propagation conditions.....	228
M.4.2	Multi-path Case G1	228
M.5	Measurement sequence chart.....	229
M.5.1	General	229
M.5.2	MS Based A-GPS Measurement Sequence Chart	229
M.5.3	MS Assisted A-GPS Measurement Sequence Chart	230
M.6	Assistance data required for testing.....	231
M.6.1	Introduction	231
M.6.2	Information elements required for MS-based.....	231
M.6.3	Information elements available for MS-assisted	232
M.7	Converting MS-assisted measurement reports into position estimates	234
M.7.1	Introduction	234
M.7.2	MS measurement reports.....	234
M.7.3	Weighted Least Squares (WLS) position solution.....	235
Annex N (normative): Reference Test Scenarios for DARP Phase II (MSRD).....		237
N.1	Interferer configurations	237
N.2	Correlation and antenna gain imbalance.....	238
N.3	Testing MSRD terminal conformance to legacy requirements.....	239

Annex O (normative):	Minimum Performance Requirements for Assisted Galileo and Additional Navigation Satellite Systems (A-GANSS)	241
O.1	General	241
O.1.1	Abbreviations	241
O.1.2	Measurement parameters.....	241
O.1.2.1	MS based A-GANSS measurement parameters.....	241
O.1.2.2	MS assisted A-GANSS measurement parameters	241
O.1.3	Response time	241
O.1.4	Time assistance	242
O.1.4.1	Use of fine time assistance.....	242
O.1.5	Error definitions	242
O.2	A-GANSS minimum performance requirements	243
O.2.1	Sensitivity.....	243
O.2.1.1	Coarse time assistance	243
O.2.1.1.1	Minimum Requirements (Coarse time assistance).....	244
O.2.1.2	Fine time assistance	244
O.2.1.2.1	Minimum Requirements (Fine time assistance).....	244
O.2.2	Nominal Accuracy.....	245
O.2.2.1	Minimum requirements (nominal accuracy)	245
O.2.3	Dynamic Range	246
O.2.3.1	Minimum requirements (dynamic range)	246
O.2.4	Multi-Path scenario	246
O.2.4.1	Minimum Requirements (multi-path scenario).....	247
O.2.5	Moving scenario and periodic location	247
O.2.5.1	Minimum Requirements (moving scenario and periodic location).....	248
O.3	Test conditions	249
O.3.1	General	249
O.3.1.1	Parameter values.....	249
O.3.1.2	Time assistance.....	249
O.3.1.3	GANSS Reference Time.....	249
O.3.1.4	Reference and MS locations	250
O.3.1.5	Satellite constellation and assistance data.....	250
O.3.1.6	Atmospheric delays.....	250
O.3.1.7	Sensors.....	250
O.3.1.8	Information elements	250
O.3.1.9	GNSS signals.....	250
O.3.1.10	RESET MS POSITIONING STORED INFORMATION Message	250
O.3.2	GNSS System Time Offsets	251
O.4	Propagation Conditions	251
O.4.1	Static propagation conditions	251
O.4.2	Multi-path case	251
O.7.1	Introduction	257
O.7.2	MS measurement reports.....	257
O.7.3	Weighted Least Squares (WLS) position solution.....	259
Annex P (normative):	Minimum receiver performance requirements for MSR BS.....	261
P.1	Reference Sensitivity and interference performance.....	261
P.2	Other receiver characteristics	261
P.2.1	Blocking characteristics	261
P.2.2	Intermodulation characteristics	261
P.2.3	AM suppression.....	262
Annex Q (normative):	Reference Test Scenarios for Voice services over Adaptive Multi-user channels on One Slot (VAMOS)	263
Q.1	Interferer configurations in downlink.....	263
Q.2	Interferer configurations in uplink	264

Q.3	Sensitivity test configuration in downlink.....	265
Q.4	Sensitivity test configuration in uplink.....	265
Q.5	Time and frequency offset in uplink	265
Q.6	VAMOS DTX scenario in downlink.....	265
Q.7	Correlation and antenna gain imbalance for VAMOS III MS.....	266
Annex R (informative):	Change history	268
History		278

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/974564f5-f0dd-414c-ad56-63671e8d5fe4/etsi-ts-145-005-v13.0.0-2016-01>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/91564f5-f0dd-414c-ad56-63671e8d5fe4/etsi-ts-145-005-v13.0.0-2016-01>

1 Scope

The present document defines the requirements for the transceiver of the pan-European digital cellular telecommunications systems GSM.

Requirements are defined for two categories of parameters:

- those that are required to provide compatibility between the radio channels, connected either to separate or common antennas, that are used in the system. This category also includes parameters providing compatibility with existing systems in the same or adjacent frequency bands;
- those that define the transmission quality of the system.

The present document defines RF characteristics for the Mobile Station (MS) and Base Station System (BSS). The BSS will contain Base Transceiver Stations (BTS), which can be normal BTS, micro-BTS or pico-BTS. The precise measurement methods are specified in 3GPP TS 51.010 and 3GPP TS 51.021.

Unless otherwise stated, the requirements defined in this EN apply to the full range of environmental conditions specified for the equipment (see annex D).

In the present document some relaxations are introduced for GSM 400 MSs, GSM 900 MSs, GSM 700 MSs and GSM 850 MSs which pertain to power class 4 or 5 (see subclause 4.1.1). In the present document these Mobile Stations are referred to as "small MS".

In the present document some relaxations to receiver requirements are introduced for a MS indicating support for Downlink Multi Carrier (DLMC), see 3GPP TS 24.008, when in DLMC configuration. DLMC configurations are specified for only GSM 850, GSM 900, DCS 1800 and PCS 1900.

MSs may operate on more than one of the frequency bands specified in clause 2. These MSs are referred to as "Multi band MSs" in this EN. Multi band MSs shall meet all requirements for each of the bands supported. The relaxation on GSM 400 MSs, GSM 900 MSs, GSM 700 MSs and GSM 850 MSs for a "small MS" are also valid for a multi band MS if it complies with the definition of a small MS.

The RF characteristics of repeaters are defined in annex E of this EN. Annexes D and E are the only clauses of this EN applicable to repeaters. Annex E does not apply to the MS or BSS. The precise measurement methods for repeaters are specified in 3GPP TS 51.026 [35].

The present document also includes specification information for mixed mode operation at 850 MHz and 1900 MHz (MXM 850 and MXM 1900). 850 MHz and 1900 MHz mixed-mode is defined as a network that deploys both 30 kHz RF carriers and 200 kHz RF carriers in geographic regions where the Federal Communications Commission (FCC) regulations are applied or adopted.

The requirements for a MS in a mixed-mode system, MXM 850 and MXM 1900, correspond to the requirements for GSM 850 MS and PCS 1900 MS respectively.

Annex M defines the minimum performance requirements for A-GPS for MSs that support A-GPS. Annex M does not apply to the BSS.

The present document also includes specific requirements for multicarrier BTS, wherever explicitly stated in the text, that apply for all classes of multicarrier BTS (Wide Area, Medium Range and Local Area) if nothing else is stated. All other requirements designated for BTS and normal BTS apply if not otherwise stated. The multicarrier BTS classes have relaxed requirements in the areas of Tx spurious emissions, intermodulation attenuation and, when multicarrier receiver is included, Rx blocking. Usage of multicarrier BTSs in some geographical regions might be subject to regulatory restrictions to protect other radio systems operating in bands of adjacent frequency assignments, in particular for all safety related applications like railway applications. In areas where such systems coexist with multicarrier BTSs, the received interference power originating from multicarrier BTSs might have to be limited.

The document also includes entry points in some tables for the multicarrier BTS requirements to which TS 37.104 [33] for Multi-Standard Radio Base Stations (MSR BS) is referring to as specific GSM/EDGE single-RAT requirements not covered by the general requirements. These entry points are marked with ^{M)} and, as described in a note in each applicable table, identify the relevant column(s) that are applicable as MSR BS requirements. In general the requirements for multicarrier BTS equipped with multicarrier receiver also apply to Multi-Standard Radio Base Stations. The GSM requirements for Multi-Standard Radio Base Stations are defined for GSM 850, GSM 900, DCS

1800 and PCS 1900 only. Requirements for other frequency bands and MXM base stations are excluded. Annex P defines the minimum performance for the receiver in MSR BS.

For equipment not declared as MSR BS the ^M indications can be ignored.

The present document defines requirements for the usage of the ER-GSM band. The national implementation might be subject to regulatory coordination agreements to avoid system impacts (RF scenarios for ER-GSM introduction are given in 3GPP TR 45.050).

1.1 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: 'Vocabulary for 3GPP Specifications'.
- [1A] 3GPP TS 25.144: 'User Equipment (UE) and Mobile Station (MS) Over the Air Performance Requirements'.
- [1B] 3GPP TS 34.114: 'User Equipment (UE) / Mobile Station (MS) Over The Air (OTA) antenna performance; Conformance testing'.
- [2] 3GPP TR 43.030: 'Radio network planning aspects'.
- [3] 3GPP TS 43.052: 'GSM Cordless Telephony System (CTS); Lower layers of the CTS radio interface; Stage 2'.
- [4] 3GPP TS 43.059: 'Functional Stage 2 description of Location Services in GERAN'.
- [5] 3GPP TS 43.064: 'General Packet Radio Service (GPRS); GPRS Radio Interface Stage 2'.
- [6] 3GPP TS 44.014: 'Individual equipment type requirements and interworking; Special conformance testing functions'.
- [7] 3GPP TS 44.018: 'Mobile radio interface layer 3 specification; Radio Resource Control Protocol'.
- [7A] 3GPP TS 44.031: 'Mobile Station (MS) - Serving Mobile Location Centre (SMLC) Radio Resource LCS Protocol (RRLP)'.
- [8] 3GPP TS 44.071: 'Mobile radio interface layer 3 Location Services (LCS) specification'.
- [9] 3GPP TS 45.001: 'Physical layer on the radio path General description'.
- [10] 3GPP TS 45.002: 'Multiplexing and multiple access on the radio path'.
- [11] 3GPP TS 45.003: 'Channel coding'.
- [12] 3GPP TS 45.004: 'Modulation'.
- [13] 3GPP TS 45.008: 'Radio subsystem link control'.
- [14] 3GPP TS 45.010: 'Radio subsystem synchronization'.
- [15] 3GPP TS 45.050: 'Background for Radio Frequency (RF) requirements'.
- [16] 3GPP TS 51.010: 'Mobile Station (MS) conformity specification'.