



Digital cellular telecommunications system (Phase 2+); Background for Radio Frequency (RF) requirements (3GPP TR 45.050 version 13.0.0 Release 13)

PREVIEW
iTech Standards (standards-iteh.ai)
Full standard available at: <https://standards.iteh.ai/catalog/standards/sist/7aa64476-919e-44b6-9d13-482ce990515b/etsi-tr-145-050-v13.0.0-2016-01>

Reference

RTR/TSGG-0145050vd00

Keywords

GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Report (TR) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	19
1 Scope	20
2 Information available	20
3 DCS1800 system scenarios	20
4 GSM900 small cell system scenarios	21
5 GSM900 and DCS1800 microcell system scenarios.....	21
6 Conversion factors.....	22
7 Repeaters	22
8 Error Patterns for Speech Coder Developments.....	23
9 Simulations of Performance	23
10 GSM900 railway system scenarios	23
11 Simulation results for GPRS receiver performance	24
12 Pico BTS RF scenarios.....	24
13 CTS system scenarios.....	24
14 GSM400 system scenarios	24
15 MXM system scenarios	24
16 LCS scenarios.....	24
17 8-PSK Scenarios.....	24
18 T-GSM 900 System Scenarios	24
19 MBMS System Scenarios.....	24
20 T-GSM 810 System Scenarios	25
21 Multicarrier BTS Class.....	25
22 ER-GSM band introduction.....	25
23 Extended Training Sequence Code Sets.....	25
23.1 Background	25
23.2 Extended TSC Sets	25
23.2.1 Scope	25
23.2.2 Design criteria.....	26
23.2.3 Design methodology	26
23.2.4 Evaluation methodology	26
23.2.5 Performance evaluation	26
Annex A: DCS1800 System scenarios.....	27
A.0 INTRODUCTION.....	27
A.1 SCENARIO 1 - SINGLE BTS AND MS.....	27
A.1.1 Constraints.....	27
A.1.1.1 Frequency Bands and Channel Arrangement (Clause 2 of GSM 05.05)	27

A.1.1.2	Proximity	28
A.1.1.3	Range	28
A.1.3	Inputs needed.....	29
A.2	SCENARIO 2 - MULTIPLE MS AND BTS, COORDINATED	29
A.2.1	Constraints.....	29
A.2.3	Inputs needed.....	30
A.3	SCENARIO 3 - MULTIPLE MS AND BTS, UNCOORDINATED.....	31
A.3.1	Constraints.....	31
A.3.3	Inputs needed.....	31
A.4	SCENARIO 4 - COLOCATED MS.....	32
A.4.1	Constraints.....	32
A.4.3	Inputs needed.....	33
A.5	SCENARIO 5 - COLOCATED BTS	33
A.5.1	Constraints.....	33
A.5.3	Inputs needed.....	33
A.6	SCENARIO 6 - COLOCATION WITH OTHER SYSTEMS	34
A.6.1	Constraints.....	34
A.6.3	Inputs needed.....	34
A.7	Title: Justifications for the proposed Rec. 05.05_DCS.....	35
A.7.1	Transmitter	36
A.7.1.1	Modulation, Spurs and Noise.....	36
A.7.1.1.1	Co-ordinated, BTS -> MS (Scenario 2, figure 2.1)	36
A.7.1.1.2	Uncoordinated, BTS -> MS (Scenario 3, figure 3.1)	36
A.7.1.1.3	Co-ordinated & Uncoordinated MS -> BTS (Scenarios 2 and 3, figures 2.1 and 3.1).....	36
A.7.1.1.4	Co-ordinated & Uncoordinated MS->MS (Scenario 4)	36
A.7.1.1.5	Co-ordinated & Uncoordinated BTS->BTS (Scenario 5)	36
A.7.1.2	Switching Transients.....	36
A.7.1.2.1	Uncoordinated MS -> BTS (Scenario 3, figure 3.1).....	36
A.7.1.2.2	Uncoordinated BTS -> MS (Scenario 3, figure 3.1)	36
A.7.1.3	Intermodulation.....	37
A.7.1.3.1	Co-ordinated, BTS -> MS (Scenario 2, figures 2.2 and 2.3).....	37
A.7.1.3.2	Uncoordinated, BTS ->MS (Scenario 3, figure 3.2 top)	37
A.7.1.3.3	Uncoordinated, MS&MS-> BTS (Scenario 4, figure 4.1 bottom)	37
A.7.1.3.4	Uncoordinated MS&MS-> MS (Scenario 4, figure 4.1 top).....	37
A.7.2	Receiver.....	37
A.7.2.1	Blocking.....	37
A.7.2.1.1	Co-ordinated & Uncoordinated BTS-> MS (Scenarios 2 and 3, figures 2.1 and 3.1).....	37
A.7.2.1.2	Co-ordinated MS-> BTS (Scenario 2, figure 2.1)	37
A.7.2.1.3	Uncoordinated MS-> BTS (Scenario 3, figure 3.1)	37
A.7.2.1.4	Co-ordinated & Uncoordinated MS-> MS (Scenario 4)	37
A.7.2.1.5	Co-ordinated & Uncoordinated BTS-> BTS (Scenario 5)	37
A.7.2.2	Intermodulation.....	38
A.7.2.2.1	Co-ordinated & Uncoordinated BTS-> MS (Scenarios 2 and 3, figure 3.2 middle)	38
A.7.2.2.2	Co-ordinated MS & MS -> BTS (Scenario 4).....	38
A.7.2.2.3	Uncoordinated MS & MS -> BTS (Scenario 4, figure 3.2 lower).....	38
A.7.2.3	Maximum level	38
A.7.2.3.1	Co-ordinated MS -> BTS (Scenario 1).....	38
A.7.2.3.2	Co-ordinated BTS -> MS (Scenario 1).....	38
A.8.1	SCOPE	38
A.8.2	FREQUENCY BANDS AND CHANNEL ARRANGEMENT	38
A.8.3	REFERENCE CONFIGURATION	38
A.8.4	TRANSMITTER CHARACTERISTICS	39
A.8.4.1	Output power	39
A.8.4.1.1	Mobile Station.....	39
A.8.4.1.2	Base Station.....	39
A.8.4.2	Output RF spectrum.....	39
A.8.4.2.1	Spectrum due to the modulation.....	39
A.8.4.2.2	Spectrum due to switching transients.....	40

A.8.4.3	Spurious emissions	40
A.8.4.3.1	Principle of the specification	40
A.8.4.3.2	Base Station	40
A.8.4.3.3	Mobile Station	40
A.8.4.4	Radio frequency tolerance	41
A.8.4.5	Output level dynamic operation	41
A.8.4.5.1	Base station	41
A.8.4.5.2	Mobile station:	41
A.8.4.6	Phase accuracy	41
A.8.4.7	Intermodulation attenuation	41
A.8.4.7.1	Base transceiver station	41
A.8.4.7.2	Intra BTS intermodulation attenuation	41
A.8.4.7.3	Intermodulation between MS	41
A.8.5	RECEIVER CHARACTERISTICS	42
A.8.5.1	Blocking characteristics	42
A.8.5.2	Intermodulation characteristics	43
A.8.5.3	Spurious response rejection	43
A.8.5.4	Spurious emissions	43
A.8.6	TRANSMITTER/RECEIVER PERFORMANCE	43
A.8.6.1	Nominal error rates (NER)	43
A.8.6.2	Reference sensitivity level	43
A.8.6.3	Reference interference level	44
A.8.6.4	Erroneous frame indication performance	44
Annex B:	GSM900 Small Cell System scenarios	45
B.1	Transmitter	46
B.1.1	Modulation, Spurs and Noise	46
B.1.1.1	Co-ordinated, BTS -> MS	46
B.1.1.2	Uncoordinated, BTS -> MS	46
B.1.1.3	Co-ordinated & Uncoordinated MS -> BTS	46
B.1.1.4	Co-ordinated & Uncoordinated MS -> MS	46
B.1.1.5	Co-ordinated & Uncoordinated BTS -> BTS	47
B.1.2	Switching Transients	47
B.1.2.1	Uncoordinated MS -> BTS	47
B.1.2.2	Uncoordinated BTS -> MS	47
B.1.3	Intermodulation	47
B.1.3.1	Coordinated, BTS -> MS	47
B.1.3.2	Uncoordinated, BTS -> MS	47
B.1.3.3	Uncoordinated, MS&MS -> BTS	47
B.1.3.4	Uncoordinated MS&MS -> MS	47
B.2	Receiver	47
B.2.1	Blocking	47
B.2.1.1	Co-ordinated & Uncoordinated BTS -> MS	47
B.2.1.2	Co-ordinated MS -> BTS	47
B.2.1.3	Uncoordinated MS -> BTS	48
B.2.1.4	Co-ordinated & Uncoordinated MS -> MS	48
B.2.1.5	Co-ordinated and Uncoordinated BTS -> BTS	48
B.2.2	Intermodulation	48
B.2.2.1	Co-ordinated & Uncoordinated BTS -> MS	48
B.2.2.2	Co-ordinated MS & MS -> BTS	48
B.2.2.3	Uncoordinated MS & MS -> BTS	48
B.2.3	Maximum level	48
B.2.3.1	Co-ordinated MS -> BTS	48
B.2.3.2	Co-ordinated BTS -> MS	48
B.3.1	Transmitter	49
B.3.1.1	Modulation, Spurs and Noise	49
B.3.1.1.1	Co-ordinated, BTS -> MS	49
B.3.1.1.2	Uncoordinated, BTS -> MS	49
B.3.1.1.3	Co-ordinated & Uncoordinated MS -> BTS	49
B.3.1.1.4	Co-ordinated & Uncoordinated MS -> MS	49
B.3.1.1.5	Co-ordinated & Uncoordinated BTS -> BTS	49

B.3.1.2	Switching Transients.....	49
B.3.1.2.1	Uncoordinated MS -> BTS	49
B.3.1.2.2	Uncoordinated BTS -> MS	49
B.3.1.3	Intermodulation.....	50
B.3.1.3.1	Coordinated, BTS -> MS	50
B.3.1.3.2	Uncoordinated, BTS -> MS	50
B.3.1.3.3	Uncoordinated, MS&MS -> BTS.....	50
B.3.1.3.4	Uncoordinated MS&MS -> MS	50
B.3.2	Receiver.....	50
B.3.2.1	Blocking.....	50
B.3.2.1.1	Co-ordinated & Uncoordinated BTS -> MS	50
B.3.2.1.2	Co-ordinated MS -> BTS	50
B.3.2.1.3	Uncoordinated MS -> BTS	50
B.3.2.1.4	Co-ordinated & Uncoordinated MS -> MS	50
B.3.2.1.5	Co-ordinated and Uncoordinated BTS -> BTS	50
B.3.2.2	Intermodulation.....	50
B.3.2.2.1	Co-ordinated & Uncoordinated BTS -> MS	50
B.3.2.2.2	Co-ordinated MS & MS -> BTS	51
B.3.2.2.3	Uncoordinated MS & MS -> BTS.....	51
B.3.2.3	Maximum level.....	51
B.3.2.3.1	Co-ordinated MS -> BTS	51
B.3.2.3.2	Co-ordinated BTS -> MS	51
Annex C:	Microcell System Scenarios.....	52
Annex D:	Conversion factors	65
Annex E:	Repeater Scenarios.....	69
E.1	INTRODUCTION.....	69
E.2	REPEATER APPLICATIONS - OUTDOOR AND INDOOR	69
E.3	OUTDOOR REPEATER SCENARIO	69
E.4	OUTDOOR REPEATER PERFORMANCE Requirements.....	70
E.4.1	Wideband Noise	70
E.4.2	Intermodulation Products and Spurious Emissions	71
E.4.3	Output Power.....	71
E.4.4	Blocking by Uncoordinated BTS	71
E.4.5	Summary of Outdoor Repeater Requirements.....	72
E.5	INDOOR REPEATER SCENARIO	72
E.6	INDOOR REPEATER PERFORMANCE REQUIREMENTS	72
E.6.1	Wideband Noise	72
E.6.2	Intermodulation Products and Spurious Emissions	73
E.6.3	Output Power.....	73
E.6.4	Blocking by Uncoordinated BTS	74
E.6.5	Summary of Indoor Repeater Requirements	74
E.7	Title: Repeater Scenarios.....	75
E.7.1	Introduction	75
E.7.2	Repeater performance.....	75
E.7.2.1	Link Equations.....	75
E.7.2.2	Co-ordinated Scenario	76
E.7.2.3	Uncoordinated Scenario.....	77
E.7.2.4	Wideband Noise.....	77
E.7.2.5	3rd order Intermodulation (IM3) performance/Spurious emissions:	77
E.7.3	Repeater scenarios	77
E.7.3.1	Rural scenario	78
E.7.3.2	Urban Scenario	78
E.7.4	Summary	79
E.7.4.1	Repeater Specification	79
E.7.4.2	Planning considerations	79

E.7.5	Out of band Gain	80
E.7.6	Planning guidelines for repeaters.....	80
E.7.7	Indoor Repeater Scenario	80
Annex F:	Error Patterns for Speech Coder Development.....	84
F.0	Introduction	84
F.1	Channel Conditions	84
F.1.1	Simulation Conditions	84
F.1.2	Available Error Patterns	84
F.2	Test Data for the half rate speech coder	85
F.2.1	File description	85
F.2.2	Soft decision values and chip error patterns.....	85
F.2.3	Error patterns of corresponding TCH/FS	86
Annex G:	Simulation of Performance	88
G.1	Implementation Losses and Noise Figure	88
G.1.1	Assumed Equalizer.....	88
G.1.2	Accuracy of Simulations	88
G.1.3	Simulation Results.....	88
G.2	Reference Structure	97
G.2.1	Error Concealment	98
G.2.2	Implementation Losses and Noise Figure	98
G.2.3	Assumed Equalizer.....	98
G.2.4	Simulation Results.....	98
G.2.5	Proposed Values for Recommendation GSM 05.05.....	98
G.3	Simulation of performance for AMR.....	99
G.3.1	System Configuration.....	99
G.3.2	Error Concealment	99
G.3.3	Implementation Losses and Noise Figure	100
G.3.4	Assumed Equalizer.....	100
G.3.5	Simulation Methods	100
G.3.5.1	Simulation for speech	100
G.3.5.2	Simulation for DTX.....	100
G.3.5.3	Simulation for inband channel.....	100
G.3.6	Remarks to the Data in GSM 05.05.....	101
Annex H:	GSM900 Railway System Scenarios.....	102
H.1	Scope.....	102
H.1.1	List of some abbreviations.....	102
H.2	Constraints.....	102
H.2.1	GSM based systems in the 900 MHz band.....	102
H.2.2	Other systems	103
H.2.3	UIC systems outline	103
H.2.4	Fixed UIC RF parameters.....	103
H.3	Methodology	103
H.3.1	Scenarios	104
H.3.2	Format of calculations	105
H.3.3	GSM900 systems parameters	105
H.3.4	Minimum Coupling Loss.....	106
H.3.5	Interference margins.....	107
H.3.6	Differences between E- and P-GSM	107
H4	Transmitter requirements	107
H.4.1	Transmitter requirements summary.....	108
H.5	Receiver requirements.....	108
H.5.1	Receiver requirements summary	109

H.6	Wanted signals levels	109
H.6.1	Maximum wanted signal level.....	110
H.6.2	Dynamic range of wanted signals.....	110
Annex I:	Void	111
Annex J:	GSM900 Railway System Scenarios.....	112
J.1	Introduction	112
J.2	Basic considerations	112
J.2.1	Types of equipment and frequency ranges	112
J.3	Discussion of the individual sections in GSM 05.05	113
J.3.1	Scope	113
J.3.2	Frequency bands and channel arrangement.....	113
J.3.3	Reference configuration	114
J.3.4	Transmitter characteristics.....	114
J.3.4.1	Output power	114
J.3.4.2	Void	114
J.3.4.2.1	Spectrum due to the modulation and wide band noise	114
J.3.4.2.2a	MS spectrum due to switching transients.....	114
J.3.4.2.2b	BTS spectrum due to switching transients	115
J.3.4.3.1	Spurious emissions.....	115
J.3.4.3.2	BTS spurious emissions	116
J.3.4.3.3	MS spurious emissions.....	116
J.3.4.3.4	MS spurious emissions onto downlinks.....	117
J.3.4.4	Radio frequency tolerance	118
J.3.4.5	Output level dynamic operation.....	118
J.3.4.5.1	BTS output level dynamic operation.....	118
J.3.4.5.2	MS output level dynamic operation.....	119
J.3.4.6	Phase accuracy.....	119
J.3.4.7.1	Intra BTS intermod attenuation.....	119
J.3.4.7.2	Intermodulation between MS (DCS1800 only).....	119
J.3.4.7.3	Mobile PBX	119
J.3.5	Receiver characteristics	120
J.3.5.1	Blocking characteristics	120
J.3.5.2	Blocking characteristics (in-band).....	120
J.3.5.3	Blocking characteristics (out-of-band).....	121
J.3.5.4	AM suppression characteristics.....	121
J.3.5.5	Intermodulation characteristics.....	121
J.3.5.6	Spurious emissions	121
J.3.6	Transmitter/receiver performance	121
J.3.6.1	Nominal error rates	121
J.3.6.2	Reference sensitivity level.....	121
Annex K:	Block Erasure Rate Performance for GPRS	123
K.1	Introduction	123
K.2	Simulation Model.....	123
K.3	Results	123
K.4	Conclusions	124
Annex L:	Proposal on how to report GPRS performance into GSM 05.05.....	125
L.1	Introduction	125
L.2	GPRS BLER performance.....	125
L.3	GPRS throughput analyses.....	126
L.3.1	TU50 ideal FH.....	127
L.3.2	TU3 no FH	128

L.4	Proposals for GPRS performance in GSM 05.05.....	128
L.4.1	TU50 ideal FH.....	128
L.4.2	TU3 no FH.....	129
L.5	Conclusions.....	129
Annex M:	GPRS simulation results in TU 3 and TU 50 no FH.....	130
M.1	Introduction.....	130
M.2	Simulation Model.....	130
M.3	Maximum GPRS throughput.....	132
M.4	Conclusion.....	133
M.5	References.....	133
Annex N:	C/I_c and E_b/N_0 Radio Performance for the GPRS Coding Schemes.....	134
N.1	Introduction.....	134
N.2	C/I simulation results.....	134
N.3	E_b/N_0 performance.....	136
N.4	Conclusions.....	138
N.5	References.....	138
Annex O:	Void.....	139
Annex P:	Block Error Rate and USF Error Rate for GPRS.....	140
P.1	Introduction.....	140
P.2	Simulation Assumptions.....	140
P.3	Simulation Results.....	141
P.3.1	Interference Simulations.....	141
P.3.1.1	TU50 Ideal Frequency Hopping.....	141
P.3.1.2	TU50 No Frequency Hopping.....	142
P.3.1.3	TU3 Ideal Frequency Hopping.....	143
P.3.1.4	TU3 No Frequency Hopping.....	144
P.3.1.5	RA250 No Frequency Hopping.....	145
P.3.2	Sensitivity Simulations.....	146
P.3.2.1	TU50 Ideal Frequency Hopping.....	146
P.3.2.2	TU50 No Frequency Hopping.....	147
P.3.2.3	HT100 No Frequency Hopping.....	148
P.3.2.4	RA250 No Frequency Hopping.....	149
P.3.2.5	Static Channel.....	150
Annex Q:	Block Error Rate and USF Error Rate for GPRS, 1800 MHz.....	151
Q.1	Introduction.....	151
Q.2	Simulation Assumptions.....	151
Q.3	Simulation Results.....	152
Q.3.1	Interference Simulations, 1 800 MHz.....	152
Q.3.1.2	TU50, Ideal Frequency Hopping.....	152
Q.3.1.3	TU50 No Frequency Hopping.....	153
Q.3.2	Sensitivity Simulations, 1800 MHz.....	154
Q.3.2.1	TU50 Ideal Frequency Hopping.....	154
Q.3.2.2	TU50 No Frequency Hopping.....	155
Q.3.2.3	HT100 No Frequency Hopping.....	156
Annex R:	Pico BTS RF Scenarios.....	157

R.1	Introduction	157
R.2	Fixed parameters	157
R.3	Maximum BTS Output Power.....	158
R.4	BTS Receiver Sensitivity	159
R.4.1	Balanced link (zero interference scenario)	159
R.4.2	Interferer at MCL scenario	159
R.4.3	Power control (zero interference scenario).....	160
R.4.4	Sensitivity overview	160
R.5	BTS Power Control Range	160
R.6	BTS Spectrum due to modulation and wideband noise.....	160
R.7	Spurious Emissions	161
R.8	Radio Frequency Tolerance.....	161
R.9	Blocking Characteristics.....	162
R.10	pico- BTS AM suppression characteristics	163
R.10.1	Modulation sidebands.....	164
R.10.1.1	Uncoordinated BTS->MS	164
R.10.1.2	Uncoordinated MS->BTS	164
R.10.2	Switching transients	164
R.10.2.1	Uncoordinated BTS->MS	164
R.10.2.2	Uncoordinated MS->BTS	164
R.10.3	Blocking	165
R.10.3.1	Uncoordinated BTS->MS	165
R.10.3.2	Uncoordinated MS->BTS	165
R.10.4	The AM suppression requirement	165
R.10.4.1	Downlink, BTS->MS.....	165
R.10.4.2	Uplink, MS->BTS.....	165
R.10.4.3	Interference levels.....	166
R.11	intermodulation	166
R.11.1	co-ordinated and uncoordinated BTS => MS (scenarios 2 & 3, figure 3.2 middle).....	166
R.11.2	coordinated MS&MS -> BTS (scenario 4).....	166
R.11.3	uncoordinated MS&MS -> BTS (scenario 4, figure 3.2 lower)	166
R.11.4	MCL relaxation	167
R.12	Pico BTS TTI.5 performance requirements.....	167
R.12.1	Nominal Error Rates for Pico-BTS	167
R.13	timing and synchronisation	168
R.13.1	Steady state timing advance error.....	168
R.13.2	Conventional BTS	169
R.13.3	Pico-BTS	169
R.13.3.1	Pico-BTS relaxation.....	169
R.13.3.2	MS impact of Pico-BTS relaxation.....	169
Annex S:	CTS system scenarios	171
S.1	Introduction	171
S.1.1	Parameter Set.....	171
S.1.1.1	Transmitter Parameter.....	171
S.1.1.2	Receiver Parameter	172
S.1.1.3	Minimum coupling loss values	172
S.1.1.4	Path loss models	172
S.1.1.5	Margins	173
S.2	Transmitter characteristics	173
S.2.1	Maximum CTS-FP Transmit Power limited by MS blocking.....	173
S.2.2	Maximum CTS-FP Transmit Power limited by Spectrum due to Modulation and WBN	174

S.2.3	Specification of max. CTS-FP Transmit Power and CTS-FP Spectrum due to modulation and wide band noise	175
S.2.3.1	Maximum CTS-FP transmit power.....	175
S.2.3.2	Spectrum due to modulation and wide band noise.....	176
S.2.4	Balanced link for zero interference scenario (Interferer at MCL scenario).....	177
S.2.5	Range of Coverage for CTS:	177
S.2.6	Minimum CTS-FP transmit power.....	178
S.2.7	Power Level Distribution	179
S.2.8	Spurious Emission.....	179
S.3	Receiver characteristics.....	180
S.3.1	Blocking.....	180
S.3.2	AM suppression.....	181
S.3.2.1	Spectrum due to modulation	181
S.3.2.2	Switching transients.....	182
S.3.2.3	Blocking.....	183
S.3.2.4	Specification of AM Suppression	183
S.3.3	Intermodulation	184
S.3.3.1	uncoordinated CTS-MSs -> GSM-BTS.....	184
S.3.3.2	uncoordinated CTS-FPs -> MS.....	184
S.3.3.3	uncoordinated GSM-MSs -> CTS-FP.....	185
S.4	CTS-FP TI5 performance requirements	185
S.4.1	Nominal Error Rates for the CTS-FP	185
S.5	Conclusion.....	186
Annex T:	GSM400 system scenarios	187
T.0	Introduction	187
T.1	Frequency bands and channel arrangement.....	187
T.2	System Scenario Calculations for GSM400 systems	188
T.2.1	Worst case proximity scenarios.....	188
T.3	Worst Case Scenario Requirements	190
T.3.1	Transmitter	190
T.3.1.1	Modulation, Spurs and noise.....	190
T.3.1.1.1	Co-ordinated BTS -> MS.....	190
T.3.1.1.2	Uncoordinated BTS -> MS.....	190
T.3.1.1.3	Coordinated & Uncoordinated MS -> BTS.....	190
T.3.1.1.4	Coordinated & Uncoordinated MS -> MS	190
T.3.1.1.5	Coordinated & Uncoordinated BTS -> BTS	190
T.3.1.2	Switching transients.....	190
T.3.1.2.1	Uncoordinated MS -> BTS	190
T.3.1.2.2	Uncoordinated BTS -> MS	190
T.3.1.3	Intermodulation.....	191
T.3.1.3.1	Coordinated BTS -> MS	191
T.3.1.3.2	Uncoordinated BTS -> MS	191
T.3.1.3.3	Uncoordinated MSs -> BTS.....	191
T.3.1.3.4	Uncoordinated MS & MS -> MS	191
T.3.2	Receiver.....	191
T.3.2.1	Blocking.....	191
T.3.2.1.1	Coordinated & Uncoordinated BTS -> MS.....	191
T.3.2.1.2	Coordinated MS -> BTS	191
T.3.2.1.3	Uncoordinated MS -> BTS	191
T.3.2.1.4	Coordinated & Uncoordinated MS -> MS	191
T.3.2.1.5	Coordinated & Uncoordinated BTS -> BTS	191
T.3.2.2	Intermodulation.....	191
T.3.2.2.1	Coordinated & Uncoordinated BTS -> MS.....	191
T.3.2.2.2	Coordinated MS -> BTS	192
T.3.2.2.3	Uncoordinated MS -> BTS	192
T.3.2.3	Maximum level.....	192

T.3.2.3.1	Coordinated MS -> BTS	192
T.3.2.3.2	Coordinated BTS -> MS	192
T.4	Transmitter characteristics	192
T.4.1	Output power.....	192
T.4.1.1	Mobile Station	192
T.4.1.2	Base Station	192
T.4.2	Output RF Spectrum.....	192
T.4.2.1	Spectrum due to the modulation and wideband noise.....	192
T.4.2.2	Spectrum due to switching transients	193
T.4.3	Spurious emissions	193
T.4.3.1	Principle of the specification	193
T.4.3.2	Base transceiver station	194
T.4.3.3	Mobile station	194
T.4.4	Radio frequency tolerance.....	194
T.4.5	Output level dynamic operation	194
T.4.5.1	Base station.....	194
T.4.5.2	Mobile station	195
T.4.6	Phase accuracy	195
T.4.7	Intermodulation attenuation.....	195
T.5	Receiver characteristics.....	195
T.5.1	Blocking characteristics	195
T.5.2	AM suppression characteristics.....	197
T.5.3	Intermodulation Characteristics.....	198
T.5.4	Spurious emissions	198
T.6	Receiver performance.....	198
Annex U:	850 MHz and 1 900 MHz Mixed-Mode Scenarios	199
U.1	Introduction	199
U.2	BTS Wide Band Noise and Intra BTS Intermodulation Attenuation	199
U.2.1	Overview	199
U.2.1.1	TIA/EIA-136.....	199
U.2.1.2	ETSI GSM	200
U.2.2	Scenario - Mixed-Mode Multi-Carrier BTS in FCC Regulated Environment.....	200
U.2.3	BTS Wide Band Noise and Intra BTS Intermodulation Attenuation Analysis.....	201
U.3	BTS Blocking and AM Suppression Characteristics.....	203
U.3.1	Overview	203
U.3.1.1	TIA/EIA-136.....	203
U.3.1.2	ETSI GSM	203
U.3.2	Scenario - Mixed-Mode Multiple MS and BTS, Uncoordinated Close Proximity.....	203
U.3.3	Blocking Analysis	204
U.3.3.1	Definition.....	204
U.3.3.2	Calculation.....	204
U.3.4	AM Suppression Analysis	205
Annex V:	LCS scenarios.....	206
V.1	Introduction	206
V.2	TOA Type A LMU in a Co-Located Deployment	206
V.2.1	Constraints.....	206
V.2.2	Frequency Bands and Channel Arrangement (clause 2 of GSM 05.05).....	206
V.2.3	Proximity for DCS1800/PCS1900	206
V.2.4	Inputs needed.....	207
V.2.5	Conclusion.....	207
V.3	Discussion of TOA LMU RF Specification	207
V.3.1	Introduction	207
V.3.2	Analysis Model	208
V.3.3	Results	208