

ETSI EN 300 444 V2.5.1 (2017-10)



Digital Enhanced Cordless Telecommunications (DECT); Generic Access Profile (GAP)

ITeH STANDARDS PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/35705-dab0-47a7-b13a-d86424e19db5/etsi-en-300-444-v2.5.1-2017-10>

ReferenceREN/DECT-00309

Keywordsaccess, DECT, generic, IMT-2000, mobility,
profile, radio, synchronization, TDD, TDMA**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	11
Foreword.....	11
Modal verbs terminology.....	11
1 Scope	12
2 References	12
2.1 Normative references	12
2.2 Informative references.....	13
3 Definitions, symbols and abbreviations	13
3.1 Definitions.....	13
3.2 Symbols.....	16
3.3 Abbreviations	16
4 Feature definitions.....	18
4.0 General	18
4.1 NetWorK (NWK) features	18
4.2 Speech coding and audio features	20
4.3 Application features	21
5 Service definitions.....	21
5.0 General	21
5.1 DLC service definitions.....	21
5.2 MAC service definitions	22
6 Inter-operability requirements.....	23
6.1 General	23
6.2 NWK features.....	24
6.3 DLC services.....	25
6.4 MAC services.....	25
6.5 Physical Layer (PHL) services	26
6.6 Application features	26
6.7 Speech coding and audio features	26
6.8 Feature/service to procedure mapping.....	27
6.8.1 NWK feature to procedure mapping.....	27
6.8.2 DLC service to procedure mapping	30
6.8.3 MAC service to procedure mapping	31
6.8.4 Application feature to procedure mapping.....	32
6.8.5 Speech coding and audio feature to procedure mapping.....	32
6.9 General requirements	32
6.9.1 NWK layer message contents	32
6.9.2 Transaction identifier.....	32
6.9.3 Length of a NWK layer message	32
6.9.4 Handling of error and exception conditions.....	32
6.9.5 GAP default setup attributes	33
6.9.6 Coexistence of MM and CC procedures.....	33
6.9.7 Coding rules for information elements	33
7 Procedure description.....	33
8 NWK layer procedures.....	34
8.0 General	34
8.1 Summary of outgoing call messages, normal cases.....	34
8.2 Outgoing call request.....	36
8.2.0 Procedure	36
8.2.1 Associated procedures	36
8.2.1.1 Timer P-<CC.03> management	36
8.2.2 Exceptional cases.....	37
8.2.2.1 Timer P-<CC.03> expiry	37

8.2.2.2	PT releases the outgoing call request	37
8.2.2.3	FT rejects the outgoing call request	38
8.3	Overlap sending	38
8.3.0	Procedure	38
8.3.1	Associated procedure	39
8.3.1.1	Timer F-<CC.01> management	39
8.3.2	Exceptional cases	39
8.3.2.1	PT releases the outgoing call request	39
8.3.2.2	FT rejects the outgoing call request	39
8.3.2.3	Timer F-<CC.01> expiry	40
8.3.2.4	FT releases the outgoing call request	40
8.4	Outgoing call proceeding	40
8.4.0	Procedure	40
8.4.1	Exceptional cases	41
8.4.1.1	PT releases the outgoing call request	41
8.4.1.2	FT releases the outgoing call request	41
8.5	Outgoing call confirmation	42
8.5.0	Procedure	42
8.5.1	Exceptional cases	42
8.5.1.1	PT releases the outgoing call request	42
8.5.1.2	FT releases the outgoing call request	43
8.6	Outgoing call connection	43
8.7	Normal call release	44
8.7.0	Procedure	44
8.7.1	Associated procedures	45
8.7.1.1	Timer P-<CC.02> management	45
8.7.1.2	Timer F-<CC.02> management	45
8.7.2	Exceptional cases	45
8.7.2.1	Release collisions	45
8.7.2.2	Timer F-<CC.02> expiry	46
8.7.2.3	Timer P-<CC.02> expiry	47
8.8	Abnormal call release	47
8.9	Partial release	48
8.10	Sending keypad information	49
8.11	Summary of incoming call related messages, normal cases	50
8.12	Incoming call request	50
8.12.0	Procedure	50
8.12.1	Associated procedure	51
8.12.1.1	Timer F-<CC.03> management	51
8.12.2	Exceptional cases	52
8.12.2.1	FT releases the incoming call request	52
8.12.2.2	PT rejects the incoming call request	52
8.12.2.3	Timer F-<CC.03> expiry	53
8.12.3	Collective and group ringing	53
8.13	Incoming call confirmation	53
8.13.0	Procedure	53
8.13.1	Exceptional cases	54
8.13.1.1	FT releases the incoming call transaction	54
8.13.1.2	PT releases the incoming call transaction	54
8.14	PT alerting	55
8.15	Incoming call connection	55
8.15.0	Procedure	55
8.15.1	Associated procedure	56
8.15.1.1	Timer P-<CC.05> management	56
8.15.2	Exceptional cases	56
8.15.2.1	FT releases the incoming call transaction	56
8.15.2.2	PT releases the incoming call transaction	57
8.15.2.3	Timer P-<CC.05> expiry	57
8.16	Display	58
8.17	Terminal capability indication	58
8.18	Internal call setup	60
8.19	Internal call keypad	60

8.20	Service call setup.....	60
8.21	Service call keypad.....	61
8.22	Identification of PP.....	61
8.22.0	Procedure.....	61
8.22.1	Associated procedure.....	62
8.22.1.1	Timer F-<MM_ident.2> management.....	62
8.22.2	Exceptional cases.....	62
8.22.2.1	Identity not existing in the PT.....	62
8.22.2.2	Timer F-<MM_ident.2> expiry.....	62
8.23	Authentication of FT using DSAA.....	63
8.23.0	Procedure.....	63
8.23.1	Associated procedure.....	64
8.23.1.1	Timer P-<MM_auth.1> management.....	64
8.23.2	Exceptional cases.....	64
8.23.2.1	Authentication algorithm/key not supported.....	64
8.23.2.2	FT Authentication failure (authentication challenge RES2 has wrong value).....	64
8.23.2.3	Timer P-<MM_auth.1> expiry.....	65
8.24	Authentication of PP using DSAA.....	65
8.24.0	Procedure.....	65
8.24.1	Associated procedure.....	67
8.24.1.1	Timer F-<MM_auth.1> management.....	67
8.24.2	Exceptional cases.....	67
8.24.2.1	Authentication algorithm/key not supported.....	67
8.24.2.2	Timer F-<MM_auth.1> expiry.....	67
8.23.2.3	PP Authentication failure (authentication challenge RES1 has wrong value).....	67
8.25	Authentication of user using DSAA.....	68
8.25.0	Procedure.....	68
8.25.1	Associated procedure.....	68
8.25.1.1	Timer F-<MM_auth.2> management.....	68
8.25.2	Exceptional cases.....	69
8.25.2.1	Authentication algorithm/key not supported.....	69
8.25.2.2	Timer F-<MM_auth.2> expiry.....	69
8.26	Incrementing the ZAP value.....	69
8.27	Storing the DCK.....	70
8.28	Location registration.....	70
8.28.0	Procedure.....	70
8.28.1	Associated procedures.....	72
8.28.1.1	Timer P-<MM_locate.1> management.....	72
8.28.1.2	Timer F-<MM_ident.1> management.....	72
8.28.2	Exceptional cases.....	72
8.28.2.1	FT rejects the location registration procedure.....	72
8.28.2.2	Failure of location registration procedure.....	73
8.28.2.3	PT rejects the identity assignment.....	73
8.28.2.4	Timer F-<MM_identity.1> expiry.....	73
8.29	Location update.....	73
8.30	Obtaining access rights.....	75
8.30.0	Procedure.....	75
8.30.1	Associated procedure.....	76
8.30.1.1	Timer P-<MM_access.1> management.....	76
8.30.2	Exceptional cases.....	77
8.30.2.1	FT rejects the access rights.....	77
8.30.2.2	Timer P-<MM_access.1> expiry.....	77
8.31	FT terminating access rights.....	77
8.31.0	Procedure.....	77
8.31.1	Associated procedure.....	78
8.31.1.1	Timer F-<MM_access.2> management.....	78
8.31.2	Exceptional cases.....	79
8.31.2.1	PT rejects the termination request.....	79
8.31.2.2	Timer F-<MM_access.2> expiry.....	79
8.32	Key allocation.....	79
8.32.0	Procedure.....	79
8.32.1	Associated procedures.....	81

8.32.1.1	Timer F-<MM_key.1> management.....	81
8.32.1.2	Timer P-<MM_auth.1> management.....	81
8.32.2	Exceptional cases.....	81
8.32.2.1	Timer F-<MM_key.1> expiry.....	81
8.32.2.2	Timer P-<MM_auth.1> expiry.....	81
8.32.2.3	Allocation-type element is unacceptable.....	82
8.32.2.4	Authentication of PT fails.....	82
8.32.2.5	Authentication of FT fails.....	82
8.33	Cipher-switching initiated by FT using DSC.....	83
8.33.0	Procedure.....	83
8.33.1	Associated procedure.....	84
8.33.1.1	Timer F-<MM_cipher.1> management.....	84
8.33.2	Exceptional cases.....	84
8.33.2.1	PT rejects the cipher request.....	84
8.33.2.2	Timer F-<MM_cipher.1> expiry.....	85
8.34	Cipher-switching initiated by PT using DSC.....	85
8.34.0	Procedure.....	85
8.34.1	Associated procedure.....	86
8.34.1.1	Timer P-<MM_cipher.2> management.....	86
8.34.2	Exceptional cases.....	86
8.34.2.1	FT rejects the cipher request.....	86
8.34.2.2	Timer P-<MM_cipher.2> expiry.....	87
8.35	Indirect FT initiated link establishment.....	87
8.35.0	Procedure.....	87
8.35.1	Associated procedure.....	88
8.35.1.1	Timer F-<LCE.03> management.....	88
8.35.2	Exceptional cases.....	89
8.35.2.1	The IPUI received in the {LCE-PAGE-RESPONSE} does not match.....	89
8.35.2.2	Timer <LCE.03> expiry.....	89
8.35.2.3	Release from the higher entity.....	90
8.36	Direct PT initiated link establishment.....	90
8.36.0	Procedure.....	90
8.36.1	Exceptional case.....	91
8.36.1.1	Link establishment failure.....	91
8.37	Link release "normal".....	92
8.37.0	Procedure.....	92
8.37.1	Associated procedure.....	93
8.37.1.1	Timer <LCE.01> management.....	93
8.37.2	Exceptional cases.....	93
8.37.2.1	Timer <LCE.01> expiry.....	93
8.37.2.2	Outstanding data has been discarded.....	94
8.38	Link release "abnormal".....	94
8.39	Link release "maintain".....	94
8.39.0	Procedure.....	94
8.39.1	Associated procedure.....	95
8.39.1.1	Timer <LCE.02> management.....	95
8.40	Enhanced FT initiated U- plane connection.....	95
8.41	Calling Line Identification Presentation (CLIP) Indication.....	96
8.42	Calling Name Identification Presentation (CNIP) Indication.....	96
8.43	Internal Call Calling Line Identification Presentation (CLIP).....	97
8.44	Internal Call Calling Name Identification Presentation (CNIP).....	98
8.45	Enhanced security procedures.....	99
8.45.0	General.....	99
8.45.1	Encryption of all calls.....	100
8.45.2	Re-keying during a call.....	100
8.45.3	Early encryption.....	101
8.45.4	Subscription requirements.....	102
8.45.5	Enhanced security regarding legacy devices.....	103
8.45.5.0	General.....	103
8.45.5.1	Behaviour of FPs regarding legacy PPs.....	103
8.45.5.2	Behaviour of PPs regarding legacy FPs.....	103
8.45.5.3	Behaviour regarding legacy 'repeater' devices.....	104

8.45.6	Authentication of FT using DSAA2	105
8.45.6.0	Procedure	105
8.45.6.1	Associated procedure	106
8.45.6.1.1	Timer P-<MM_auth.1> management	106
8.45.6.2	Exceptional cases	107
8.45.6.2.1	Authentication algorithm/key not supported	107
8.45.6.2.2	FT Authentication failure (authentication challenge RES2 has wrong value).....	107
8.45.6.2.3	Timer P-<MM_auth.1> expiry	107
8.45.7	Authentication of PP using DSAA2	107
8.45.7.0	Procedure	107
8.45.7.1	Associated procedure	110
8.45.7.1.1	Timer F-<MM_auth.1> management	110
8.45.7.2	Exceptional cases	110
8.45.7.2.1	Authentication algorithm/key not supported	110
8.45.7.2.2	Timer F-<MM_auth.1> expiry	110
8.45.7.2.3	PP Authentication failure (authentication challenge RES1 has wrong value).....	110
8.45.8	Authentication of user using DSAA2	111
8.45.8.0	Procedure	111
8.45.8.1	Associated procedure	111
8.45.8.1.1	Timer F-<MM_auth.2> management	111
8.45.8.2	Exceptional cases	112
8.45.8.2.1	Authentication algorithm/key not supported	112
8.45.8.2.2	Timer F-<MM_auth.2> expiry	112
8.45.9	Key allocation using DSAA2.....	112
8.45.9.0	Procedure	112
8.45.9.1	Associated procedures.....	114
8.45.9.1.1	Timer F-<MM_key.1> management	114
8.45.9.1.2	Timer P-<MM_auth.1> management	114
8.45.9.2	Exceptional cases	115
8.45.9.2.1	Timer F-<MM_key.1> expiry	115
8.45.9.2.2	Timer P-<MM_auth.1> expiry	115
8.45.9.2.3	Allocation-type element is unacceptable.....	115
8.45.9.2.4	Authentication of PT fails.....	115
8.45.9.2.5	Authentication of FT fails.....	116
8.45.10	Cipher-switching initiated by FT using DSC2.....	116
8.45.10.0	Procedure	116
8.45.10.1	Associated procedure	117
8.45.10.1.1	Timer F-<MM_cipher.1> management	117
8.45.10.2	Exceptional cases	117
8.45.10.2.1	PT rejects the cipher request.....	117
8.45.10.2.2	Timer F-<MM_cipher.1> expiry	118
8.45.11	Cipher-switching initiated by PT using DSC2.....	118
8.45.11.0	Procedure	118
8.45.11.1	Associated procedure	120
8.45.11.1.1	Timer P-<MM_cipher.2> management	120
8.45.11.2	Exceptional cases	120
8.45.11.2.1	FT rejects the cipher request.....	120
8.45.11.2.2	Timer P-<MM_cipher.2> expiry	120
8.45.12	Additional procedures for devices supporting DSC2.....	121
8.45.12.1	General	121
8.45.12.2	Support of additional octet in <<AUTH-TYPE>>.....	121
9	DLC layer procedures	121
9.1	Class A link establishment	121
9.1.0	Procedure	121
9.1.1	Associated procedures	123
9.1.1.1	Timer P<DL.07> management.....	123
9.1.1.2	Re-transmission counter management.....	123
9.1.1.3	Multiple frame operation variables management.....	123
9.1.1.4	Lower Layer Management Entity (LLME) establishment of a MAC connection.....	123
9.1.2	Exceptional cases.....	124
9.1.2.1	Timer P<DL.07> expiry.....	124

9.1.2.2	Receipt of a request for link release	125
9.1.2.3	Receipt of an indication for a connection release	125
9.2	Class A Acknowledged Information transfer	125
9.2.0	Procedure	125
9.2.1	Acknowledgement with an I_frame	125
9.2.2	Acknowledgement with a RR_frame	126
9.2.3	Class A acknowledged information transfer with segment reassemble	127
9.2.4	Associated procedures	127
9.2.4.1	Timer <DL.04> management	127
9.2.4.2	Re-transmission counter management	127
9.2.4.3	Multiple frame operation variables management	127
9.2.5	Exceptional cases	128
9.2.5.1	Timer <DL.04> expiry	128
9.2.5.2	Receipt of a request for link release	128
9.2.5.3	Receipt of an indication for a connection release	128
9.2.5.4	DLC wants to make a connection handover	128
9.3	Class A link release	128
9.3.0	Procedure	128
9.3.1	Associated procedures	129
9.3.1.1	LLME U-plane release	129
9.3.1.2	LLME release a MAC connection	129
9.4	Class A link re-establishment	129
9.5	C _S channel fragmentation and recombination	129
9.6	Normal broadcast	129
9.7	Class A basic connection handover	130
9.7.0	Procedure	130
9.7.1	Voluntary handover	131
9.7.2	Associated procedure	131
9.7.2.1	LLME connection handover management	131
9.7.3	Exceptional case	131
9.7.3.1	Receipt of a request for link release	131
9.8	Encryption switching	131
9.8.0	Procedure	131
9.8.1	Associated procedure	132
9.8.1.1	Providing Encryption key to the MAC layer	132
9.8.2	Exceptional cases	132
9.8.2.1	Encryption fails	132
9.8.2.2	Connection handover of ciphered connections	132
9.9	U-plane class 0/min delay	132
9.9.0	Procedure	132
9.9.1	Associated procedure	132
9.9.1.1	LLME U-plane establishment	132
9.10	FU1 frame operation	133
10	MAC layer procedures	133
10.1	General	133
10.2	Downlink broadcast	134
10.2.0	Procedure	134
10.2.1	N _T message	134
10.2.2	Q _T - static system information	134
10.2.3	Q _T - FP capabilities	135
10.2.3.0	Q _T - FP capabilities	135
10.2.3.1	Q _T - Extended FP capabilities	135
10.2.3.2	Q _T - Extended FP capabilities (part 2)	135
10.2.4	Q _T - SARI list contents	136
10.3	Paging broadcast	136
10.3.0	Procedure	136
10.3.1	Short page, normal/extended paging	137
10.3.2	Zero page, normal/extended paging	137
10.3.3	Blind slot information	138
10.3.4	Bearer handover information	138
10.4	Setup of basic connection, basic bearer setup (A-field)	138

10.4.0	Procedure	138
10.4.1	M _T message.....	139
10.4.2	Associated procedures	139
10.4.2.1	Timer T200 management	139
10.4.2.2	Counter N200 management.....	139
10.4.3	Exceptional cases.....	140
10.4.3.1	Bearer setup attempt fails N200+1 times	140
10.4.3.2	Timer T200 expiry	141
10.5	Connection/bearer release	141
10.5.0	Procedure	141
10.5.1	M _T message.....	142
10.6	Bearer handover request.....	142
10.6.0	Procedure	142
10.6.1	M _T message.....	142
10.7	Connection handover request	142
10.7.0	Procedure	142
10.7.1	M _T message.....	143
10.8	C _S channel data.....	143
10.9	Q2 bit setting	143
10.10	RFPI handshake.....	143
10.11	Antenna diversity	143
10.12	Sliding collision.....	143
10.13	Encryption process - initialization and synchronization	143
10.14	Encryption mode control	144
10.14.0	Procedure	144
10.14.1	M _T message.....	144
10.15	Handover encryption process	145
10.16	Extended frequency allocation	145
10.17	Re-keying	145
10.18	Early Encryption	145
10.19	AES/DSC2 Encryption.....	145
11	Physical Layer (PHL) requirements	145
11.1	General	145
11.2	Minimum Normal Transmit Power (NTP).....	145
11.3	Radio receiver sensitivity	146
11.4	Z-field.....	146
11.5	Sliding collision detection	146
11.6	Physical channel availability	146
11.7	Synchronization window	146
12	Requirements regarding the speech transmission.....	146
12.1	General	146
12.2	User controlled volume control.....	146
13	Management procedures.....	147
13.1	Management of MM procedures	147
13.2	Location registration initiation	147
13.3	Assigned individual TPUI management.....	147
13.4	PMID management.....	147
13.5	DCK management	148
13.6	Broadcast attributes management.....	148
13.6.0	Procedure	148
13.6.1	Higher layer capabilities	148
13.6.2	Extended higher layer capabilities	148
13.6.3	Extended higher layer capabilities (part 2)	149
13.7	Storage of subscription related data	149
14	Application procedures.....	150
14.1	Subscription control	150
14.2	AC to bitstring mapping	150
14.3	Manual entry of the PARK.....	150
14.4	Terminal Identity number assignment in mono cell system.....	151

14.4.1	General.....	151
14.4.2	Procedure description	151
14.4.3	Related Procedures	152
Annex A (informative):	PP locking procedure for on-air subscription.....	153
Annex B (informative):	Tones, progress indicator and U-plane connection.....	155
B.1	General	155
B.2	Connection of U-plane and provision of tones.....	155
B.3	Provision of tones before connection of the U-plane	155
B.4	Provision of tones and <<Progress indicator>> information element.....	155
B.5	Summary	156
Annex C (normative):	Synchronization requirements for fixed parts	157
Annex D (informative):	Change history	158
History		159

iTeh STANDARD PREVIEW
 (standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/c356d705-dab0-47a7-b13a-d86424e19db5/etsi-en-300-444-v2.5.1-2017-10>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT).

The present document is based on ETSI EN 300 175, parts 1 [1] to 8 [8]. General attachment requirements and speech attachment requirements are based on ETSI EN 301 406 [11] (replacing ETSI TBR 006 [i.1]) and ETSI EN 300 176-2 [10] (previously covered by ETSI TBR 010 [i.2]).

The present document has been developed in accordance to the rules of documenting a profile specification as described in ISO/IEC 9646-6 [i.4].

National transposition dates

Date of adoption of this EN:	9 October 2017
Date of latest announcement of this EN (doa):	31 January 2018
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 July 2018
Date of withdrawal of any conflicting National Standard (dow):	31 July 2019

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document specifies that set of technical requirements for Digital Enhanced Cordless Telecommunications (DECT) Fixed Part (FP) and DECT Portable Part (PP) necessary for the support of the Generic Access Profile (GAP).

The GAP is applicable to all DECT Portable radio Terminations (PT) and Fixed radio Terminations (FT) which under the scope of ETSI EN 300 176-2 [10] (i.e. 3,1 kHz telephony teleservice) and specifies the minimum functionality that is supported by all other 3,1 kHz voice profiles.

The objective of the present document is to ensure the Air Interface (AI) inter-operability of DECT equipment capable of 3,1 kHz telephony applications, in such a way that any DECT PT conforming to the procedures described in the present document is inter-operable with any DECT FT conforming to the procedures described in the present document.

The profile consists of the minimum mandatory requirements that allow a 3,1 kHz teleservice connection to be established, maintained and released between a FT and a PT with the appropriate access rights, irrespective of whether the FP provides residential, business or public access services.

In addition, the present document defines the features, services, procedures etc. for both the FT and the PT, which are provision mandatory either in the PT or in the FT, as well as some elements that are provision optional but still process mandatory.

Mobility Management (MM) procedures at the DECT AI to support incoming calls and outgoing calls are included.

Inter-working between the FT and the attached network is outside the scope of the present document.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 175-1: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview".
- [2] ETSI EN 300 175-2: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 2: Physical layer (PHL)".
- [3] ETSI EN 300 175-3: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer".
- [4] ETSI EN 300 175-4: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 4: Data Link Control (DLC) layer".
- [5] ETSI EN 300 175-5: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer".
- [6] ETSI EN 300 175-6: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 6: Identities and addressing".
- [7] ETSI EN 300 175-7: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 7: Security features".

- [8] ETSI EN 300 175-8: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 8: Speech and audio coding and transmission".
- [9] ETSI EN 300 176-1: "Digital Enhanced Cordless Telecommunications (DECT); Test specification; Part 1: Radio".
- [10] ETSI EN 300 176-2: "Digital Enhanced Cordless Telecommunications (DECT); Test specification; Part 2: Audio and speech".
- [11] ETSI EN 301 406: "Digital Enhanced Cordless Telecommunications (DECT); Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU".
- [12] ETSI EN 300 700: "Digital Enhanced Cordless Telecommunications (DECT); Wireless Relay Station (WRS)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TBR 006: "Digital Enhanced Cordless Telecommunications (DECT); General terminal attachment requirements".
- [i.2] ETSI TBR 010: "Digital Enhanced Cordless Telecommunications (DECT); General Terminal Attachment Requirements; Telephony Applications".
- [i.3] ETSI TS 102 527-3: "Digital Enhanced Cordless Telecommunications (DECT); New Generation DECT; Part 3: Extended wideband speech services".
- [i.4] ISO/IEC 9646-6: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 6: Protocol profile test specification".
- [i.5] ISO/IEC 9646-7: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements".
- [i.6] ISO/IEC 8073 (1997): "Information technology - Open Systems Interconnection - Protocol for providing the connection-mode transport service".
- [i.7] Recommendation ITU-T G.726: "40, 32, 24, 16 kbit/s Adaptive Differential Pulse Code Modulation (ADPCM)".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ETSI EN 300 175-1 [1] and the following apply:

attach: process whereby a PP within the coverage area of a FP to which it has access rights, notifies this FP that it is operative

NOTE 1: The reverse process is detach, which reports the PP as inoperative.

NOTE 2: An operative PP is assumed to be ready to receive calls.