



**Satellite Earth Stations and Systems (SES);
GNSS based location systems;
Part 5: Performance Test Specification**

ITEH STANDARD PREVIEW
(standardpreview.iteh.ai)
Full standard at <https://standards.iteh.ai/catalogue/etsi-ts-103-246-5-v1.2.1-6fa9-475b-9d99-06512db50c5e>
2017-03



Reference
RTS/SES-00410

Keywords
GNSS, location, MSS, navigation, performance,
receiver, satellite, system, terminal

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	6
Introduction	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references.....	7
3 Definitions, symbols and abbreviations	8
3.1 Definitions	8
3.2 Symbols	10
3.3 Abbreviations	10
4 General	11
4.1 GBLS Performance Features.....	11
4.2 Conformance Test Statistics	11
4.3 GBLS Performance Class Determination.....	11
5 General test conditions	11
5.1 Introduction	11
5.2 Environmental conditions.....	12
5.3 GNSS signal conditions.....	12
5.3.1 Applicable GNSS constellations.....	12
5.3.2 GNSS signal level.....	12
5.3.3 GNSS frequency	12
5.3.4 GNSS Multi-system Time Offsets	12
5.4 Operational Environments.....	12
5.5 Assistance Data	12
5.6 Differential Data.....	13
5.7 Test Configurations	13
5.7.1 General Set-Up	13
5.7.2 GNSS Signal Generator.....	13
5.7.3 Sensor Simulators/Stimulators.....	14
5.7.4 Telecoms RF Simulators.....	14
5.7.5 GBLS output measurement data	14
6 Horizontal and Vertical Position Accuracy.....	15
6.1 Test Objectives & Case definitions	15
6.2 Method of Test	15
6.2.1 Introduction.....	15
6.2.2 Initial conditions	15
6.2.3 Measurement Procedures.....	15
6.2.3.1 Test cases T-HVA-01/02/03: Moving location target	15
6.2.3.2 Test cases T-HVA-04/05/06: Static location target.....	16
6.2.4 Measurement Data Analysis	16
6.2.4.1 General	16
6.2.4.2 Horizontal Position Error	16
6.2.4.2.1 Moving location target	16
6.2.4.2.2 Static location target.....	17
6.2.4.3 Vertical Position Error	17
6.2.4.4 Confidence Intervals	18
6.2.5 Pass/fail criteria	18
6.2.6 GBLS Class Allocation.....	18
7 Time-to-First-Fix (TTFF).....	18
7.1 Test Objectives & Case definitions	18

7.2	Method of Test	19
7.2.1	Introduction.....	19
7.2.2	Initial conditions	19
7.2.3	Measurement Procedures	19
7.2.3.1	Test cases T-TTF-01 to -05: Moving location target	19
7.2.3.2	Test cases T-TTF-05 to -08: Static location target.....	20
7.3	Pass/fail criteria	20
7.4	GBLS Class Allocation	20
8	Position Authenticity.....	20
8.1	Test Objectives & Case definitions	20
8.2	Method of test.....	21
8.2.1	Introduction.....	21
8.2.2	Initial conditions	21
8.2.3	Measurement procedures	21
8.2.3.1	Test cases T-PA-01 and T-PA-02: Moving location target.....	21
8.2.3.2	Test cases T-PA-03 and T-PA-04: Static location target	22
8.2.4	Measurement Data Analysis	22
8.2.4.1	Probability of False Alarm (Test cases T-PA-01 and T-PA-03)	22
8.2.4.2	Probability of Detection (Test cases T-PA-02 and T-PA-04)	22
8.3	Pass/Fail Criteria	22
8.3.1	T-PA-01 and T-PA-03	22
8.3.2	T-PA-02 and T-PA-04	23
8.4	GBLS Class allocation	23
9	Robustness to Interference	23
9.1	Test Objectives & Case definitions	23
9.2	Method of Test	23
9.2.1	Initial conditions	23
9.2.2	Measurement Procedures	23
9.3	Pass/fail criteria	24
9.4	GBLS Class Allocation	24
10	GNSS sensitivity	24
10.1	Test Objectives & Case definitions	24
10.2	Method of Test	25
10.2.1	Initial conditions	25
10.2.2	Measurement Procedures	25
10.3	Pass/fail criteria	26
10.4	GBLS Class Allocation	26
11	Position Integrity	27
11.1	Test Objectives & Case definitions	27
11.2	Method of Test	27
11.2.1	Initial conditions	27
11.2.2	Measurement Procedures.....	28
11.3	Pass/fail criteria	28
11.4	GBLS Class Allocation	28
12	Position day-to-day repeatability (Horizontal or Vertical plane)	28
12.1	Test Objectives & Case definitions	28
12.2	Method of Test	29
12.2.1	Introduction.....	29
12.2.2	Initial conditions	29
12.2.3	Measurement Procedures	29
12.2.3.1	Test cases T-DDR-01/02/03: Moving location target	29
12.2.3.2	Test cases T-DDR-04/05/06: Static location target.....	30
12.2.4	Measurement Data Analysis	30
12.2.4.1	General.....	30
12.2.4.2	Horizontal performance	31
12.2.4.3	Vertical performance	31
12.2.4.4	Confidence Intervals	32
12.2.5	Pass/fail criteria	32
12.2.6	GBLS Class Allocation	32

13	Time to Fix Ambiguities (TTFA).....	32
13.1	Test Objectives & Case definitions	32
13.2	Method of Test	33
13.2.1	Introduction.....	33
13.2.2	Initial conditions	33
13.2.3	Measurement Procedures.....	33
13.2.3.1	Test cases T-TTFA-01/02/03: Moving location target.....	33
13.2.3.2	Test cases T-TTFA-04/05/06: Static location target	34
13.2.4	Measurement Data Analysis	34
13.2.4.1	General	34
13.2.4.2	Time to Fix Ambiguities	34
13.2.5	Pass/fail criteria and GBLS Class Allocation	35
Annex A (normative):	Test Configurations	36
A.1	Anechoic Chamber Test Configuration.....	36
A.2	Wired Connections Test Configuration.....	36
Annex B (normative):	Scenarios for tests	37
B.1	GNSS Scenario.....	37
B.1.1	General Scenario	37
B.1.2	GNSS Scenario for the <i>Position day-to-day repeatability</i> Test Case	37
B.2	Telecoms Scenarios.....	37
B.3	Sensor Scenarios	38
Annex C (normative):	Formulae to convert East and North coordinates to Along- and Cross-Track coordinates.....	39
C.1	Coordinates conversion formulae	39
Annex D (normative):	Rules for statistical testing	40
D.1	For 95 % success rate, 95 % Confidence Level	40
D.2	For 90 % success rate, 95 % CL.....	42
D.3	Formulae to compute the confidence interval for the mean value of one-dimensional errors	43
D.4	Formulae to compute the confidence level for percentile values of one-dimensional errors	44
Annex E (informative):	GBLS Implementation profiles.....	45
E.1	Overview	45
E.2	Implementation Profile #1	46
E.3	Implementation Profile #2.....	47
E.4	Implementation Profile #3.....	48
E.5	Implementation Profile #4.....	49
E.6	Implementation Profile #5.....	50
E.7	Implementation Profile #6.....	51
E.8	Implementation Profile #7	52
Annex F (informative):	Bibliography.....	53
	History	54

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

The present document is part 5 of a multi-part deliverable covering GNSS-based Location Systems (GBLS), as identified in part 1 [1].

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Introduction

The increasing expansion of location-based applications aims to satisfy more and more complex and diversified user requirements: this is highlighted for example by the widespread adoption of multi-functional smart-phones or by the ever wider adoption of tracking devices (e.g. in transport), etc. This requirement for new and innovative location-based applications is generating a requirement for increasingly complex location systems.

The wide spectrum of location-based applications identified in ETSI TR 103 183 [i.1] calls for a new and broader concept for location systems, taking into account solutions in which GNSS technologies are complemented with other technologies to improve robustness and performance. The notion of **GNSS-based location systems** is introduced and defined in the present document.

Additional clauses and information related to the implementation in **GNSS-based location systems** of the various differential GNSS technologies, namely D-GNSS, RTK and PPP are also included in order to facilitate the use of this set of standards by manufacturers and service providers.

1 Scope

This multi-part deliverable addresses integrated GNSS based location systems (GBLS) that combine Global Navigation Satellite Systems (GNSS), with other navigation technologies, as well as with telecommunication networks in order to deliver location-based services to users. As a consequence the present document is not applicable to GNSS only receivers.

The present document specifies the procedures for testing conformance of complex GNSS based Location System (GBLS) with the performance requirements specified in ETSI TS 103 246-3 [3].

This multi-part deliverable proposes a list of functional and performance requirements and related test procedures. For each performance requirement, different classes are defined allowing the benchmark of different GNSS Based Location Systems (GBLS) addressing the same applications.

The tests specified are of a complete GBLS, considered as "Black Box" i.e. the tests are made at outputs of the system in response to stimuli applied at the inputs. The tests are defined for laboratory testing only, and not in the "field".

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 103 246-1: "Satellite Earth Stations and Systems (SES); GNSS based location systems; Part 1: Functional requirements".
- [2] ETSI TS 103 246-2: "Satellite Earth Stations and Systems (SES); GNSS based location systems; Part 2: Reference Architecture".
- [3] ETSI TS 103 246-3: "Satellite Earth Stations and Systems (SES); GNSS based location systems; Part 3: Performance requirements".
- [4] ETSI TS 103 246-4: "Satellite Earth Stations and Systems (SES); GNSS based location systems; Part 4: Requirements for location data exchange protocols".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TR 103 183: "Satellite Earth Stations and Systems (SES); Global Navigation Satellite Systems (GNSS) based applications and standardisation needs".

- [i.2] ETSI TS 137 571-1: "Universal Mobile Telecommunications System (UMTS); LTE; Universal Terrestrial Radio Access (UTRA) and Evolved UTRA (E-UTRA) and Evolved Packet Core (EPC); User Equipment (UE) conformance specification for UE positioning; Part 1: Conformance test specification (3GPP TS 37.571-1)".
- [i.3] IEEE 802.11™: "IEEE Standard for Information technology--Telecommunications and information exchange between systems Local and metropolitan area networks--Specific requirements Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications".
- [i.4] IEEE 802.15.1™: "IEEE Standard for Telecommunications and Information Exchange Between Systems - LAN/MAN - Specific Requirements - Part 15: Wireless Medium Access Control (MAC) and Physical Layer (PHY) Specifications for Wireless Personal Area Networks (WPANs)".
- [i.5] IEEE 802.15.4a™: "IEEE Standard for Information technology-- Local and metropolitan area networks-- Specific requirements-- Part 15.4: Wireless Medium Access Control (MAC) and Physical Layer (PHY) Specifications for Low-Rate Wireless Personal Area Networks (WPANs): Amendment 1: Add Alternate PHY".
- [i.6] ETSI TS 145 001: "Digital cellular telecommunications system (Phase 2+); Physical layer on the radio path; General description (3GPP TS 45.001)".
- [i.7] ETSI TS 125 104: "Universal Mobile Telecommunications System (UMTS); Base Station (BS) radio transmission and reception (FDD) (3GPP TS 25.104)".
- [i.8] ETSI TS 136 171: "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements for Support of Assisted Global Navigation Satellite System (A-GNSS) (3GPP TS 36.171)".
- [i.9] M.M. Desu, D. Raghavarao: "Non-parametric Statistical Methods For Complete and Censored Data", CRC press, 29th September 2003.
- [i.10] RINEX: "The Receiver Independent Exchange Format", Version 2.10.
- [i.11] RINEX: "The Receiver Independent Exchange Format", Version 3.02.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ETSI TS 103 246-1 [1] and the following apply:

accuracy (or error): difference between a measured or estimated value and its real value

almanac: information providing coarse orbit and coarse clock model information for GNSS satellites. Database providing location information for a reference network used for positioning

assistance: use of position data from, typically, a telecommunications network to enable a GBLS to acquire the GNSS signals and to calculate position more quickly (e.g. A-GNSS)

availability: percentage of time when a location system is able to provide the required location-related data

class A, B, C: classes categorize the performance level of the GBLS for a given performance feature

NOTE: In all cases Class A is the highest performance class and C is the lowest.

cold-start: condition of the GBLS GNSS receiver having no accurate prior information on the position, velocity and time of the location target, or on the positions of any of the GNSS satellites

continuity: likelihood that the the location system functionality will be available during the complete duration of the intended operation if the system is operational at the beginning of the operation

D-GNSS: technique aiming at enhancing position accuracy and integrity of a GNSS receiver by using differential pseudorange corrections and "do not use flag" for faulty satellites delivered by a GNSS reference station located at a known location

NOTE: In the present document, the term D-GNSS refer to conventional differential GNSS.

electromagnetic interference: any source of RF transmission that is within the frequency band used by a communication link, and that degrades the performance of this link

estimator: rule in statistics for calculating an estimate of a given quantity based on observed data

GNSS-based location system (GBLS): location system using GNSS as the primary source of positioning

GNSS only receiver: location receiver using GNSS as the unique source of positioning

GNSS Signal Generator (GSG): device or system capable of generating simulated GNSS satellite transmissions in order to create the required test environment for the GNSS sensor under test

integrity: measure of the trust in the accuracy of the location-related data provided by the location system and the ability to provide timely and valid warnings to users when the location system does not fulfil the condition for intended operation

NOTE: Integrity is expressed through the computation of a protection level. The Integrity function is designed to deliver a warning (or alert) of any malfunction to users within a given period of time (time-to-alert). Related to the Integrity concept, a Loss of Integrity event occurs when an unsafe condition (i.e. a positioning error higher than the protection level) occurs without a warning to the users for a time longer than the time-to-alert limit.

jamming: deliberate transmission of interference to disrupt communications

location: 3-dimensional position or location

location-based application: application which is able to deliver a service to one or several users, built on the processing of the location information (location-related data) related to one or several targets

location-related data: set of data associated with a given location target, containing at least one or several of the following time-tagged information elements: location target position, location target motion indicators (velocity and acceleration), and Quality of Service indicators (estimates of the position accuracy, reliability or authenticity)

location system: system responsible for providing to a location based application the location-related data of one or several location targets

location target: physical entity (mobile or stationary) whose position is the focus of the location related data to be built by the location system.

percentile: percentage of a set of observations of a parameter which give a successful result (i.e. success rate)

performance feature: set of performance requirements for a given location-related data category produced by the GBLS

position: 3-dimensional position or location

positioning: process of determining the position or location of a location target

Precise Point Positioning (PPP): differential GNSS technique that uses a worldwide distributed network of reference stations to provide, in quasi real time, a highly accurate geodetic positioning of a receiver

Protection Level (PL): upper bound to the positioning error such that the probability: $P(\epsilon > PL) < I_{risk}$, where I_{risk} is the integrity risk and ϵ is the position error

NOTE: The protection level is provided by the location system, and with the integrity risk, is one of the two sub-features of the integrity system.

pseudorange: pseudo distance between a satellite and a navigation receiver computed by multiplying the propagation delay determined by the receiver with the speed of light

Pseudo Range Correction (PRC): simple difference between a pseudorange measured by a GNSS reference station, set at a known location and the estimated range between the satellite and this known location

Real Time Kinematic (RTK): particular Differential GNSS technique that provides, in real time, highly accurate positioning of a target based on carrier phase measurements

spoofing: device or system that generates false GNSS signals intended to deceive location processing into reporting false location target data

spoofing: transmission of signals intended to deceive location processing into reporting false location target data

target: See location target.

time-to-alert: time from when an unsafe integrity condition occurs to when an alerting message reaches the user

WGS84: reference coordinate system used by the Global Positioning System

3.2 Symbols

For the purposes of the present document, the symbols given in ETSI TS 103 246-1 [1] apply.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI TS 103 246-1 [1] and the following apply:

3GPP	3 rd Generation Partnership Project
A-GNSS	Assisted GNSS
AT	Along-Track
BDS	BeiDou Navigation Satellite System
CL	Confidence Level
CT	Cross-Track
DGE	Data Gathering Equipment
DUT	Device Under Test
ENU	East/North/Up reference frame
EN	East/North reference frame
E-UTRA	Evolved - UMTS Terrestrial Radio Access
FFS	For Further Study
GBLS	GNSS Based Location System
GLONASS	Global Navigation Satellite System (Russian based system)
GMLC	Gateway Mobile Location Centre
GNSS	Global Navigation Satellite System
GPS	Global Positioning System
GSG	GNSS Signal Generator
GSM	Global System for Mobile communications
HPE	Horizontal Positioning Error
HPL	Horizontal Protection Level
ITS	Intelligent Transport Systems
LoS	Line of Sight
LPP	LTE Positioning Protocol
LPPe	LTE Positioning Protocol extension
LTE	Long-Term Evolution
n/a	not applicable
PL	Protection Level
PVT	Position, Velocity and Time
RF	Radio Frequency
SMLC	Serving Mobile Location Centre
SNR	Signal-to-Noise Ratio
TBD	To Be Defined
TTFF	Time-To-First-Fix
UMTS	Universal Mobile Telecommunications System
UTRA	UMTS Terrestrial Radio Access

Wi-Fi®	Wireless Fidelity
WPAN	Wireless Personal Area Network

4 General

4.1 GBLS Performance Features

Clauses 6 to 13 define the test procedures required to test conformance with the Performance Features defined in ETSI TS 103 246-3 [3].

These Features are:

- 1) Horizontal Position Accuracy.
- 2) Vertical Position Accuracy.
- 3) Time-to-First-Fix (TTFF).
- 4) Position Authenticity.
- 5) Robustness to Interference.
- 6) GNSS Sensitivity.
- 7) Position Integrity (Protection Level).
- 8) Position day-to-day repeatability.
- 9) Time To Fix Ambiguity.

NOTE: The test procedure for the feature "GNSS Time Accuracy" defined in ETSI TS 103 246-3 [3] is FFS.

4.2 Conformance Test Statistics

Performance requirements in ETSI TS 103 246-3 [3] are expressed either as a single value or, when it has a statistical nature, as a success rate.

When testing a parameter with a statistical nature, a confidence level is set in the conformance test defined herein which establishes the probability that the GBLS passing the test meets the requirement and determines how many times a test has to be repeated.

4.3 GBLS Performance Class Determination

Performance features are defined in ETSI TS 103 246-3 [3] for GBLS performance classes A, B and C.

Results of the conformance tests herein allow a GBLS to be allocated to one of the three classes according to the definition in ETSI TS 103 246-3 [3], unless otherwise specified.

5 General test conditions

5.1 Introduction

This clause defines the common test conditions required for all tests in the remainder of the present document, unless otherwise specified.

5.2 Environmental conditions

The environmental conditions for test will be defined by the GBLS vendor.

5.3 GNSS signal conditions

5.3.1 Applicable GNSS constellations

The applicable GNSS's are defined in clause A.2 of ETSI TS 103 246-3 [3].

Each test defined in the following clauses shall be performed with the combination of GNSS constellation(s) and satellite signal(s) simultaneously supported by the GBLS under test.

5.3.2 GNSS signal level

The GNSS signal is defined at the GNSS antenna connector of the GBLS. For a GBLS with only an integral GNSS antenna, this is assumed to be an antenna with a gain of 0 dBi. The reference input signal power levels are defined in table 5.1.

Table 5.1: Reference Power and Relative signal power levels for each GNSS signal type

	Galileo		GPS/Modernized GPS		GLONASS		BDS (note 2)	
Reference power (dBm)		-130		-128,5		-131		-130
Signal power level relative to reference power level (dB)	E1	0	L1 C/A	0	G1	0	B1 D1	0
	E6	+2	L1C	+1,5	G2	-6	B1 D2	+5
	E5	+2	L5	+3,6				
NOTE 1: The GNSS signal power levels in the table represent the total signal power per channel for pilot and data channels.								
NOTE 2: For test cases which involve "BeiDou", D1 represents MEO/IGSO satellites of B1I signal type and D2 represents GEO satellites of B1I signal type.								

5.3.3 GNSS frequency

GNSS signals shall be transmitted with a frequency accuracy of $\pm 2,5 \times 10^{-8}$.

5.3.4 GNSS Multi-system Time Offsets

If more than one GNSS is used in a test, the accuracy of the GNSS-GNSS Time Offsets at the GSG shall be better than 1 ns. The particular case where the GBLS uses D-GNSS, RTK or PPP is FFS.

5.4 Operational Environments

General operational environments are as defined in clause A.3 of ETSI TS 103 246-3 [3], and specifically in each of the clauses for Performance Features in ETSI TS 103 246-3 [3].

5.5 Assistance Data

Any assistance data required by the GBLS shall relate to the scenario(s) being generated and shall be provided by the appropriate means (e.g. by simulating a server such as an SLP, GMLC, SMLC and by transmission over a suitable telecommunications link).

5.6 Differential Data

Any GNSS differential data required by the GBLS shall relate to the scenario(s) being generated and shall be provided by the appropriate means:

- Simultaneous simulation of the GNSS signals as received differentially by one reference station and by the location target from a common scenario.
- Simultaneous simulation of the GNSS signals as received by the location target and of a communication link carrying the corresponding differential messages simulated as supplied by a differential service provider from a network of stations.

5.7 Test Configurations

5.7.1 General Set-Up

In general the tests for GBLS signal performance shall be conducted using RF simulators generating GNSS and telecoms transmission and reception signals and other sensor simulators, connected either:

- 1) using antennas in an anechoic chamber (e.g. if the GBLS has integral antennas); or
- 2) with wired RF connections only when access to the GBLS antenna connectors is available.

5.7.2 GNSS Signal Generator

In each case the test set-up consists of a GNSS Signal Generator (GSG) connected to the GBLS input and generating a set of emulated GNSS RF signals as defined in clause 5.3 and in annex A of ETSI TS 103 246-3 [3].

The GSG shall simulate atmospheric effects (ionosphere, etc.) as specified in annex B.

The GSG shall simulate the satellites that satisfy all the following conditions:

- elevation > 5 degrees from the GBLS GNSS sensor position (clause B.1);
- those that are practically visible by the GBLS in sky attenuation conditions applicable to the relevant test (see clause A.3.2 of ETSI TS 103 246-3 [3]) (i.e. where sky attenuation < 100 dB).

In any case the maximum number of satellites to be simulated per constellation is given in table 5.2. The selection of these visible satellites shall be at the discretion of the test operator.

Table 5.2: Maximum number of visible Satellites to be simulated by the GSG

GNSS receiver capability of the GBLS	Maximum number of satellites to be simulated
Single constellation receiver	8
Dual constellation receiver	8
Triple constellation receiver	8
Quad constellation receiver	6

When the GBLS under test is to be tested in GNSS differential mode and when only one reference station is used (conventional D-GNSS and RTK), then the GSG shall generate a set of emulated GNSS RF signals as defined in clause 5.6 and in ETSI TS 103 246-3 [3] on at least two RF outputs, one for the location target GNSS sensor and one for the GNSS sensors included in the reference stations. For both RF outputs the satellite transmitters are the same and at the same location, but the geometric range used to generate the received signal are different (target location and reference station location).

When the GBLS under test is to be tested in GNSS differential mode and when a network of stations is used (NRTK or PPP), then the GSG shall generate a set of emulated GNSS RF signals as defined in clause 5.6 and in ETSI TS 103 246-3 [3], and a simulator of a network of reference stations shall simultaneously compute the consistent observable and/or correction data that could have been sent by an appropriate differential GNSS service provider network.