



**SLOVENSKI STANDARD**  
**SIST EN 301 489-22 V2.1.1:2020**

**01-december-2020**

---

**Standard elektromagnetne združljivosti (EMC) za radijsko opremo in storitve - 22. del: Posebne zahteve za talno mobilno in fiksno letalniško (aeronavtično) radijsko opremo - Harmonizirani standard za elektromagnetno združljivost**

ElectroMagnetic Compatibility (EMC) standard for radio equipment and services - Part 22: Specific conditions for ground based aeronautical mobile and fixed radio equipment - Harmonised Standard for ElectroMagnetic Compatibility

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 301 489-22 V2.1.1:2020](https://standards.iteh.ai/catalog/standards/sist/da6184d2-42ce-458b-b576-c4a1d6f2504b/sist-en-301-489-22-v2-1-1-2020)

[https://standards.iteh.ai/catalog/standards/sist/da6184d2-42ce-458b-b576-](https://standards.iteh.ai/catalog/standards/sist/da6184d2-42ce-458b-b576-c4a1d6f2504b/sist-en-301-489-22-v2-1-1-2020)

[c4a1d6f2504b/sist-en-301-489-22-v2-1-1-2020](https://standards.iteh.ai/catalog/standards/sist/da6184d2-42ce-458b-b576-c4a1d6f2504b/sist-en-301-489-22-v2-1-1-2020)

**Ta slovenski standard je istoveten z: ETSI EN 301 489-22 V2.1.1 (2020-10)**

---

**ICS:**

33.060.01	Radijske komunikacije na splošno	Radiocommunications in general
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general

**SIST EN 301 489-22 V2.1.1:2020**      **en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 301 489-22 V2.1.1:2020

<https://standards.iteh.ai/catalog/standards/sist/da6184d2-42ce-458b-b576-c4a1d6f2504b/sist-en-301-489-22-v2-1-1-2020>

# ETSI EN 301 489-22 V2.1.1 (2020-10)



**ElectroMagnetic Compatibility (EMC)**  
standard for radio equipment and services;  
**Part 22: Specific conditions for ground based  
aeronautical mobile and fixed radio equipment;**  
**Harmonised Standard for ElectroMagnetic Compatibility**

SIST EN 301 489-22 V2.1.1:2020  
https://standards.etsi.org/standards-search/?query=301-489-22-v2-1-1-2020  
c4a1d6f2504b/sist-en-301-489-22-v2-1-1-2020

---

**Reference**REN/ERM-EMC-355

---

**Keywords**aeronautical, EMC, harmonised standard, UHF,  
VHF**ETSI**650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

---

**Important notice**

<https://standards.iteh.ai/catalog/standards/sist/da6184d2-42ce-458b-b576-c4a03f304b/sist-en-301-489-22-v2.1.1-2020>  
The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	5
Foreword.....	5
Modal verbs terminology.....	5
1 Scope .....	6
2 References .....	6
2.1 Normative references .....	6
2.2 Informative references.....	7
3 Definition of terms, symbols and abbreviations.....	7
3.1 Terms.....	7
3.2 Symbols.....	8
3.3 Abbreviations .....	8
4 Test conditions .....	8
4.1 General .....	8
4.2 Arrangements for test signals .....	8
4.2.0 General.....	8
4.2.1 Arrangement for test signals at the input to the transmitter .....	8
4.2.2 Arrangements for test signals at the output from the transmitter.....	9
4.2.3 Arrangements for test signals at the input to the receiver .....	9
4.2.4 Arrangements for test signals at the output from the receiver .....	9
4.2.5 Arrangements for testing transmitters and receivers together (as a system) .....	9
4.3 RF exclusion band for radio communications equipment .....	9
4.3.1 General.....	9
4.3.2 Transmitter exclusion bands for EM emission measurements .....	9
4.3.3 Receiver exclusion bands for EM emission measurements .....	10
4.3.4 Transmitter exclusion bands for immunity tests .....	10
4.3.5 Receiver exclusion bands for immunity tests .....	10
4.4 Narrow band responses of receivers .....	10
4.5 Normal test modulation .....	11
5 Performance assessment.....	11
5.1 Void.....	11
5.2 Equipment which can provide a continuous communications link .....	11
5.3 Void.....	11
5.4 Ancillary equipment .....	11
5.5 Equipment classification .....	12
6 Performance criteria .....	12
6.1 General Requirements .....	12
6.2 Performance criteria A for continuous phenomena applied to transmitters and receivers.....	13
6.3 Performance criteria B for transient phenomena applied to transmitters and receivers .....	13
6.4 Performance criteria C for immunity tests with power interruptions .....	13
7 Applicability overview .....	14
7.1 Emission.....	14
7.1.1 General.....	14
7.1.2 Methods of measurement and limits modifications .....	14
7.2 Immunity .....	15
7.2.1 General.....	15
7.2.2 Test methods and levels modifications .....	16
<b>Annex A (informative): Relationship between the present document and the essential requirements of Directive 2014/53/EU .....</b>	<b>18</b>
<b>Annex B (normative): Minimum Performance Levels (MPL).....</b>	<b>20</b>
B.1 Ground based aeronautical VHF and UHF radio .....	20

B.2	VHF Digital Link Mode 2 (VDL Mode 2) and Mode 4 (VDL Mode 4).....	20
<b>Annex C (informative):</b>	<b>Test Report .....</b>	<b>21</b>
<b>Annex D (informative):</b>	<b>Change history .....</b>	<b>22</b>
History .....		23

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 489-22 V2.1.1:2020](https://standards.iteh.ai/catalog/standards/sist/da6184d2-42ce-458b-b576-c4a1d6f2504b/sist-en-301-489-22-v2-1-1-2020)

<https://standards.iteh.ai/catalog/standards/sist/da6184d2-42ce-458b-b576-c4a1d6f2504b/sist-en-301-489-22-v2-1-1-2020>

## Intellectual Property Rights

### Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

### Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

## Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.2] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document is part 22 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

National transposition dates	
Date of adoption of this EN:	8 October 2020
Date of latest announcement of this EN (doa):	31 January 2021
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 July 2021
Date of withdrawal of any conflicting National Standard (dow):	31 July 2022

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

# 1 Scope

The present document covers in respect of ElectroMagnetic Compatibility (EMC), the assessment of:

- 1) ground based aeronautical VHF radio communications equipment characterized by the following operating conditions:
  - a) operating in the frequency range 118 MHz to 136,975 MHz, at 8,33 kHz or 25 kHz channel spacing;
  - b) using DSB AM modulation;
- 2) ground-based UHF radio transmitters, receivers and transceivers for the UHF aeronautical mobile service characterized by the following operating conditions:
  - a) operating in the frequency range 225 MHz to 399,975 MHz at 12,5 kHz or 25 kHz channel spacing;
  - b) using DSB AM modulation;
- 3) VDL Mode 2 ground base station radio equipment operating in the frequency range 117,975 MHz to 137,000 MHz;
- 4) VDL Mode 4 ground base station radio equipment operating in the frequency range 112,000 MHz to 136,975 MHz.

NOTE: The relationship between the present document and essential requirements of article 3.1(b) of Directive 2014/53/EU [i.1] is given in Annex A.

**iTeh STANDARD PREVIEW**

---

## 2 References (standards.iteh.ai)

### 2.1 Normative references

[SIST EN 301 489-22 V2.1.1:2020](https://standards.iteh.ai/standards/sist/da6184d2-42ce-458b-b576-c4a1d6f2504b/sist-en-301-489-22-v2-1-1-2020)

<https://standards.iteh.ai/standards/sist/da6184d2-42ce-458b-b576-c4a1d6f2504b/sist-en-301-489-22-v2-1-1-2020>

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 301 489-1 (V2.2.3) (11-2019): "ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements; Harmonised Standard for ElectroMagnetic Compatibility".
- [2] ETSI EN 301 841-1 (V1.4.1) (04-2015): "VHF air-ground Digital Link (VDL) Mode 2; Technical characteristics and methods of measurement for ground-based equipment; Part 1: Physical layer and MAC sub-layer".
- [3] ETSI EN 301 842-1 (V1.4.1) (04-2015): "VHF air-ground Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for ground-based equipment; Part 1: EN for ground equipment".
- [4] ETSI EN 300 676-1 (V1.5.2) (03-2011): "Ground-based VHF hand-held, mobile and fixed radio transmitters, receivers and transceivers for the VHF aeronautical mobile service using amplitude modulation; Part 1: Technical characteristics and methods of measurement".



- [5] ETSI EN 302 617 (V2.3.1) (07-2018): "Ground-based UHF radio transmitters, receivers and transceivers for the UHF aeronautical mobile service using amplitude modulation; Harmonised Standard for access to radio spectrum".

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.3] ITU Radio Regulations (2016).
- [i.4] Recommendation ITU-T P.53: "Psophometer for use on telephone-type circuits".

[standards.iteh.ai](https://standards.iteh.ai/)

## 3 Definition of terms, symbols and abbreviations

### 3.1 Terms

For the purposes of the present document, the terms given in ETSI EN 301 489-1 [1] and the following apply:

**base station:** aeronautical radio equipment, used in the aeronautical mobile service, for use with an external antenna and intended for use at a fixed location

**centre frequency (Fc):** centre of the transmitter necessary bandwidth

**integral antenna equipment:** radio communications equipment with an antenna integrated into the equipment without the use of an external connector and considered to be part of the equipment

**necessary bandwidth:** for a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions

NOTE: This is the definition in the ITU Radio Regulations, clause 146 [i.3].

**occupied bandwidth:** width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage  $\beta/2$  of the total mean power of a given emission

NOTE: Unless otherwise specified by ITU-R for the appropriate class of emission, the value of  $\beta/2$  should be taken as 0,5 % as defined in the ITU Radio Regulations [i.3].

**operating frequency range:** range(s) of continuous radio frequencies covered by the Equipment Under Test (EUT)

**product standard:** functional standard describing frequency management parameters of radio product

**simplex:** instantaneous one-way communications link

## 3.2 Symbols

Void.

## 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AC	Alternating Current
AM	Amplitude Modulation
BER	Bit Error Ratio
BW	BandWidth
DC	Direct Current
DSB	Double Side Band full carrier
EM	ElectroMagnetic
EMC	ElectroMagnetic Compatibility
EUT	Equipment Under Test
Fc	centre frequency
MPL	Minimum Performance Levels
RF	Radio Frequency
rms	root mean of squares
SINAD	Signal In Noise And Distortion
THD	Total Harmonic Distortion
UHF	Ultra High Frequency
VDL	VHF Digital Link
VHF	Very High Frequency

STANDARD PREVIEW  
(standards.itech.ai)

## 4 Test conditions

[SIST EN 301 489-22 V2.1.1:2020](https://standards.itech.ai/catalog/standards/sist/da6184d2-42ce-458b-b576-c4a1d6f2504b/sist-en-301-489-22-v2-1-1-2020)

### 4.1 General

<https://standards.itech.ai/catalog/standards/sist/da6184d2-42ce-458b-b576-c4a1d6f2504b/sist-en-301-489-22-v2-1-1-2020>

The test configuration and mode of operation shall represent the intended use and shall be recorded in the test report.

## 4.2 Arrangements for test signals

### 4.2.0 General

The provisions of ETSI EN 301 489-1 [1], clause 4.2 shall apply with the following modification:

- For integral antenna radio communications equipment a temporary 50 Ω RF connection point may be provided for connection to the measuring equipment.

### 4.2.1 Arrangement for test signals at the input to the transmitter

The provisions of ETSI EN 301 489-1 [1], clause 4.2.1 shall apply with the following modification:

- The transmitter shall be modulated with normal test modulation by an internal or external signal source capable of producing the appropriate drive signal (see clause 4.5).

## 4.2.2 Arrangements for test signals at the output from the transmitter

The provisions of ETSI EN 301 489-1 [1], clause 4.2.2 shall apply with the following modifications:

- The transmitter shall be operated at its maximum rated RF carrier output. If the maximum power cannot be maintained due to thermal limitations, any tests should be paused and the transmitter allowed to cool, until full power can be maintained again.
- The RF output signal of the transmitter shall be coupled to the measuring equipment via a shielded transmission line such as a coaxial cable. The measuring equipment shall comprise a combination of a modulation analyser and an audio distortion meter.

## 4.2.3 Arrangements for test signals at the input to the receiver

The provisions of ETSI EN 301 489-1 [1], clause 4.2.3 shall apply with the following modifications:

- The wanted RF input signal coupled to the receiver shall be modulated with normal test modulation (see clause 4.5).

## 4.2.4 Arrangements for test signals at the output from the receiver

The provisions of ETSI EN 301 489-1 [1], clause 4.2.4 shall apply.

## 4.2.5 Arrangements for testing transmitters and receivers together (as a system)

The provisions of ETSI EN 301 489-1 [1], clause 4.2.5 shall apply.

ITeH STANDARD PREVIEW  
(standards.iteh.ai)

## 4.3 RF exclusion band for radio communications equipment

<https://standards.iteh.ai/catalog/standards/sist/da6184d2-42ce-458b-b576-c4a1d6f2504b/sist-en-301-489-22-v2-1-1-2020>

### 4.3.1 General

Frequencies on which radio communications equipment is intended to operate are excluded from immunity tests with radiated RF test signals.

The provisions of ETSI EN 301 489-1 [1], clause 4.3 shall apply with the following modifications:

- The transmitter exclusion bands and the receiver exclusion bands as defined in clauses 4.3.2 to 4.3.5 shall apply.

### 4.3.2 Transmitter exclusion bands for EM emission measurements

Exclusion bands shall apply when measuring transmitters in transmit mode of operation.

Exclusion bands shall not apply when measuring transmitters in standby mode of operation.

The exclusion bands for transmitters are given in table 1.