

ETSI EN 302 296 V2.1.1 (2017-06)



**Digital Terrestrial TV Transmitters;
Harmonised Standard covering the essential requirements
of article 3.2 of Directive 2014/53/EU**

*iTeh STANDARDS PREVIEW
(standards.iteh.ai)
Full standard: <https://standards.iteh.ai/catalog/standards/sis/48809a1c-7fa6-46a9-9f2b-93160496816c/etsi-en-302-296-v2-1-2017-06>*

Reference

REN/ERM-TG17-24

Keywords

broadcasting, digital, harmonised standard, radio, regulation, terrestrial, transmitter, TV, video

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and LTE™ are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	5
Introduction	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	7
3 Definitions, symbols and abbreviations	8
3.1 Definitions.....	8
3.2 Symbols.....	9
3.3 Abbreviations	9
4 Technical requirements specifications	10
4.1 Environmental profile.....	10
4.2 Conformance requirements	10
4.2.1 Introduction.....	10
4.2.2 Spurious emissions	10
4.2.2.1 Definition	10
4.2.2.2 Limits	11
4.2.2.3 Conformance test	11
4.2.3 Out-of-band emissions.....	12
4.2.3.1 Definition	12
4.2.3.2 Classification of transmitters.....	12
4.2.3.3 Limits	12
4.2.3.4 Conformance test	16
5 Testing for compliance with technical requirements.....	17
5.1 Environmental conditions for testing	17
5.2 Interpretation of the measurement results.....	17
5.3 Test conditions	17
5.3.1 Test frequency range.....	17
5.3.2 Test modulation signal.....	18
5.4 Essential radio test suites.....	18
5.4.1 Introduction.....	18
5.4.2 Spurious emissions	18
5.4.2.1 Measurement approaches.....	18
5.4.2.2 Initial conditions	19
5.4.2.3 Test procedure.....	19
5.4.2.4 Test requirements.....	19
5.4.2.5 Test arrangement.....	20
5.4.3 Out-of-band emissions.....	20
5.4.3.1 Initial conditions	20
5.4.3.2 Test procedure.....	21
5.4.3.3 Test requirements.....	21
5.4.3.4 Test arrangement.....	21
Annex A (informative): Relationship between the present document and the essential requirements of Directive 2014/53/EU	22
Annex B (informative): Void	23
Annex C (informative): Practical measurement of spurious domain emissions for broadcast transmitters	24
C.0 Introduction	24

C.1	Directional coupler issues	24
C.2	Spectrum analyser settings	26
C.3	Composite measurement of spurious emissions.....	26
Annex D (informative):	Practical Measurement of out-of-band Domain Emissions.....	27
D.1	Composite measurement of out-of-band emissions	27
D.2	System considerations	28
D.3	Spectrum analyser settings for OOB measurements	29
D.4	OOB domain emissions - typical spectrum analyser traces	29
D.5	ACLR measurement.....	30
Annex E (informative):	Impact of ACLR of low power broadcast transmitters on adjacent DVB-T/T2 services for co-sited networks	31
E.0	Introduction	31
E.1	Equipment Configuration	31
E.2	Results	32
E.3	Theoretical impact of MER on END.....	33
E.4	Conclusions	33
Annex F (informative):	Energy Efficiency and the impact on unwanted Out of Block Emissions	34
Annex G (informative):	Bibliography	35
Annex H (informative):	Change history	36
History		37

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.3] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

National transposition dates	
Date of adoption of this EN:	26 June 2017
Date of latest announcement of this EN (doa):	30 September 2017
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 March 2018
Date of withdrawal of any conflicting National Standard (dow):	31 March 2019

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document has been produced to update the existing standard in line with the requirements of article 3.2 of Directive 2014/53/EU [i.2].

1 Scope

The present document specifies technical characteristics and methods of measurements for digital terrestrial television transmitters as defined in table 1.1 and in table 1.2. The output power classification (table 1.1) and emission classification (table 1.2) are combined to define a transmitter category. For example, power classification H and emission classification 0 denotes a high power transmitter (category H0) whose OOB emissions comply with a non-critical mask.

Table 1.1: Transmitter power classification

Power Class	Description	Notes
H	High power transmitter	Transmitter with an output power ≥ 25 W operating in the VHF band (174 MHz to 230 MHz) or UHF band (470 MHz to 694 MHz).
L	Low power transmitter	Transmitter with an output power < 25 W operating in the VHF band (174 MHz to 230 MHz) or UHF band (470 MHz to 694 MHz).

Table 1.2: Transmitter emission classification

Emission Classification	Conformance approach	Notes
0	Non critical mask	For high power transmitters, the mask defines the level of the OOB relative to the channel power (dBc). For low power transmitters the mask defines the absolute power limit of the OOB (dBm). The former approach is mandated by RRC-06 (non-critical case) [i.4] for transmitters subject to coordination.
1	Critical mask	A similar but more stringent approach based on RRC-06 (sensitive case) [i.4].
2	Non-critical ACLR	A set of ACLR limits defining permitted relative emission levels into adjacent channels.
3	Critical ACLR	A set of more stringent ACLR limits defining permitted relative emission levels into adjacent channels.

The present document covers the essential requirements of article 3.2 of Directive 2014/53/EU [i.2] under the conditions identified in annex A.

2 References

2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Void.
- [2] Void.
- [3] Void.

- [4] Void.
- [5] CENELEC EN 55016-4-2:2011/A1:2014: "Specification for radio disturbance and immunity measuring apparatus and methods. Part 4-2: Uncertainties, statistics and limit modelling - Measurement instrumentation uncertainty".
- [6] Recommendation ITU-R SM.329-12 (09/2012): "Unwanted emissions in the spurious domain".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TR 101 290 (V1.2.1) (05-2001): "Digital Video Broadcasting (DVB); Measurement guidelines for DVB systems".
- [i.2] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.3] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.4] ITU RRC-06: "Final Acts of the Regional Radiocommunication Conference for planning of the digital terrestrial broadcasting service in parts of Regions 1 and 3, in the frequency bands 174-230 MHz and 470-862 MHz", Geneva, 15 May - 16 June 2006.
- [i.5] The Paris climate agreement (COP21), December 2015.

NOTE: Available at http://ec.europa.eu/clima/policies/international/negotiations/future/index_en.htm.

- [i.6] ETSI EN 300 744 (V1.6.2) (10-2015): "Digital Video Broadcasting (DVB); Framing structure, channel coding and modulation for digital terrestrial television".
- [i.7] ETSI EN 302 755 (V1.4.1) (07-2015): "Digital Video Broadcasting (DVB); Frame structure channel coding and modulation for a second generation digital terrestrial television broadcasting system (DVB-T2)".
- [i.8] ETSI TR 100 028 (all parts) (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.9] ETSI TR 100 028-2 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in Directive 2014/53/EU [i.2] and the following apply:

adjacent channel leakage ratio: ratio of the wanted mean power of the DVB-T/T2 signal to the unwanted mean power measured in the receiver bandwidth of a given adjacent victim service

antenna port: port of an apparatus intended to be connected to an antenna using coaxial cable or coaxial line; typically the output of the channel filter or combiner

carrier power: mean power supplied to the antenna port by a transmitter with COFDM

channel bandwidth: frequency band of defined width (as a multiple of the carrier grid) for operation on adjacent channels, located symmetrically around carrier frequency in the carrier grid

composite approach: measurement method whereby the power amplifier emissions are measured separately to the frequency response of subsequent frequency selective components and the overall emissions of the transmitter are calculated by combining the two sets of measurements

co-sited: DVB-T/T2 transmitters which are located at the same physical site so minimizing the effects of adjacent channel interference

dBc: decibels relative to the *mean power P* of the emission

digital signal: discretely timed signal in which information is represented by a finite number of well-defined discrete values that its characteristic quantities may take in time

digital television: television in which all information is represented by a digital signal

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

harmonic: component of order greater than 1 of the Fourier series of a periodic quantity

high power transmitter: transmitter whose conducted output power is greater than or equal to 25 W (this category of transmitter also includes medium power category of transmitters as defined in ITU-R)

intermodulation products: unwanted frequencies resulting from intermodulation between carriers or harmonics of emission, or between any oscillations generated to produce the carrier

low power transmitter: transmitter whose conducted output power is less than 25 W

mean power: average power supplied to the antenna port by a transmitter during an interval of time sufficiently long compared with the lowest frequency encountered in the modulation taken under normal operating conditions

moding: operation of a coaxial component in unwanted waveguide modes (e.g. Transverse Electric (TE) or Transverse Magnetic (TM)) resulting in anomalous behaviour from that associated with the intended Transverse Electromagnetic (TEM) mode

necessary bandwidth: for a given class of emission, the width of the frequency band which is sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions

OOB emissions: unwanted emissions which fall at frequencies separated from the centre frequency of the wanted emission by less than or equal to 250 % of the channel bandwidth

output power: conducted power delivered by a transmitter under specified conditions of operation

receiver bandwidth: bandwidth used for victim service ACLR measurements, i.e. 7,6 MHz for 8 MHz DVB-T, 6,7 MHz for 7 MHz DVB-T, 7,8 MHz for 8 MHz DVB-T2, 6,8 MHz for 7 MHz DVB-T2 and 9 MHz for LTE

reference bandwidth: bandwidth in which the emission level is specified

spurious domain emissions: unwanted emissions at frequencies separated by more than 250 % of the channel bandwidth from the centre of the occupied spectrum

3.2 Symbols

For the purposes of the present document, the following symbols apply:

m	milli
μ	micro
n	nano
"	inch

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI EN 300 744 [i.6], ETSI EN 302 755 [i.7] and the following apply:

ACLR	Adjacent Channel Leakage Ratio
COFDM	Coded Orthogonal Frequency Division Multiplexing
CSV	Comma Separated Values
dB	Logarithmic ratio (tenths of a "Bel")
dBm	dB relative to one milliwatt
DIN	Deutsches Institut für Normung
DTT	Digital Terrestrial Television
DVB	Digital Video Broadcasting
DVB-T	Digital Video Broadcasting - Terrestrial
EFTA	European Free Trade Association
END	Equivalent Noise Degradation
EUT	Equipment Under Test
FFT	Fast Fourier Transform
GHz	GigaHertz
ITU	International Telecommunication Union
ITU-R	International Telecommunication Union - Radiocommunication
kHz	kiloHertz
MER	Modulation Error Ratio
MHz	MegaHertz
OOB	Out-Of-Band
PA	Power Amplifier
QAM	Quadrature Amplitude Modulation
RBW	Reference BandWidth
RF	Radio Frequency
RMS	Root Mean Square
RRC	Regional Radiocommunication Conference
TV	Television
UHF	Ultra High Frequency
UK	United Kingdom
VBW	Video BandWidth
VHF	Very High Frequency
W	Watt

4 Technical requirements specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the manufacturer. The equipment shall comply with all the technical requirements of the present document which are identified as applicable in annex A at all times when operating within the boundary limits of the declared operational environmental profile.

4.2 Conformance requirements

4.2.1 Introduction

The essential parameters and corresponding technical requirements aiming to meet the requirements of article 3.2 of Directive 2014/53/EU [i.2] are shown in table 4.1. To fulfil this essential parameter the compliance with all the corresponding technical requirements in table 4.1 shall be verified.

Table 4.1: Cross references

Essential parameter	Corresponding technical requirements
Conducted emissions at the antenna port	4.2.2 Spurious emissions
	4.2.3 Out-of-band emissions (OOB)

Both spurious emission limits and OOB limits are defined in terms of conducted power at the antenna port.

The boundary between spurious domain emissions and out-of-band emissions is shown in figure 4.1.




Figure 4.1: Definition of out-of-band and Spurious Domains

4.2.2 Spurious emissions

4.2.2.1 Definition

Spurious emissions are unwanted emissions at frequencies separated by more than 250 % of the channel bandwidth from the centre of the occupied spectrum. These include harmonic emissions, parasitic emissions, intermodulation products and frequency conversion products but exclude out-of-band emissions.

For the purposes of the present document spurious emissions are emissions at frequencies outside the frequency range $f_0 \pm 17,5$ MHz for 7 MHz channels, $f_0 \pm 20$ MHz for 8 MHz channels, where f_0 is the centre frequency of the channel, irrespective of the number of carriers employed.

4.2.2.2 Limits

Spurious emissions shall not exceed the values set out in table 4.2 additionally shown in figure 4.2, for the frequency range 9 kHz to 3 GHz.

In the case of a DVB-T/T2 transmitter supplied without an internal bandpass output filter, the manufacturer shall specify the characteristics of the filter necessary to fulfil the spurious emission limits defined in table 4.2. The manufacturer shall include this information in the test report.

Table 4.2: Spurious emission limits for DVB-T/T2 transmitters

Frequency range of the spurious emission	Limits of the spurious emission		Reference bandwidth
9 kHz to 470 MHz	≤ -36 dBm (250 nW) ≥ 105 dBc	for $P \leq 69$ dBm for 69 dBm $< P$	100 kHz
> 470 MHz to 694 MHz	≤ -36 dBm ≥ 75 dBc ≤ -25 dBm (3 μ W)	for $P \leq 39$ dBm for 39 dBm $< P \leq 50$ dBm for 50 dBm $< P$	100 kHz
> 694 MHz	≤ -36 dBm (250 nW) ≥ 105 dBc	for $P \leq 69$ dBm for 69 dBm $< P$	100 kHz

NOTE: P = mean power of the transmitter measured at the antenna port.




Figure 4.2: Spurious emission limits measured at the antenna port (100 kHz reference bandwidth)

4.2.2.3 Conformance test

Conformance tests described in clause 5.4.1 shall be carried out.