
Primarni nadzorni radar (PSR) - Harmonizirani standard za dostop do radijskega spektra - 1. del: Senzorji PSR za nadzor zračnega prometa (ATC), ki delujejo v frekvenčnem pasu od 1215 MHz do 1400 MHz (pas L) - 1. poddel: Radarski sistemi z reflektorskimi antenami

Primary Surveillance Radar (PSR) - Harmonised Standard for access to radio spectrum - Part 1: Air Traffic Control (ATC) PSR sensors operating in the frequency band 1 215 MHz to 1 400 MHz (L band) - Sub-part 1: radar systems using reflector antennas

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

Ta slovenski standard je istoveten z: ETSI EN 303 364-1-1 V1.0.0 (2025-03)

ICS:

03.220.50	Zračni transport	Air transport
33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications

oSIST prEN 303 364-1-1 V1.0.0:2025 **en**

Draft **ETSI EN 303 364-1-1** V1.0.0 (2025-03)



**Primary Surveillance Radar (PSR);
Harmonised Standard for access to radio spectrum;
Part 1: Air Traffic Control (ATC) PSR sensors operating in the
frequency band 1 215 MHz to 1 400 MHz (L band);
Sub-part 1: radar systems using reflector antennas**

[oSIST prEN 303 364-1-1 V1.0.0:2025](https://standards.iteh.ai/catalog/standards/sist/a48a984c-40f6-4273-8585-e15896a5e26c/osist-pren-303-364-1-1-v1-0-0-2025)

<https://standards.iteh.ai/catalog/standards/sist/a48a984c-40f6-4273-8585-e15896a5e26c/osist-pren-303-364-1-1-v1-0-0-2025>

Reference

DEN/ERM-TGAERO-31-1

Keywords

aeronautical, harmonised standard, radar, radio

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2025.
All rights reserved.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references.....	7
3 Definition of terms, symbols and abbreviations.....	8
3.1 Terms.....	8
3.2 Symbols.....	9
3.3 Abbreviations	10
4 Technical requirements specifications	11
4.1 Environmental profile.....	11
4.2 Conformance Requirements	11
4.2.1 Transmitter requirements	11
4.2.1.1 Occupied bandwidth.....	11
4.2.1.1.1 Definition.....	11
4.2.1.1.2 Limits	11
4.2.1.1.3 Conformance	11
4.2.1.2 Transmitter Peak Power	11
4.2.1.2.1 Definition.....	11
4.2.1.2.2 Limits	11
4.2.1.2.3 Conformance	11
4.2.1.3 Measured B ₄₀ bandwidth	11
4.2.1.3.1 Definition.....	11
4.2.1.3.2 Limits	12
4.2.1.3.3 Conformance	12
4.2.1.4 Unwanted emissions.....	12
4.2.1.4.1 General requirements.....	12
4.2.1.4.2 Out-of-band Emissions.....	12
4.2.1.4.3 Emissions in the spurious domain	14
4.2.1.4.4 Stand-by mode emissions	14
4.2.2 Receiver requirements	15
4.2.2.1 General requirement.....	15
4.2.2.2 System Noise Figure	15
4.2.2.2.1 Definition.....	15
4.2.2.2.2 Limits	15
4.2.2.2.3 Conformance	15
4.2.2.3 Receiver Compression Level	15
4.2.2.3.1 Definition.....	15
4.2.2.3.2 Limits	16
4.2.2.3.3 Conformance	16
4.2.2.4 Receiver selectivity	16
4.2.2.4.1 Definition.....	16
4.2.2.4.2 Limit	16
4.2.2.4.3 Conformance	17
4.2.2.5 Receiver non-linearity.....	17
4.2.2.5.1 Definition.....	17
4.2.2.5.2 Limits	18
4.2.2.5.3 Conformance	18
5 Testing for compliance with technical requirements.....	18
5.1 Environmental conditions for testing	18
5.1.1 General requirements.....	18
5.1.2 Test conditions.....	18

5.1.2.1	Thermal Balance	18
5.1.2.2	Environmental Test Conditions.....	18
5.1.2.2.1	Temperature and humidity.....	18
5.1.2.2.2	Power supply (AC only)	19
5.2	Radio test suites.....	19
5.2.1	Transmitter test specification.....	19
5.2.1.1	Occupied bandwidth.....	19
5.2.1.2	Transmitter Peak Power	19
5.2.1.3	Measured B ₄₀ bandwidth.....	20
5.2.1.4	Unwanted emissions.....	20
5.2.1.4.1	Out-of-band Emissions.....	20
5.2.1.4.2	Emissions in the spurious domain	21
5.2.1.4.3	Stand-by mode emissions	21
5.2.1.5	Pulse Length.....	21
5.2.1.6	Pulse Rise Time	22
5.2.1.7	Pulse Fall Time	22
5.2.2	Receiver test specification	23
5.2.2.1	System Noise Figure	23
5.2.2.2	Receiver Compression Level	23
5.2.2.2.1	General setup	23
5.2.2.2.2	Test Signal.....	23
5.2.2.2.3	Measurement Procedure	23
5.2.2.3	Receiver selectivity	24
5.2.2.3.1	General setup.....	24
5.2.2.3.2	Disturbing Test Signals	24
5.2.2.3.3	Measurement Procedure.....	24
5.2.2.4	Receiver non-linearity.....	24
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	26
Annex B (normative):	Calculation of the B₄₀ bandwidth.....	28
Annex C (normative):	Occupied bandwidth and B₄₀ measurement set-up	30
Annex D (normative):	Transmitter Peak Power measurement set-up.....	31
Annex E (normative):	Out-of-Band Emissions measurement set-up	32
Annex F (normative):	Spurious Emissions and Stand-By Mode emissions measurement set-up	33
Annex G (normative):	Pulse Length, Pulse Rise Time and Pulse Fall time measurement set-up	35
Annex H (normative):	System Noise Figure measurement set-up	36
Annex I (normative):	Compression level measurement set-up.....	38
Annex J (normative):	Selectivity measurement set-up	39
Annex K (normative):	Receiver non-linearity measurement set-up	40
Annex L (informative):	Maximum Measurement Uncertainty.....	41
Annex M (informative):	Checklist	42
Annex N (informative):	Bibliography.....	44
History		45

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](https://standards.itec.ai/ETSI-IPR-online-database).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI Standardisation Request deliverable Approval Procedure (SRdAP).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.2] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in Table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 1, sub-part 1, of a multi-part deliverable covering Primary Surveillance Radar (PSR), as identified below:

Part 1: "Air Traffic Control (ATC) PSR sensors operating in the frequency band 1 215 MHz to 1 400 MHz (L band)";

Sub-part 1: "radar systems using reflector antennas";

Sub-part 2: "radar systems using phased array antennas".

Part 2: "Air Traffic Control (ATC) PSR sensors operating in the frequency band 2 700 MHz to 3 100 MHz (S band)";

Part 3: "Air Traffic Control (ATC) PSR sensors operating in the frequency band 8 500 MHz to 10 000 MHz (X band)".

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[oSIST prEN 303 364-1-1 V1.0.0:2025](#)

<https://standards.iteh.ai/catalog/standards/sist/a48a984c-40f6-4273-8585-e15896a5e26c/osist-pren-303-364-1-1-v1-0-0-2025>

1 Scope

The present document specifies technical characteristics and methods of measurements for ground based monostatic ATC solid state primary surveillance radars that are intended to work with a waveguide-based rotating passive antenna and have the following characteristics:

- operation in the 1 215 MHz to 1 400 MHz frequency range;
- transmitter output peak power up to 100 kW;
- the transceiver output uses an RF circulator;
- a piece of waveguide of at least 66 cm is integral to the transceiver.

NOTE 1: Phased array ATC primary surveillance radars are not covered by the present document.

NOTE 2: 66 cm equals 2 times the cut-off wavelength of a WR650/WG6/R14 waveguide which is typically used in the 1 215 MHz to 1 400 MHz frequency range.

NOTE 3: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.1] is given in Annex A.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found in the [ETSI docbox](#).

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] [ETSI EN 300 019-1-3 \(V2.4.1\) \(04-2014\)](#): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-3: Classification of environmental conditions; Stationary use at weather protected locations".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] [Directive 2014/53/EU](#) of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.

- [i.2] [Commission Implementing Decision C \(2015\) 5376 final of 4.8.2015](#) on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.3] ITU Radio Regulations (2024).
- [i.4] Recommendation ITU-R SM.1541-7 (09/2024): "Unwanted emissions in the out-of-band domain".
- [i.5] ETSI EG 203 336 (V1.2.1): "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.6] IEC 60153-2 (2016): "Hollow metallic waveguides - Part 2: Relevant specifications for ordinary rectangular waveguides".
- [i.7] Recommendation ITU-R SM.331-4 (07/78): "Noise and sensitivity of receivers".
- [i.8] Recommendation ITU-R SM.332-4 (07/78): "Selectivity of receivers".
- [i.9] [ECC Recommendation \(02\)05 \(October 2012\)](#): "Unwanted emissions".
- [i.10] [ERC Recommendation 74-01 \(May 2022\)](#): "Unwanted emissions in the spurious domain".
- [i.11] Recommendation ITU-R M.1177-4 (04/2011): "Techniques for measurement of unwanted emissions of radar systems".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

active state: state which produces the authorized emission

allocated frequency band: frequency range that regionally or nationally is allocated to one or more radio services on a primary or secondary basis

chirp bandwidth: total frequency shift during the pulse generation of an FM/chirped radar

EXAMPLE: If the Frequency Modulation is from 1 250 MHz to 1 280 MHz, the chirp bandwidth is 30 MHz.

declared frequency band: band or bands within which the equipment under test is declared to operate

NOTE: The declared frequency band for a given region or country is always contained within the allocated frequency band.

dummy load: device connected to a waveguide or coaxial cable and matched to their impedance (typically 50 Ω) to absorb the RF energy propagating inside

Equipment Under Test (EUT): device that is the subject of the specific test investigation being described

idle/stand-by state: state where the transmitter is available for traffic, but is not in the active state

matched filter: receiver filter that matches the transmitted radar waveform, i.e. this is the filter that maximizes the signal-to-noise ratio of the received pulse

necessary bandwidth: width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions for a given class of emission

NOTE 1: This definition is taken from ITU Radio Regulation [i.3].

NOTE 2: For Primary radars the necessary bandwidth B_N is considered to be B_{-20} (20 dB bandwidth) as defined in Recommendation ITU-R SM.1541-7 [i.4].

occupied bandwidth: width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage $\beta/2$ of the total mean power of a given emission

NOTE 1: Unless otherwise specified in an ITU-R Recommendation for the appropriate class of emission, the value of $\beta/2$ should be taken as 0,5 %.

NOTE 2: This definition is taken from ITU Radio Regulations [i.3], chapter I, 1.153.

operating frequencies: frequencies on which the radar is tuned to operate

operating mode: predefined configuration for a given service accessible to the operator of the radar system

NOTE 1: Several operating modes may be available.

NOTE 2: Changing operating mode might affect the radio characteristics of the radar system.

Peak Envelope Power (PEP): average power supplied to the antenna transmission line by a transmitter during one radio frequency cycle at the crest of the modulation envelope taken under normal operating conditions

NOTE: This definition is taken from ITU Radio Regulations [i.3], chapter I, 1.157.

product configuration: hardware variant of the same typology of system under test (e.g. different power outputs, magnetrons)

pulse fall time: time taken for the trailing edge of the pulse to decrease from 90 % to 10 % of the maximum amplitude (voltage)

pulse length: time between the 50 % amplitude (voltage) points

pulse rise time: time taken for the leading edge of the pulse to increase from 10 % to 90 % of the maximum amplitude (voltage)

radar equipment: equipment and its associated primary navigational display intended for the navigation of aircraft in airways

receiver output: output of the digital matched filter function

system coupler: directional waveguide coupler with forward and reverse port or only a forward port

NOTE: The system coupler is inserted in the waveguide run between the circulator and the antenna but not directly located behind the antenna. Usually it is located very close behind the circulator.

unwanted emissions: consist of spurious emissions and out-of-band emissions

NOTE: This definition is taken from ITU Radio Regulation [i.3].

3.2 Symbols

For the purposes of the present document, the following symbols apply:

B_{-20}	-20 dB bandwidth below PEP of the spectrum of the transmitted waveform
B_{-40}	-40 dB bandwidth below PEP of the spectrum of the transmitted waveform
B_C	Chirp bandwidth
B_m	Measurement bandwidth
B_N	Necessary bandwidth
B_{ref}	Reference bandwidth
B_{res}	3 dB resolution bandwidth of transceiver
dB/dec	dB per decade
dBm	Power ratio expressed in decibels (dB) with reference to 1 milliwatt
$dBpp$	Power ratio expressed in decibels (dB) with reference to peak power
f_o	Operating Frequency
f_{co}	Cut-off Frequency
f_{IF}	Intermediate Frequency
f_{RF}	Receiver operating Frequency
f_{image}	Image Frequency

k	Boltzmann's constant
f_{LO}	Local Oscillator Frequency
P_{meas}	Spectrum Peak Power
P_t	Pulse power of transmission
RF	Radio Frequency
S/N	Signal-to-Noise ratio
t	Pulse length
T_C	Pulse length (of individual chirp waveforms) in seconds
t_r	Pulse rise time
t_f	Pulse fall time
T_0	Temperature in Kelvin
$\beta/2$	Percentage of the total mean power of a given emission
λ	Wavelength

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AC	Alternating Current
ATC	Air Traffic Control
COF	Cut-Off Frequency
CW	Continuous Wave
DC	Direct Coupling
EIA	Electronic Industries Alliance
EN	European Norm
ENR	Excess Noise Ratio
EUT	Equipment Under Test
FM	Frequency Modulation
Hz	Hertz
IEC	International Electrotechnical Commission
IF	Intermediate Frequency
IMD	InterModulation Distortion
ITU-R	International Telecommunications Union - Radiocommunications
kHz	kiloHertz
kW	kiloWatt
NA	Not Available
NF	Noise Factor
OoB	Out-of-Band
PEP	Peak Envelope Power
ppm	parts per million
PSR	Primary Surveillance Radar
RCL	Receiver Compression level
RF	Radio Frequency
SM	Spectrum Management
STD	Standard Deviation
SWT	Sweep Time