



SLOVENSKI STANDARD
oSIST prEN 301 908-14 V13.0.1:2018
01-februar-2018

**Celična omrežja IMT - Harmonizirani standard za dostop do radijskega spektra -
14. del: Bazne postaje za razviti prizemni radijski dostop za UMTS (E-UTRA)**

IMT cellular networks - Harmonised Standard for access to radio spectrum - Part 14:
Evolved Universal Terrestrial Radio Access (E-UTRA) Base Stations (BS)

Ta slovenski standard je istoveten z: ETSI EN 301 908-14 V13.0.1 (2017-12)

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.070.99	Druge mobilne storitve	Other mobile services

oSIST prEN 301 908-14 V13.0.1:2018 en

Draft **ETSI EN 301 908-14** V13.0.1 (2017-12)



**IMT cellular networks;
Harmonised Standard for access to radio spectrum;
Part 14: Evolved Universal Terrestrial Radio Access (E-UTRA)
Base Stations (BS)**

Reference

REN/MSG-TFES-13-14

Keywords

3G, 3GPP, cellular, digital, E-UTRA, IMT, IMT-2000, LTE, mobile, radio, regulation, UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	8
Introduction	8
1 Scope	9
2 References	10
2.1 Normative references	10
2.2 Informative references.....	11
3 Definitions, symbols and abbreviations	11
3.1 Definitions.....	11
3.2 Symbols.....	18
3.3 Abbreviations	19
4 Technical requirements specifications	20
4.1 Environmental profile.....	20
4.2 Conformance requirements	21
4.2.1 Introduction.....	21
4.2.2 Operating band unwanted emissions	27
4.2.2.1 Definition	27
4.2.2.2 Limits	28
4.2.2.2.0 General	28
4.2.2.2.1 Limits for Wide Area BS (bands 1, 3, 8, 32, 33, 34, or 65).....	29
4.2.2.2.2 Limits for Wide Area BS (bands 7, 22, 38, 40, 42, 43 and 69)	31
4.2.2.2.3 Limits for Wide Area BS (bands 20, 28, 67 and 68)	34
4.2.2.2.4 Limits for Local Area BS	35
4.2.2.2.5 Limits for Home BS	37
4.2.2.2.6 Limits for protection of DTT	39
4.2.2.2.7 Limits for protection of adjacent band services.....	40
4.2.2.2.8 Limits for Medium Range BS	40
4.2.2.2.9 Limits for operation in band 32	44
4.2.2.2.10 Minimum requirements for Local Area and Medium Range BS in band 46	46
4.2.2.2.11 Minimum requirements for stand-alone NB-IoT Wide Area BS.....	47
4.2.2.3 Conformance.....	47
4.2.3 Adjacent Channel Leakage Power Ratio (ACLR)	48
4.2.3.1 Definition	48
4.2.3.2 Void.....	48
4.2.3.3 Void.....	48
4.2.3.4 Limits	48
4.2.3.4.1 ACLR Limits	48
4.2.3.4.2 Cumulative ACLR test requirement in non-contiguous spectrum limits.....	51
4.2.3.5 Conformance.....	52
4.2.4 Transmitter spurious emissions.....	52
4.2.4.1 Definition	52
4.2.4.2 Limits	53
4.2.4.2.1 Spurious emissions	53
4.2.4.2.2 Co-existence with other systems	53
4.2.4.2.3 Protection of the BS receiver of own or different BS	55
4.2.4.2.4 Co-existence with Home BS operating in other bands	56
4.2.4.3 Conformance.....	57
4.2.5 Base Station maximum output power	58
4.2.5.1 Definition	58
4.2.5.2 Limit.....	58
4.2.5.3 Conformance.....	58
4.2.6 Transmitter intermodulation	58
4.2.6.1 Definition	58

4.2.6.2	Limit.....	59
4.2.6.3	Conformance.....	59
4.2.7	Receiver spurious emissions.....	59
4.2.7.1	Definition.....	59
4.2.7.2	Limit.....	60
4.2.7.3	Conformance.....	60
4.2.8	Blocking characteristics.....	60
4.2.8.1	Definition.....	60
4.2.8.2	Limit.....	61
4.2.8.3	Conformance.....	66
4.2.9	Receiver intermodulation characteristics.....	66
4.2.9.1	Definition.....	66
4.2.9.2	Limit.....	66
4.2.9.3	Conformance.....	72
4.2.10	Adjacent Channel Selectivity (ACS) and narrow-band blocking.....	73
4.2.10.1	Definition.....	73
4.2.10.2	Limit.....	73
4.2.10.3	Conformance.....	79
4.2.11	Home BS output power for adjacent UTRA channel protection.....	79
4.2.11.1	Definition.....	79
4.2.11.2	Limit.....	79
4.2.11.3	Conformance.....	80
4.2.12	Home BS output power for adjacent E-UTRA channel protection.....	80
4.2.12.1	Definition and applicability.....	80
4.2.12.2	Limit.....	80
4.2.12.3	Conformance.....	81
4.2.13	Home BS output power for co-channel E-UTRA protection.....	81
4.2.13.1	Definition and applicability.....	81
4.2.13.2	Limit.....	82
4.2.13.3	Conformance.....	83
4.2.14	Reference sensitivity level.....	83
4.2.14.1	Definition.....	83
4.2.14.2	Limits.....	83
4.2.14.3	Conformance.....	85
4.2.15	Downlink channel access procedure (Listen before talk - LBT).....	85
4.2.15.1	General.....	85
4.2.15.2	Limits.....	85
4.2.15.3	Conformance.....	85
4.2.16	Dynamic frequency selection (DFS).....	85
4.2.16.1	General.....	85
4.2.16.2	Limits.....	85
4.2.16.3	Conformance.....	85
5	Testing for compliance with technical requirements.....	85
5.1	Environmental conditions for testing.....	85
5.2	Interpretation of the measurement results.....	86
5.3	Essential radio test suites.....	87
5.3.0	Introduction.....	87
5.3.1	Operating band unwanted emissions.....	88
5.3.1.0	General.....	88
5.3.1.1	Initial conditions.....	88
5.3.1.2	Procedure.....	88
5.3.1.3	Test requirement.....	89
5.3.2	Adjacent Channel Leakage power Ratio (ACLR).....	89
5.3.2.1	Initial conditions.....	89
5.3.2.2	Procedure.....	90
5.3.2.3	Test requirement.....	90
5.3.3	Transmitter spurious emissions.....	91
5.3.3.0	General.....	91
5.3.3.1	Initial conditions.....	91
5.3.3.2	Procedure.....	91
5.3.3.3	Test requirements.....	92

5.3.4	Base Station maximum output power	92
5.3.4.0	General	92
5.3.4.1	Initial conditions	92
5.3.4.2	Procedure	93
5.3.4.3	Test requirement	93
5.3.5	Transmitter intermodulation	93
5.3.5.0	General	93
5.3.5.1	Initial conditions	93
5.3.5.2	Procedures	94
5.3.5.3	Test requirement	95
5.3.6	Receiver spurious emissions	95
5.3.6.0	General	95
5.3.6.1	Initial conditions	95
5.3.6.2	Procedure	96
5.3.6.3	Test requirement	96
5.3.7	Blocking characteristics	96
5.3.7.0	General	96
5.3.7.1	Initial conditions	96
5.3.7.2	Procedure	97
5.3.7.3	Test requirement	99
5.3.8	Receiver intermodulation characteristics	99
5.3.8.0	General	99
5.3.8.1	Initial conditions	99
5.3.8.2	Procedures	99
5.3.8.3	Test requirement	101
5.3.9	Adjacent Channel Selectivity (ACS) and narrow-band blocking	101
5.3.9.0	General	101
5.3.9.1	Initial conditions	101
5.3.9.2	Procedure for Adjacent Channel Selectivity	101
5.3.9.3	Procedure for narrow-band blocking	102
5.3.9.4	Test requirement	104
5.3.10	Home BS output power for adjacent UTRA channel protection	104
5.3.10.1	Initial conditions	104
5.3.10.2	Procedure	104
5.3.10.3	Test requirement	105
5.3.11	Home BS output power for adjacent E-UTRA channel protection	105
5.3.11.1	Initial conditions	105
5.3.11.2	Procedure	105
5.3.11.3	Test requirement	106
5.3.12	Home BS output power for co-channel E-UTRA protection	106
5.3.12.1	Initial conditions	106
5.3.12.2	Procedure	106
5.3.12.3	Test requirement	107
5.3.13	Reference sensitivity level	107
5.3.13.0	General	107
5.3.13.1	Initial conditions	107
5.3.13.2	Procedure	107
5.3.13.3	Test requirement	108
5.3.14	Downlink channel access procedure	108
5.3.14.1	General	108
5.3.14.2	Initial conditions	108
5.3.14.3	Procedure	108
5.3.14.4	Test requirements	109
5.3.15	Dynamic frequency selection (DFS)	109
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	110
Annex B (normative):	Base Station configurations	112
B.1	Reception with multiple receiver antenna connectors, receiver diversity	112
B.2	Duplexers	112

B.3	Power supply options	112
B.4	Ancillary RF amplifiers.....	113
B.5	BS using antenna arrays	113
B.5.0	General	113
B.5.1	Receiver tests.....	114
B.5.2	Transmitter tests	114
B.6	Transmission with multiple transmitter antenna connectors	115
B.7	BS with integrated Iuant BS modem.....	115
Annex C (informative):	Environmental profile specification	116
Annex D (informative):	Bibliography.....	117
Annex E (informative):	Change history	118
History		119