



**IMT cellular networks;
Harmonised Standard for access to radio spectrum;
Part 14: Evolved Universal Terrestrial Radio Access (E-UTRA)
Base Stations (BS)**

iTeh Standard Review
Full Standard
https://standards.iteh.ai/catalog/etsi-301-908-14-1-1-2019-09
4989-beeb-e4d6050aacd2/etsi-en-301-908-14-1-1-2019-09

Reference

REN/MSG-TFES-13-14

Keywords3G, 3GPP, cellular, digital, E-UTRA, IMT,
IMT-2000, LTE, mobile, radio, regulation, UMTS**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and LTE™ are trademarks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.
GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	8
Introduction	8
1 Scope	9
2 References	10
2.1 Normative references	10
2.2 Informative references.....	11
3 Definitions, symbols and abbreviations	11
3.1 Definitions	11
3.2 Symbols	18
3.3 Abbreviations	19
4 Technical requirements specifications	20
4.1 Environmental profile.....	20
4.2 Conformance requirements	21
4.2.1 Introduction.....	21
4.2.2 Operating band unwanted emissions	27
4.2.2.1 Definition	27
4.2.2.2 Limits	28
4.2.2.2.0 General	28
4.2.2.2.1 Limits for Wide Area BS (bands 1, 3, 8, 32, 33, 34, or 65).....	29
4.2.2.2.2 Limits for Wide Area BS (bands 7, 22, 38, 40, 42, 43 and 69)	31
4.2.2.2.3 Limits for Wide Area BS (bands 20, 28, 67 and 68)	34
4.2.2.2.4 Limits for Local Area BS	35
4.2.2.2.5 Limits for Home BS	37
4.2.2.2.6 Limits for protection of DTT	39
4.2.2.2.7 Limits for protection of adjacent band services.....	40
4.2.2.2.8 Limits for Medium Range BS	40
4.2.2.2.9 Limits for operation in band 32	44
4.2.2.2.10 Minimum requirements for Local Area and Medium Range BS in band 46	46
4.2.2.2.11 Minimum requirements for stand-alone NB-IoT Wide Area BS.....	47
4.2.2.3 Conformance	47
4.2.3 Adjacent Channel Leakage Power Ratio (ACLR)	48
4.2.3.1 Definition	48
4.2.3.2 Void.....	48
4.2.3.3 Void.....	48
4.2.3.4 Limits	48
4.2.3.4.1 ACLR Limits	48
4.2.3.4.2 Cumulative ACLR test requirement in non-contiguous spectrum limits.....	51
4.2.3.5 Conformance	52
4.2.4 Transmitter spurious emissions.....	52
4.2.4.1 Definition	52
4.2.4.2 Limits	53
4.2.4.2.1 Spurious emissions	53
4.2.4.2.2 Co-existence with other systems	53
4.2.4.2.3 Protection of the BS receiver of own or different BS	55
4.2.4.2.4 Co-existence with Home BS operating in other bands	56
4.2.4.3 Conformance	57
4.2.5 Base Station maximum output power	58
4.2.5.1 Definition	58
4.2.5.2 Limit.....	58
4.2.5.3 Conformance	58
4.2.6 Transmitter intermodulation	58
4.2.6.1 Definition	58

4.2.6.2	Limit.....	59
4.2.6.3	Conformance	59
4.2.7	Receiver spurious emissions	59
4.2.7.1	Definition	59
4.2.7.2	Limit.....	60
4.2.7.3	Conformance	60
4.2.8	Blocking characteristics	60
4.2.8.1	Definition	60
4.2.8.2	Limit.....	61
4.2.8.3	Conformance	66
4.2.9	Receiver intermodulation characteristics	66
4.2.9.1	Definition	66
4.2.9.2	Limit.....	66
4.2.9.3	Conformance	72
4.2.10	Adjacent Channel Selectivity (ACS) and narrow-band blocking	73
4.2.10.1	Definition	73
4.2.10.2	Limit.....	73
4.2.10.3	Conformance	79
4.2.11	Home BS output power for adjacent UTRA channel protection.....	79
4.2.11.1	Definition	79
4.2.11.2	Limit.....	79
4.2.11.3	Conformance	80
4.2.12	Home BS output power for adjacent E-UTRA channel protection.....	80
4.2.12.1	Definition and applicability.....	80
4.2.12.2	Limit.....	80
4.2.12.3	Conformance	81
4.2.13	Home BS output power for co-channel E-UTRA protection.....	81
4.2.13.1	Definition and applicability.....	81
4.2.13.2	Limit.....	82
4.2.13.3	Conformance	83
4.2.14	Reference sensitivity level	83
4.2.14.1	Definition	83
4.2.14.2	Limits	83
4.2.14.3	Conformance	85
4.2.15	Downlink channel access procedure (Listen before talk - LBT).....	85
4.2.15.1	General	85
4.2.15.2	Limits	85
4.2.15.3	Conformance	85
4.2.16	Dynamic frequency selection (DFS).....	85
4.2.16.1	General	85
4.2.16.2	Limits	85
4.2.16.3	Conformance	85
5	Testing for compliance with technical requirements.....	85
5.1	Environmental conditions for testing	85
5.2	Interpretation of the measurement results	86
5.3	Essential radio test suites.....	87
5.3.0	Introduction.....	87
5.3.1	Operating band unwanted emissions	88
5.3.1.0	General	88
5.3.1.1	Initial conditions	88
5.3.1.2	Procedure	88
5.3.1.3	Test requirement	89
5.3.2	Adjacent Channel Leakage power Ratio (ACLR)	89
5.3.2.1	Initial conditions	89
5.3.2.2	Procedure	90
5.3.2.3	Test requirement	90
5.3.3	Transmitter spurious emissions.....	91
5.3.3.0	General	91
5.3.3.1	Initial conditions	91
5.3.3.2	Procedure	91
5.3.3.3	Test requirements	92

5.3.4	Base Station maximum output power	92
5.3.4.0	General	92
5.3.4.1	Initial conditions	92
5.3.4.2	Procedure	93
5.3.4.3	Test requirement	93
5.3.5	Transmitter intermodulation	93
5.3.5.0	General	93
5.3.5.1	Initial conditions	93
5.3.5.2	Procedures	94
5.3.5.3	Test requirement	95
5.3.6	Receiver spurious emissions	95
5.3.6.0	General	95
5.3.6.1	Initial conditions	95
5.3.6.2	Procedure	96
5.3.6.3	Test requirement	96
5.3.7	Blocking characteristics	96
5.3.7.0	General	96
5.3.7.1	Initial conditions	96
5.3.7.2	Procedure	97
5.3.7.3	Test requirement	99
5.3.8	Receiver intermodulation characteristics	99
5.3.8.0	General	99
5.3.8.1	Initial conditions	99
5.3.8.2	Procedures	99
5.3.8.3	Test requirement	101
5.3.9	Adjacent Channel Selectivity (ACS) and narrow-band blocking	101
5.3.9.0	General	101
5.3.9.1	Initial conditions	101
5.3.9.2	Procedure for Adjacent Channel Selectivity	101
5.3.9.3	Procedure for narrow-band blocking	102
5.3.9.4	Test requirement	104
5.3.10	Home BS output power for adjacent UTRA channel protection	104
5.3.10.1	Initial conditions	104
5.3.10.2	Procedure	104
5.3.10.3	Test requirement	105
5.3.11	Home BS output power for adjacent E-UTRA channel protection	105
5.3.11.1	Initial conditions	105
5.3.11.2	Procedure	105
5.3.11.3	Test requirement	106
5.3.12	Home BS output power for co-channel E-UTRA protection	106
5.3.12.1	Initial conditions	106
5.3.12.2	Procedure	106
5.3.12.3	Test requirement	107
5.3.13	Reference sensitivity level	107
5.3.13.0	General	107
5.3.13.1	Initial conditions	107
5.3.13.2	Procedure	107
5.3.13.3	Test requirement	108
5.3.14	Downlink channel access procedure	108
5.3.14.1	General	108
5.3.14.2	Initial conditions	108
5.3.14.3	Procedure	108
5.3.14.4	Test requirements	109
5.3.15	Dynamic frequency selection (DFS)	109

Annex A (informative): Relationship between the present document and the essential requirements of Directive 2014/53/EU.....110

Annex B (normative): Base Station configurations.....112

B.1	Reception with multiple receiver antenna connectors, receiver diversity	112
B.2	Duplexers	112

B.3	Power supply options	112
B.4	Ancillary RF amplifiers.....	113
B.5	BS using antenna arrays	113
B.5.0	General	113
B.5.1	Receiver tests.....	114
B.5.2	Transmitter tests	114
B.6	Transmission with multiple transmitter antenna connectors	115
B.7	BS with integrated Iuant BS modem.....	115
Annex C (informative):	Environmental profile specification	116
Annex D (informative):	Bibliography	117
Annex E (informative):	Change history	118
History	119	

iTeh STANDARD PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/5c839685-5554-4989-beeb-e4d6050aacd2/etsi-en-301-908-14-v13.1.1-2019-09>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

For non EU countries the present document may be used for regulatory (Type Approval) purposes.

The present document has been prepared under Commission's standardisation request C(2015) 5376 [i.1] final to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A-1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 14 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.7].

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document is part of a set of standards developed by ETSI that are designed to fit in a modular structure to cover radio equipment within the scope of the Radio Equipment Directive [i.2]. The present document is produced following the guidance in ETSI EG 203 336 [i.3] as applicable.

iTeh STANDARD PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/5c839685-5554-4989-beeb-e4d6050aacd2/etsi-en-301-908-14-v13.1.1-2019-09>

1 Scope

The present document applies to the following radio equipment types:

- 1) Base Station for Evolved Universal Terrestrial Radio Access (E-UTRA).
- 2) Base Station for Evolved Universal Terrestrial Radio Access (E-UTRA) with NB-IoT.
- 3) Base Station for NB-IoT standalone.

This radio equipment type is capable of operating in all or any part of the operating bands given in table 1-1. Unless stated otherwise, requirements specified for the TDD duplex mode apply for downlink and uplink operations in Frame Structure Type 2. NB-IoT is designed to operate in the E-UTRA operating bands 1, 3, 8, 20, 28 which are defined in table 1-1.

Table 1-1: E-UTRA Base Station operating bands

E-UTRA band	Direction of transmission	E-UTRA Base Station operating bands
1	Transmit	2 110 MHz to 2 170 MHz
	Receive	1 920 MHz to 1 980 MHz
3	Transmit	1 805 MHz to 1 880 MHz
	Receive	1 710 MHz to 1 785 MHz
7	Transmit	2 620 MHz to 2 690 MHz
	Receive	2 500 MHz to 2 570 MHz
8	Transmit	925 MHz to 960 MHz
	Receive	880 MHz to 915 MHz
20	Transmit	791 MHz to 821 MHz
	Receive	832 MHz to 862 MHz
22	Transmit	3 510 MHz to 3 590 MHz
	Receive	3 410 MHz to 3 490 MHz
28	Transmit	758 MHz to 803 MHz
	Receive	703 MHz to 748 MHz
(note 1, note 2)	Transmit	1 452 MHz to 1 496 MHz
	Receive	N/A
33	Transmit and Receive	1 900 MHz to 1 920 MHz
34	Transmit and Receive	2 010 MHz to 2 025 MHz
38	Transmit and Receive	2 570 MHz to 2 620 MHz
40	Transmit and Receive	2 300 MHz to 2 400 MHz
42	Transmit and Receive	3 400 MHz to 3 600 MHz
43	Transmit and Receive	3 600 MHz to 3 800 MHz
46 (note 3, note 4)	Transmit and Receive	5 150 MHz to 5 925 MHz
65	Transmit	2 110 MHz to 2 200 MHz
	Receive	1 920 MHz to 2 010 MHz
67	Transmit	738 MHz to 758 MHz
	Receive	N/A
68	Transmit	753 MHz to 783 MHz
	Receive	698 MHz to 728 MHz
69 (note 1)	Transmit	2 570 MHz to 2 620 MHz
	Receive	N/A

NOTE 1: Restricted to E-UTRA operation when carrier aggregation is configured. The downlink operating band is paired with the uplink operating band (external) of the carrier aggregation configuration that is supporting the configured Pcell.

NOTE 2: Radio equipment in band 32 is only allowed to operate between 1 452 MHz and 1 492 MHz

NOTE 3: This band is an unlicensed band restricted to licensed-assisted operation using Frame Structure Type 3. Radio equipment in band 46 is only allowed to operate between 5 150 MHz and 5 725 MHz.

NOTE 4: In this version of the present document, restricted to E-UTRA DL operation when carrier aggregation is configured. Band 46 is divided into three sub-bands as in table 1-2.

Table 1-2: Sub-bands for band 46

E-UTRA Operating Band	Uplink (UL) operating band BS receive UE transmit	Downlink (DL) operating band BS transmit UE receive
	$F_{UL_low} - F_{UL_high}$	$F_{DL_low} - F_{DL_high}$
46a	5 150 MHz - 5 250 MHz	5 150 MHz - 5 250 MHz
46b	5 250 MHz - 5 350 MHz	5 250 MHz - 5 350 MHz
46c	5 470 MHz - 5 725 MHz	5 470 MHz - 5 725 MHz

The present document covers requirements for E-UTRA Base Stations for 3GPP Release 8, 9, 10, 11, 12 and 13. This includes the requirements for E-UTRA Base Station operating bands and E-UTRA CA operating bands from 3GPP Release 14.

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.2] is given annex A.

2 References

2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 136 141 (V13.9.0) (10-2017): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) conformance testing (3GPP TS 36.141 version 13.9.0 Release 13)".
- [2] ETSI TS 125 104 (V13.4.0) (04-2017): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) radio transmission and reception (FDD) (3GPP TS 25.104 version 13.4.0 Release 13)".
- [3] ETSI TS 125 105 (V13.2.0) (07-2017): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) radio transmission and reception (TDD) (3GPP TS 25.105 version 13.2.0 Release 13)".
- [4] ETSI TS 136 104 (V13.8.0) (07-2017): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception (3GPP TS 36.104 version 13.8.0 Release 13)".
- [5] ETSI TS 125 141 (V13.3.0) (08-2016): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) conformance testing (FDD) (3GPP TS 25.141 version 13.3.0 Release 13)".
- [6] ETSI TS 136 211 (V13.6.0) (08-2017): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Physical channels and modulation (3GPP TS 36.211 version 13.6.0 Release 13)".
- [7] ETSI EN 301 908-18 (V13.0.1) (11-2017): "IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 18: E-UTRA, UTRA and GSM/EDGE Multi-Standard Radio (MSR) Base Station (BS)".
- [8] ETSI EN 301 893 (V2.1.1) (05-2017): "5 GHz RLAN; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU".

- [9] ETSI TS 136 213 (V13.6.0) (08-2017): "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer procedures (3GPP TS 36.213 version 13.6.0 Release 13)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Commission implementing decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.2] Directive 2014/53/EU of the European parliament and of the council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.3] ETSI EG 203 336 (V1.1.1) (08-2015): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.4] Recommendation ITU-R SM.329-12 (09-2012): "Unwanted emissions in the spurious domain".
- [i.5] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.6] Void.
- [i.7] ETSI EN 301 908-1: "IMT cellular networks; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU; Part 1: Introduction and common requirements".
- [i.8] Void.
- [i.9] ETSI TS 136 214 (V13.4.0) (01-2017): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer; Measurements (3GPP TS 36.214 version 13.4.0 Release 13)".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

aggregated channel bandwidth: RF bandwidth in which a Base Station transmits and/or receives multiple contiguously aggregated carriers

NOTE: The Aggregated Channel Bandwidth is measured in MHz.

base station class: Wide Area Base Station, Medium Range Base Station, Local Area Base Station or Home Base Station, as declared by the manufacturer

base station RF bandwidth: RF bandwidth in which a Base Station transmits and/or receives single or multiple carrier(s) within a supported operating band

NOTE: In single carrier operation, the Base Station RF Bandwidth is equal to the channel bandwidth.

base station RF bandwidth edge: frequency of one of the edges of the Base Station RF Bandwidth

NOTE: Base Station RF Bandwidth edges are separated by the Base Station RF Bandwidth

carrier: modulated waveform conveying the E-UTRA or UTRA (WCDMA) physical channels

carrier aggregation: aggregation of two or more component carriers in order to support wider transmission bandwidths

carrier aggregation band: set of one or more operating bands across which multiple carriers are aggregated with a specific set of technical requirements

NOTE: Carrier aggregation band(s) for an E-UTRA BS is declared by the manufacturer according to the designations in tables 4.2.1-3 to 4.2.1-4.

channel bandwidth: RF bandwidth supporting a single E-UTRA RF carrier with the transmission bandwidth configured in the uplink or downlink of a cell

NOTE: The channel bandwidth is measured in MHz and is used as a reference for transmitter and receiver RF requirements.

channel edge: lowest or highest frequency of the E-UTRA carrier

NOTE: Channel edges are separated by the channel bandwidth.

clear channel assessment: mechanism used by an equipment to identify other transmissions in the channel

contiguous carriers: two or more carriers configured in a spectrum block where there are no RF requirements based on co-existence for un-coordinated operation within the spectrum block

contiguous spectrum: spectrum consisting of a contiguous block of spectrum with no sub-block gaps

downlink operating band: part of the operating band designated for downlink (BS transmit)

home base station: Base Stations characterized by requirements derived from femtocell scenarios

inter RF bandwidth gap: frequency gap between two consecutive Base Station RF Bandwidths that are placed within two supported operating bands

inter-band carrier aggregation: carrier aggregation of component carriers in different operating bands

NOTE: Carriers aggregated in each band can be contiguous or non-contiguous.

intra-band contiguous carrier aggregation: contiguous carriers aggregated in the same operating band

inter-band gap: frequency gap between two supported consecutive operating bands

intra-band non-contiguous carrier aggregation: non-contiguous carriers aggregated in the same operating band

Listen Before Talk (LBT): mechanism by which an equipment applies clear channel assessment (CCA) before using the channel

local area base station: Base Stations characterized by requirements derived from picocell scenarios with a BS to UE minimum coupling loss equal to 45 dB

lower sub-block edge: frequency at the lower edge of one sub-block

NOTE: It is used as a frequency reference point for both transmitter and receiver requirements.

maximum Base Station RF Bandwidth: maximum RF bandwidth supported by a BS within each supported operating band

maximum output power: mean power level per carrier of the Base Station measured at the antenna connector in a specified reference condition

maximum radio bandwidth: maximum frequency difference between the upper edge of the highest used carrier and the lower edge of the lowest used carrier

maximum throughput: maximum achievable throughput for a reference measurement channel

mean power: when applied to E-UTRA transmission, power measured in the channel bandwidth of the carrier where the period of measurement is at least one subframe (1 ms), unless otherwise stated

medium range base station: base stations characterized by requirements derived from micro cell scenarios with a BS to UE minimum coupling loss equal to 53 dB

multi-band Base Station: base station characterized by the ability of its transmitter and/or receiver to process two or more carriers in common active RF components simultaneously, where at least one carrier is configured at a different operating band (which is not a sub-band or superseding-band of another supported operating band) than the other carrier(s)

multi-band receiver: receiver characterized by the ability to process two or more carriers in common active RF components simultaneously, where at least one carrier is configured at a different operating band (which is not a sub-band or superseding-band of another supported operating band) than the other carrier(s)

multi-band transmitter: transmitter characterized by the ability to process two or more carriers in common active RF components simultaneously, where at least one carrier is configured at a different operating band (which is not a sub-band or superseding-band of another supported operating band) than the other carrier(s)

multi-carrier transmission configuration: set of one or more contiguous carriers that a BS is able to transmit simultaneously according to the manufacturer's specification

NB-IoT In-band operation: operation of NB-IoT utilizing the resource block(s) within a normal E-UTRA carrier

NB-IoT guard band operation: operation of NB-IoT utilizing the unused resource block(s) within a E-UTRA carrier's guard-band

NB-IoT standalone operation: operation of NB-IoT utilizing its own spectrum

NOTE: For example, the spectrum currently being used by GERAN systems as a replacement of one or more GSM carriers, as well as scattered spectrum for potential IoT deployment.

non-contiguous spectrum: spectrum consisting of two or more sub-blocks separated by sub-block gap(s)

operating band: frequency range (paired or unpaired) that is defined with a specific set of technical requirements, in which E-UTRA operates

NOTE: The operating band(s) for an E-UTRA BS is declared by the manufacturer according to the designations in table 1-1. Operating bands for E-UTRA are designated with Arabic numerals, while the corresponding operating bands for UTRA are designated with Roman numerals.

output power: mean power of one carrier of the Base Station, delivered to a load with resistance equal to the nominal load impedance of the transmitter

rated output power: mean power level per carrier that the manufacturer has declared to be available at the antenna connector

rated total output power: mean power level that the manufacturer has declared to be available at the antenna connector

resource block: physical resource consisting of a number of symbols in the time domain and a number of consecutive subcarriers spanning 180 kHz in the frequency domain

sub-band: part of the uplink and downlink frequency range of the operating band

sub-block: one contiguous allocated block of spectrum for transmission and reception by the same Base Station

NOTE: There may be multiple instances of sub-blocks within an Base Station RF Bandwidth.

sub-block bandwidth: bandwidth of one sub-block