



SLOVENSKI STANDARD
SIST ETS 300 959 E1:2003
01-december-2003

8 [[]HJb]`WV] b]`hY`ca i b]_UW`g_]`g]ghYa `E`AcXi `UW`Uf] GA`\$) '\$(žfUn`]]WU) '\$`%&

Digital cellular telecommunications system; Modulation (GSM 05.04 version 5.0.1)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: **ETS 300 959 Edition 1**

[SIST ETS 300 959 E1:2003](https://standards.iteh.ai/catalog/standards/sist/a4d46a39-c489-4505-aad8-c9b776de506a/sist-ets-300-959-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/a4d46a39-c489-4505-aad8-c9b776de506a/sist-ets-300-959-e1-2003>

ICS:

33.070.50	Globalni sistem za mobilno telekomunikacijo (GSM)	Global System for Mobile Communication (GSM)
-----------	---	--

SIST ETS 300 959 E1:2003

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ETS 300 959 E1:2003

<https://standards.iteh.ai/catalog/standards/sist/a4d46a39-c489-4505-aad8-c9b776de506a/sist-ets-300-959-e1-2003>



EUROPEAN
TELECOMMUNICATION
STANDARD

ETS 300 959

May 1997

Source: ETSI TC-SMG

Reference: DE/SMG-020504Q

ICS: 33.020

Key words: Digital cellular telecommunications system, Global System for Mobile communications (GSM)



**Digital cellular telecommunications system;
Modulation
(GSM 05.04 version 5.0.1)**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1997. All rights reserved.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 959 E1:2003](https://standards.iteh.ai/catalog/standards/sist/a4d46a39-c489-4505-aad8-c9b776de506a/sist-ets-300-959-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/a4d46a39-c489-4505-aad8-c9b776de506a/sist-ets-300-959-e1-2003>

Contents

Foreword	5
1 Scope	7
1.1 Normative references	7
1.2 Abbreviations	7
2 Modulation format.....	7
2.1 Modulating bit rate	7
2.2 Start and stop of the burst	7
2.3 Differential encoding	8
2.4 Filtering	8
2.5 Output phase	9
2.6 Modulation	9
History.....	10

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 959 E1:2003](https://standards.iteh.ai/catalog/standards/sist/a4d46a39-c489-4505-aad8-c9b776de506a/sist-ets-300-959-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/a4d46a39-c489-4505-aad8-c9b776de506a/sist-ets-300-959-e1-2003>

Blank page

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 959 E1:2003](https://standards.iteh.ai/catalog/standards/sist/a4d46a39-c489-4505-aad8-c9b776de506a/sist-ets-300-959-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/a4d46a39-c489-4505-aad8-c9b776de506a/sist-ets-300-959-e1-2003>

Foreword

This European Telecommunication Standard (ETS) has been produced by the Special Mobile Group (SMG) Technical Committee (TC) of the European Telecommunications Standards Institute (ETSI).

This ETS specifies the modulation format used within the digital cellular telecommunications system. This ETS corresponds to GSM 05.04 Phase 2 version 4.0.3. This ETS is a GSM technical specification version 5 and is part of the 1996 release of the GSM Technical Specifications.

The specification from which this ETS has been derived was originally based on CEPT documentation, hence the presentation of this ETS may not be entirely in accordance with the ETSI/PNE rules.

Transposition dates	
Date of adoption:	18 April 1997
Date of latest announcement of this ETS (doa):	31 August 1997
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	28 February 1998
Date of withdrawal of any conflicting National Standard (dow):	28 February 1998

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 959 E1:2003](https://standards.iteh.ai/catalog/standards/sist/a4d46a39-c489-4505-aad8-c9b776de506a/sist-ets-300-959-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/a4d46a39-c489-4505-aad8-c9b776de506a/sist-ets-300-959-e1-2003>

Blank page

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 959 E1:2003](https://standards.iteh.ai/catalog/standards/sist/a4d46a39-c489-4505-aad8-c9b776de506a/sist-ets-300-959-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/a4d46a39-c489-4505-aad8-c9b776de506a/sist-ets-300-959-e1-2003>

1 Scope

The modulator receives the bits from the encryption unit, see GSM 05.01 [1], and produces an RF signal. The filtering of the Radio Frequency (RF) signal necessary to obtain the spectral purity is not defined, neither are the tolerances associated with the theoretical filter requirements specified. These are contained in GSM 05.05 [4].

1.1 Normative references

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references, the latest edition of the publication referred to applies.

- [1] GSM 01.04 (ETR 350): "Digital cellular telecommunications system (Phase 2+); Abbreviations and acronyms".
- [2] GSM 05.01: "Digital cellular telecommunications system (Phase 2+); Physical layer on the radio path General description".
- [3] GSM 05.02 (ETS 300 908): "Digital cellular telecommunications system (Phase 2+); Multiplexing and multiple access on the radio path".
- [4] GSM 05.05 (ETS 300 910): "Digital cellular telecommunications system (Phase 2+); Radio transmission and reception".

1.2 Abbreviations

Abbreviations used in this ETS are listed in GSM 01.04 [1].

2 Modulation format

2.1 Modulating bit rate

The modulating bit rate is $1/T = 1\ 625/6$ kbit/s (i.e. approximately 270,833 kbit/s).

2.2 Start and stop of the burst

Before the first bit of the bursts as defined in GSM 05.02 [3] enters the modulator, the modulator has an internal state as if a modulating bit stream consisting of consecutive ones ($d_i = 1$) had entered the differential encoder. Also after the last bit of the time slot, the modulator has an internal state as if a modulating bit stream consisting of consecutive ones ($d_i = 1$) had continued to enter the differential encoder. These bits are called dummy bits and define the start and the stop of the active and the useful part of the burst as illustrated in figure 1. Nothing is specified about the actual phase of the modulator output signal outside the useful part of the burst.