



**Digital cellular telecommunications system (Phase 2+) (GSM);
Mobile Switching Centre - Base Station system (MSC-BSS)
interface;
Layer 3 specification
(3GPP TS 48.008 version 13.1.0 Release 13)**

REF ID: TS 148 008 V13.1.0
<https://standards.etsi.org/standard/etsi-ts-148-008-v13.1.0-e1e8-4b20-8cf5-811d-92a0-16c3f61f3040a>



Reference

RTS/TSGG-0248008vd10

Keywords

GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	11
1 Scope	12
1.1 References	12
1.2 Definitions and Abbreviations.....	14
2 Application to interface structures	15
2.1 The BSS Operation and Maintenance Application Part	15
2.2 The Direct Transfer Application Part	15
2.3 The BSS Management Application Part.....	16
2.4 Handling of abnormal events related to the BSSAP Header	16
3 The BSS Management Application Part	16
3.1 BSSMAP Procedures	16
3.1.1 Assignment	17
3.1.1.1 Successful Operation.....	17
3.1.1.2 Assignment Failure	20
3.1.1.3 Abnormal Conditions	21
3.1.2 Blocking and Unblocking	22
3.1.2.1 Successful Operation.....	22
3.1.2.2 Abnormal Conditions	23
3.1.2.2.1 Applying to the Single Circuit Block Procedure	23
3.1.2.2.2 Applying to the Circuit Group Block Procedure	24
3.1.3 Resource Indication	25
3.1.3.1 Successful Operation.....	25
3.1.4 Reset	26
3.1.4.1 Global Reset Procedure.....	26
3.1.4.1.1 Reset at the BSS	26
3.1.4.1.2 Reset at the MSC	26
3.1.4.1.3 Abnormal Conditions	27
3.1.4.1.3.1 Abnormal Condition at the BSS.....	27
3.1.4.1.3.2 Abnormal Condition at the MSC	27
3.1.4.2 Reset Circuit.....	27
3.1.4.2.1 Reset Circuit at the BSS	27
3.1.4.2.2 Reset Circuit at the MSC	27
3.1.4.2.3 Abnormal conditions	28
3.1.4.3 Reset IP Resource	28
3.1.4.3.1 Reset IP Resource procedure initiated by the BSS	28
3.1.4.3.2 Reset IP Resource procedure initiated by the MSC.....	28
3.1.4.3.3 Abnormal conditions	29
3.1.5 External Handover	29
3.1.5.1 Handover Required Indication	29
3.1.5.1.1 Generation of the HANOVER REQUIRED message	30
3.1.5.1.2 Abnormal conditions for DTM Handover	32
3.1.5.2 Handover Resource allocation	33
3.1.5.2.1 Operation of the procedure	33
3.1.5.2.2 Handover Resource Allocation Failure	37
3.1.5.2.3 Abnormal conditions	38
3.1.5.3 Handover execution	38
3.1.5.3.1 Operation of the procedure	39
3.1.5.3.2 Handover Failure	40
3.1.5.3.3 Abnormal Conditions	41
3.1.5a Handover from GSM to another System.....	41
3.1.5a.1 Generation of the HANOVER REQUIRED message for intersystem handover	42

3.1.5a.2	Inter-System Handover Resource Allocation Failure.....	43
3.1.5a.3	Intersystem handover Execution	44
3.1.5a.4	Inter System Handover Failure	45
3.1.5a.5	Abnormal Conditions	45
3.1.5b	Handover from another system to GSM	45
3.1.5b.1	General	45
3.1.5b.2	Inter-System Handover Resource Allocation.....	46
3.1.5c	BSS Internal Handover with MSC support.....	46
3.1.5c.1	Internal Handover Preparation	46
3.1.5c.1.1	Internal Handover Required Reject	47
3.1.5c.2	Internal Handover Execution	47
3.1.5c.2.1	Internal Handover failure.....	48
3.1.5c.2.2	Abnormal Conditions	48
3.1.5c.3	Internal Handover Enquiry	49
3.1.6	Internal Intra-Cell Handover Procedure.....	49
3.1.7	Internal Inter-Cell Handover Procedure.....	50
3.1.8	Handover Candidate Enquiry.....	50
3.1.8.1	Successful Operation.....	51
3.1.8.2	Abnormal conditions	51
3.1.9	Release of Radio Resource And Terrestrial Resource	51
3.1.9.1	Release Due To Transaction Completion.....	51
3.1.9.1a	Release of radio resources and the terrestrial resources for VGCS/VBS calls:.....	52
3.1.9.2	Release due to BSS generated reason	52
3.1.9.3	Release due to successful handover	54
3.1.9.4	Release due to uplink release	54
3.1.10	Paging	54
3.1.11	Trace Invocation	54
3.1.12	Flow Control.....	55
3.1.12.1	Philosophy.....	55
3.1.12.2	Processor Overload at the MSC	55
3.1.12.3	Processor/CCCH overload at the BSS	56
3.1.12.4	Message throughput congestion	56
3.1.13	Classmark Handling Procedures	56
3.1.13.1	Classmark request procedure	56
3.1.13.2	Classmark updating procedure	56
3.1.14	Cipher Mode Control	56
3.1.14.1	Successful Operation.....	56
3.1.14.2	Abnormal Conditions	57
3.1.15	General SCCP Abnormal Conditions	57
3.1.16	Initial MS message.....	58
3.1.17	Queuing Indication	58
3.1.17.1	Operation of the procedure in case of assignment procedure.....	58
3.1.17.2	Operation of the procedure in case of hand-over resource allocation procedure	59
3.1.18	Data Link Control SAPI not Equal to "0"	59
3.1.18.1	Data link set up across the radio interface.....	59
3.1.18.1.1	MS to MSC direction.....	59
3.1.18.1.2	MSC to MS Direction.....	59
3.1.18.2	Choice of the signalling link	59
3.1.19	BSSMAP Error Handling	60
3.1.19.1	Definitions of Types of Information Elements.....	60
3.1.19.2	Erroneous Events	61
3.1.19.3	Non-erroneous Events.....	61
3.1.19.4	Other Events.....	61
3.1.19.5	Appropriate Error Message and Cause Value	62
3.1.19.6	Unequipped Circuit Identification Code	62
3.1.19.7	Field Elements.....	63
3.1.20	Load Indication Procedure.....	63
3.1.20.1	Operation of the procedure.....	64
3.1.21	Voice group call service and voice broadcast service call set-up and resource assignment	64
3.1.21.1	Successful operation.....	65
3.1.21.2	VGCS/VBS call set-up abnormal cases	65
3.1.21.3	VGCS/VBS call set-up failure	65

3.1.22	Voice group call service and voice broadcast service Assignment procedure	65
3.1.22.1	Successful operation.....	66
3.1.22.2	VGCS/VBS Assignment abnormal cases.....	68
3.1.22.3	VGCS/VBS Assignment failure.....	69
3.1.22.4	VGCS/VBS Queuing Indication	70
3.1.23	(void)	70
3.1.24	Voice group call uplink control procedure - talker priority not supported by the network.....	70
3.1.24.1	Uplink allocation procedure.....	70
3.1.24.1.1	Successful uplink allocation operation	71
3.1.24.1.2	Unsuccessful uplink allocation operation	71
3.1.24.2	Uplink release procedure.....	71
3.1.24.3	Uplink seize procedure.....	71
3.1.24a	Voice group call uplink control procedure - talker priority supported by the network.....	71
3.1.24.a.1	General	71
3.1.24a.2	Uplink allocation procedure	72
3.1.24a.2.1	Successful uplink allocation operation	72
3.1.24a.2.1.1	Normal Priority Request	72
3.1.24a.2.1.2	Privileged or Emergency Priority Request via Uplink Access procedure.....	72
3.1.24a.2.1.3	Privileged or Emergency Priority Request via Priority Uplink Request procedure	73
3.1.24a.2.2	Unsuccessful uplink allocation operation	73
3.1.24a.2.2.1	Normal Priority Uplink Request	73
3.1.24a.2.2.2	Privileged or Emergency Uplink Request via Uplink Access procedure.....	73
3.1.24a.2.2.3	Privileged or Emergency Uplink Request via Priority Uplink Request procedure	74
3.1.24a.3	Uplink release procedure.....	74
3.1.24a.4	Uplink seize procedure.....	74
3.1.24a.5	Emergency Reset procedure via UPLINK ACCESS message	74
3.1.24a.5.1	Unsuccessful	74
3.1.24a.6	Emergency Reset procedure via PRIORITY UPLINK REQUEST message	74
3.1.24a.6.1	Unsuccessful	74
3.1.24b	Talker Information.....	75
3.1.24c	SMS to ongoing VGCS call all	75
3.1.24d	Distributing application specific data to ongoing VGCS call	75
3.1.25	PDSS1 flow control	75
3.1.26	Circuit re-selection procedure	76
3.1.27	LSA handling	76
3.1.28	Location Acquisition	76
3.1.28.1	(void).....	77
3.1.28.2	Location request	77
3.1.28.2.1	Successful Operation.....	77
3.1.28.2.2	Unsuccessful Operation	78
3.1.28.2.3	Abnormal cases	78
3.1.28.2.4	Overload	78
3.1.29	Connectionless Information Transfer procedure	78
3.1.29.1	Unsuccessful Operation	78
3.1.29.2	Abnormal cases	78
3.1.29.3	Segmentation	78
3.1.30	Common ID	79
3.1.31	VGCS/VBS Cell Re-established - no A-interface link sharing	79
3.1.32	Rerouting procedure in case of MOCN configuration for network sharing	79
3.1.32.1	General	79
3.1.32.2	Reroute command	80
3.1.32.3	Reroute complete	81
3.1.32.4	Abnormal Conditions	81
3.1.33	Local Call Local Switch	81
3.1.33.1	General	81
3.1.33.2	Local switch establishment	81
3.1.33.2.1	Call Leg Correlation	81
3.1.33.2.2	Successful Operation	81
3.1.33.2.3	Unsuccessful Operation	82
3.1.33.3	Local switch break	82
3.1.33.3.1	Local switching break request from MSC	82
3.1.33.3.2	Local switching break initiated by BSS.....	83

3.1.33.3.3	Local Switching break at Handover	83
3.1.33.4	Local switch prevention	83
3.1.33.5	LCLS Notification.....	83
3.2	Message Formats and Coding	84
3.2.1	Message Contents	87
3.2.1.1	ASSIGNMENT REQUEST	87
3.2.1.2	ASSIGNMENT COMPLETE.....	88
3.2.1.3	ASSIGNMENT FAILURE	90
3.2.1.4	BLOCK	91
3.2.1.5	BLOCKING ACKNOWLEDGE	91
3.2.1.6	UNBLOCK	91
3.2.1.7	UNBLOCKING ACKNOWLEDGE	91
3.2.1.8	HANDOVER REQUEST	92
3.2.1.9	HANDOVER REQUIRED	95
3.2.1.10	HANDOVER REQUEST ACKNOWLEDGE.....	97
3.2.1.11	HANDOVER COMMAND	98
3.2.1.12	HANDOVER COMPLETE	98
3.2.1.13	HANDOVER SUCCEEDED.....	99
3.2.1.14	HANDOVER CANDIDATE ENQUIRE.....	99
3.2.1.15	HANDOVER CANDIDATE RESPONSE	99
3.2.1.16	HANDOVER FAILURE	99
3.2.1.17	RESOURCE REQUEST	101
3.2.1.18	RESOURCE INDICATION	101
3.2.1.19	PAGING	102
3.2.1.20	CLEAR REQUEST	102
3.2.1.21	CLEAR COMMAND	103
3.2.1.22	CLEAR COMPLETE.....	103
3.2.1.23	RESET	103
3.2.1.24	RESET ACKNOWLEDGE	104
3.2.1.25	HANDOVER PERFORMED	105
3.2.1.26	OVERLOAD.....	106
3.2.1.27	MSC INVOKE TRACE	106
3.2.1.28	BSS INVOKE TRACE	106
3.2.1.29	CLASSMARK UPDATE.....	107
3.2.1.30	CIPHER MODE COMMAND.....	107
3.2.1.31	CIPHER MODE COMPLETE	107
3.2.1.32	COMPLETE LAYER 3 INFORMATION.....	108
3.2.1.33	QUEUEING INDICATION.....	108
3.2.1.34	SAPI "n" REJECT.....	108
3.2.1.35	(void).....	109
3.2.1.36	(void).....	109
3.2.1.37	HANDOVER REQUIRED REJECT	109
3.2.1.38	RESET CIRCUIT	109
3.2.1.39	RESET CIRCUIT ACKNOWLEDGE.....	110
3.2.1.40	HANDOVER DETECT	110
3.2.1.41	CIRCUIT GROUP BLOCK.....	110
3.2.1.42	CIRCUIT GROUP BLOCKING ACKNOWLEDGE	110
3.2.1.43	CIRCUIT GROUP UNBLOCK	111
3.2.1.44	CIRCUIT GROUP UNBLOCKING ACKNOWLEDGE	111
3.2.1.45	CONFUSION	111
3.2.1.46	CLASSMARK REQUEST	112
3.2.1.47	UNEQUIPPED CIRCUIT.....	112
3.2.1.48	CIPHER MODE REJECT	112
3.2.1.49	LOAD INDICATION	113
3.2.1.50	VGCS/VBS SETUP	113
3.2.1.51	VGCS/VBS SETUP ACK.....	113
3.2.1.52	VGCS/VBS SETUP REFUSE	114
3.2.1.53	VGCS/VBS ASSIGNMENT REQUEST	114
3.2.1.54	VGCS/VBS ASSIGNMENT RESULT	115
3.2.1.55	VGCS/VBS ASSIGNMENT FAILURE	115
3.2.1.56	VGCS/VBS QUEUING INDICATION	116
3.2.1.57	UPLINK REQUEST	116

3.2.1.58	UPLINK REQUEST ACKNOWLEDGE	117
3.2.1.59	UPLINK REQUEST CONFIRMATION.....	117
3.2.1.59a	UPLINK APPLICATION DATA.....	117
3.2.1.60	UPLINK RELEASE INDICATION	117
3.2.1.61	UPLINK REJECT COMMAND.....	118
3.2.1.62	UPLINK RELEASE COMMAND	118
3.2.1.63	UPLINK SEIZED COMMAND	118
3.2.1.64	SUSPEND.....	118
3.2.1.65	RESUME	119
3.2.1.66	CHANGE CIRCUIT	119
3.2.1.67	CHANGE CIRCUIT ACKNOWLEDGE	119
3.2.1.68	Common ID.....	119
3.2.1.69	LSA INFORMATION	120
3.2.1.70	(void).....	120
3.2.1.71	PERFORM LOCATION REQUEST	120
3.2.1.72	PERFORM LOCATION RESPONSE.....	121
3.2.1.73	PERFORM LOCATION ABORT	121
3.2.1.74	CONNECTIONLESS INFORMATION.....	121
3.2.1.75	CHANNEL MODIFY REQUEST	121
3.2.1.76	EMERGENCY RESET INDICATION	122
3.2.1.77	EMERGENCY RESET COMMAND	122
3.2.1.78	VGCS ADDITIONAL INFORMATION	122
3.2.1.79	VGCS/VBS AREA CELL INFO	122
3.2.1.80	VGCS/VBS ASSIGNMENT STATUS.....	122
3.2.1.81	VGCS SMS	123
3.2.1.82	NOTIFICATION DATA	124
3.2.1.83	INTERNAL HANDOVER REQUIRED	124
3.2.1.84	INTERNAL HANDOVER REQUIRED REJECT	125
3.2.1.85	INTERNAL HANDOVER COMMAND	125
3.2.1.86	INTERNAL HANDOVER ENQUIRY.....	126
3.2.1.87	RESET IP RESOURCE	126
3.2.1.88	RESET IP RESOURCE ACKNOWLEDGE	126
3.2.1.89	REROUTE COMMAND	127
3.2.1.90	REROUTE COMPLETE	127
3.2.1.91	LCLS-CONNECT-CONTROL	127
3.2.1.92	LCLS-CONNECT-CONTROL-ACK	127
3.2.1.93	LCLS-NOTIFICATION	127
3.2.2	Signalling element coding.....	128
3.2.2.0	General.....	128
3.2.2.1	Message Type	132
3.2.2.2	Circuit Identity Code.....	133
3.2.2.3	Connection Release Requested	134
3.2.2.4	Resource Available	134
3.2.2.5	Cause	135
3.2.2.6	IMSI	137
3.2.2.7	TMSI	138
3.2.2.8	Number Of MSs	138
3.2.2.9	Layer 3 Header Information	138
3.2.2.10	Encryption Information	139
3.2.2.11	Channel Type	139
3.2.2.12	Periodicity	145
3.2.2.13	Extended Resource Indicator	146
3.2.2.14	Total Resource Accessible	146
3.2.2.15	LSA Identifier	147
3.2.2.16	LSA Identifier List	147
3.2.2.17	Cell Identifier	148
3.2.2.18	Priority	151
3.2.2.19	Classmark Information Type 2	151
3.2.2.20	Classmark Information Type 3	152
3.2.2.21	Interference Band To Be Used	152
3.2.2.22	RR Cause	152
3.2.2.23	LSA Information	153

3.2.2.24	Layer 3 Information	153
3.2.2.25	DLCI	154
3.2.2.26	Downlink DTX Flag	154
3.2.2.27	Cell Identifier List	154
3.2.2.27a	Cell Identifier List Segment	157
3.2.2.27b	Cell Identifier List Segment for established cells.....	160
3.2.2.27c	Cell Identifier List Segment for cells to be established.....	163
3.2.2.27d	(void).....	164
3.2.2.27e	Cell Identifier List Segment for released cells - no user present.....	164
3.2.2.27f	Cell Identifier List Segment for not established cells - no establishment possible	164
3.2.2.28	Response Request	164
3.2.2.29	Resource Indication Method	165
3.2.2.30	Classmark Information Type 1.....	165
3.2.2.31	Circuit Identity Code List.....	165
3.2.2.32	Diagnostics.....	166
3.2.2.33	Chosen Channel	167
3.2.2.34	Cipher Response Mode	168
3.2.2.35	Layer 3 Message Contents	168
3.2.2.36	Channel Needed	169
3.2.2.37	Trace Type	169
3.2.2.38	TriggerID	169
3.2.2.39	Trace Reference	169
3.2.2.40	TransactionID.....	169
3.2.2.41	Mobile Identity.....	170
3.2.2.42	OMCID	170
3.2.2.43	Forward Indicator.....	170
3.2.2.44	Chosen Encryption Algorithm	170
3.2.2.45	Circuit Pool	171
3.2.2.46	Circuit Pool List	176
3.2.2.47	Time Indication	176
3.2.2.48	Resource Situation	176
3.2.2.49	Current Channel Type 1	178
3.2.2.50	Queuing Indicator	179
3.2.2.51	Speech Version	179
3.2.2.52	Assignment Requirement	179
3.2.2.53	(void).....	180
3.2.2.54	Talker Flag	180
3.2.2.55	Group Call Reference	180
3.2.2.56	eMLPP Priority	180
3.2.2.57	Configuration Evolution Indication	180
3.2.2.58	Old BSS to New BSS information	181
3.2.2.59	(void).....	182
3.2.2.60	LCS QoS	182
3.2.2.61	LSA Access Control Suppression	182
3.2.2.62	LCS Priority	182
3.2.2.63	Location Type	182
3.2.2.64	Location Estimate	183
3.2.2.65	Positioning Data	183
3.2.2.66	LCS Cause.....	183
3.2.2.67	LCS Client Type	183
3.2.2.68	APDU.....	184
3.2.2.69	Network Element Identity	184
3.2.2.70	GPS Assistance Data.....	184
3.2.2.71	Deciphering Keys.....	184
3.2.2.72	Return Error Request.....	185
3.2.2.73	Return Error Cause.....	185
3.2.2.74	Segmentation.....	185
3.2.2.75	Service Handover	186
3.2.2.76	Source RNC to target RNC transparent information (UMTS).....	186
3.2.2.77	Source RNC to target RNC transparent information (cdma2000).....	186
3.2.2.78	GERAN Classmark	187
3.2.2.79	GERAN BSC Container.....	187

3.2.2.80	New BSS to Old BSS Information	188
3.2.2.81	Inter-System Information	189
3.2.2.82	SNA Access Information	189
3.2.2.83	VSTK_RAND Information	190
3.2.2.84	VSTK information	190
3.2.2.85	Paging Information	191
3.2.2.86	IMEI	191
3.2.2.87	Velocity Estimate	191
3.2.2.88	VGCS Feature Flags	192
3.2.2.89	Talker Priority	193
3.2.2.90	Emergency Set Indication	193
3.2.2.91	Talker Identity	193
3.2.2.92	SMS to VGCS	194
3.2.2.93	VGCS talker mode	194
3.2.2.94	VGCS/VBS Cell Status	195
3.2.2.95	GANSS Assistance Data	195
3.2.2.96	GANSS Positioning Data	195
3.2.2.97	GANSS Location Type	196
3.2.2.98	Application Data	196
3.2.2.99	Data Identity	196
3.2.2.100	Application Data Information	196
3.2.2.101	MSISDN	197
3.2.2.102	AoIP Transport Layer Address	197
3.2.2.103	Speech Codec List	197
3.2.2.104	Speech Codec	201
3.2.2.105	Call Identifier	202
3.2.2.106	Call Identifier List	202
3.2.2.107	A-Interface Selector for RESET	202
3.2.2.108	(void)	203
3.2.2.109	Kc ₁₂₈	203
3.2.2.110	CSG Identifier	203
3.2.2.111	Redirect Attempt Flag	203
3.2.2.112	Reroute Reject Cause	204
3.2.2.113	Send Sequence Number	204
3.2.2.114	Reroute complete outcome	204
3.2.2.115	Global Call Reference	205
3.2.2.116	LCLS-Configuration	205
3.2.2.117	LCLS-Connection-Status-Control	206
3.2.2.118	LCLS-Correlation-Not-Needed	206
3.2.2.119	LCLS-BSS-Status	206
3.2.2.120	LCLS-Break-Request	207
3.2.2.121	CSFB Indication	207
3.2.2.122	CS to PS SRVCC	207
3.2.2.123	Source eNB to target eNB transparent information (E-UTRAN)	207
3.2.2.124	CS to PS SRVCC Indication	207
3.2.2.125	CN to MS transparent information	207
3.2.2.126	Selected PLMN ID	208
3.2.2.127	Last used E-UTRAN PLMN ID	208
3.2.3	Signalling Field Element Coding	208
3.2.3.1	Extra information	209
3.2.3.2	Current Channel type 2	210
3.2.3.3	Target cell radio information	210
3.2.3.4	GPRS Suspend Information	211
3.2.3.5	MultiRate configuration Information	211
3.2.3.6	Dual Transfer Mode information	211
3.2.3.7	Inter RAT Handover Info	212
3.2.3.8	cdma2000 Capability Information	212
3.2.3.9	Downlink Cell Load Information	212
3.2.3.10	Uplink Cell Load Information	213
3.2.3.11	Cell Load Information Group	213
3.2.3.12	Cell Load Information	213
3.2.3.13	PS Indication	214

3.2.3.14	DTM Handover Command Indication	214
3.2.3.15	D-RNTI.....	214
3.2.3.16	IRAT Measurement Configuration.....	215
3.2.3.17	Source Cell ID	215
3.2.3.18	IRAT Measurement Configuration (extended E-ARFCNs).....	216
3.2.4	List of Timers in the BSSMAP Procedures	217
3.3	SDL Representation Of The Procedures At The BSS	217
4	Broadcast Information Control Channel	217
5	Definitions	217
6	List of diagrams.....	219
Annex A (informative):	Change History	230
History		231

iteh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/61f3040a-e1e8-4b20-8cf5-81fc692d110/etsi-ts-148-008-v13.1.0-2016-04>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iteh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/6252040a-e1e8-4b20-8cf5-815c692d110/etsi-ts-148-008-v13.1.0-2016-04>

1 Scope

The present document specifies the layer 3 procedures used on the Base Station System (BSS) to Mobile-services Switching Centre (MSC) interface for control of GSM services.

For the purposes of call control and mobility management, messages are not interpreted at the Base Station System (BSS) which acts as a relay function. These messages and procedures are documented in 3GPP TS 24.008, the only relevant issues covering these messages in the present document are those concerned with error conditions at the interface, and the headers that are required for the correct addressing of the messages. This is specified in more detail in 3GPP TS 48.002.

The functional split between MSC and BSS is defined in 3GPP TS 48.002 and states that the BSS is responsible for local radio resource allocation and in order to support this the required procedures between BSS and MSC are defined in detail in the present document.

3GPP TS 48.002 also states that the BSS is responsible for the scheduling of all CCCH/BCCH messages and therefore some procedures for providing the BSS with the necessary information to be passed on these channels for individual calls (i.e. paging) are defined in the present document, but the scheduling is not discussed.

This interface and consequently these layer 3 procedures are designed to support BSSs providing one or more cells.

1.1 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
[2] 3GPP TS 23.003: "Numbering, addressing and identification".
[3] 3GPP TS 23.009: "Handover procedures".
[3a] 3GPP TS 23.032: "Universal Geographical Area Description (GAD)".
[4] (void)
[5] 3GPP TS 43.059: "Functional stage 2 description of Location Services (LCS) in GERAN".
[6] 3GPP TS 24.008: "Mobile radio interface Layer 3 specification; Core network protocols; Stage 3".
[7] (void).
[8] (void).
[9] (void).
[10] (void).
[11] (void).
[12] (void).
[13] (void).