

ETSI TS 136 101 V13.3.0 (2016-05)



LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
User Equipment (UE) radio transmission and reception
(3GPP TS 36.101 version 13.3.0 Release 13)

PREVIEW
iTech (Cambridge, ai)
https://standards.iteh.ai/catalog/standards/sist/7261a666-2c94-4952-98e8-69bd4b35a188/etsi-ts-136-101-v13.3.0-2016-05



Reference

RTS/TSGR-0436101vd30

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	21
1 Scope	22
2 References	22
3 Definitions, symbols and abbreviations	22
3.1 Definitions	22
3.2 Symbols.....	24
3.3 Abbreviations	26
4 General	27
4.1 Relationship between minimum requirements and test requirements	27
4.2 Applicability of minimum requirements	28
4.3 Void.....	28
4.3A Applicability of minimum requirements (CA, UL-MIMO, ProSe, Dual Connectivity, UE category 0, UE category M1)	28
4.4 RF requirements in later releases	29
5 Operating bands and channel arrangement.....	30
5.1 General	30
5.2 Void.....	30
5.3 Void.....	30
5.4 Void.....	30
5.5 Operating bands.....	30
5.5A Operating bands for CA	32
5.5B Operating bands for UL-MIMO	42
5.5C Operating bands for Dual Connectivity	42
5.5D Operating bands for ProSe.....	44
5.6 Channel bandwidth.....	44
5.6.1 Channel bandwidths per operating band.....	45
5.6A Channel bandwidth for CA.....	47
5.6A.1 Channel bandwidths per operating band for CA.....	49
5.6B Channel bandwidth for UL-MIMO	68
5.6B.1 Void	68
5.6C Channel bandwidth for Dual Connectivity	68
5.6C.1 Void	68
5.6D Channel bandwidth for ProSe.....	68
5.6D.1 Channel bandwidths per operating band for ProSe.....	68
5.7 Channel arrangement.....	69
5.7.1 Channel spacing.....	69
5.7.1A Channel spacing for CA.....	69
5.7.2 Channel raster	70
5.7.2A Channel raster for CA.....	70
5.7.3 Carrier frequency and EARFCN.....	70
5.7.4 TX–RX frequency separation	72
5.7.4A TX–RX frequency separation for CA	72
6 Transmitter characteristics	72
6.1 General	72
6.2 Transmit power	73
6.2.1 Void	73
6.2.2 UE maximum output power.....	73
6.2.2A UE maximum output power for CA.....	75
6.2.2B UE maximum output power for UL-MIMO	76
6.2.2C Void	78

6.2.2D	UE maximum output power for ProSe.....	78
6.2.2E	UE maximum output power for Category M1 UE.....	78
6.2.3	UE maximum output power for modulation / channel bandwidth.....	79
6.2.3A	UE Maximum Output power for modulation / channel bandwidth for CA	79
6.2.3B	UE maximum output power for modulation / channel bandwidth for UL-MIMO	81
6.2.3D	UE maximum output power for modulation / channel bandwidth for ProSe.....	81
6.2.3E	UE maximum output power for modulation / channel bandwidth for category M1	82
6.2.4	UE maximum output power with additional requirements	83
6.2.4A	UE maximum output power with additional requirements for CA	93
6.2.4A.1	A-MPR for CA_NS_01 for CA_1C	94
6.2.4A.2	A-MPR for CA_NS_02 for CA_1C	95
6.2.4A.3	A-MPR for CA_NS_03 for CA_1C	95
6.2.4A.4	A-MPR for CA_NS_04.....	96
6.2.4A.5	A-MPR for CA_NS_05 for CA_38C	97
6.2.4A.6	A-MPR for CA_NS_06.....	97
6.2.4A.7	A-MPR for CA_NS_07.....	98
6.2.4A.8	A-MPR for CA_NS_08.....	99
6.2.4B	UE maximum output power with additional requirements for UL-MIMO.....	99
6.2.4D	UE maximum output power with additional requirements for ProSe.....	100
6.2.4E	UE maximum output power with additional requirements for category M1 UE	100
6.2.5	Configured transmitted power	101
6.2.5A	Configured transmitted power for CA	115
6.2.5B	Configured transmitted power for UL-MIMO.....	117
6.2.5C	Configured transmitted power for Dual Connectivity.....	118
6.2.5D	Configured transmitted power for ProSe	119
6.3	Output power dynamics.....	120
6.3.1	(Void).....	120
6.3.2	Minimum output power	120
6.3.2.1	Minimum requirement	120
6.3.2A	UE Minimum output power for CA	121
6.3.2A.1	Minimum requirement for CA	121
6.3.2B	UE Minimum output power for UL-MIMO	121
6.3.2B.1	Minimum requirement	121
6.3.2C	Void	122
6.3.2D	UE Minimum output power for ProSe	122
6.3.3	Transmit OFF power.....	122
6.3.3.1	Minimum requirement	122
6.3.3A	UE Transmit OFF power for CA	122
6.3.3A.1	Minimum requirement for CA	122
6.3.3B	UE Transmit OFF power for UL-MIMO	123
6.3.3B.1	Minimum requirement	123
6.3.3D	Transmit OFF power for ProSe.....	123
6.3.4	ON/OFF time mask.....	124
6.3.4.1	General ON/OFF time mask	124
6.3.4.2	PRACH and SRS time mask	124
6.3.4.2.1	PRACH time mask	124
6.3.4.2.2	SRS time mask	125
6.3.4.3	Slot / Sub frame boundary time mask	126
6.3.4.4	PUCCH / PUSCH / SRS time mask.....	126
6.3.4A	ON/OFF time mask for CA	128
6.3.4B	ON/OFF time mask for UL-MIMO	128
6.3.4D	ON/OFF time mask for ProSe.....	128
6.3.4D.1	General time mask for ProSe	128
6.3.4D.2	PSSS/SSSS time mask	129
6.3.4D.3	PSSS / SSSS / PSBCH time mask.....	130
6.3.4D.4	PSSCH / SRS time mask	131
6.3.5	Power Control.....	131
6.3.5.1	Absolute power tolerance.....	131
6.3.5.1.1	Minimum requirements	131
6.3.5.2	Relative Power tolerance.....	131
6.3.5.2.1	Minimum requirements	131
6.3.5.3	Aggregate power control tolerance	132

6.3.5.3.1	Minimum requirement.....	132
6.3.5A	Power control for CA.....	133
6.3.5A.1	Absolute power tolerance.....	133
6.3.5A.1.1	Minimum requirements	133
6.3.5A.2	Relative power tolerance.....	133
6.3.5A.2.1	Minimum requirements	133
6.3.5A.3	Aggregate power control tolerance	134
6.3.5A.3.1	Minimum requirements	134
6.3.5B	Power control for UL-MIMO	134
6.3.5D	Power Control for ProSe.....	134
6.3.5D.1	Absolute power tolerance.....	134
6.4	Void.....	135
6.5	Transmit signal quality	135
6.5.1	Frequency error.....	135
6.5.1A	Frequency error for CA.....	135
6.5.1B	Frequency error for UL-MIMO	135
6.5.1D	Frequency error for ProSe.....	135
6.5.2	Transmit modulation quality	135
6.5.2.1	Error Vector Magnitude	135
6.5.2.1.1	Minimum requirement.....	136
6.5.2.2	Carrier leakage	136
6.5.2.2.1	Minimum requirements	136
6.5.2.3	In-band emissions	137
6.5.2.3.1	Minimum requirements	137
6.5.2.4	EVM equalizer spectrum flatness	137
6.5.2.4.1	Minimum requirements	138
6.5.2A	Transmit modulation quality for CA.....	139
6.5.2A.1	Error Vector Magnitude	139
6.5.2A.2	Carrier leakage for CA.....	139
6.5.2A.2.1	Minimum requirements	139
6.5.2A.3	In-band emissions	139
6.5.2A.3.1	Minimum requirement for CA.....	139
6.5.2B	Transmit modulation quality for UL-MIMO	141
6.5.2B.1	Error Vector Magnitude	142
6.5.2B.2	Carrier leakage	142
6.5.2B.3	In-band emissions	142
6.5.2B.4	EVM equalizer spectrum flatness for UL-MIMO	142
6.5.2D	Transmit modulation quality for ProSe.....	142
6.5.2D.1	Error Vector Magnitude.....	142
6.5.2D.2	Carrier leakage.....	142
6.5.2D.3	In-band emissions	143
6.5.2D.4	EVM equalizer spectrum flatness for ProSe	143
6.6	Output RF spectrum emissions.....	143
6.6.1	Occupied bandwidth	143
6.6.1A	Occupied bandwidth for CA	143
6.6.1B	Occupied bandwidth for UL-MIMO.....	144
6.6.2	Out of band emission	144
6.6.2.1	Spectrum emission mask.....	144
6.6.2.1.1	Minimum requirement.....	144
6.6.2.1A	Spectrum emission mask for CA.....	145
6.6.2.2	Additional spectrum emission mask	146
6.6.2.2.1	Minimum requirement (network signalled value "NS_03", "NS_11", "NS_20", and "NS_21")..	146
6.6.2.2.2	Minimum requirement (network signalled value "NS_04").....	147
6.6.2.2.3	Minimum requirement (network signalled value "NS_06" or "NS_07")	147
6.6.2.2A	Additional Spectrum Emission Mask for CA.....	148
6.6.2.2A.1	Minimum requirement (network signalled value "CA_NS_04").....	148
6.6.2.3	Adjacent Channel Leakage Ratio.....	148
6.6.2.3.1	Minimum requirement E-UTRA	149
6.6.2.3.1A	Void.....	150
6.6.2.3.1Aa	Void.....	150
6.6.2.3.2	Minimum requirements UTRA	150
6.6.2.3.2A	Minimum requirement UTRA for CA.....	150

6.6.2.3.3A	Minimum requirements for CA E-UTRA.....	152
6.6.2.4	Void.....	153
6.6.2.4.1	Void.....	153
6.6.2A	Void.....	153
6.6.2B	Out of band emission for UL-MIMO.....	153
6.6.2C	Void.....	153
6.6.2D	Out of band emission for ProSe.....	153
6.6.3	Spurious emissions	154
6.6.3.1	Minimum requirements.....	154
6.6.3.1A	Minimum requirements for CA.....	154
6.6.3.2	Spurious emission band UE co-existence	155
6.6.3.2A	Spurious emission band UE co-existence for CA	161
6.6.3.3	Additional spurious emissions	168
6.6.3.3.1	Minimum requirement (network signalled value "NS_05").....	168
6.6.3.3.2	Minimum requirement (network signalled value "NS_07").....	168
6.6.3.3.3	Minimum requirement (network signalled value "NS_08").....	169
6.6.3.3.4	Minimum requirement (network signalled value "NS_09").....	169
6.6.3.3.5	Minimum requirement (network signalled value "NS_12").....	169
6.6.3.3.6	Minimum requirement (network signalled value "NS_13").....	170
6.6.3.3.7	Minimum requirement (network signalled value "NS_14").....	170
6.6.3.3.8	Minimum requirement (network signalled value "NS_15").....	170
6.6.3.3.9	Minimum requirement (network signalled value "NS_16").....	170
6.6.3.3.10	Minimum requirement (network signalled value "NS_17").....	171
6.6.3.3.11	Minimum requirement (network signalled value "NS_18").....	171
6.6.3.3.12	Minimum requirement (network signalled value "NS_19").....	171
6.6.3.3.13	Minimum requirement (network signalled value "NS_11").....	171
6.6.3.3.14	Minimum requirement (network signalled value "NS_20").....	172
6.6.3.3.15	Minimum requirement (network signalled value "NS_21").....	172
6.6.3.3.16	Minimum requirement (network signalled value "NS_22").....	172
6.6.3.3.17	Minimum requirement (network signalled value "NS_23").....	173
6.6.3.3.18	Void.....	173
6.6.3.3.19	Minimum requirement (network signalled value "NS_04").....	173
6.6.3.3.20	Minimum requirement (network signalled value "NS_24").....	174
6.6.3.3.21	Minimum requirement (network signalled value "NS_25").....	174
6.6.3.3.22	Minimum requirement (network signalled value "NS_26").....	174
6.6.3.3A	Additional spurious emissions for CA	175
6.6.3.3A.1	Minimum requirement for CA_1C (network signalled value "CA_NS_01").....	175
6.6.3.3A.2	Minimum requirement for CA_1C (network signalled value "CA_NS_02").....	175
6.6.3.3A.3	Minimum requirement for CA_1C (network signalled value "CA_NS_03").....	175
6.6.3.3A.4	Minimum requirement for CA_38C (network signalled value "CA_NS_05").....	176
6.6.3.3A.5	Minimum requirement for CA_7C (network signalled value "CA_NS_06").....	176
6.6.3.3A.6	Minimum requirement for CA_39C and CA_39C-41A (network signalled value "CA_NS_07").....	176
6.6.3.3A.7	Minimum requirement for CA_42C (network signalled value "CA_NS_08").....	177
6.6.3A	Void.....	177
6.6.3B	Spurious emission for UL-MIMO	177
6.6.3C	Void.....	177
6.6.3D	Spurious emission for ProSe.....	177
6.6A	Void.....	178
6.6B	Void.....	178
6.7	Transmit intermodulation	178
6.7.1	Minimum requirement	178
6.7.1A	Minimum requirement for CA.....	178
6.7.1B	Minimum requirement for UL-MIMO.....	179
6.8	Void.....	179
6.8.1	Void.....	179
6.8A	Void.....	179
6.8B	Time alignment error for UL-MIMO	179
6.8B.1	Minimum Requirements	179
7	Receiver characteristics.....	179
7.1	General	179

7.2	Diversity characteristics	180
7.3	Reference sensitivity power level.....	181
7.3.1	Minimum requirements (QPSK).....	181
7.3.1A	Minimum requirements (QPSK) for CA.....	197
7.3.1B	Minimum requirements (QPSK) for UL-MIMO	231
7.3.1D	Minimum requirements (QPSK) for ProSe.....	231
7.3.1E	Minimum requirements (QPSK) for UE category 0	233
7.3.2	Void	236
7.4	Maximum input level	236
7.4.1	Minimum requirements.....	236
7.4.1A	Minimum requirements for CA	237
7.4.1B	Minimum requirements for UL-MIMO	238
7.4.1D	Minimum requirements for ProSe	238
7.4A	Void.....	239
7.4A.1	Void	239
7.5	Adjacent Channel Selectivity (ACS).....	239
7.5.1	Minimum requirements.....	239
7.5.1A	Minimum requirements for CA	240
7.5.1B	Minimum requirements for UL-MIMO	243
7.5.1D	Minimum requirements for ProSe	243
7.6	Blocking characteristics	244
7.6.1	In-band blocking.....	244
7.6.1.1	Minimum requirements.....	245
7.6.1.1A	Minimum requirements for CA.....	246
7.6.1.1D	Minimum requirements for ProSe.....	249
7.6.2	Out-of-band blocking.....	250
7.6.2.1	Minimum requirements.....	250
7.6.2.1A	Minimum requirements for CA.....	251
7.6.2.1D	Minimum requirements for ProSe.....	254
7.6.3	Narrow band blocking	255
7.6.3.1	Minimum requirements.....	255
7.6.3.1A	Minimum requirements for CA.....	256
7.6.3.1D	Minimum requirements for ProSe.....	257
7.6A	Void.....	258
7.6B	Blocking characteristics for UL-MIMO.....	258
7.7	Spurious response.....	258
7.7.1	Minimum requirements.....	258
7.7.1A	Minimum requirements for CA.....	259
7.7.1B	Minimum requirements for UL-MIMO	260
7.7.1D	Minimum requirements for ProSe	260
7.8	Intermodulation characteristics	261
7.8.1	Wide band intermodulation.....	261
7.8.1.1	Minimum requirements.....	261
7.8.1A	Minimum requirements for CA	262
7.8.1B	Minimum requirements for UL-MIMO	264
7.8.1D	Minimum requirements for ProSe	264
7.8.2	Void	265
7.9	Spurious emissions	265
7.9.1	Minimum requirements.....	265
7.9.1A	Minimum requirements.....	266
7.10	Receiver image	266
7.10.1	Void	266
7.10.1A	Minimum requirements for CA	266
8	Performance requirement	267
8.1	General	267
8.1.1	Receiver antenna capability	267
8.1.1.1	Simultaneous unicast and MBMS operations.....	268
8.1.1.2	Dual-antenna receiver capability in idle mode	268
8.1.2	Applicability of requirements	268
8.1.2.1	Applicability of requirements for different channel bandwidths.....	268
8.1.2.2	Definition of CA capability.....	268

8.1.2.2A	Definition of dual connectivity capability	271
8.1.2.3	Applicability and test rules for different CA configurations and bandwidth combination sets	272
8.1.2.3A	Applicability and test rules for different dual connectivity configuration and bandwidth combination set	274
8.1.2.3B	Applicability and test rules for different TDD-FDD CA configurations and bandwidth combination sets	275
8.1.2.4	Test coverage for different number of component carriers	277
8.1.2.5	Applicability of performance requirements for Type B receiver	277
8.1.2.6	Applicability of performance requirements for 4Rx receivers	277
8.1.3	UE category and UE DL category	278
8.2	Demodulation of PDSCH (Cell-Specific Reference Symbols)	278
8.2.1	FDD (Fixed Reference Channel)	278
8.2.1.1	Single-antenna port performance	278
8.2.1.1.1	Minimum Requirement	278
8.2.1.1.2	Void	283
8.2.1.1.3	Void	283
8.2.1.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN	283
8.2.1.2	Transmit diversity performance	283
8.2.1.2.1	Minimum Requirement 2 Tx Antenna Port	283
8.2.1.2.2	Minimum Requirement 4 Tx Antenna Port	284
8.2.1.2.3	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS)	285
8.2.1.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	287
8.2.1.2.4	Enhanced Performance Requirement Type A - 2 Tx Antenna Ports with TM3 interference model	289
8.2.1.2.5	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	291
8.2.1.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	292
8.2.1.3	Open-loop spatial multiplexing performance	293
8.2.1.3.1	Minimum Requirement 2 Tx Antenna Port	293
8.2.1.3.1B	Enhanced Performance Requirement Type C - 2Tx Antenna Ports	297
8.2.1.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	298
8.2.1.3.2	Minimum Requirement 4 Tx Antenna Port	299
8.2.1.3.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	299
8.2.1.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	303
8.2.1.4	Closed-loop spatial multiplexing performance	305
8.2.1.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port	305
8.2.1.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port	306
8.2.1.4.1B	Enhanced Performance Requirement Type A - Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	306
8.2.1.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	308
8.2.1.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	310
8.2.1.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	312
8.2.1.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	313
8.2.1.4.2A	Enhanced Performance Requirement Type C - Multi-layer Spatial Multiplexing 2Tx Antenna Ports	313
8.2.1.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	314
8.2.1.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	318
8.2.1.5	MU-MIMO	319
8.2.1.6	[Control channel performance: D-BCH and PCH]	319
8.2.1.7	Carrier aggregation with power imbalance	319
8.2.1.7.1	Minimum Requirement	319
8.2.1.8	Intra-band non-contiguous carrier aggregation with timing offset	320
8.2.1.8.1	Minimum Requirement	320

8.2.2	TDD (Fixed Reference Channel)	321
8.2.2.1	Single-antenna port performance	322
8.2.2.1.1	Minimum Requirement	322
8.2.2.1.2	Void	326
8.2.2.1.3	Void	326
8.2.2.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN.....	326
8.2.2.2	Transmit diversity performance	326
8.2.2.2.1	Minimum Requirement 2 Tx Antenna Port	326
8.2.2.2.2	Minimum Requirement 4 Tx Antenna Port	327
8.2.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	328
8.2.2.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	329
8.2.2.2.4	Enhanced Performance Requirement Type A – 2 Tx Antenna Ports with TM3 interference model.....	331
8.2.2.2.5	Minimum Requirement 2 Tx Antenna Port (when <i>EIMTA-MainConfigServCell-r12</i> is configured)	333
8.2.2.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model.....	333
8.2.2.2.7	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model.....	335
8.2.2.3	Open-loop spatial multiplexing performance.....	336
8.2.2.3.1	Minimum Requirement 2 Tx Antenna Port.....	336
8.2.2.3.1A	Soft buffer management test.....	338
8.2.2.3.1B	Enhanced Performance Requirement Type C - 2Tx Antenna Ports.....	339
8.2.2.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	339
8.2.2.3.2	Minimum Requirement 4 Tx Antenna Port	340
8.2.2.3.3	Minimum Requirement 2Tx antenna port (demodulation subframe overlaps with aggressor cell ABS).....	341
8.2.2.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	345
8.2.2.4	Closed-loop spatial multiplexing performance	347
8.2.2.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port.....	347
8.2.2.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port.....	348
8.2.2.4.1B	Enhanced Performance Requirement Type A – Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	348
8.2.2.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured).....	350
8.2.2.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	352
8.2.2.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	354
8.2.2.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	355
8.2.2.4.2A	Enhanced Performance Requirement Type C Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	356
8.2.2.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	357
8.2.2.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	360
8.2.2.4.4	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	362
8.2.2.5	MU-MIMO.....	363
8.2.2.6	[Control channel performance: D-BCH and PCH]	363
8.2.2.7	Carrier aggregation with power imbalance	363
8.2.2.7.1	Minimum Requirement	363
8.2.2.8	Intra-band contiguous carrier aggregation with minimum channel spacing.....	364
8.2.2.8.1	Minimum Requirement	364
8.2.3	TDD FDD CA (Fixed Reference Channel).....	365
8.2.3.1	Single-antenna port performance	366
8.2.3.1.1	Minimum Requirement for FDD PCell	366
8.2.3.1.2	Minimum Requirement for TDD PCell	369
8.2.3.2	Open-loop spatial multiplexing performance 2Tx Antenna port.....	372
8.2.3.2.1	Minimum Requirement for FDD PCell	372

8.2.3.2.1A	Soft buffer management test for FDD PCell	374
8.2.3.2.2	Minimum Requirement for TDD PCell	375
8.2.3.2.2A	Soft buffer management test for TDD PCell	378
8.2.3.3	Closed-loop spatial multiplexing performance 4Tx Antenna Port	379
8.2.3.3.1	Minimum Requirement for FDD PCell	379
8.2.3.3.2	Minimum Requirement for TDD PCell	382
8.3	Demodulation of PDSCH (User-Specific Reference Symbols).....	385
8.3.1	FDD	385
8.3.1.1	Single-layer Spatial Multiplexing	386
8.3.1.1A	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model.....	387
8.3.1.1B	Single-layer Spatial Multiplexing (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	389
8.3.1.1C	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM9 interference model.....	391
8.3.1.1D	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with CRS interference model.....	393
8.3.1.1E	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM3 interference model.....	394
8.3.1.1F	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM10 serving cell configuration and TM9 interference model	395
8.3.1.1G	Single-layer Spatial Multiplexing (CRS assistance information is configured).....	397
8.3.1.2	Dual-Layer Spatial Multiplexing	399
8.3.1.2A	Enhanced Performance Requirement Type C - Dual-Layer Spatial Multiplexing	400
8.3.1.3	Performance requirements for DCI format 2D and non Quasi Co-located Antenna Ports	401
8.3.1.3.1	Minimum requirement with Same Cell ID (with single NZP CSI-RS resource).....	401
8.3.1.3.2	Minimum requirements with Same Cell ID (with multiple NZP CSI-RS resources).....	403
8.3.1.3.3	Minimum requirement with Different Cell ID and Colliding CRS (with single NZP CSI-RS resource)	405
8.3.1.3.4	Minimum requirement with Different Cell ID and non-colliding CRS (with single NZP CSI-RS resource and CRS assistance information is configured).....	407
8.3.1.3.5	Minimum requirements with different Cell ID and non-colliding CRS (with multiple NZP CSI-RS resources and CRS assistance information is configured).....	409
8.3.2	TDD	411
8.3.2.1	Single-layer Spatial Multiplexing	412
8.3.2.1A	Single-layer Spatial Multiplexing (with multiple CSI-RS configurations)	414
8.3.2.1B	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model.....	416
8.3.2.1C	Single-layer Spatial Multiplexing (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	418
8.3.2.1D	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM9 interference.....	420
8.3.2.1E	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with CRS interference model.....	422
8.3.2.1F	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM3 interference.....	424
8.3.2.1G	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM10 serving cell configuration and TM9 interference model	425
8.3.2.1H	Single-layer Spatial Multiplexing (CRS assistance information is configured).....	427
8.3.2.2	Dual-Layer Spatial Multiplexing	429
8.3.2.2A	Enhanced Performance Requirement Type C - Dual-Layer Spatial Multiplexing	430
8.3.2.3	Dual-Layer Spatial Multiplexing (with multiple CSI-RS configurations)	430
8.3.2.4	Performance requirements for DCI format 2D and non Quasi Co-located Antenna Ports	431
8.3.2.4.1	Minimum requirement with Same Cell ID (with single NZP CSI-RS resource).....	431
8.3.2.4.2	Minimum requirements with Same Cell ID (with multiple NZP CSI-RS resources).....	433
8.3.2.4.3	Minimum requirement with Different Cell ID and Colliding CRS (with single NZP CSI-RS resource)	435
8.3.2.4.4	Minimum requirement with Different Cell ID and non-Colliding CRS (with single NZP CSI-RS resource and CRS assistance information is configured).....	437
8.3.2.4.5	Minimum requirements with different Cell ID and non-colliding CRS (with multiple NZP CSI-RS resources and CRS assistance information is configured).....	439
8.4	Demodulation of PDCCH/PCFICH	441

8.4.1	FDD	441
8.4.1.1	Single-antenna port performance	442
8.4.1.2	Transmit diversity performance	442
8.4.1.2.1	Minimum Requirement 2 Tx Antenna Port	442
8.4.1.2.2	Minimum Requirement 4 Tx Antenna Port	442
8.4.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	443
8.4.1.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	447
8.4.2	TDD	451
8.4.2.1	Single-antenna port performance	452
8.4.2.2	Transmit diversity performance	452
8.4.2.2.1	Minimum Requirement 2 Tx Antenna Port	452
8.4.2.2.2	Minimum Requirement 4 Tx Antenna Port	452
8.4.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	453
8.4.2.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	457
8.5	Demodulation of PHICH	461
8.5.1	FDD	461
8.5.1.1	Single-antenna port performance	461
8.5.1.2	Transmit diversity performance	462
8.5.1.2.1	Minimum Requirement 2 Tx Antenna Port	462
8.5.1.2.2	Minimum Requirement 4 Tx Antenna Port	462
8.5.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	462
8.5.1.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	464
8.5.2	TDD	466
8.5.2.1	Single-antenna port performance	467
8.5.2.2	Transmit diversity performance	467
8.5.2.2.1	Minimum Requirement 2 Tx Antenna Port	467
8.5.2.2.2	Minimum Requirement 4 Tx Antenna Port	468
8.5.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	468
8.5.2.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	470
8.6	Demodulation of PBCH	472
8.6.1	FDD	472
8.6.1.1	Single-antenna port performance	472
8.6.1.2	Transmit diversity performance	473
8.6.1.2.1	Minimum Requirement 2 Tx Antenna Port	473
8.6.1.2.2	Minimum Requirement 4 Tx Antenna Port	473
8.6.1.2.3	Minimum Requirement 2 Tx Antenna Port under Time Domain Measurement Resource Restriction with CRS Assistance Information	473
8.6.2	TDD	475
8.6.2.1	Single-antenna port performance	475
8.6.2.2	Transmit diversity performance	475
8.6.2.2.1	Minimum Requirement 2 Tx Antenna Port	475
8.6.2.2.2	Minimum Requirement 4 Tx Antenna Port	475
8.6.2.2.3	Minimum Requirement 2 Tx Antenna Port under Time Domain Measurement Resource Restriction with CRS Assistance Information	476
8.7	Sustained downlink data rate provided by lower layers	477
8.7.1	FDD (single carrier and CA)	477
8.7.2	TDD (single carrier and CA)	483
8.7.3	FDD (EPDCCH scheduling)	486
8.7.4	TDD (EPDCCH scheduling)	487
8.7.5	TDD FDD CA	489
8.7.5.1	Minimum Requirement FDD PCell	490
8.7.5.2	Minimum Requirement TDD PCell	494
8.7.6	FDD (DC)	498
8.7.7	TDD (DC)	502
8.8	Demodulation of EPDCCH	504

8.8.1	Distributed Transmission	504
8.8.1.1	FDD.....	504
8.8.1.1.1	Void.....	505
8.8.1.2	TDD	505
8.8.1.2.1	Void.....	506
8.8.2	Localized Transmission with TM9	506
8.8.2.1	FDD.....	506
8.8.2.1.1	Void.....	507
8.8.2.1.2	Void.....	507
8.8.2.2	TDD	507
8.8.2.2.1	Void.....	509
8.8.2.2.2	Void.....	509
8.8.3	Localized transmission with TM10 Type B quasi co-location type.....	509
8.8.3.1	FDD.....	509
8.8.3.2	TDD	511
8.9	Demodulation (single receiver antenna).....	513
8.9.1	PDSCH	513
8.9.1.1	FDD and half-duplex FDD (Fixed Reference Channel).....	513
8.9.1.1.1	Transmit diversity performance (Cell-Specific Reference Symbols)	514
8.9.1.1.2	Closed-loop spatial multiplexing performance (Cell-Specific Reference Symbols)	514
8.9.1.1.3	Closed-loop spatial multiplexing performance (User-Specific Reference Symbols)	515
8.9.1.2	TDD (Fixed Reference Channel)	516
8.9.1.2.1	Transmit diversity performance (Cell-Specific Reference Symbols).....	517
8.9.1.2.2	Closed-loop spatial multiplexing performance (Cell-Specific Reference Symbols)	518
8.9.1.2.3	Closed-loop spatial multiplexing performance (User-Specific Reference Symbols)	518
8.9.2	PHICH	520
8.9.2.1	FDD and half-duplex FDD.....	520
8.9.2.1.1	Transmit diversity performance.....	520
8.9.2.2	TDD	520
8.9.2.2.1	Transmit diversity performance.....	520
8.9.3	PBCH.....	520
8.9.3.1	FDD and half-duplex FDD.....	520
8.9.3.1.1	Transmit diversity performance.....	520
8.9.3.2	TDD	521
8.9.3.2.1	Transmit diversity performance.....	521
8.10	Demodulation (4 receiver antenna ports).....	521
8.10.1	PDSCH	521
8.10.1.1	FDD (Fixed Reference Channel).....	521
8.10.1.1.1	Transmit diversity performance with 2Tx Antenna Ports (Cell-Specific Reference Symbols)	521
8.10.1.1.2	Open-loop spatial multiplexing performance with 2Tx Antenna Ports (Cell-Specific Reference Symbols).....	522
8.10.1.1.3	Closed-loop spatial multiplexing Enhanced Performance Requirements Type A - Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model (Cell-Specific Reference Symbols).....	522
8.10.1.1.4	Closed-loop spatial multiplexing performance, Multi-Layer Spatial Multiplexing 4 Tx Antenna Port (Cell-Specific Reference Symbols)	523
8.10.1.1.5	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model (User-Specific Reference Symbols).....	524
8.10.1.1.6	Dual-Layer Spatial Multiplexing (User-Specific Reference Symbols)	526
8.10.1.1.7	Open-loop spatial multiplexing, 3 Layer Multiplexing with 4 Tx Antenna Ports (Cell-Specific Reference Symbols).....	528
8.10.1.1.8	Closed-loop spatial multiplexing performance, 4 Layers spatial multiplexing 4 Tx antennas (Cell-Specific Reference Symbols)	528
8.10.1.1.9	4 Layer Spatial Multiplexing (User-Specific Reference Symbols)	529
8.10.1.2	TDD (Fixed Reference Channel)	531
8.10.1.2.1	Transmit diversity performance with 2Tx Antenna Ports (Cell-Specific Reference Symbols)	531
8.10.1.2.2	Open-loop spatial multiplexing performance with 2Tx Antenna Ports (Cell-Specific Reference Symbols).....	531
8.10.1.2.3	Closed-loop spatial multiplexing Enhanced Performance Requirements Type A - Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model (Cell-Specific Reference Symbols).....	532