



# SLOVENSKI STANDARD

## SIST EN 300 113 V2.2.1:2017

01-februar-2017

---

**Storitev kopenskih mobilnih komunikacij - Radijska oprema za prenos podatkov (oziroma govora), ki uporablja modulacijo s konstantno ali nekonstantno ovojnico in ima antenski priključek - Harmonizirani standard, ki zajema bistvene zahteve člena 3.2 direktive 2014/53/EU**

Land Mobile Service - Radio equipment intended for the transmission of data (and/or speech) using constant or non-constant envelope modulation and having an antenna connector - Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU

**STANDARD PREVIEW**  
(standards.iteh.ai)

[SIST EN 300 113 V2.2.1:2017](https://standards.iteh.ai/catalog/standards/sist/46347f86-2685-41dc-9caf-9978ee984b45/sist-en-300-113-v2-2-1-2017)

<https://standards.iteh.ai/catalog/standards/sist/46347f86-2685-41dc-9caf-9978ee984b45/sist-en-300-113-v2-2-1-2017>

**Ta slovenski standard je istoveten z: ETSI EN 300 113 V2.2.1 (2016-12)**

---

**ICS:**

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.070.01	Mobilni servisi na splošno	Mobile services in general

**SIST EN 300 113 V2.2.1:2017** en

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 300 113 V2.2.1:2017](https://standards.iteh.ai/catalog/standards/sist/46347f86-2685-41dc-9caf-9978ee984b45/sist-en-300-113-v2-2-1-2017)

<https://standards.iteh.ai/catalog/standards/sist/46347f86-2685-41dc-9caf-9978ee984b45/sist-en-300-113-v2-2-1-2017>

# ETSI EN 300 113 V2.2.1 (2016-12)



**Land Mobile Service;**  
**Radio equipment intended for the transmission of data**  
**(and/or speech) using constant or non-constant envelope**  
**modulation and having an antenna connector;**  
**Harmonised Standard covering the essential requirements**  
**of article 3.2 of the Directive 2014/53/EU**

---

Reference

REN/ERM-TGDMR-361

---

Keywords

antenna, data, harmonised standard, mobile, PMR, radio, regulation, speech, TDD, TDMA

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 300 113 V2.2.1:2017

<https://standards.iteh.ai/catalog/standards/sist/46347f86-2685-41dc-9caf-9978ee984444/sist-en-300-113-v2-2-1-2017>

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.  
**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	8
Foreword.....	8
Modal verbs terminology.....	8
1 Scope .....	9
2 References .....	9
2.1 Normative references .....	9
2.2 Informative references.....	10
3 Definitions, symbols and abbreviations .....	11
3.1 Definitions.....	11
3.2 Symbols.....	12
3.3 Abbreviations .....	12
4 General and operational requirements.....	13
4.1 General .....	13
4.1.1 Environmental profile .....	13
4.1.2 Choice of model for testing .....	13
4.1.2.0 General.....	13
4.1.2.1 Auxiliary test equipment .....	13
4.1.2.2 Declarations by the manufacturer .....	13
4.2 Mechanical and electrical design.....	14
4.2.1 General.....	14
4.2.2 Controls .....	14
4.2.3 Transmitter shut-off facility.....	14
4.3 Testing using bit streams or messages.....	14
4.4 Measuring continuous mode equipment.....	14
4.5 Measuring discontinuous mode equipment.....	14
4.6 Constant and non-constant envelope modulation.....	14
4.7 Combined full bandwidth analogue speech/full bandwidth digital equipment.....	15
5 Test conditions, power sources and ambient temperatures .....	16
5.1 Normal and extreme test conditions .....	16
5.2 Test power source.....	16
5.3 Normal test conditions.....	16
5.3.1 Normal temperature and humidity .....	16
5.3.2 Normal test power source .....	16
5.3.2.1 Mains voltage.....	16
5.3.2.2 Regulated lead-acid battery power sources used on vehicles.....	16
5.3.2.3 Other power sources.....	17
5.4 Extreme test conditions .....	17
5.4.1 Extreme temperatures .....	17
5.4.2 Extreme test source voltages.....	17
5.4.2.1 Mains voltage.....	17
5.4.2.2 Regulated lead-acid battery power sources used on vehicles.....	17
5.4.2.3 Power sources using other types of batteries.....	17
5.4.2.4 Other power sources.....	17
5.5 Procedure for tests at extreme temperatures.....	18
5.5.0 Thermal balance.....	18
5.5.1 Procedure for equipment designed for continuous transmission.....	18
5.5.2 Procedure for equipment designed for intermittent transmission .....	18
5.5.3 Testing of equipment that does not have an external 50 $\Omega$ RF connector (integral antenna equipment).....	18
6 General conditions of measurement .....	19
6.1 Arrangements for test signals applied to the receiver input.....	19
6.2 Receiver mute or squelch facility .....	19
6.3 Normal test signals (wanted and unwanted signals).....	19

6.3.1	Equipment measured as constant envelope angle modulation equipment .....	19
6.3.2	Equipment measured as non-constant envelope modulation equipment.....	20
6.4	Encoder for receiver measurements .....	20
6.5	Transceiver data interface.....	20
6.6	Impedance .....	21
6.7	Artificial antenna.....	21
6.8	Tests of equipment with a duplex filter .....	21
6.9	Facilities for access .....	21
6.9.1	Analogue access.....	21
6.9.2	Test points for bit stream measurements.....	21
6.9.3	Coupling arrangements .....	22
6.9.3.0	General .....	22
6.9.3.1	Arrangements for measurements with continuous bit streams .....	22
6.9.3.2	Arrangements for measurements with messages.....	22
6.10	Test site and general arrangements for measurements involving the use of radiated fields .....	22
6.11	Modes of operation of the transmitter for constant envelope equipment .....	22
7	Technical characteristics of the transmitter .....	23
7.1	Frequency error .....	23
7.1.0	General.....	23
7.1.1	Definition.....	23
7.1.2	Method of measurement .....	23
7.1.3	Limits.....	23
7.2	Transmitter power (conducted) .....	24
7.2.1	Definitions .....	24
7.2.1.1	Equipment measured as constant envelope angle modulation equipment.....	24
7.2.1.2	Equipment measured as non-constant envelope modulation equipment .....	24
7.2.2	Method of measurement .....	24
7.2.2.1	Equipment measured as constant envelope angle modulation equipment.....	24
7.2.2.2	Equipment measured as non-constant envelope modulation equipment .....	25
7.2.3	Limits.....	25
7.3	Maximum Effective radiated power.....	25
7.3.1	Definition.....	25
7.3.1.0	General .....	25
7.3.1.1	Equipment measured as constant envelope angle modulation equipment.....	25
7.3.1.2	Equipment measured as non-constant envelope modulation equipment .....	26
7.3.2	Methods of measurement.....	26
7.3.2.0	General .....	26
7.3.2.1	Equipment measured as constant envelope angle modulation equipment.....	27
7.3.2.2	Equipment measured as non-constant envelope modulation equipment .....	28
7.3.3	Limits.....	29
7.4	Adjacent and alternate channel power.....	30
7.4.1	Definition.....	30
7.4.2	Method of measurement .....	30
7.4.3	Limits.....	31
7.5	Unwanted emissions in the spurious domain.....	32
7.5.1	Definition.....	32
7.5.2	Method of measuring the power level .....	32
7.5.2.0	General .....	32
7.5.2.1	Equipment measured as constant envelope angle modulation equipment.....	33
7.5.2.2	Equipment measured as non-constant envelope modulation equipment .....	33
7.5.3	Method of measuring the effective radiated power.....	33
7.5.3.0	General .....	33
7.5.3.1	Equipment measured as constant envelope angle modulation equipment.....	34
7.5.3.2	Equipment measured as non-constant envelope modulation equipment .....	34
7.5.4	Limits.....	36
7.6	Intermodulation attenuation.....	37
7.6.1	Definition.....	37
7.6.2	Method of measurement .....	37
7.6.3	Limits.....	38
7.7	Transmitter attack time.....	38
7.7.1	Definition.....	38

7.7.2	Method of measurement .....	38
7.7.3	Limit .....	39
7.8	Transmitter release time .....	39
7.8.1	Definition.....	39
7.8.2	Method of measurement .....	39
7.8.3	Limits.....	40
7.9	Transient behaviour of the transmitter.....	40
7.9.1	Definitions .....	40
7.9.2	Timings, frequencies and powers .....	41
7.9.3	Methods of measurement.....	45
7.9.3.0	General .....	45
7.9.3.1	Time domain measurements of power and frequency.....	45
7.9.3.2	Test arrangement and characteristics of the FM modulation meter .....	46
7.9.3.3	Adjacent channel transient power measurements.....	46
7.9.3.3.1	Definition.....	46
7.9.3.3.2	Measurement method for constant envelope angle modulation equipment.....	46
7.9.3.3.3	Measurement method for non-constant envelope modulation equipment .....	47
7.9.3.3.4	Alternative measurement method using a spectrum analyser .....	48
7.9.3.4	Characteristics of the adjacent channel transient power measuring device.....	49
7.9.4	Limits.....	49
7.9.4.0	General .....	49
7.9.4.1	Time domain analysis of power and frequency for constant envelope transmissions .....	50
7.9.4.2	Adjacent and alternate channel transient power.....	50
7.9.4.2.1	Equipment measured as constant envelope angle modulation equipment .....	50
7.9.4.2.2	Equipment measured as non-constant envelope modulation equipment .....	50
8	Technical characteristics of the receiver .....	51
8.1	Maximum usable sensitivity (conducted) .....	51
8.1.1	Definition.....	51
8.1.2	Method of measurement .....	51
8.1.2.1	Method of measurement with continuous bit streams .....	51
8.1.2.2	Method of measurement with messages.....	52
8.1.2.3	Method of measurement with packets.....	52
8.1.3	Limits.....	53
8.2	Average usable sensitivity (field strength) .....	53
8.2.1	Definition.....	53
8.2.2	Method of measurement .....	53
8.2.3	Limits.....	54
8.3	Level of the wanted signal for the degradation measurements.....	54
8.4	Error behaviour at high input levels .....	55
8.4.1	Definition.....	55
8.4.2	Method of measurement .....	55
8.4.2.1	Method of measurement with continuous bit streams .....	55
8.4.2.2	Method of measurement with messages.....	55
8.4.2.3	Method of measurement with packets.....	56
8.4.3	Limits.....	56
8.5	Co-channel rejection.....	56
8.5.1	Definition.....	56
8.5.2	Method of measurement .....	57
8.5.2.1	Method of measurement with continuous bit streams .....	57
8.5.2.2	Method of measurement with messages.....	58
8.5.2.3	Method of measurement with packets.....	59
8.5.3	Limits.....	59
8.6	Adjacent channel selectivity.....	60
8.6.1	Definition.....	60
8.6.2	Method of measurement .....	60
8.6.2.1	Method of measurement with continuous bit streams .....	60
8.6.2.2	Method of measurement with messages.....	61
8.6.2.3	Method of measurement with packets.....	62
8.6.3	Limits.....	63
8.7	Spurious response rejection.....	63
8.7.1	Definition.....	63

8.7.2	Introduction to the method of measurement .....	63
8.7.3	Method of search over the "limited frequency range" .....	64
8.7.4	Method of measurement with continuous bit streams.....	65
8.7.5	Method of measurement with messages .....	65
8.7.6	Method of measurement with packets .....	66
8.7.7	Limits.....	67
8.8	Intermodulation response rejection .....	67
8.8.1	Definition.....	67
8.8.2	Method of measurement .....	68
8.8.2.1	Method of measurement with continuous bit streams .....	68
8.8.2.2	Method of measurement with messages.....	69
8.8.2.3	Method of measurement with packets.....	70
8.8.3	Limits.....	70
8.9	Blocking or desensitization .....	71
8.9.1	Definition.....	71
8.9.2	Method of measurement .....	71
8.9.2.1	Method of measurement with continuous bit streams .....	71
8.9.2.2	Method of measurement with messages.....	72
8.9.2.3	Method of measurement with packets.....	73
8.9.3	Limits.....	73
8.10	Spurious radiations .....	73
8.10.1	Definition.....	73
8.10.2	Method of measuring the power level .....	74
8.10.3	Method of measuring the effective radiated power.....	75
8.10.4	Limits.....	76
9	Duplex operation .....	77
9.1	Receiver desensitization (with simultaneous transmission and reception) .....	77
9.1.1	Definition.....	77
9.1.2	Desensitization measured with continuous bit streams.....	78
9.1.2.1	Method of measurement when the equipment has a duplex filter.....	78
9.1.2.2	Method of measurement when the equipment has to operate with two antennas.....	79
9.1.3	Limits.....	80
9.2	Receiver spurious response rejection (with simultaneous transmission and reception) .....	80
9.2.1	Definition.....	80
9.2.2	Method of measurement .....	80
9.2.3	Limits.....	82
10	Testing for compliance with technical requirements.....	82
10.1	Test conditions, power supply and ambient temperatures.....	82
10.2	Interpretation of the measurement results .....	82
<b>Annex A (normative):</b>	<b>Relationship between the present document and the essential requirements of Directive 2014/53/EU .....</b>	<b>84</b>
<b>Annex B (normative):</b>	<b>Radiated measurement.....</b>	<b>86</b>
B.1	Test sites and general arrangements for measurements involving the use of radiated fields .....	86
B.1.0	General .....	86
B.1.1	Anechoic chamber .....	86
B.1.2	Anechoic chamber with a conductive ground plane .....	87
B.1.3	Open Area Test Site (OATS) .....	88
B.1.4	Test antenna.....	89
B.1.5	Substitution antenna .....	89
B.1.6	Measuring antenna .....	90
B.2	Guidance on the use of radiation test sites .....	90
B.2.0	General .....	90
B.2.1	Verification of the test site .....	90
B.2.2	Preparation of the EUT.....	90
B.2.3	Power supplies to the EUT.....	90
B.2.4	Volume control setting for analogue speech tests .....	90
B.2.5	Range length.....	91



B.2.6	Site preparation .....	91
B.3	Coupling of signals.....	92
B.3.0	General .....	92
B.3.1	Data signals .....	92
B.3.2	Speech and analogue signals .....	92
B.3.2.0	General.....	92
B.3.2.1	Acoustic coupler description.....	92
B.3.2.2	Calibration .....	93
<b>Annex C (normative): Specification for some particular measurement arrangements.....</b>		<b>94</b>
C.1	Power measuring receiver specification.....	94
C.1.0	General .....	94
C.1.1	IF filter .....	94
C.1.2	Attenuation indicator.....	95
C.1.3	RMS value indicator.....	95
C.1.4	Oscillator and amplifier.....	95
C.2	Spectrum analyser specification.....	96
C.2.1	Adjacent and alternate channel power measurement.....	96
C.2.2	Unwanted emissions measurement.....	96
C.3	Integrating and power summing device .....	96
<b>Annex D (informative): Change History .....</b>		<b>97</b>
History .....		98

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 300 113 V2.2.1:2017](https://standards.iteh.ai/catalog/standards/sist/46347f86-2685-41dc-9caf-9978ee984b45/sist-en-300-113-v2-2-1-2017)

<https://standards.iteh.ai/catalog/standards/sist/46347f86-2685-41dc-9caf-9978ee984b45/sist-en-300-113-v2-2-1-2017>

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.3] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

(standards.iteh.ai)

National transposition dates	
Date of adoption of this EN:	7 December 2016
Date of latest announcement of this EN (doa):	31 March 2017
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 September 2017
Date of withdrawal of any conflicting National Standard (dow):	30 September 2018

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# 1 Scope

The present document covers the technical requirements for radio transmitters and receivers used in stations in the Private Mobile Radio (PMR) service.

It applies to use in the land mobile service, operating on radio frequencies between 30 MHz and 1 GHz, with channel separations of 12,5 kHz, 20 kHz and 25 kHz, intended for speech and/or data.

**Table 1: Radiocommunications service frequency bands**

	<b>Radiocommunications service frequency bands</b>
Transmit	30 MHz to 1 000 MHz
Receive	30 MHz to 1 000 MHz

It applies to equipment for continuous and/or discontinuous transmission of data and/or digital speech.

The equipment comprises a transmitter and associated encoder and modulator and/or a receiver and associated demodulator and decoder. The types of equipment covered by the present document are as follows:

- base station (equipment fitted with an antenna connector, intended for use in a fixed location);
- mobile station (equipment fitted with an antenna connector, normally used in a vehicle or as a transportable); and
- those handportable stations:
  - a) fitted with an antenna connector; or
  - b) without an external antenna connector, but fitted with a permanent internal or a temporary internal 50  $\Omega$  Radio Frequency (RF) connector which allows access to the transmitter output and the receiver input.

Handportable equipment without an external or internal RF connector and without the possibility of having a temporary internal 50  $\Omega$  RF connector is not covered by the present document.

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the Radio Equipment Directive [i.2] may apply to equipment within the scope of the present document.

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 086 (V2.1.2) (08-2016): "Land Mobile Service; Radio equipment with an internal or external RF connector intended primarily for analogue speech; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU".

- [2] ETSI EN 300 390 (V2.1.1) (03-2016): "Land Mobile Service; Radio equipment intended for the transmission of data (and speech) and using an integral antenna; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU".
- [3] Void.
- [4] Recommendation ITU-T O.153 (10-1992): "Basic parameters for the measurement of error performance at bit rates below the primary rate".
- [5] ANSI C63.5 (2006): "American National Standard for Calibration of Antennas Used for Radiated Emission Measurements in Electro Magnetic Interference".
- [6] IEC 60489-3 (1988): "Methods of measurement for radio equipment used in the mobile services. Part 3: Receivers for A3E or F3E emissions".
- [7] CEPT/ERC/REC 74-01E: "Unwanted emissions in the spurious domain" (Siófok 1998, Nice 1999, Sesimbra 2002, Hradec Kralove 2005).
- [8] Void.

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TR 102 273 (V1.2.1) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [i.2] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.

NOTE: Article 3.2 and article 10.8.

- [i.3] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.4] ETSI EN 300 793 (V1.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Presentation of equipment for type testing".
- [i.5] ETSI TR 100 028 (V1.4.1) (12-2001) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.6] ETSI TR 100 028-2 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".

## 3 Definitions, symbols and abbreviations


### 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

**50  $\Omega$** : 50 ohm non-reactive impedance

**adjacent channels**: channel offset from the wanted channel by the channel spacing (see figure 1)

**alternate channels**: two channels offset from the wanted channel by double the channel spacing (see figure 1)



**Figure 1: Adjacent and alternate channel definitions**

**angle modulation**: either phase modulation or frequency modulation

**base station**: equipment fitted with an antenna connector, for use with an external antenna, and intended for use in a fixed location

**bit**: binary digit

**block**: the smallest quantity of information that is sent over the radio channel

NOTE: A constant number of useful bits are always sent together with the corresponding redundancy bits.

**burst or transmission (physical)**: one or several packets transmitted between power on and power off of a particular transmitter

**conducted measurements**: measurements which are made using direct 50  $\Omega$  connection to the equipment under test

**data transmission systems**: systems which transmit and/or receive data and/or digitized voice

**handportable station**: equipment either fitted with an antenna connector or integral antenna, or both, normally used on a stand-alone basis, to be carried on a person or held in the hand

**integral antenna**: antenna designed to be connected to the equipment without the use of a 50  $\Omega$  external connector and considered to be part of the equipment

NOTE: An integral antenna may be fitted internally or externally to the equipment.

**message**: user data to be transferred in one or more packets in a session

**mobile station**: mobile equipment fitted with an antenna connector, for use with an external antenna, normally used in a vehicle or as a transportable station

**packet:** one block or a contiguous stream of blocks sent by one (logical) transmitter to one particular receiver or one particular group of receivers

**Peak Envelope Power (PEP):** mean power delivered to the artificial antenna during a radio frequency cycle at the highest crest of the modulation envelope

**radiated measurements:** measurements which involve the absolute measurement of a radiated field

**session:** set of inter-related exchange of packets occupying one or several windows or part thereof (if applicable)

NOTE: corresponds to a complete interactive procedure for interchanging data between users, comprising initiation, data transmission and termination procedures. The session can be short (e.g. 2 packets), or long (e.g. one full page of text).

**switching range:** maximum frequency range, as specified by the manufacturer, over which the receiver or the transmitter can be operated within the alignment range without reprogramming or realignment

**window:** set of inter-related transmissions which may be limited in time by an appropriate access protocol and corresponding occupation rules

## 3.2 Symbols

For the purposes of the present document, the following symbols apply:

D-M0, D-M1, etc. names of signals defined in clause 6.3.1 and clause 6.3.2.

NOTE: The symbols used in the clauses relating to transients and timings can be found in clause 7.9.1.

$f_{I1}$	1 <sup>st</sup> intermediate frequency
$f_{I2}$	2 <sup>nd</sup> intermediate frequency
$f_{In}$	n <sup>th</sup> intermediate frequency
$f_l$	frequency of the limited frequency range
$f_{LO}$	Local oscillator frequency
$T_{max}$	Maximum extreme test temperature
$T_{min}$	Minimum extreme test temperature
$V_{max}$	Maximum extreme test voltage
$V_{min}$	Minimum extreme test voltage

## 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ac	alternating current
BW	BandWidth
CBW	Channel BandWidth
CEPT	European Conference of Postal and Telecommunications administrations
CSP	Channel SeParation
CW	Continuous Wave
dB	decibel
dBc	decibels relative to the carrier power
dBm	dB relative to 1 mW in 50 ohms
dc	direct current
EC	European Community
emf	electromotive force
EU	European Union
EUT	Equipment Under Test
FM	Frequency Modulation
FSK	Frequency Shift Keying
GMSK	Gaussian Minimum Shift Keying

IEC	International Electrotechnical Commission
IF	Intermediate Frequency
ITU-T	International Telecommunication Union - Telecommunication Standardisation Sector
OATS	Open Area Test Site
PEP	Peak Envelope Power
PLL	Phase Locked Loop
PMR	Private Mobile Radio
RBW	Relative BandWidth
RF	Radio Frequency
rms	root mean square
Rx	Receiver
SINAD	Signal, Noise And Distortion
sr	switching range
Tx	Transmitter
VSWR	Voltage Standing Wave Ratio

---

## 4 General and operational requirements

### 4.1 General

#### 4.1.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the manufacturer, but as a minimum, shall be that specified in the test conditions contained in the present document.

(standards.iteh.ai)

#### 4.1.2 Choice of model for testing

SIST EN 300 113 V2.2.1:2017

##### 4.1.2.0 General

<https://standards.iteh.ai/catalog/standards/sist/46347f86-2685-41dc-9caf-9978ee984b45/sist-en-300-113-v2-2-1-2017>

Stand-alone equipment shall be complete with any ancillary equipment needed for testing.

If an equipment has several optional features, considered not to affect the RF parameters, then the tests need only be performed on the equipment configured with the combination of features considered to be the most complex.

Where practicable, equipment to be tested shall provide a 50  $\Omega$  connector for conducted RF power level measurements.

In the case of integral antenna equipment, if the equipment does not have an internal permanent 50  $\Omega$  connector then it is permissible to use a second sample of the equipment with a temporary antenna connector fitted to facilitate testing. Any such modified sample shall not be used for any radiated measurements, except as noted in clause 5.5.3.

The performance of the equipment to be tested shall be representative of the performance of the corresponding production model.

Guidance on the presentation of equipment is also given in ETSI EN 300 793 [i.4].

##### 4.1.2.1 Auxiliary test equipment

All necessary test signal sources, setting up instructions and other product information shall be made available with the equipment to be tested.

##### 4.1.2.2 Declarations by the manufacturer

All necessary setting up instructions and other product information shall be made available with the equipment to be tested, in accordance with article 10.8 of Directive 2014/53/EU [i.2].