

## SLOVENSKI STANDARD SIST EN 303 471 V1.1.1:2019

01-marec-2019

Okoljski inženiring (EE) - Metodologija merjenja energijske učinkovitosti in meritve za virtualizacijo omrežnih funkcij (NFV)

Environmental Engineering (EE) - Energy Efficiency measurement methodology and metrics for Network Function Virtualisation (NFV)

# iTeh STANDARD PREVIEW (standards.iteh.ai)

Ta slovenski standard je istoveten z. standard je istoveten z. standard sta

1e532266475b/sist-en-303-471-v1-1-1-2019

ICS:

19.040 Preskušanje v zvezi z

okoljem

27.015 Energijska učinkovitost.

Ohranjanje energije na

splošno

Environmental testing

Energy efficiency. Energy

conservation in general

SIST EN 303 471 V1.1.1:2019

en

SIST EN 303 471 V1.1.1:2019

# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 303 471 V1.1.1:2019 https://standards.iteh.ai/catalog/standards/sist/60b8969c-5f96-40fe-a83f-1e532266475b/sist-en-303-471-v1-1-1-2019 SIST EN 303 471 V1.1.1:2019

# ETSI EN 303 471 V1.1.1 (2019-01)



# Environmental Engineering (EE); Energy Efficiency measurement methodology and metrics for Network Function Virtualisation (NFV)

<u>SIST EN 303 471 V1.1.1:2019</u> https://standards.iteh.ai/catalog/standards/sist/60b8969c-5f96-40fe-a83f-1e532266475b/sist-en-303-471-v1-1-1-2019

#### Reference

#### DEN/EE-EEPS26

Keywords

energy efficiency, energy management, ICT, NFV

#### **ETSI**

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la

Teh Sous-Préfecture de Grasse (06) N° 7803/88/ IEW

(standards.iteh.ai)

#### Important notice

https://standards.iteh.ai/catalog/standards/sist/60b8969c-5f96-40fe-a83f-The present document can be downloaded from: http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at <a href="https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx">https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx</a>

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommiteeSupportStaff.aspx

#### Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019. All rights reserved.

**DECT**<sup>TM</sup>, **PLUGTESTS**<sup>TM</sup>, **UMTS**<sup>TM</sup> and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP**<sup>TM</sup> and **LTE**<sup>TM</sup> are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

**GSM**® and the GSM logo are trademarks registered and owned by the GSM Association.

# Contents

Intelle	ectual Property Rights	5		
Forev	word	5		
Modal verbs terminology				
Introd	luction	5		
1	Scope	6		
2	References	6		
2.1 2.2	Normative references			
	Informative references			
3 3.1	Definitions, symbols and abbreviations			
3.2	Symbols	9		
3.3	Abbreviations			
4 4.1	Network Function Virtualisation (NFV) configurations			
4.2	NFV and energy consumption	11		
5	NFV KPIs for energy efficiency			
5.1	Energy efficiency based on data transfer (KPI <sub>EE-transfer</sub> )	11		
5.1.1 5.1.2	GeneralData volume measured in bitsA.N.D.A.R.D.P.R.F.V.F.W	11		
5.1.3				
5.2	Data volume measured in packets	12		
6	Measurement conditions  General requirements SIST EN 303 471 V1.1.12019  Measurement period and ards. itch. ai/catalog/standards/sist/60b8969c-5f96-40fe-a83f-	12		
6.1	General requirements SISTEN 303 4/1 V1.1.1.2019  https://ctopdords.iteh.or/catalog/ctopdords/sigt/f/0189060c_5406_40fa_083f	12		
6.1.1 6.1.2	Detailed treatment of assessment periodist-en-303-471-v1-1-2019	12		
6.2	Renewable energy			
6.3	Measurement and test equipment			
7	Measurement methods	15		
7.1	Measurement method for KPI <sub>EE-bit_transfer</sub> and KPI <sub>EE-packet_transfer</sub>			
7.1.1	Definition of data volume			
7.1.2	Formulae			
7.1.3	Definition of terms	16		
8	Measurement report	16		
Anne	ex A (informative): History of network schematics	17		
Anne	ex B (informative): Milestones for NFV effectiveness	18		
B.1	Introduction	18		
B.2	Assessment	18		
B.3	Comparisons	19		
Histor	rv	20		

# List of figures

Figure 1: Updated schematic of fixed and mobile access networks	10
Figure 2: Schematic of KPI <sub>EE-transfer</sub>	11
Figure 3: Schematic showing application of $T_{KPI}$ , $T_{REPEAT}$ and $\Delta t$	13
Figure 4: Detailed treatment of assessment timing	14
Figure A.1: Schematic of fixed and mobile communication networks (June 2011)	17

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 303 471 V1.1.1:2019</u> https://standards.iteh.ai/catalog/standards/sist/60b8969c-5f96-40fe-a83f-1e532266475b/sist-en-303-471-v1-1-1-2019

# Intellectual Property Rights

#### **Essential patents**

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

#### **Trademarks**

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

#### **Foreword**

This European Standard (EN) has been produced by ETSI Technical Committee Environmental Engineering (EE).

(standards.iteh.ai) National transposition dates				
Date of adoption of this EN:  SIST EN 303 471 V1.1.1:2019  https://standards.iteh.ai/catalog/standards/sist/60b8969c-5f96-40fe-a83f- Date of latest announcement of this EN 6doa);6475b/sist-en-303-471-v1-1-1-2019  30 April 2019				
Date of latest publication of new National Store endorsement of this EN (dop/e):	tandard 31 October 2019			
Date of withdrawal of any conflicting Nation	nal Standard (dow): 31 October 2019			

## Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

## Introduction

The present document specifies the method and metrics to determine the energy efficiency of operational Network Function Virtualisation (NFV) applications and their associated infrastructure.

Any such implementation of NFV within the access network served is addressed by the general engineering and associated energy management KPIs of the access network itself as described in ETSI EN 305 200-2-2 [i.2], ETSI EN 305 200-2-3 [i.3] and ETSI GR NFV 001 [i.4].

## 1 Scope

The present document specifies the method and metrics to determine the energy efficiency of operational Network Function Virtualisation (NFV) applications and their associated infrastructure when that infrastructure is implemented outside the boundaries of the access fixed, cable and mobile networks which they serve.

#### The present document:

- Extends the Objective KPIs of ETSI EN 305 200-2-2 [i.2] (fixed access networks) and ETSI EN 305 200-2-3 [i.3] (mobile access networks) to assess the impact of NFV when applied to those networks as described in ETSI GR NFV 001 [i.4].
- Does not consider any assessment of energy saved by the implementation of NFV as there can be no timestamped comparison of an operational infrastructure from which functions have been removed to a virtualized environment.

NOTE: In an ICT network (e.g. a fixed access network) comprising many Network Distribution Nodes (NDNs) with different loading levels it is not clear that there will always be an energy consumption benefit - the more relevant benefit being network and operational flexibility (such as reduced maintenance or increased reliability).

#### The present document:

- Does not address the operational energy efficiency of specific Information Technology Equipment (ITE) such
  as servers which may provide NFV facilities. Other ETSI EN documents (e.g. ETSI EN 303 470 [i.1]) have
  been prepared to address such factors.
- Does not specify any assessment of the overall effectiveness of an NFV implementation although it contains information in an informative annex regarding the technical milestones that would be required for this to be addressed in a future revision of the present document.

The KPIs specified are primarily intended for trend analysis 7 not to enable comparison between individual implementations of NFV unless the conditions of operation are "similar" unless the conditions of operation are "similar" 1e532266475b/sist-en-303-471-v1-1-2019

### 2 References

#### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <a href="https://docbox.etsi.org/Reference/">https://docbox.etsi.org/Reference/</a>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

[1] ETSI ES 202 336-12: "Environmental Engineering (EE); Monitoring and control interface for infrastructure equipment (power, cooling and building environment systems used in telecommunication networks); Part 12: ICT equipment power, energy and environmental parameters monitoring information model".

7

#### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

[i.1]	ETSI EN 303 470: "Environmental Engineering (EE); Energy Efficiency measurement methodology and metrics for servers".
[i.2]	ETSI EN 305 200-2-2: "Access, Terminals, Transmission and Multiplexing (ATTM); Energy management; Operational infrastructures; Global KPIs; Part 2: Specific requirements; Sub-part 2: Fixed broadband access networks".
[i.3]	ETSI EN 305 200-2-3: "Access, Terminals, Transmission and Multiplexing (ATTM); Energy management; Operational infrastructures; Global KPIs; Part 2: Specific requirements; Sub-part 3: Mobile broadband access networks".
[i.4]	ETSI GR NFV 001: "Network Functions Virtualisation (NFV); Use Cases".
[i.5]	ETSI GS NFV 003: "Network Functions Virtualisation (NFV); Terminology for Main Concepts in NFV".
[i.6]	ETSI GS NFV-TST 008: "Network Functions Virtualisation (NFV) Release 2; Testing; NFVI Compute and Network Metrics Specification".
[i.7]	ISO/IEC 17788: "Information technology Cloud computing Overview and vocabulary".
[i.8]	Mandate M/462: "Standardisation mandate addressed to CEN, CENELEC and ETSI in the field of ICT to enable efficient energy use in fixed and mobile information and communication networks". 1e5322664/5b/sist-en-303-471-v1-1-1-2019
[i.9]	CEN-CENELEC-ETSI (12-2011): "Framework Document for ESO Response to EU Mandate M/462".
NOTE:	Available at <a href="https://portal.etsi.org/Portals/0/TBpages/ee/Docs/ESO%20response%20to%20M462%20phase%201%20">https://portal.etsi.org/Portals/0/TBpages/ee/Docs/ESO%20response%20to%20M462%20phase%201%20</a> .

# 3 Definitions, symbols and abbreviations

#### 3.1 Definitions

pdf.

For the purposes of the present document, the following terms and definitions apply:

**Base Station (BS):** radio access network component which serves one or more radio cells and interfaces the user terminal (through air interface) and a wireless network infrastructure

Base Station (BS) site: Network Distribution Node (NDN) which accommodates a Base Station (BS)

**Cloud Service Customer (CSC):** entity responsible for operation of a network services for cloud service users to consume

NOTE: Source: ISO/IEC 17788 [i.7] modified.

Cloud Service Provider (CSP): entity which makes cloud services available

NOTE: Source: ISO/IEC 17788 [i.7] modified.

ETSI EN 303 471 V1.1.1 (2019-01)

8

cloud service user: end user, or applications operating on their behalf, using cloud services

NOTE: Source: ISO/IEC 17788 [i.7] modified.

**core network:** functional elements (that is equipment and infrastructure) that enable communication between Operator Sites (OSs) or equivalent ICT sites

Customer Premises (CP): any location which is the sole responsibility of the customer

energy efficiency: relation between the useful output (telecom service, etc.) and energy consumption

**Fibre Node (FN):** device which performs a media conversion between an optical fibre cable link and a coaxial cable link in a cable access network

Head-End (HE): facility for receiving television signals for processing and distribution over a cable access network

ICT equipment: equipment providing data storage, processing and transport services

NOTE: A combination of Information Technology Equipment and Network Telecommunications Equipment.

**ICT site:** site containing structures or group of structures dedicated to the accommodation, interconnection and operation of ICT equipment together with all the facilities and infrastructures for power distribution and environmental control together with the necessary levels of resilience and security required to provide the desired service availability

**Information Technology Equipment (ITE):** equipment providing data storage, processing and transport services for subsequent distribution by Network Telecommunications Equipment (NTE)

**Last Operators Connection point (LOC):** interface to the fixed access transport networks of one or more operators from which cabling is routed to a customer network.

ARD PREVIEW

Network Data Centre (NDC): data centre embedded within the core network

NOTE: An NDC of a cable access network may be termed a master head-end.

Network Distribution Node (NDN): grouping of Network Teledommunications Equipment (NTE) within the boundaries of an access network providing distribution of service from an Operator Site (OS)

NOTE: Where all the NTE at a given location is under common governance, any supporting infrastructure for power distribution and environmental control together with the necessary levels of resilience and security required to provide the desired service availability is included as part of the NDN.

**Network Functions Virtualisation (NFV):** principle of separating network functions from the hardware they run on by using virtual hardware abstraction

NOTE: Source: ETSI GS NFV 003 [i.5].

**Network Functions Virtualisation Infrastructure (NFVI):** totality of all hardware and software components which build up the environment in which VNFs are deployed

NOTE: Source: ETSI GS NFV 003 [i.5] modified.

**Network Interface Unit (NIU):** principal device within customer premises allowing user access to the services provided by the cable access network

**Network Telecommunications Equipment (NTE):** equipment between the boundaries of, and dedicated to providing direct connection to, core and/or access networks

**Operator Site (OS):** premises accommodating Network Telecommunications Equipment (NTE) providing direct connection to the core and access networks and which may also accommodate Information Technology Equipment (ITE)

NOTE 1: An OS that is only connected to the core network is considered as a Network Data Centre (NDC).

NOTE 2: An OS of a cable access network may be termed a local head-end.

9

**Repeater (R):** device with two RF ports, both of which are intended to be connected to antennas, which is capable of receiving, amplifying and transmitting simultaneously in one direction a signal in a base station's transmit band and in the other direction a signal in the corresponding base station's receive band

**Terminal Equipment (TE):** principal device within customer premises allowing user access to the services provided by the fixed access network

User Equipment (UE): device allowing user access to the services provided by the mobile access network

NOTE: Examples of user equipment include a mobile phone, tablet, data modem and connected devices such as meter or actuator.

#### 3.2 Symbols

For the purposes of the present document, the following symbols apply:

 $\Delta t$  the maximum time variation between measurement points of the different Objective KPIs within a

given Global KPI

k assessment period index

data\_volume<sub>NFVI</sub> volume of data transported to and from the NFVI during an assessment period

 $EC_{NFVI}$  energy consumption of NFVI during an assessment period  $KPI_{EE-transfer}$  KPI of NFVI energy efficiency based on data volume  $T_{KPI}$  period of time over which  $KPI_{EE-transfer}$  is assessed

 $T_{REPEAT}$  the time between which the KPI are assessed to determine relevant trend information

# 3.3 Abbreviations STANDARD PREVIEW

For the purposes of the present document, the following abbreviations apply:

BS Base Station

CP Customer Premises SIST EN 303 471 V1.1.1.2019

CSC Cloudservice: Customerai/catalog/standards/sist/60b8969c-5f96-40fe-a83f-

CSP Cloud Service Provider266475b/sist-en-303-471-v1-1-1-2019

FN Fibre Node HE Head-End

ICT Information and Communications Technology

ITE Information Technology Equipment

KPI Key Performance Indicator LOC Last Operator Connection point

LON Last Operator Node

NDC Network Data Centre

NDN Network Distribution Node

NFV Network Functions Virtualisation

NFVI Network Functions Virtualisation Infrastructure

NIU Network Interface Unit

NTE Network Telecommunications Equipment

ODC Operator Data Centre

OS Operator Site R Repeater

TE Terminal Equipment UE User Equipment