

Draft **ETSI EN 300 487** V2.2.0 (2024-09)



**Satellite Earth Stations and Systems (SES);
Receive-Only Mobile Earth Stations (ROMES) providing data
communications operating in the 1,5 GHz frequency band;
Harmonised Standard for access to radio spectrum**

[ETSI EN 300 487 V2.2.0 \(2024-09\)](https://standards.iteh.ai/catalog/standards/etsi/233e7a29-6b5c-4a50-be48-b5e9cfec58cf/etsi-en-300-487-v2-2-0-2024-09)

<https://standards.iteh.ai/catalog/standards/etsi/233e7a29-6b5c-4a50-be48-b5e9cfec58cf/etsi-en-300-487-v2-2-0-2024-09>

Reference

REN/SES-00412

Keywordsdata, earth station, LMSS, MES, mobile, RO,
satellite**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
ETSI [Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#).

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	6
Introduction	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references.....	7
3 Definition of terms, symbols and abbreviations.....	8
3.1 Terms.....	8
3.2 Symbols.....	8
3.3 Abbreviations	8
4 Test conditions	8
4.1 Environment profile	8
4.2 Test report	9
4.3 Special Test Equipment (STE).....	9
4.4 Equipment Under Test (EUT)	9
5 Receiver requirements.....	9
5.1 Environmental conditions for testing	9
5.2 Radiated emission requirements.....	9
5.2.1 Purpose	9
5.2.2 Specification	9
5.2.3 Verification	10
5.3 Receiver Adjacent Channel Selectivity requirements	10
5.3.1 Purpose	10
5.3.2 Technical requirements	10
5.3.3 Conformance test	10
5.4 Receiver Blocking Characteristics requirements.....	11
5.4.1 Purpose	11
5.4.2 Technical requirements.....	11
5.4.3 Conformance test.....	11
6 Method of Testing Receiver requirements	11
6.1 Radiated emissions	11
6.2 Receiver Adjacent Channel Selectivity	11
6.2.1 General.....	11
6.2.2 Test arrangement	11
6.2.3 Test Procedures.....	12
6.3 Receiver Blocking Characteristics	12
6.3.1 General.....	12
6.3.2 Test arrangement	12
6.3.3 Test procedures.....	12
Annex A (informative): Relationship between the present document and the essential requirements of Directive 2014/53/EU	14
Annex B (normative): RF emissions - test procedure.....	15
B.1 Introduction	15
B.2 Measuring apparatus.....	15
B.3 Equipment Under Test (EUT).....	15

B.4	Special Test Equipment (STE).....	15
B.5	Measurement procedure	15
Annex C:	Void	18
Annex D (informative):	Applicability of parameters given in ETSI EG 203 336	19
Annex E (informative):	Maximum measurement uncertainty	23
Annex F (informative):	Bibliography	24
Annex G (informative):	Change history	25
History		26

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 300 487 V2.2.0 \(2024-09\)](https://standards.iteh.ai/catalog/standards/etsi/233e7a29-6b5c-4a50-be48-b5e9cfce58cf/etsi-en-300-487-v2-2-0-2024-09)

<https://standards.iteh.ai/catalog/standards/etsi/233e7a29-6b5c-4a50-be48-b5e9cfce58cf/etsi-en-300-487-v2-2-0-2024-09>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI Standardisation Request deliverable Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.1] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document is intended to cover the provisions of Directive 2014/53/EU [i.2] (RE Directive) article 3.2 which states that "...radio equipment shall be so constructed that it both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference".

Recital 10 of Directive 2014/53/EU [i.2] states that "*in order to ensure that radio equipment uses the radio spectrum effectively and supports the efficient use of radio spectrum, radio equipment should be constructed so that: in the case of a transmitter, when the transmitter is properly installed, maintained and used for its intended purpose it generates radio waves emissions that do not create harmful interference, while unwanted radio waves emissions generated by the transmitter (e.g. in adjacent channels) with a potential negative impact on the goals of radio spectrum policy should be limited to such a level that, according to the state of the art, harmful interference is avoided; and, in the case of a receiver, it has a level of performance that allows it to operate as intended and protects it against the risk of harmful interference, in particular from shared or adjacent channels, and, in so doing, supports improvements in the efficient use of shared or adjacent channel*".

Recital 11 of Directive 2014/53/EU [i.2] states that "*although receivers do not themselves cause harmful interference, reception capabilities are an increasingly important factor in ensuring the efficient use of radio spectrum by way of an increased resilience of receivers against harmful interference and unwanted signals on the basis of the relevant essential requirements of Union harmonisation legislation*".

As a consequence, the present document includes receiving parameters aiming to maximize the efficient use of radio spectrum.

[ETSI EN 300 487 V2.2.0 \(2024-09\)](#)

<https://standards.iteh.ai/catalog/standards/etsi/233e7a29-6b5c-4a50-be48-b5e9cfee58cf/etsi-en-300-487-v2-2-0-2024-09>

1 Scope

The present document specifies technical characteristics and methods of measurement for Receive-Only Mobile Earth Stations (ROMES) radio equipment operating under the Land Mobile Satellite Service (LMSS), in the frequency band 1 518 MHz to 1 559 MHz (space-to-earth band).

The ROMESs operate as part of a satellite system providing one-way data communications.

ROMESs could have several configurations, including:

- either Portable Equipment (PE) or Vehicle Installed Equipment (VIE);
- a number of modules including a display/control interface to the user.

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.2] is given in annex A.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Void.
- [2] [ETSI ETS 300 133-5 ed.2 \(11-1997\)](#): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Enhanced Radio MESSage System (ERMES); Part 5: Receiver conformance specification".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] [Commission Implementing Decision C\(2015\) 5376 final of 4.8.2015](#) on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.2] [Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014](#) on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.

[i.3] ETSI EG 203 336 (V1.2.1): "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

bearer type: carrier with certain bandwidth, certain modulation type and using certain error coding rate

effective receive operating band: receive band within 1 518 MHz to 1 559 MHz where the tests associated with table 3 are met

in-band signals: signals which are located in the operating band plus an offset of 10 MHz outside this operating band

operating frequency band: frequency range 1 518 MHz to 1 559 MHz

transition frequency: frequency which separates adjacent frequency ranges in a table of limits

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

BW	Bandwidth
CDMA	Code Division Multiple Access
CW	Continuous Wave
E_b/N_0	Energy per bit to noise power spectral density ratio
EC	European Commission
EFTA	European Free Trade Association
EIRP	Equivalent Isotropically Radiated Power
ETS	European Telecommunication Standard
EUT	Equipment Under Test
LMSS	Land Mobile Satellite Service
LO	Local Oscillator
LTE	Long Term Evolution
PE	Portable Equipment
QoS	Quality of Service
RED	Radio Equipment Directive
RF	Radio Frequency
ROMES	Receive-Only Mobile Earth Station
SNR	Signal to Noise Ratio
STE	Special Test Equipment
VIE	Vehicle Installed Equipment
VSWR	Voltage Standing Wave Ratio

4 Test conditions

4.1 Environment profile

The technical requirements of the present document apply under the environmental conditions described in clause 5.1.

4.2 Test report

The test report shall contain:

- the environmental parameters under which the tests were carried out;
- the results of the tests;
- all parameters and operational conditions;
- the value of the highest frequency conversion oscillator;
- measurement uncertainties.

4.3 Special Test Equipment (STE)

To enable the tests specified in the present document to be carried out, the use of STE, supplied by the manufacturer or system provider, may be necessary. Since the STE will be specific for the particular equipment, it is not possible to provide detailed specifications in the present document. However, the following baseline is provided:

- the STE shall enable the ROMES to tune to every channel in the operating frequency band, to enable spurious emissions to be measured;
- if the connection of the STE affects any of the parameters specified in the present document then the effects shall clearly be stated by the manufacturer.

4.4 Equipment Under Test (EUT)

The EUT shall include all units necessary for the intended operation.

5 Receiver requirements

5.1 Environmental conditions for testing

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be in accordance with its intended use. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the operational environmental profile defined by its intended use.

Tests defined in the present document shall be carried out at representative points within the boundary limits of the operational environmental profile defined by its intended use.

5.2 Radiated emission requirements

5.2.1 Purpose

To protect terrestrial and satellite radio services from emissions caused by ROMESs to which the present document applies.

5.2.2 Specification

The radiated power from the equipment, including its antenna, shall not exceed the limits in table 1.

Table 1

Frequency range (MHz) (see note)	EIRP limit (dBpW) (see note)	Measurement bandwidth (kHz)
30,0 to 1 000,0	33	100
1 000,0 to 1 518,0	43	100
1 518,0 to 1 559,0	17	3
1 559,0 to 12 750,0	43	100
12 750,0 to 21 200,0	48	100
21 200,0 to 40 000,0	60	100

NOTE: The lower limits shall apply at the transition frequency.

5.2.3 Verification

The equipment shall be tested according to the test procedure given in annex B. The upper frequency to which tests shall be performed shall be at least the 10th harmonic of the highest frequency conversion oscillator or ten times the highest operational frequency, whichever is greater.

5.3 Receiver Adjacent Channel Selectivity requirements

5.3.1 Purpose

To enable reception of a wanted signal in the presence of other signals in the adjacent channel.

Adjacent channel selectivity is a measure of a receiver's ability to receive a signal at its assigned channel frequency in the presence of a signal in the adjacent channel at a given frequency offset from the centre frequency of the assigned channel.

5.3.2 Technical requirements

The frequency offset and relative power level of the adjacent signal compared to the wanted signal shall take the values given in table 2. The adjacent signal shall occupy the same bandwidth as the wanted signal where BW is the wanted signal occupied bandwidth. There shall be no more than 0,5 dB degradation in the receiver signal to noise ratio under these conditions.

Table 2: Adjacent Channel frequency and power level

Signal	Centre frequency offset from wanted signal	Power level relative to wanted signal
Adjacent signal	BW	12 dB

5.3.3 Conformance test

Conformance tests shall be carried out in accordance with clause 6.2.