

SLOVENSKI STANDARD SIST EN 301 444 V2.2.1:2021

01-junij-2021

Satelitske zemeljske postaje in sistemi (SES) - Kopenske mobilne zemeljske postaje (LMES) in pomorske mobilne zemeljske postaje (MMES), ki zagotavljajo govorne in/ali podatkovne komunikacije in delujejo v frekvenčnih pasovih 1,5 GHz in 1,6 GHz - Harmonizirani standard za dostop do radijskega spektra

Satellite Earth Stations and Systems (SES) - Land Mobile Earth Stations (LMES) and Maritime Mobile Earth Stations (MMES) providing voice and/or data communications, operating in the 1,5 GHz and 1,6 GHz frequency bands - Harmonised Standard for access to radio spectrum eh STANDARD PREVIEW

(standards.iteh.ai)

SIST EN 301 444 V2.2.1:2021 https://standards.iteh.ai/catalog/standards/sist/1ca7156c-19e2-4c00-85e6-bb568a50a20e/sist-en-301-444-v2-2-1-2021

Ta slovenski standard je istoveten z: ETSI EN 301 444 V2.2.1 (2021-04)

ICS:

33.060.30 Radiorelejni in fiksni satelitski Radio relay and fixed satellite

komunikacijski sistemi communications systems

SIST EN 301 444 V2.2.1:2021 en

SIST EN 301 444 V2.2.1:2021

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 444 V2.2.1:2021 https://standards.iteh.ai/catalog/standards/sist/1ca7156c-19e2-4c00-85e6-bb568a50a20e/sist-en-301-444-v2-2-1-2021 SIST EN 301 444 V2.2.1:2021

ETSI EN 301 444 V2.2.1 (2021-04)



Satellite Earth Stations and Systems (SES);
Land Mobile Earth Stations (LMES) and
Maritime Mobile Earth Stations (MMES)
providing voice and/or data communications,
operating in the 1,5 GHz and 1,6 GHz frequency bands;
Harmonised Standard for access to radio spectrum

Reference REN/SES-00416

Keywords earth station, LMES, regulation, satellite

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la

Teh Sous-Préfecture de Grasse (06) N° 7803/88/ IEW

(standards.iteh.ai)

Important notice

https://standards.iteh.ai/catalog/standards/sist/1ca7156c-19e2-4c00-85e6-The present document can be downloaded from:

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommiteeSupportStaff.aspx

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021. All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M[™] logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intelle	ectual Property Rights	6
Forew	ord	6
Modal	l verbs terminology	6
Introd	uction	7
1	Scope	8
	References	
2.1	Normative references	
2.2	Informative references.	
	Definition of terms, symbols and abbreviations	
3.1	Terms	
3.2	Symbols	
3.3	Abbreviations	10
4	Technical requirement specifications	11
4.1	Environmental profile	
4.2	Conformance requirements	
4.2.0	Maximum EIRP	
4.2.0.1		
4.2.0.2	1	
4.2.0.3		11
4.2.1	Unwanted emissions outside the band 1 625,8 MHz to 1 661,2 MHz and outside the band	10
4211	1 667,3 MHz to 1 675,7 MHz tandards iteh ai	12
4.2.1.1 4.2.1.2		
4.2.1.2 4.2.1.3	~ r · · · · · · · · · · · · · · · · · ·	12 1 <i>1</i>
4.2.1. <i>3</i> 4.2.2	Maximum unwanted emissions within the band 1/625,8 MHz to 1/664,2 MHz and within the band	
7.2.2	1 667,3 MHz to 1 675,7 MHz8a50a20e/sist-en-301-444-v2-2-1-2021	
4.2.2.1		
4.2.2.2		
4.2.2.3	1	
4.2.3	Control and Monitoring Functions (CMF)	
4.2.3.1	General	15
4.2.3.2		
4.2.3.2		
4.2.3.2	1	
4.2.3.2		
4.2.3.3		
4.2.3.3		
4.2.3.3	1	
4.2.3.3 4.2.3.4		
4.2.3.4 4.2.3.4		
4.2.3.4 4.2.3.4		
4.2.3.4		
4.2.3.5		
4.2.3.5	` ' 1	
4.2.3.5		
4.2.3.5	1	
4.2.3.6	Network control commands	17
4.2.3.6		17
4.2.3.6		17
4.2.3.6		
4.2.3.7		
4.2.3.7		
4.2.3.7	.2 Specification	18

Annex A (informative): Relationship between the present document and the essential			
5.2.6.4.2	Maximum EIRP		
5.2.6.4.1	Test arrangements		
5.2.6.4	Procedure		
5.2.6.3	Test method.		
5.2.6.2	Test site		
5.2.6.1	General		
5.2.5.5 5.2.6	EIRP		
5.2.5.2 5.2.5.3	Test procedures		
5.2.5.1	Test arrangement		
5.2.5 5.2.5.1	Receiver Blocking Characteristics		
5.2.4.3 5.2.5	Test procedures		
	Test procedures		
5.2.4.1 5.2.4.2	General Test arrangement		
5.2.4	Receiver Adjacent Channel Selectivity		
5.2.3.8.1	Test method		
5.2.3.8	Initial burst transmission		
5.2.3.7.1	Test method		
5.2.3.7	Network control commands		
5.2.3.6.1	Test method		
5.2.3.6	Control Channel (CC) reception		
5.2.3.5.1	Test method		
5.2.3.5	Power-on/Reset		
5.2.3.4.1	Test method		
5.2.3.4	Transmit subsystem monitoring	25	
5.2.3.3.1	Test method	25	
5.2.3.3	Processor monitoring to the hard and a standards/sixt/1ea7156c-19e2-4c00-85e6-	25	
5.2.3.2	Test arrangement		
5.2.3.1	General		
5.2.3	LMES and MMES Control and Monitoring Functions (CMF)	24	
5.2.2.4.3	Unwanted emissions above 1 000 MHz	23	
5.2.2.4.2	Test arrangements	23	
5.2.2.4.1			
5.2.2.4	Procedure		
5.2.2.3.1	Receive test equipment		
5.2.2.3.1	Installation		
5.2.2.3	Test method.		
5.2.2.1	Test site		
5.2.2.1	General		
5.2.1	Measurement of unwanted emissions		
5.2 5.2.1	Radio test suites		
5.1	Environmental conditions for testing		
	esting for compliance with technical requirements		
4.2.6.3	Conformance test		
4.2.6.2	Specification		
4.2.6.1	Justification		
4.2.6	Receiver Blocking Characteristics		
4.2.5.3	Conformance test		
4.2.5.1	Specification		
4.2.5 4.2.5.1	Receiver Adjacent Channel Selectivity		
4.2.4.3 4.2.5	Conformance test		
4.2.4.2	Technical requirements		
4.2.4.1	Purpose		
	the band 1 668,0 MHz to 1 670,0 MHz	18	
4.2.4	Protection of the radio astronomy service operation in the band 1 660,0 MHz to 1 660,5 MHz an		
4.2.3.7.3	Conformance test		

5

ETSI EN 301 444 V2.2.1 (2021-04)

Annex B (informative):	Maximum Measurement Uncertainty	33
Annex C (informative):	Applicability of parameters given in ETSI EG 203 336	34
Annex D (informative):	Bibliography	38
Annex E (informative):	Change history	39
History		40

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 444 V2.2.1:2021 https://standards.iteh.ai/catalog/standards/sist/1ca7156c-19e2-4c00-85e6-bb568a50a20e/sist-en-301-444-v2-2-1-2021

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.3] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.6].https://standards.iteh.ai/catalog/standards/sist/1ca7156c-19e2-4c00-85e6-

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

National transposition dates			
Date of adoption of this EN:	12 April 2021		
Date of latest announcement of this EN (doa):	31 July 2021		
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2022		
Date of withdrawal of any conflicting National Standard (dow):	31 January 2023		

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Introduction

Following the WRC-03 decision [i.4] to allocate to MSS the bands 1 518 MHz to 1 525 MHz (space to Earth) and 1 668 MHz to 1 675 MHz (Earth to space) and the conclusions of WRC-07 [i.5], a new set of emission requirements for LMESs and MMESs that are capable of transmitting in the frequency band from 1 668,0 MHz to 1 675,0 MHz is specified.

The two parts of the L-band frequency allocations are treated as two sub-bands which may be used separately or in any combination. The standard L-band allocation is referenced in the present document as "sub-band 1" and the extended L-band is referenced as "sub-band 2".

Table 2c is applicable for LMESs and MMESs that are capable of transmitting in any combination of either or both of these sub-bands. Table 2c is recommended for all new LMESs and MMESs including LMES and MMES that can only operate in sub-band 1.

The manufacturer may choose between tables 2b and 2c for new LMESs and MMES that are capable of transmitting in only the sub-band 1. The manufacturer has to declare which alternative is used.

The present document specifies a new set of receiver performance requirements for LMESs and MMESs under the new Radio Equipment Directive 2014/53/EU [i.6].

Figure 1: Void

The present document is intended to cover the provisions of Directive 2014/53/EU [i.6] (RE Directive) article 3.2 which states that "....radio equipment shall be so constructed that it both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference".

Recital 10 of Directive 2014/53/EU [i.6] states that "in order to ensure that radio equipment uses the radio spectrum effectively and supports the efficient use of radio spectrum, radio equipment should be constructed so that: in the case of a transmitter, when the transmitter is properly installed, maintained and used for its intended purpose it generates radio waves emissions that do not create harmful interference, while unwanted radio waves emissions generated by the transmitter (e.g. in adjacent channels) with a potential negative impact on the goals of radio spectrum policy should be limited to such a level that, according to the state of the art, harmful interference is avoided; and, in the case of a receiver, it has a level of performance that allows it to operate as intended and protects it against the risk of harmful interference, in particular from shared or adjacent channels, and, in so doing, supports improvements in the efficient use of shared or adjacent channels".

Recital 11 of Directive 2014/53/EU [i.6] states that "although receivers do not themselves cause harmful interference, reception capabilities are an increasingly important factor in ensuring the efficient use of radio spectrum by way of an increased resilience of receivers against harmful interference and unwanted signals on the basis of the relevant essential requirements of Union harmonisation legislation".

As a consequence, the present document includes both transmitting and receiving parameters aiming to maximize the efficient use of radio spectrum.

1 Scope

The present document applies to Land Mobile Earth Stations (LMESs) and Maritime Mobile Earth Stations (MMESs) radio equipment with an EIRP of greater than or equal to 15 dBW and less than or equal to 33 dBW and which have the following characteristics:

- the LMES could be either vehicle mounted or portable equipment;
- these MMESs are installable equipment on ships;
- these LMESs and MMESs are controlled and monitored by a Network Control Facility (NCF). The NCF is outside the scope of the present document;
- the LMES and MMES operate through geostationary satellites as part of a network providing voice and/or data communications:
- these LMESs and MMESs operate with user bit-rates greater than 9,6 kbits/s;
- the LMES and MMESs are capable of operating in any combination of all or any part of the frequency ranges sub-band 1 and sub-band 2 defined in table 1a.

Table 1a: Land and Maritime Mobile Satellite Service frequency bands

Sub-Band	Direction of transmission	LMSS frequency bands
1	Transmit 1 (Earth to space)	1 626,5 MHz to 1 660,5 MHz
'	Receive 1 (space to Earth)	1 525,0 MHz to 1 559,0 MHz
2 • 1 0	Transmit 2 (Earth to space)	1 668 0 MHz to 1 675,0 MHz
² 11en S	Receive 2 (space to Earth)	1 518,0 MHz to 1 525,0 MHz

(standards.iteh.ai)

The present document is intended to cover the provisions of Directive 2014/53/EU [i.6] (RE Directive) article 3.2 which states that "....radio equipment shall be so constructed that it both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference" standards/sist/1ca7156c-19e2-4c00-85e6-

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.6] is given in annex A.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at https://docbox.etsi.org/Reference/.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Void.
- [2] CISPR 16-1-4 (2019): "Specification for radio disturbance and immunity measuring apparatus and methods Part 1-4: Radio disturbance and immunity measuring apparatus Antennas and test sites for radiated disturbance measurements".
- [3] Void.

ETSI EN 301 444 V2.2.1 (2021-04)

- [4] Void.
- [5] Void.
- [6] Void.

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Void.
- [i.2] Void.
- [i.3] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.4] World Radiocommunication Conference 2003 (WRC-03) Final Acts.
- [i.5] World Radiocommunication Conference 2007 (WRC-07) Finals Acts.
- [i.6] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC (RE Directive) \$566-
- [i.7] bb568a50a20e/sist-en-301-444-v2-2-1-2021
 The latest version of the ITU Master International Frequency Register (MIFR), available from the
 - ITU website.
- [i.8] ETSI EG 203 336 (V1.2.1): "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the terms given in Directive 2014/53/EU [i.6] and the following apply:

antenna transmit gain: ratio, expressed in decibels, of the power that would have to be supplied to an isotropic radiator to the power supplied to the antenna being considered, so that they produce the same field strength at the same distance in the same direction

carrier-off state: state in which the LMES or MMES is not transmitting a carrier

carrier-on state: state in which the LMES or MMES is transmitting a carrier

Control Channel (CC): channel or channels by which LMES and MMES receive control information from the NCF for their network

effective receive operating band: receive band within 1 518 MHz to 1 559 MHz where the tests associated with table 5 are met; the effective receive operating band shall be indicated by the manufacturer

10

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

Externally Mounted Equipment (EME): equipment consisting of those of the modules of the Installable Equipment (IE) which are intended to be mounted externally to the vehicle as stated by the manufacturer

in-band signals: signals which are located in the operating band plus an offset of 10 MHz outside this operating band

Installable Equipment (IE): equipment which is intended to be fitted to a vehicle

NOTE: An IE may consist of one or several interconnected modules.

Internally Mounted Equipment (IME): modules of the IE which are not declared by the manufacturer as EME are defined as Internally Mounted Equipment (IME)

manufacturer: any natural or legal person who manufactures radio equipment or has radio equipment designed or manufactured, and markets that equipment under his name or trade mark

nominated bandwidth: bandwidth of the LMES or MMES radio frequency transmission nominated by the manufacturer

NOTE:

The nominated bandwidth is wide enough to encompass all spectral elements of the transmission which have a level greater than the specified unwanted emissions limits. The nominated bandwidth is wide enough to take account of the transmit carrier frequency stability. The nominated bandwidth is within the transmit frequency band within which the LMES and MMES operates.

operating band: frequency range over which the receiving equipment is able to operate as intended

Portable Equipment (PE): equipment generally intended to be self-contained, free standing and portable

NOTE: A PE would normally consist of a single module, but may consist of several interconnected modules. (standards.iteh.ai)

sub-band: contiguous portion of the operating band

NOTE: Two sub-bands are defined (see table 1a).01 444 V2.2.1.2021

https://standards.iteh.ai/catalog/standards/sist/1ca7156c-19e2-4c00-85e6-

transition frequency: frequency which separates adjacent frequency tranges and table of limits

unwanted emissions: emissions falling outside the nominated bandwidth

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

BER Bit Error Rate
BW BandWidth
CC Control Channel

CDMA Code-Division Multiple Access

CISPR International Special Committee on Radio Interference

CMF Control and Monitoring Functions

CW Continuous Wave

EFTA European Free Trade Association
EIRP Equivalent Isotropically Radiated Power

EMC ElectroMagnetic Compatibility
EME Externally Mounted Equipment

ETS European Telecommunication Standard

EUT Equipment Under Test IE Installable Equipment

IME Internally Mounted Equipment

LMES Land Mobile Earth Station
LMSS Land Mobile Satellite Service

LO Local Oscillator
LTE Long Term Evolution
MES Mobile Earth Station

MMES Maritime Mobile Earth Station
MSS Mobile Satellite Service
NCF Network Control Facility
PE Portable Equipment

R&TTE Radio and Telecommunications Terminal Equipment

RA Radio Astronomy RE Radio Equipment

RED Radio Equipment Directive

RF Radio Frequency
SNR Signal to Noise Ratio
STE Special Test Equipment
TBR Technical Basis for Regulation

TC-SES Technical Committee-Satellite Earth Stations and Systems

WRC World Radiocommunication Conference

4 Technical requirement specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be in accordance with its intended use. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the operational environmental profile defined by its intended use. The environmental profile for operation of the equipment shall include the ranges of humidity, temperature and supply voltage. 2.2.12021

https://standards.iteh.ai/catalog/standards/sist/1ca7156c-19e2-4c00-85e6-

bb568a50a20e/sist-en-301-444-v2-2-1-2021

4.2 Conformance requirements

4.2.0 Maximum EIRP

4.2.0.1 Justification

Protection of other radio services from in band emissions.

4.2.0.2 Specification

The EIRP of the LMES and MMES shall not exceed 33 dBW.

4.2.0.3 Conformance test

Conformance test shall be carried out in accordance with clause 5.2.6.