



**Digital cellular telecommunications system (Phase 2+) (GSM);
Functional stage 2 description of
Location Services (LCS) in GERAN
(3GPP TS 43.059 version 13.2.0 Release 13)**

PREVIEW
iteh.ai
https://standards.iteh.ai/standard/0cca453c-
c460-4ff9-86e3-666dd6200000/ETSI-143-059-V13.2.0-
2016-08-08

Reference

RTS/TSGG-0143059vd20

Keywords

GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

| | |
|-----------------------------------------------------------------------------------|----|
| Intellectual Property Rights | 2 |
| Foreword..... | 2 |
| Modal verbs terminology..... | 2 |
| Foreword..... | 7 |
| 1 Scope | 8 |
| 2 References | 8 |
| 3 Definitions and abbreviations..... | 10 |
| 3.1 Definitions | 10 |
| 3.2 Abbreviations | 11 |
| 4 Main concepts | 12 |
| 4.1 Assumptions | 12 |
| 4.2 Standard LCS Methods | 12 |
| 4.2.1 Timing Advance | 12 |
| 4.2.2 Enhanced Observed Time Difference (E-OTD) positioning mechanism..... | 12 |
| 4.2.3 Global Navigation Satellite System (GNSS) based positioning mechanism | 12 |
| 4.2.4 Uplink Time Difference of Arrival (U-TDOA) positioning mechanism | 13 |
| 5 GERAN LCS Architecture | 13 |
| 5.1 LCS Operations | 14 |
| 5.2 High-Level Functions..... | 15 |
| 5.2.1 Co-ordination, Measurement and Calculation Functions..... | 15 |
| 5.3 GERAN LCS Functional Entities..... | 16 |
| 5.3.1 Internal Client Group | 16 |
| 5.3.1.1 Internal GERAN Location Client Function (LCF)..... | 16 |
| 5.3.2 GERAN System Handling group..... | 16 |
| 5.3.2.1 GERAN Location System Control Function (LSCF)..... | 16 |
| 5.3.2.2 GERAN Location System Operations Function (LSOF) | 16 |
| 5.3.2.3 Location System Broadcast Function (LSBcF)..... | 16 |
| 5.3.3 Positioning group..... | 17 |
| 5.3.3.1 GERAN Position Radio Co-ordination Function (PRCF)..... | 17 |
| 5.3.3.2 GERAN Position Calculation Function (PCF)..... | 17 |
| 5.3.3.3 GERAN Position Signal Measurement Function (PSMF) | 18 |
| 5.3.3.4 GERAN Position Radio Resource Management (PRRM) | 18 |
| 5.4 Assignment of LCS Functional Entities to GERAN Elements..... | 18 |
| 5.5 Functional Description of GERAN LCS Network Elements | 18 |
| 5.5.1 BSC..... | 18 |
| 5.5.2 SMLC | 18 |
| 5.5.3 CBC | 19 |
| 5.5.4 LMU | 19 |
| 5.5.5 MS | 19 |
| 6 Signalling Protocols and Interfaces | 19 |
| 6.1 Protocol layering in A/Gb mode..... | 19 |
| 6.1.1 Generic Signalling Model..... | 19 |
| 6.1.2 Message Segmentation in A/Gb mode..... | 20 |
| 6.1.2.1 Network Level Segmentation..... | 20 |
| 6.1.2.2 Intermediate Level Segmentation..... | 21 |
| 6.1.2.3 RRLP Pseudo-Segmentation | 21 |
| 6.1.3 Signalling between an SMLC, MSC and BSC..... | 21 |
| 6.1.3a Signalling between an SMLC, SGSN and BSS | 21 |
| 6.1.4 Signaling between SMLC and MS | 22 |
| 6.1.5 SMLC Signalling to a Type A LMU | 23 |
| 6.1.5.1 Circuit Switched Signalling using an SDCCH..... | 23 |

| | | |
|---------|-----------------------------------------------------------------------------------------------------------------------------------|----|
| 6.1.5.2 | Signalling using a TCH..... | 23 |
| 6.1.6 | SMLC signalling to a Type B LMU | 24 |
| 6.1.7 | SMLC Signalling to a peer SMLC..... | 25 |
| 6.2 | Protocol layering in Iu mode | 25 |
| 6.2.1 | Signalling between SMLC and MSC/SGSN | 25 |
| 6.2.2 | Signalling between SMLC and MS | 26 |
| 6.2.3 | SMLC signalling to a Type A LMU | 27 |
| 6.2.4 | SMLC signalling to a Type B LMU | 27 |
| 6.2.5 | SMLC signalling to a peer SMLC | 27 |
| 7 | GERAN Network Location Procedures | 27 |
| 7.1 | State description for SMLC..... | 27 |
| 7.1.1 | SMLC States | 27 |
| 7.1.1.1 | NULL State | 27 |
| 7.1.1.2 | LOCATION State | 27 |
| 7.1.2 | State Functionality | 28 |
| 7.1.2.1 | State Transitions..... | 28 |
| 7.1.2.2 | LOCATION Timer Function | 28 |
| 7.2 | State Description for the BSC | 28 |
| 7.2.1 | BSC States | 28 |
| 7.2.1.1 | IDLE State..... | 28 |
| 7.2.1.2 | LOCATION State | 28 |
| 7.2.2 | State Functionality | 29 |
| 7.2.2.1 | State Transitions..... | 29 |
| 7.2.2.2 | LOCATION Timer Function | 29 |
| 7.3 | Usage of SCCP Connection on the Lb interface in the CS domain in A/Gb mode | 29 |
| 7.3.1 | SCCP Connection for positioning of a target MS..... | 29 |
| 7.3.2 | SCCP connection to access a Type A LMU..... | 30 |
| 7.4 | Usage of SCCP Connection on the Lb interface in the PS domain in A/Gb mode..... | 30 |
| 7.4.1 | SCCP Connection for positioning of a target MS..... | 30 |
| 8 | Common Procedures to Support Positioning | 31 |
| 8.1 | Information Transfer between an SMLC and a Target MS in the CS Domain in A/Gb mode for E-OTD and A-GNSS positioning methods | 31 |
| 8.1a | Information Transfer between an SMLC and a Target MS in the PS Domain in A/Gb mode | 32 |
| 8.1b | Information Transfer between an SMLC and a Target MS in Iu Mode | 33 |
| 8.2 | Information Transfer between an SMLC and a BSC..... | 34 |
| 8.3 | Common Procedures to Support Access to an LMU..... | 34 |
| 8.3.1 | Location Update Procedure between an SMLC and a Type A LMU | 35 |
| 8.3.2 | IMSI Detach Procedure between an SMLC and a Type A LMU | 35 |
| 8.3.3 | LCS Information Transfer between an SMLC and a Type A LMU | 36 |
| 8.3.3.1 | Information Transfer using an SDCCH..... | 36 |
| 8.3.3.2 | Information Transfer using a TCH..... | 38 |
| 8.3.4 | LCS Information Transfer between an SMLC and a Type B LMU..... | 39 |
| 8.4 | Common Control Procedures for LMUs | 39 |
| 8.4.1 | Reset Procedure | 40 |
| 8.4.2 | Status Query Procedure | 40 |
| 8.4.3 | Status Update Procedure..... | 40 |
| 8.5 | Exception Procedures | 41 |
| 8.5.1 | Procedures in the SMLC..... | 41 |
| 8.5.2 | Procedures in an LMU | 42 |
| 8.5.3 | Procedures in the BSC in the CS Domain..... | 42 |
| 8.5.3.1 | General Procedures | 42 |
| 8.5.3.2 | Rejection of an SMLC Positioning Request..... | 42 |
| 8.5.3.3 | Interaction with Inter-BSC Handover | 42 |
| 8.5.3.4 | Interaction with Intra-BSC Handover and other RR Management Procedures..... | 43 |
| 8.5.3.5 | Priority of Handover and Other RR Management Procedures | 43 |
| 8.5.3.6 | Interaction with Segmentation support for Legacy MS..... | 43 |
| 8.5.3.7 | Overload..... | 43 |
| 8.5.4 | Procedures in the BSS in the PS Domain | 44 |
| 8.5.4.1 | General Procedures | 44 |
| 8.5.4.2 | Rejection of an SMLC Positioning Request..... | 44 |

| | | |
|-----------|--------------------------------------------------------------------------------------------------|----|
| 8.5.4.3 | Overload..... | 44 |
| 8.5.4.4 | Inter BSS Cell Change | 44 |
| 8.5.5 | Void | 45 |
| 8.6 | Procedures in the Target MS | 45 |
| 8.7 | Further Procedures for Handover | 45 |
| 9 | Positioning procedures | 45 |
| 9.1 | Positioning Procedure Initiation | 45 |
| 9.1.1 | Core Network Position Procedure Initiation over the A interface | 45 |
| 9.1.2 | Positioning Procedure Initiation from an Internal LCS Client for the CS Domain (A/Gb mode) | 46 |
| 9.1.3 | Core Network Position Procedure Initiation over the Gb interface | 46 |
| 9.1.4 | Positioning Procedure Initiation from Core Network (Iu mode) | 47 |
| 9.1.5 | Positioning Procedure Initiation from Internal LCS Client (Iu mode)..... | 47 |
| 9.2 | Common Positioning Procedure for CS Domain in A/Gb mode..... | 47 |
| 9.2a | Common Positioning Procedure for PS Domain in A/Gb mode | 48 |
| 9.2b | Common Positioning Procedure for Iu mode | 49 |
| 9.2c | GPRS Cell Change for the PS Domain in A/Gb mode..... | 50 |
| 9.2c.1 | Intra-BSS Cell Change..... | 50 |
| 9.2c.2 | Inter-BSS Cell Change..... | 50 |
| 9.3 | TA Based Positioning in CS Domain for A/Gb-mode | 51 |
| 9.3.1 | Definition of TA states | 51 |
| 9.3.1.1 | MS in IDLE State..... | 51 |
| 9.3.1.2 | MS in DEDICATED State | 51 |
| 9.3.2 | TA Positioning Procedure..... | 52 |
| 9.3.3 | Unsuccessful TA positioning procedure in BSC | 52 |
| 9.3a | TA Based Positioning in PS Domain for A/Gb-mode | 52 |
| 9.3a.1 | Definition of PS Domain TA Modes | 53 |
| 9.3a.1.1 | MS in Packet Idle Mode..... | 53 |
| 9.3a.1.2 | MS in Packet Transfer Mode | 53 |
| 9.3a.2 | TA Positioning Procedure..... | 53 |
| 9.3a.2a | TA Positioning Procedure for an MS in EC operation..... | 54 |
| 9.3a.3 | Unsuccessful TA positioning procedure in BSS | 55 |
| 9.4 | E-OTD and A-GNSS Positioning Procedures..... | 55 |
| 9.4.1 | General procedures | 55 |
| 9.4.2 | Positioning Request | 55 |
| 9.4.3 | Assistance Data Delivery | 56 |
| 9.4.3a | Positioning Capability Transfer | 57 |
| 9.4.4 | Error Handling for E-OTD and A-GNSS in CS Domain..... | 58 |
| 9.4.5 | Error Handling for the SMLC in CS Domain | 59 |
| 9.4.5a | Error Handling for E-OTD and A-GNSS in PS Domain | 59 |
| 9.4.6 | Broadcast of Assistance Data..... | 60 |
| 9.4.6.1 | Point-To-Multipoint Assistance Data Broadcast Flow..... | 60 |
| 9.4.6.2 | Ciphering..... | 61 |
| 9.4.6.2.1 | Algorithm | 61 |
| 9.4.6.3 | Deciphering key control and delivery to MS | 62 |
| 9.5 | U-TDOA Positioning Procedures..... | 64 |
| 9.5.0 | General..... | 64 |
| 9.5.1 | U-TDOA Positioning in CS Domain for A/Gb-mode..... | 64 |
| 9.5.1.1 | General Procedures | 64 |
| 9.5.1.2 | CS U-TDOA Messages and Procedures on the Lb Interface | 64 |
| 9.5.1.3 | RR Procedure effecting the CS U-TDOA channel description | 65 |
| 9.5.1.4 | BSC Error Handling during CS U-TDOA Positioning Procedure | 66 |
| 9.5.2 | U-TDOA Positioning in PS Domain for A/Gb-mode | 66 |
| 9.5.2.1 | Introduction | 66 |
| 9.5.2.2 | General Procedures | 66 |
| 9.5.2.2.1 | MS in packet idle mode | 67 |
| 9.5.2.2.2 | MS in packet transfer mode..... | 67 |
| 9.5.2.3 | PS U-TDOA Messages and Procedures on the Lb Interface | 67 |
| 9.5.2.4 | RLC/MAC Procedure affecting the PS U-TDOA TBF description | 68 |
| 9.5.2.5 | Error Handling during PS U-TDOA Positioning Procedure | 68 |
| 10 | Information storage | 69 |

10.1 SMLC69
10.2 Recovery and Restoration Procedures70
Annex A (informative): Change history71
History73

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/0cca453c-c460-4ff9-86e3-666dd6200073/etsi-ts-143-059-v13.2.0-2016-08>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/0c3453c-c460-4ff9-86e3-666dd6200073/etsi-ts-143-059-v13.2.0-2016-08>

1 Scope

The present document specifies the stage 2 of the LoCation Services (LCS) feature in GERAN, which provides the mechanisms to support mobile location services for operators, subscribers and third party service providers.

The purpose of this stage 2 specification is to define the GERAN LCS architecture, functional entities and operations to support location methods. This description is confined to the aspects of LCS within the GERAN and does not define nor describe the LCS entities or operations within the Core Network.

Location Services may be considered as a network provided enabling technology consisting of standardised service capabilities, which enable the provision of location applications. The application(s) may be service provider specific. The description of the numerous and varied possible location applications which are enabled by this technology are outside the scope of the present document. However, clarifying examples of how the functionality being described may be used to provide specific location services may be included.

This stage 2 specification covers the GERAN LCS functional model and entities, the location methods, state descriptions, and message flows.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 22.071: "Location Services (LCS); Service description - Stage 1".
- [3] 3GPP TS 22.101: "Service aspects; Service principles".
- [4] 3GPP TS 23.007: "Restoration procedures".
- [5] 3GPP TS 23.032: "Universal Geographical Area Description (GAD)".
- [6] 3GPP TS 23.041: "Technical realization of Cell Broadcast Service (CBS)".
- [7] 3GPP TS 23.271: "Functional stage 2 description of location services".
- [8] 3GPP TS 24.008: "Mobile Radio Interface Layer 3 specification; Core Network Protocols; Stage 3".
- [9] 3GPP TS 24.030: "Location Services (LCS); Supplementary service operations; Stage 3".
- [10] 3GPP TS 24.080: "Mobile radio Layer 3 Supplementary Services specification; Formats and coding".
- [11] 3GPP TS 43.051: "GSM/EDGE Radio Access Network (GERAN) overall description; Stage 2".
- [12] 3GPP TS 44.006: "Mobile Station - Base Station System (MS - BSS) interface; Data Link (DL) layer specification".
- [13] 3GPP TS 44.012: "Short Message Service Cell Broadcast (SMSCB) Support on the Mobile Radio Interface".

- [14] 3GPP TS 44.018: "Mobile radio interface layer 3 specification; Radio Resource Control Protocol".
- [15] 3GPP TS 44.031: "Location Services (LCS); Mobile Station (MS) - Serving Mobile Location Centre (SMLC) Radio Resource LCS Protocol (RRLP)".
- [16] 3GPP TS 44.035: "Location Services (LCS); Broadcast Network Assistance for Enhanced Observed Time Difference (E-OTD) and Global Positioning System (GPS) Positioning Methods".
- [17] 3GPP TS 44.071: "Location Services (LCS); Mobile Radio Interface Layer 3 Location Services (LCS) specification".
- [18] 3GPP TS 48.008: "Mobile-services Switching Centre - Base Station System (MSC - BSS) interface; Layer 3 specification".
- [19] 3GPP TS 48.031: "Location Services (LCS); Serving Mobile Location Centre - Serving Mobile Location Centre (SMLC - SMLC); SMLCPP specification".
- [20] 3GPP TS 48.058: "Base Station Controller - Base Transceiver Station (BSC - BTS) interface; Layer 3 specification".
- [21] 3GPP TS 48.071: "Serving Mobile Location Center – Base Station System (SMLC-BSS) interface; Layer 3 specification".
- [22] 3GPP TS 49.031: "Location Services (LCS); Base Station System Application Part LCS Extension (BSSAP-LE)".
- [23] TIA/EIA/IS-J-STD-036 (2000): "Emergency Services Data Communications".
- [24] 3GPP TS 48.016: "General Packet Radio Service (GPRS); Base Station System (BSS) - Serving GPRS Support Node (SGSN) interface; Network Service".
- [25] 3GPP TS 48.018: "General Packet Radio Service (GPRS); Base Station System (BSS) - Serving GPRS Support Node (SGSN); BSS GPRS Protocol (BSSGP)".
- [26] 3GPP TS 44.064: "Mobile Station - Serving GPRS Support Node (MS-SGSN) Logical Link Control (LLC) layer specification".
- [27] 3GPP TS 23.060: "General Packet Radio Service (GPRS); Service description; Stage 2".
- [28] 3GPP TS 44.060: "General Packet Radio Service (GPRS); Mobile Station (MS) - Base Station System (BSS) interface; Radio Link Control/Medium Access Control (RLC/MAC) protocol".
- [29] 3GPP TS 25.410: "UTRAN Iu Interface: General Aspects and Principles".
- [30] 3GPP TS 25.411: "UTRAN Iu Interface Layer 1".
- [32] 3GPP TS 25.412: "UTRAN Iu Interface signalling transport".
- [33] 3GPP TS 25.413: "UTRAN Iu Interface RANAP signalling".
- [34] 3GPP TS 44.118: "Mobile radio interface layer 3 specification; Radio Resource Control (RRC) Protocol Iu Mode".
- [35] IETF STD 51, RFC 1661(07/1994): "The Point-To-Point Protocol (PPP)".
- [36] IETF STD 51, RFC 1662(07/1994): "PPP in HDLC-like Framing".
- [37] IETF RFC 2507(02/1999): "IP header compression".
- [38] IETF RFC 1990(07/1994): "The PPP Multilink Protocol (MP)".
- [39] IETF RFC 2686(09/1999): "The Multi-Class Extension to Multi-Link PPP".
- [40] IETF RFC 2509(02/1999): "IP Header Compression over PPP".
- [41] 3GPP TS 43.064: "General Packet Radio Service (GPRS); Overall description of the GPRS radio interface; Stage 2".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document the following terms and definitions apply and the terms and definitions given in 3GPP TS 22.101.

A/Gb mode: see 3GPP TS 43.051 [11].

Coverage Class: see 3GPP TS 43.064 [41].

EC-GSM-IoT: see 3GPP TS 43.064 [41].

EC operation: see 3GPP TS 43.064 [41].

Iu mode: see 3GPP TS 43.051 [11].

LCS (LoCation Services): LCS is a service concept in system standardisation. LCS specifies all the necessary network elements and entities, their functionality, interfaces, as well as communication messages, necessary to implement the positioning functionality in a cellular network.

NOTE 1: LCS does not specify any location based (value added) services except locating of emergency calls.

LCS Client: software and/or hardware entity that interacts with a LCS Server for the purpose of obtaining location information for one or more Mobile Stations. LCS Clients subscribe to LCS in order to obtain location information. LCS Clients may or may not interact with human users. The LCS Client is responsible for formatting and presenting data and managing the user interface (dialogue). The LCS Client may reside in the Mobile Station (MS).

LCS Server: software and/or hardware entity offering LCS capabilities. The LCS Server accepts requests, services requests, and sends back responses to the received requests. The LCS server consists of LCS components, which are distributed to one or more PLMN and/or service provider.

Location Estimate: geographic location of an MS and/or valid Mobile Equipment (ME), expressed in latitude and longitude data. The Location Estimate shall be represented in a well-defined universal format. Translation from this universal format to another geographic location system may be supported, although the details are considered outside the scope of the primitive services.

Location Request: request for a Location Estimate and optionally a Velocity Estimate.

Mobile Assisted positioning: any mobile centric positioning method (e.g. E-OTD, A-GNSS) in which the MS provides position measurements to the network for computation of a location estimate by the network. The network may provide assistance data to the MS to enable position measurements and/or improve measurement performance.

Mobile Based positioning: any mobile centric positioning method (e.g. E-OTD, A-GNSS) in which the MS performs both position measurements and computation of a location estimate and where assistance data useful or essential to one or both of these functions is provided to the MS by the network. Position methods where an MS performs measurements and location computation without network assistance data are not considered within this category.

Mobile Station: consists of Mobile or User Equipment (ME or MS) with a valid SIM or USIM attached.

Positioning (/location detecting): positioning is a functionality, which detects a geographical location (of e.g. a mobile terminal).

Positioning technology (/locating technology): technology or system concept including the specifications of RF interfaces, data types, etc. to process the estimation of a geographical location, e.g. A-GNSS and E-OTD.

Radio Interface Timing: Comprise Absolute Time Differences (ATDs) or Real Time Differences (RTDs) of the signals transmitted by Base Stations, where timing differences are measured relative to either some absolute time difference (ATD) or the signals of another Base Station (RTD).

RRLP maximum PDU size: maximum PDU size for the RRLP protocol, which is 242 octets.

RRLP pseudo-segmentation: use of several RRLP data messages to deliver a large amount of information.

Target MS: Mobile Station being positioned.

Type A LMU: accessed exclusively over the air interface (Um interface): there is no wired connection to any other network element.

Type B LMU: is accessed over the Abis interface from a BSC. The LMU may be either a standalone network element addressed using some pseudo-cell ID or connected to or integrated in a BTS.

Velocity Estimate: speed and bearing of an MS and/or valid Mobile Equipment (ME), expressed as speed in kilometres per hour and bearing in degrees measured clockwise from North.

NOTE 2: Abis interface is beyond the scope of the present document.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations and the abbreviations given in 3GPP TS 21.905 apply.

| | |
|----------|--------------------------------------------------------|
| 2G- | Second Generation |
| 3G- | Third Generation |
| A | Interface between GERAN BSS and MSC |
| A-GNSS | Assisted GNSS |
| A-GPS | Assisted GPS |
| ATD | Absolute Time Difference |
| BDS | BeiDou Navigation Satellite System |
| BSSLAP | Base Station System Application Part |
| BSSAP-LE | Base Station System Application Part LCS Extension |
| CBC-BSC | Interface between CBC and BSC |
| CBC-SMLC | Interface between CBC and SMLC |
| D-GPS | Differential GPS |
| E-OTD | Enhanced Observed Time Difference |
| GNSS | Global Navigation Satellite System (e.g. GPS, Galileo) |
| Iu | Interface between GERAN BSS and 3G Core Network |
| Iu-cs | Interface between GERAN BSS and 3G MSC |
| Iu-ps | Interface between GERAN BSS and 3G SGSN |
| Gb | Interface between GERAN BSS and SGSN |
| Lb | Interface between SMLC and BSC |
| LCCF | Location Client Control Function |
| LCF | Location Client Function |
| LSBcF | Location System Broadcast Function |
| LSCF | Location System Control Function |
| LSOF | Location System Operation Function |
| PCF | Position Calculation Function |
| PRCF | Positioning Radio Co-ordination Function |
| PRRM | Positioning Radio Resource Management |
| PSMF | Positioning Signal Measurement Function |
| RIT | Radio Interface Timing |
| RRLP | Radio Resource Link Protocol |
| RTD | Real Time Difference |
| SMSCB | Short Message Service Cell Broadcast |
| SMLCPP | Serving Mobile Location Center Peer Protocol |
| TA | Timing Advance |
| UDT | SCCP Unitdata message |
| Um | GERAN Air Interface |
| UTC | Universal Coordinated Time |
| U-TDOA | Uplink Time Difference of Arrival |

4 Main concepts

A general description of location services and the service requirements is given in the specification 3GPP TS 22.071. By measuring radio signals the capability to determine the geographic location of the mobile station (MS) shall be provided. The location information may be requested by and reported to a client (application) associated with the MS, or by a client within or attached to the Core Network. The location information may also be utilised internally by GERAN, for example to support features such as home location billing. The location information shall be reported in standard formats, such as those for cell based or geographical coordinates of the location of the MS.

It shall be possible for the majority of the MS (active or idle) within a network to use the feature without compromising the radio transmission or signalling capabilities of the GERAN.

Four positioning mechanisms are supported for LCS: Timing Advance (TA), Enhanced Observed Time Difference (E-OTD), Global Navigation Satellite System (GNSS) based positioning (A-GNSS) and Uplink Time Difference Of Arrival (U-TDOA).

4.1 Assumptions

- SMLC is either an integrated functionality in BSS or a standalone network element within GERAN.
- LMU is either an integrated functionality in BTS (Type B LMU) or a standalone network element (Type A LMU) where communication is over the Um interface.

4.2 Standard LCS Methods

4.2.1 Timing Advance

The TA is based on the existing Timing Advance (TA) parameter. The TA value is known for the serving BTS. To obtain TA values in case the MS is in idle mode a special procedure, not noticed by the GSM subscriber (no ringing tone), is set up. The cell-ID of the serving cell and the TA is returned as the result of the TA.

TA may be used to assist all positioning mechanisms.

4.2.2 Enhanced Observed Time Difference (E-OTD) positioning mechanism

The E-OTD method is based on measurements in the MS of the Enhanced Observed Time Difference of arrival of bursts of nearby pairs of BTSs. For E-OTD measurement synchronization, normal and dummy bursts are used. When the transmission frames of BTSs are not synchronized, the network needs to measure the Real or Absolute Time Differences (RTDs or ATDs) between them. To obtain accurate trilateration, E-OTD measurements and, for non-synchronized BTSs, RTD or ATD measurements are needed for at least three distinct pairs of geographically dispersed BTSs. Based on the measured E-OTD values the location of MS can be calculated either in the network or in the MS itself, if all the needed information is available in MS.

4.2.3 Global Navigation Satellite System (GNSS) based positioning mechanism

Global Navigation Satellite System (GNSS) refers to satellite systems that are set up for positioning purposes. Systems belonging to this category, that are operational today or will be in the near future are e.g., GPS, Galileo, Satellite Based Augmentation Systems (SBAS), Modernized GPS, Quasi Zenith Satellite System (QZSS), GLONASS and BDS.

A mobile station with GNSS measurement capability may operate in an autonomous mode or in an assisted mode for example MS-assisted or MS-based mode. In autonomous mode MS determines its position based on signals received from GNSS without assistance from network. In assisted mode, MS receives assistance data from network. MS may support one or several GNSSs and the assistance data content may vary depending on this capability.

A-GNSS refers to a concept which supports several global navigation satellite systems and their different navigation signals, including e.g. GPS, Galileo, Satellite Based Augmentation Systems (SBAS), Modernized GPS, Quasi Zenith