

ETSI TS 145 005 V13.1.0 (2016-08)



TECHNICAL SPECIFICATION

**Digital cellular telecommunications system (Phase 2+) (GSM);
Radio transmission and reception
(3GPP TS 45.005 version 13.1.0 Release 13)**

Standard Preview
Full standards
https://standards.iteh.ai/catalog/standards/sist/8c3f1a69-d06e-4610-906a-8299737d11bd/etsi-ts-145-005-v13.1.0-2016-08



Reference

RTS/TSGG-0145005vd10

Keywords

GSM**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	10
1 Scope	11
1.1 References	12
1.2 Abbreviations	14
1.3 Definitions.....	14
2 Frequency bands and channel arrangement.....	15
3 Reference configuration	17
4 Transmitter characteristics	18
4.1 Output power.....	18
4.1.1 Mobile Station	18
4.1.2 Base station.....	23
4.1.2.1 Additional requirements for PCS 1 900 and MXM 1900 Base stations.....	25
4.1.2.2 Additional requirements for GSM 850 and MXM 850 Base stations.....	25
4.1.2.3 Additional requirements for GSM 700 Base stations.....	26
4.1.2.4 Additional requirements for ER-GSM 900 Base stations.....	26
4.1.2.4.1 Uncoordinated deployment.....	26
4.1.2.4.2 Coordinated deployment.....	26
4.2 Output RF spectrum	26
4.2.1 Spectrum due to the modulation and wide band noise.....	27
4.2.1.1 General requirements for all types of Base stations and MS.....	27
4.2.1.2 Additional requirements for multicarrier BTS	27
4.2.1.3 Tables for spectrum requirements due to modulation and wideband noise.....	28
4.2.1.4 Exceptions for spectrum due to modulation and wideband noise	32
4.2.1.4.1 Mobile Stations and Base Transceiver Stations except multicarrier BTS	32
4.2.1.4.2 Multicarrier BTS	33
4.2.2 Spectrum due to switching transients	34
4.2.2.1 General requirements.....	34
4.3 Spurious emissions	35
4.3.1 Principle of the specification	36
4.3.2 Base Transceiver Station	38
4.3.2.1 General requirements	38
4.3.2.2 Additional requirements for co-existence with GSM systems on other frequency bands.....	39
4.3.2.3 Additional requirements for co-existence with 3 G	40
4.3.3 Mobile Station	41
4.3.3.1 Mobile Station GSM 400, T-GSM 810, GSM 900, ER-GSM 900 and DCS 1 800	41
4.3.3.2 Mobile Station GSM 700, GSM 850 and PCS 1 900.....	42
4.4 Radio frequency tolerance.....	43
4.5 Output level dynamic operation	43
4.5.1 Base Transceiver Station	43
4.5.2 Mobile Station	43
4.6 Modulation accuracy	44
4.6.1 GMSK modulation.....	44
4.6.2 QPSK, AQPSK, 8-PSK, 16-QAM and 32-QAM modulations	44
4.6.2.1 RMS EVM	45
4.6.2.1.1 MS requirements	45
4.6.2.1.2 Requirements for BTS.....	45
4.6.2.2 Origin Offset Suppression.....	46
4.6.2.3 Peak EVM.....	46
4.6.2.4 95:th percentile.....	46
4.6.3 Phase and amplitude coherency when using blind physical layer transmissions.....	47

4.6.3.1	General	47
4.6.3.2	EC-GSM-IoT MS	47
4.6.3.3	BTS supporting EC-GSM-IoT	47
4.7	Intermodulation attenuation	47
4.7.1	Base transceiver station	47
4.7.2	Intra BTS intermodulation attenuation	47
4.7.2.1	GSM 400, GSM 900, ER-GSM 900, DCS 1800	48
4.7.2.1.1	Requirements for BTS except multicarrier BTS	48
4.7.2.1.2	Requirements for multicarrier BTS	48
4.7.2.2	MXM 850 and MXM 1900	48
4.7.2.3	GSM 700, GSM 850 and PCS 1900	49
4.7.3	Void	49
4.7.4	Mobile PBX (GSM 900 only)	49
5	Receiver characteristics	49
5.1	Blocking characteristics	50
5.1.1	Definitions of applicable frequency ranges	50
5.1.2	Requirements for MS	52
5.1.3	Requirements for BTS	54
5.1.4	Signal levels of blocking signal	55
5.1.5	Micro- and pico-BTS	60
5.2	AM suppression characteristics	60
5.2.1	Requirements for MS	60
5.2.2	Requirements for BTS	61
5.3	Intermodulation characteristics	62
5.3.1	Requirements for MS	62
5.3.2	Requirements for BTS	62
5.4	Spurious emissions	63
6	Transmitter/receiver performance	63
6.1a	MS conditions	63
6.1b	BTS conditions	64
6.1	Nominal Error Rates (NER)	66
6.1.1	GMSK modulation	66
6.1.1.1	General performance requirements	66
6.1.1.2	Requirements for MS	66
6.1.1.3	Requirements for BTS	66
6.1.2	QPSK/8-PSK modulation	67
6.1.2.1	Requirements for MS	67
6.1.2.2	Requirements for BTS	67
6.1.3	16-QAM/32-QAM modulation	68
6.1.3.1	Requirements for MS	68
6.1.3.2	Requirements for BTS	69
6.2	Reference sensitivity level	69
6.2.1	Circuit-switched channels	69
6.2.1a	Reference performance in VAMOS mode	72
6.2.2	Packet-switched channels	73
6.2.3	Flexible Layer One	75
6.2.4	Repeated associated control channel performance	75
6.2.4a	Extended Coverage control channel and data channel performance for EC-GSM-IoT	76
6.2.5	Enhanced MS receiver performance	76
6.2.6	Additional performance conditions	76
6.3	Reference interference level	77
6.3.1	GMSK modulated speech channels and associated control channels	77
6.3.2	Co-channel reference interference performance	78
6.3.2.1	MS requirements	78
6.3.2.2	BTS requirements	78
6.3.3	Adjacent channel reference interference performance	79
6.3.3.1	Normal symbol rate used	79
6.3.3.1.1	MS requirements	79
6.3.3.1.2	BTS requirements	80
6.3.3.2	Higher symbol rate used:	80

6.3.3.2.1	MS requirements	80
6.3.3.2.2	BTS requirements	81
6.3.4	Reference interference performance – signal levels	81
6.3.5	Additional reference interference performance requirements and conditions.....	83
6.4	Erroneous frame indication performance	84
6.5	Random access and paging performance at high input levels	85
6.6	Frequency hopping performance under interference conditions	86
6.7	Incremental Redundancy Performance for EGPRS and EGPRS2 MS	86
Annex A (informative): Spectrum characteristics (spectrum due to the modulation).....		190
Annex B (normative): Transmitted power level versus time		198
Annex C (normative): Propagation conditions.....		204
C.1	Simple wideband propagation model	204
C.2	Doppler spectrum types	204
C.3	Propagation models	205
C.3.1	Typical case for rural area (RAx): (6 tap setting)	205
C.3.2	Typical case for hilly terrain (HTx): (12 tap setting).....	205
C.3.3	Typical case for urban area (TUx): (12 tap setting).....	206
C.3.4	Profile for equalization test (EQx): (6 tap setting)	206
C.3.5	Typical case for very small cells (Tix): (2 tap setting).....	206
Annex D (normative): Environmental conditions		207
D.1	General	207
D.2	Environmental requirements for the MSS.....	207
D.2.1	Temperature (GSM 400, GSM 900, ER-GSM 900 and DCS 1 800)	207
D.2.1.1	Environmental Conditions (PCS 1 900, GSM 850 and GSM 700).....	207
D.2.2	Voltage	207
D.2.3	Vibration (GSM 400, GSM 900, ER-GSM 900 and DCS 1 800).....	208
D.2.3.1	Vibration (PCS 1 900, GSM 850 and GSM 700).....	208
D.3	Environmental requirements for the BSS equipment	208
D.3.1	Environmental requirements for the BSS equipment	209
Annex E (normative): Repeater characteristics		210
E.1	Introduction	210
E.2	Spurious emissions	210
E.3	Intermodulation products	211
E.4	Out of band gain	211
E.5	Frequency error and modulation accuracy	211
E.5.1	Frequency error	211
E.5.2	Modulation accuracy at GMSK modulation.....	212
E.5.3	Modulation accuracy at 8-PSK, 16-QAM, 32-QAM, QPSK and AQPSK modulation.....	212
Annex F (normative): Antenna Feeder Loss Compensator Characteristics (GSM 400, GSM 900 and DCS 1800).....		214
F.1	Introduction	214
F.2	Transmitting path	214
F.2.1	Maximum output power	214
F.2.2	Gain	215
F.2.3	Burst transmission characteristics	215
F.2.4	Phase error	215
F.2.5	Frequency error	216
F.2.6	Group delay	216

F.2.7	Spurious emissions	216
F.2.8	VSWR	217
F.2.9	Stability	217
F.3	Receiving path	217
F.3.1	Gain	217
F.3.2	Noise figure	217
F.3.3	Group delay	217
F.3.4	Intermodulation performance	217
F.3.5	VSWR	217
F.3.6	Stability	217
F.4	Guidelines (informative)	217
Annex G (normative):	Calculation of Error Vector Magnitude	219
Annex H (normative):	Requirements on Location Measurement Unit	221
H.1	TOA LMU Requirements	221
H.1.1	Void	221
H.1.2	LMU characteristics	221
H.1.2.1	Blocking characteristics	221
H.1.2.2	AM suppression characteristics	221
H.1.2.3	Intermodulation characteristics	222
H.1.2.4	Spurious emissions	222
H.1.3	Time-of-Arrival Measurement Performance	222
H.1.3.1	Sensitivity Performance	222
H.1.3.2	Interference Performance	223
H.1.3.3	Multipath Performance	224
H.1.4	Radio Interface Timing Measurement Performance	224
H.2	E-OTD LMU Requirements	224
H.2.1	LMU Characteristics	224
H.2.1.1	Blocking characteristics	225
H.2.1.2	AM suppression characteristics	225
H.2.1.3	Intermodulation characteristics	225
H.2.2	Sensitivity and Interference Performance	225
H.2.2.1	Sensitivity Performance	225
H.2.2.2	Interference Performance	226
H.2.2.3	Multipath Performance	226
Annex I (normative):	E-OTD Mobile Station Requirements	228
I.1	Introduction	228
I.2	Sensitivity and Interference Performance	228
I.2.1	Sensitivity Performance	228
I.2.2	Interference Performance	229
I.2.3	Multipath Performance	229
Annex J (informative):	Guidance on the Usage of Dynamic ARFCN Mapping	230
J.1	Introduction	230
J.2	Dynamic allocation of GSM 400, GSM 800, GSM 900, ER-GSM 900, DCS 1800 and PCS 1900 ARFCNs	230
J.3	Controlling changes in dynamic mapping	230
Annex K (normative):	Reference TFCs for FLO	232
Annex L (normative):	Reference Test Scenarios for DARP	234
Annex M (normative):	Minimum Performance Requirements for Assisted Global Positioning System (A-GPS)	236

M.1	General	236
M.1.1	Abbreviations	236
M.1.2	Measurement parameters.....	236
M.1.2.1	MS based A-GPS measurement parameters	236
M.1.2.2	MS assisted A-GPS measurement parameters	236
M.1.3	Response time	236
M.1.4	Time assistance	236
M.1.4.1	Use of fine time assistance.....	237
M.1.4.2	2D position error.....	237
M.2	A-GPS minimum performance requirements	237
M.2.1	Sensitivity.....	237
M.2.1.1	Coarse time assistance	237
M.2.1.1.1	Minimum Requirements (Coarse time assistance).....	238
M.2.1.2	Fine time assistance	238
M.2.1.2.1	Minimum Requirements (Fine time assistance).....	238
M.2.2	Nominal Accuracy.....	238
M.2.2.1	Minimum requirements (nominal accuracy).....	239
M.2.3	Dynamic Range	239
M.2.3.1	Minimum requirements (dynamic range)	239
M.2.4	Multi-Path scenario	239
M.2.4.1	Minimum Requirements (multi-path scenario).....	240
M.2.5	Moving scenario and periodic location	240
M.2.5.1	Minimum Requirements (moving scenario and periodic location).....	241
M.3	Test conditions	241
M.3.1	General	241
M.3.1.1	Parameter values.....	241
M.3.1.2	Time assistance	242
M.3.1.3	GPS Reference Time	242
M.3.1.4	Reference and MS locations.....	242
M.3.1.5	Satellite constellation and assistance data.....	242
M.3.1.6	Atmospheric delays.....	242
M.3.1.7	GSM Frequency and frequency error.....	243
M.3.1.8	Information elements	243
M.3.1.9	GPS signals	243
M.3.1.10	RESET MS POSITIONING STORED INFORMATION Message	243
M.4	Propagation Conditions	243
M.4.1	Static propagation conditions.....	243
M.4.2	Multi-path Case G1	243
M.5	Measurement sequence chart.....	244
M.5.1	General	244
M.5.2	MS Based A-GPS Measurement Sequence Chart	244
M.5.3	MS Assisted A-GPS Measurement Sequence Chart	245
M.6	Assistance data required for testing.....	246
M.6.1	Introduction	246
M.6.2	Information elements required for MS-based.....	246
M.6.3	Information elements available for MS-assisted	247
M.7	Converting MS-assisted measurement reports into position estimates	249
M.7.1	Introduction	249
M.7.2	MS measurement reports.....	249
M.7.3	Weighted Least Squares (WLS) position solution.....	250
Annex N (normative): Reference Test Scenarios for DARP Phase II (MSRD).....		252
N.1	Interferer configurations	252
N.2	Correlation and antenna gain imbalance.....	253
N.3	Testing MSRD terminal conformance to legacy requirements.....	254

Annex O (normative):	Minimum Performance Requirements for Assisted Galileo and Additional Navigation Satellite Systems (A-GANSS)	256
O.1	General	256
O.1.1	Abbreviations	256
O.1.2	Measurement parameters.....	256
O.1.2.1	MS based A-GANSS measurement parameters.....	256
O.1.2.2	MS assisted A-GANSS measurement parameters	256
O.1.3	Response time	256
O.1.4	Time assistance	257
O.1.4.1	Use of fine time assistance.....	257
O.1.5	Error definitions	257
O.2	A-GANSS minimum performance requirements	258
O.2.1	Sensitivity.....	258
O.2.1.1	Coarse time assistance	258
O.2.1.1.1	Minimum Requirements (Coarse time assistance).....	259
O.2.1.2	Fine time assistance	259
O.2.1.2.1	Minimum Requirements (Fine time assistance).....	259
O.2.2	Nominal Accuracy.....	260
O.2.2.1	Minimum requirements (nominal accuracy)	260
O.2.3	Dynamic Range	261
O.2.3.1	Minimum requirements (dynamic range)	261
O.2.4	Multi-Path scenario	261
O.2.4.1	Minimum Requirements (multi-path scenario).....	262
O.2.5	Moving scenario and periodic location	262
O.2.5.1	Minimum Requirements (moving scenario and periodic location).....	263
O.3	Test conditions	264
O.3.1	General	264
O.3.1.1	Parameter values.....	264
O.3.1.2	Time assistance.....	264
O.3.1.3	GANSS Reference Time.....	264
O.3.1.4	Reference and MS locations	265
O.3.1.5	Satellite constellation and assistance data.....	265
O.3.1.6	Atmospheric delays.....	265
O.3.1.7	Sensors.....	265
O.3.1.8	Information elements	265
O.3.1.9	GNSS signals.....	265
O.3.1.10	RESET MS POSITIONING STORED INFORMATION Message	265
O.3.2	GNSS System Time Offsets	266
O.4	Propagation Conditions	266
O.4.1	Static propagation conditions	266
O.4.2	Multi-path case	266
O.7.1	Introduction	272
O.7.2	MS measurement reports.....	272
O.7.3	Weighted Least Squares (WLS) position solution.....	274
Annex P (normative):	Minimum receiver performance requirements for MSR BS.....	276
P.1	Reference Sensitivity and interference performance.....	276
P.2	Other receiver characteristics	276
P.2.1	Blocking characteristics	276
P.2.2	Intermodulation characteristics	276
P.2.3	AM suppression.....	277
Annex Q (normative):	Reference Test Scenarios for Voice services over Adaptive Multi-user channels on One Slot (VAMOS).....	278
Q.1	Interferer configurations in downlink.....	278
Q.2	Interferer configurations in uplink	279

Q.3	Sensitivity test configuration in downlink.....	280
Q.4	Sensitivity test configuration in uplink.....	280
Q.5	Time and frequency offset in uplink	280
Q.6	VAMOS DTX scenario in downlink.....	280
Q.7	Correlation and antenna gain imbalance for VAMOS III MS.....	281
Annex R (normative):	Reference Test Scenarios for Overlaid CDMA	283
R.1	Frequency offset in uplink.....	283
Annex S (normative):	Normalized coherency error	284
Annex T (normative):	Calculation of the equivalent combined power	285
Annex U (informative):	Change history	286
History		296

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/8e3f1a69-d06e-4610-906a-829f9737d11b/etsi-ts-145-005-v13.1.0-2016-08>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/82919737d11bd/etsi-ts-145-005-v13.1.0-2016-08>
d06e-4610-906a-82919737d11bd/etsi-ts-145-005-v13.1.0-2016-08

1 Scope

The present document defines the requirements for the transceiver of the pan-European digital cellular telecommunications systems GSM.

Requirements are defined for two categories of parameters:

- those that are required to provide compatibility between the radio channels, connected either to separate or common antennas, that are used in the system. This category also includes parameters providing compatibility with existing systems in the same or adjacent frequency bands;
- those that define the transmission quality of the system.

The present document defines RF characteristics for the Mobile Station (MS) and Base Station System (BSS). The BSS will contain Base Transceiver Stations (BTS), which can be normal BTS, micro-BTS or pico-BTS. The precise measurement methods are specified in 3GPP TS 51.010 and 3GPP TS 51.021.

Unless otherwise stated, the requirements defined in this EN apply to the full range of environmental conditions specified for the equipment (see annex D).

In the present document some relaxations are introduced for GSM 400 MSs, GSM 900 MSs, GSM 700 MSs and GSM 850 MSs which pertain to power class 4, 5 or 6 (see subclause 4.1.1). In the present document these Mobile Stations are referred to as "small MS".

In the present document some relaxations to receiver requirements are introduced for a MS indicating support for Downlink Multi Carrier (DLMC), see 3GPP TS 24.008, when in DLMC configuration. DLMC configurations are specified for only GSM 850, GSM 900, DCS 1800 and PCS 1900.

MSs may operate on more than one of the frequency bands specified in clause 2. These MSs are referred to as "Multi band MSs" in this EN. Multi band MSs shall meet all requirements for each of the bands supported. The relaxation on GSM 400 MSs, GSM 900 MSs, GSM 700 MSs and GSM 850 MSs for a "small MS" are also valid for a multi band MS if it complies with the definition of a small MS.

The RF characteristics of repeaters are defined in annex E of this EN. Annexes D and E are the only clauses of this EN applicable to repeaters. Annex E does not apply to the MS or BSS. The precise measurement methods for repeaters are specified in 3GPP TS 51.026 [35].

The present document also includes specification information for mixed mode operation at 850 MHz and 1900 MHz (MXM 850 and MXM 1900). 850 MHz and 1900 MHz mixed-mode is defined as a network that deploys both 30 kHz RF carriers and 200 kHz RF carriers in geographic regions where the Federal Communications Commission (FCC) regulations are applied or adopted.

The requirements for a MS in a mixed-mode system, MXM 850 and MXM 1900, correspond to the requirements for GSM 850 MS and PCS 1900 MS respectively.

Annex M defines the minimum performance requirements for A-GPS for MSs that support A-GPS. Annex M does not apply to the BSS.

The present document also includes specific requirements for multicarrier BTS, wherever explicitly stated in the text, that apply for all classes of multicarrier BTS (Wide Area, Medium Range and Local Area) if nothing else is stated. All other requirements designated for BTS and normal BTS apply if not otherwise stated. The multicarrier BTS classes have relaxed requirements in the areas of Tx spurious emissions, intermodulation attenuation and, when multicarrier receiver is included, Rx blocking. Usage of multicarrier BTSs in some geographical regions might be subject to regulatory restrictions to protect other radio systems operating in bands of adjacent frequency assignments, in particular for all safety related applications like railway applications. In areas where such systems coexist with multicarrier BTSs, the received interference power originating from multicarrier BTSs might have to be limited.

The document also includes entry points in some tables for the multicarrier BTS requirements to which TS 37.104 [33] for Multi-Standard Radio Base Stations (MSR BS) is referring to as specific GSM/EDGE single-RAT requirements not covered by the general requirements. These entry points are marked with ^M and, as described in a note in each applicable table, identify the relevant column(s) that are applicable as MSR BS requirements. In general the requirements for multicarrier BTS equipped with multicarrier receiver also apply to Multi-Standard Radio Base Stations. The GSM requirements for Multi-Standard Radio Base Stations are defined for GSM 850, GSM 900, DCS

1800 and PCS 1900 only. Requirements for other frequency bands and MXM base stations are excluded. Annex P defines the minimum performance for the receiver in MSR BS.

For equipment not declared as MSR BS the ^{M)} indications can be ignored.

The present document defines requirements for the usage of the ER-GSM band. The national implementation might be subject to regulatory coordination agreements to avoid system impacts (RF scenarios for ER-GSM introduction are given in 3GPP TR 45.050).

The present document defines requirements for supporting a low-complexity, low data throughput service in environments experiencing high propagation attenuation as indoors in basements etc. This service, based on EGPRS, with extended coverage is called EC-GSM-IoT. For EC-GSM-IoT, in case no specific requirement is explicitly stated, the requirements for EGPRS apply.

1.1 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: 'Vocabulary for 3GPP Specifications'.
- [1A] 3GPP TS 25.144: 'User Equipment (UE) and Mobile Station (MS) Over the Air Performance Requirements'.
- [1B] 3GPP TS 34.114: 'User Equipment (UE) / Mobile Station (MS) Over The Air (OTA) antenna performance; Conformance testing'.
- [2] 3GPP TR 43.030: 'Radio network planning aspects'.
- [3] 3GPP TS 43.052: 'GSM Cordless Telephony System (CTS); Lower layers of the CTS radio interface; Stage 2'.
- [4] 3GPP TS 43.059: 'Functional Stage 2 description of Location Services in GERAN'.
- [5] 3GPP TS 43.064: 'General Packet Radio Service (GPRS); GPRS Radio Interface Stage 2'.
- [6] 3GPP TS 44.014: 'Individual equipment type requirements and interworking; Special conformance testing functions'.
- [7] 3GPP TS 44.018: 'Mobile radio interface layer 3 specification; Radio Resource Control Protocol'.
- [7A] 3GPP TS 44.031: 'Mobile Station (MS) - Serving Mobile Location Centre (SMLC) Radio Resource LCS Protocol (RRLP)'.
- [8] 3GPP TS 44.071: 'Mobile radio interface layer 3 Location Services (LCS) specification'.
- [9] 3GPP TS 45.001: 'Physical layer on the radio path General description'.
- [10] 3GPP TS 45.002: 'Multiplexing and multiple access on the radio path'.
- [11] 3GPP TS 45.003: 'Channel coding'.
- [12] 3GPP TS 45.004: 'Modulation'.