

ETSI TS 145 008 V13.2.0 (2016-08)



Digital cellular telecommunications system (Phase 2+) (GSM); Radio subsystem link control (3GPP TS 45.008 version 13.2.0 Release 13)

Standard PREVIEW
(standard: iteh.ai)
Full standard: https://standards.iteh.ai/catalog/standards/8093cb67-29cb-43a4-b8e1-8045f5d66c1a/etsi-ts-145-008-v13.2.0-2016-08



Reference

RTS/TSGG-0145008vd20

Keywords

GSM**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	8
1 Scope	9
1.1 References	9
1.2 Abbreviations	11
1.3 Definitions	11
1.4 Restrictions	11
2 General	12
3 Handover	13
3.1 Overall process	13
3.2 MS measurement procedure	13
3.3 BSS measurement procedure.....	13
3.4 Strategy	14
4 RF power control.....	14
4.1 Overall process	14
4.2 MS implementation	14
4.2.1 General.....	14
4.2.2 (EC-)RACH	15
4.2.2.1 Random access procedure when EC operation is not enabled	15
4.2.2.2 Random access procedure when EC operation is enabled	16
4.3 MS power control range	17
4.4 BSS implementation.....	17
4.4.1 VAMOS subchannel power control for BSS in downlink	17
4.5 BSS power control range.....	17
4.6 Strategy	18
4.7 Timing	18
4.7.1 Normal Power Control.....	18
4.7.2 Fast Power Control	18
4.7.3 Enhanced Power Control	19
4.8 Dedicated channels used for a voice group call or voice broadcast.....	19
5 Radio link failure.....	19
5.1 Criterion	19
5.2 MS procedure	20
5.3 BSS procedure.....	20
6 Idle mode tasks.....	20
6.1 Introduction	20
6.2 Measurements for normal cell selection	22
6.3 Measurements for stored list cell selection.....	22
6.4 Criteria for cell selection and reselection	23
6.4.1 C1 path loss criterion	23
6.4.2 C2 reselection criterion	24
6.4.3 C4 criteria	25
6.4.4 Disabling of EC operation	26
6.5 Downlink signalling failure	26
6.6 Measurements for Cell Reselection.....	26
6.6.0 General.....	26
6.6.1 Monitoring of received signal level and BCCH data.....	27
6.6.1.1 Applicability.....	27
6.6.1.2 Monitoring of received signal level	27

6.6.1.3	Monitoring of BCCH data and BSIC decoding	27
6.6.1.4	Determination of available PLMNs	28
6.6.1.5	Requirements for synchronization and reading of BCCH data	28
6.6.1a	Reduced Monitoring of received signal level and (EC-)BCCH data	28
6.6.1a.1	General	28
6.6.1a.2	Monitoring of the serving cell	28
6.6.1a.3	Criteria for triggering measurements for cell re-selection	29
6.6.1a.4	Monitoring of non-serving cells	29
6.6.2	Path loss criteria and timings for cell re-selection	30
6.6.3	Cell reselection algorithm for SoLSA	31
6.6.4	Measurements on cells of other radio access technologies	31
6.6.5	Algorithm for cell re-selection from GSM to UTRAN based on cell ranking	35
6.6.6	Algorithm for inter-RAT cell re-selection based on priority information	36
6.6.7	Cell selection and re-selection to CSG cells and hybrid cells	39
6.6.7.1	Cell re-selection to CSG cells	39
6.6.7.1a	Cell re-selection to hybrid cells	40
6.6.7.2	Manual CSG ID selection	40
6.7	Release of TCH, SDCCH and DBPSCH	40
6.7.1	Normal case	40
6.7.2	Call re-establishment	41
6.8	Abnormal cases and emergency calls	41
6.9	RLA_EC signal level and SLA measurements	42
6.9.1	General	42
6.9.2	Physical parameters	42
6.9.3	Statistical parameter	42
6.9.4	Accuracy requirements	43
6.9.5	Void	43
6.9a	RLA_GC signal level measurements	43
6.9a.1	General	43
6.9a.2	Physical parameter	43
6.9a.3	Statistical parameter	43
6.9a.4	Accuracy requirements	43
6.10	Coverage class selection for EC-GSM-IoT	43
6.10.1	General	43
6.10.2	Downlink coverage class selection	44
6.10.3	Uplink coverage class selection	44
6.10.4	Coverage class adaptation for EC-CCCH	45
6.10.5	Downlink coverage class update	45
7	Network pre-requisites	45
7.1	BCCH carriers	45
7.2	Identification of surrounding BSS	47
7.2.1	General	47
7.2.2	Identification of surrounding BSS for handover measurements	47
7.3	Handover measurements on other radio access technologies	49
7.4	Handover measurements on UTRAN CSG cells and hybrid cells	52
8	Radio link measurements	53
8.1	Signal level	53
8.1.1	General	53
8.1.2	Physical parameter	53
8.1.3	Statistical parameters	54
8.1.4	Range of parameter	54
8.1.5	Measurement quantity for other radio access technologies	55
8.1.5.1	UTRAN FDD	55
8.1.5.2	UTRAN TDD	55
8.1.5.3	cdma2000	55
8.1.5.4	E-UTRAN FDD	56
8.1.5.5	E-UTRAN TDD	57
8.2	Signal quality	57
8.2.1	General	57
8.2.2	Physical parameter	57

8.2.3	Statistical parameters	58
8.2.3.1	RXQUAL	58
8.2.3.2	MEAN_BEP and CV_BEP	58
8.2.4	Range of parameter RXQUAL	59
8.2.5	Range of parameters MEAN_BEP and CV_BEP	60
8.3	Aspects of discontinuous transmission (DTX)	64
8.4	Measurement reporting	65
8.4.1	Measurement reporting for the MS	65
8.4.1a	Measurement reporting for the MS in FPC mode	67
8.4.1b	Measurement reporting for the MS in EPC mode	67
8.4.2	Measurement reporting for the MS on a SDCCH	68
8.4.3	Additional cell reporting requirements for multi band MS	68
8.4.4	Common aspects for the MS on a TCH, a SDCCH or a DBPSCH	69
8.4.5	Measurement reporting for the BSS	69
8.4.6	Extended measurement reporting	70
8.4.7	Additional cell reporting requirements for multi-RAT MS	70
8.4.8	Enhanced Measurement Reporting	72
8.4.8.1	Reporting Priority	72
8.4.8.2	Measurement Reporting	73
8.4.8.3	NBR_RCVD_BLOCKS for FLO	74
8.4.9	Requirements for measurement and reporting of CSG cells and hybrid cells	74
8.5	Absolute MS-BTS distance	75
8.5.1	General	75
8.5.2	Physical parameter	75
9	Control parameters	76
10	GPRS mode tasks	85
10.1	Cell Re-selection	85
10.1.0	General	85
10.1.1	Monitoring the received signal level and PBCCH data	86
10.1.1.0	General	86
10.1.1.1	Packet idle mode or MAC-Idle state	87
10.1.1.2	Packet transfer mode or MAC-Shared state	87
10.1.1.2a	Broadcast/multicast receive mode	89
10.1.1.3	Monitoring cells of other radio access technologies	89
10.1.2	Cell Re-selection Criteria	93
10.1.3	Cell Re-selection Algorithm	94
10.1.3.1	Abnormal cell reselection	95
10.1.3.2	Algorithm for cell re-selection from GSM to UTRAN based on cell ranking	96
10.1.3.3	Algorithm for inter-RAT cell re-selection based on priority information	97
10.1.3.4	Cell selection and re-selection to CSG cells and hybrid cells	97
10.1.4	Network controlled Cell re-selection	97
10.1.4.1	Measurement reporting	98
10.1.4.2	Cell re-selection command	103
10.1.4.3	Exceptional cases	103
10.1a	Measurement and Reporting of CSG Cells and hybrid cells	103
10.2	RF Power Control	104
10.2.1	MS output power	104
10.2.2	BTS output power	105
10.2.3	Measurements at MS side	106
10.2.3.1	Deriving the C value	107
10.2.3.1.1	Packet idle mode or MAC-Idle state	107
10.2.3.1.2	Packet transfer mode or MAC-Shared state	107
10.2.3.1.2.1	MS that have not enabled EC operation	107
10.2.3.1.2.2	MS that have enabled EC operation	109
10.2.3.2	Derivation of Channel Quality Report	109
10.2.3.2.1	Packet transfer mode or MAC-Shared state	110
10.2.3.2.2	Void	113
10.2.3.2.3	Measurement reporting	113
10.2.3.2.4	Measurement reporting - additional requirements for downlink dual carrier	114
10.2.3.2.5	Measurement reporting - additional requirements for downlink multi carrier	115

10.2.3.3	Range of parameters MEAN_BEP and CV_BEP for EGPRS2	115
10.2.4	Measurements at BSS side.....	119
10.2a	Packet-switched Handover	119
10.3	Measurement requirements	119
10.4	Control parameters	119
11	CTS mode tasks.....	127
11.1	CTS idle mode tasks.....	127
11.1.1	CTS cell selection	128
11.1.1.1	Synchronization and measurements for CTS cell selection	128
11.1.1.2	Initial sychronization of CTS-MS	128
11.1.2	Criterion for CTS cell selection	128
11.1.3	Monitoring of CTSBCH and CTSPCH.....	129
11.1.3.1	Monitoring of received signal level	129
11.1.3.2	Downlink beacon failure	129
11.1.3.3	Downlink paging failure	129
11.1.4	Procedures with reporting to the CTS-FP	129
11.1.4.1	AFA monitoring	129
11.1.4.2	BCCH detection	130
11.1.4.3	Observed Frequency Offset (OFO) measurement	130
11.2	Intra-cell handover	130
11.2.1	Overall process	130
11.2.2	CTS-MS measurement procedure.....	130
11.2.3	CTS-FP measurement procedure	131
11.2.4	Strategy	131
11.3	RF power control.....	131
11.3.1	Overall process	131
11.3.2	CTS-MS implementation.....	131
11.3.3	CTS-MS power control range.....	131
11.3.4	CTS-FP implementation	132
11.3.5	CTS-FP power control range.....	132
11.3.6	Strategy	132
11.3.7	Timing	132
11.4	Radio link failure.....	132
11.4.1	Criterion.....	132
11.4.2	CTS-MS procedure	132
11.4.3	CTS-FP procedure	133
11.5	Radio link measurements	133
11.5.1	Signal strength	133
11.5.1.1	General	133
11.5.1.2	Physical parameter	133
11.5.1.3	Statistical parameters	133
11.5.1.4	Range of parameter	133
11.5.2	Signal quality	134
11.5.2.1	General	134
11.5.2.2	Physical parameter	134
11.5.2.3	Statistical parameters	134
11.5.2.4	Range of parameter	134
11.5.3	Aspects of discontinuous transmission (DTX)	134
11.5.4	Measurement reporting for the CTS-MS on a TCH.....	134
11.6	Control of CTS-FP service range	135
11.7	Control parameters	135
12	COMPACT Mode Tasks	137
12.1	Introduction	137
12.2	Network Pre-requisites	137
12.2.1	CPBCCCH carriers.....	137
12.3	COMPACT Idle Mode Tasks.....	137
12.3.1	Introduction.....	137
12.3.2	Measurements for COMPACT Cell Selection.....	137
12.3.3	Measurements for COMPACT Stored List Cell Selection	138
12.3.4	Criteria for COMPACT Cell Selection.....	138

12.3.5	Downlink Signalling Failure.....	138
12.4	COMPACT Cell Reselection	138
12.4.1	Monitoring the received signal level and CPBCCCH data.....	139
12.4.1.1	Packet idle mode or MAC-Idle state	139
12.4.1.2	Packet transfer mode or MAC-Shared state	139
12.4.2	COMPACT cell reselection criteria.....	140
12.4.3	COMPACT cell reselection algorithm.....	140
12.4.4	Network controlled Cell reselection	140
12.4.5	COMPACT cell reselection measurement opportunities	140
Annex A (informative): Definition of a basic GSM or DCS 1 800 handover and RF power control algorithm		141
A.1	Scope	141
A.2	Functional requirement.....	141
A.3	BSS pre-processing and threshold comparisons.....	142
A.3.1	Measurement averaging process.....	142
A.3.2	Threshold comparison process	143
A.3.2.1	RF power control process	143
A.3.2.2	Handover Process	144
A.4	BSS decision algorithm.....	145
A.4.1	Internal intracell handover according to radio criteria: (Interference problems).....	145
A.4.2	Internal handover according to other criteria.....	146
A.4.3	General considerations	146
A.5	Channel allocation.....	146
A.6	Handover decision algorithm in the MSC.....	147
Annex B (informative): Power Control Procedures.....		149
B.1	Open loop control.....	149
B.2	Closed loop control	150
B.3	Quality based control.....	150
B.4	BTS power control	151
B.5	Example.....	151
B.6	Interworking between normal and fast power control for ECSD.....	152
B.7	Interworking between normal and enhanced power control (EPC)	153
Annex C (informative): Example Interference Measurement Algorithm.....		155
Annex D (informative): Example Selection of Modulation and Coding Schemes based on Link Quality Reports.....		156
Annex E (informative): Change history		157
History		167

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/8013cb67-29cb-43a4-b8e1-8045f5d66c1a/etsi-ts-145-008-v13.2.0-2016-08>

1 Scope

The present document specifies the Radio sub-system link control implemented in the Mobile Station (MS), Base Station System (BSS) and Mobile Switching Centre (MSC) of the digital cellular telecommunications systems GSM.

Unless otherwise specified, references to GSM also include operation in any supported band (see TS 45.005).

1.1 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: 'Vocabulary for 3GPP Specifications'.
- [2] 3GPP TS 23.003: 'Numbering, addressing and identification'.
- [3] 3GPP TS 23.009: 'Handover procedures'.
- [4] 3GPP TS 23.122: 'NAS Functions related to Mobile Station (MS) in idle mode'.
- [5] 3GPP TS 25.101: 'UE Radio transmission and reception (FDD)'.
- [6] 3GPP TS 25.123: 'Requirements for support of Radio Resource Management (TDD)'.
- [7] 3GPP TS 25.133: 'Requirements for support of Radio Resource Management (FDD)'.
- [8] 3GPP TS 25.304: 'UE Procedures in Idle Mode and Procedures for Cell Reselection in Connected Mode'.
- [9] 3GPP TS 25.331: 'Radio Resource Control (RRC); Protocol Specification'.
- [10] 3GPP TS 26.093: 'AMR Speech Codec; Source Controlled Rate operation'.
- [11] 3GPP TS 43.022: 'Functions related to Mobile Station (MS) in idle mode and group receive mode'.
- [12] 3GPP TS 43.064: 'Overall description of the GPRS Radio Interface; Stage 2'.
- [13] 3GPP TS 43.246: 'Multimedia Broadcast Multicast Service (MBMS) in the GERAN; Stage 2'.
- [14] 3GPP TS 43.068: 'Voice Group Call Service (VGCS); Stage 2'.
- [15] 3GPP TS 44.004: 'Layer 1; General requirements'.
- [16] 3GPP TS 44.006: 'Mobile Station - Base Station System (MS - BSS) interface; Data Link (DL) layer specification'.
- [17] 3GPP TS 44.018: 'Mobile radio interface layer 3 specification; Radio Resource Control Protocol'.
- [18] 3GPP TS 44.056: 'GSM Cordless Telephony System (CTS), Phase 1; CTS radio interface layer 3 specification'.
- [19] 3GPP TS 44.060: 'General Packet Radio Service (GPRS); Mobile Station (MS) - Base Station System (BSS) interface; Radio Link Control (RLC) / Medium Access Control (MAC) protocol'.

- [20] 3GPP TS 44.118: 'Mobile radio interface layer 3 specification, Radio Resource Control (RRC) Protocol, Iu Mode'.
- [21] 3GPP TS 44.160: 'Mobile Station (MS) - Base Station System (BSS) interface; Radio Link Control/Medium Access Control (RLC/MAC) protocol; Iu mode'.
- [22] 3GPP TS 45.002: 'Multiplexing and multiple access on the radio path'.
- [23] 3GPP TS 45.003: 'Channel coding'
- [24] 3GPP TS 45.005: 'Radio transmission and reception'.
- [25] 3GPP TS 45.010: 'Radio subsystem synchronization'.
- [26] 3GPP TS 45.056: 'CTS-FP radio subsystem'.
- [27] 3GPP TR 45.902: 'Flexible Layer One'.
- [28] 3GPP TS 46.011: 'Full rate speech; Substitution and muting of lost frames for full rate speech channels'.
- [29] 3GPP TS 46.012: 'Full rate speech; Comfort noise aspect for full rate speech traffic channels'.
- [30] 3GPP TS 46.031: 'Full rate speech; Discontinuous Transmission (DTX) for full rate speech traffic channels'.
- [31] 3GPP TS 48.008: 'Mobile-services Switching Centre - Base Station System (MSC - BSS) interface, Layer 3 specification'.
- [32] 3GPP TS 48.058: 'Base Station Controller - Base Transceiver Station (BSC - BTS) interface; Layer 3 specification'.
- [33] 3GPP TS 51.010: 'Mobile Station (MS) conformity specification'.
- [34] 3GPP TS 51.011: 'Specification of the Subscriber Identity Module - Mobile Equipment (SIM - ME) interface'.
- [35] TIA/EIA/IS-2000-5-A: 'Upper Layer (Layer 3) Signaling Standard for cdma2000 Spread Spectrum Systems'.
- [36] TIA/EIA/IS-833: 'Multi-Carrier Specification for Spread Spectrum Systems on GSM MAP (MC-MAP) (Lower Layers Air Interface)'.
- [37] 3GPP TS 36.101: 'Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio transmission and reception'.
- [38] 3GPP TS 36.104: 'Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception'.
- [39] 3GPP TS 36.133: 'Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements for support of radio resource management'.
- [40] 3GPP TS 36.304: 'Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) procedures in idle mode'.
- [41] 3GPP TS 36.331: 'Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC); Protocol Specification'.
- [42] 3GPP TS 31.102: 'Characteristics of the Universal Subscriber Identity Module (USIM) application'.
- [43] 3GPP TS 24.301: 'Non-Access-Stratum (NAS) protocol for Evolved Packet System (EPS); Stage 3'.
- [44] 3GPP TS 22.268: 'Public Warning System (PWS) requirements; Stage 1'.
- [45] 3GPP TS 23.251: "Network sharing; Architecture and functional description".

- [46] 3GPP TS 24.008: "Mobile Radio Interface Layer 3 specification; Core Network Protocols - Stage 3".
- [47] 3GPP TS 25.306: "UE Radio Access capabilities".
- [48] 3GPP TR 45.926: 'Solutions for GSM/EDGE BTS Energy Saving'.

1.2 Abbreviations

Abbreviations used in the present document are listed in 3GPP TR 21.905.

UFPS Unique Frequency Parameter Set

1.3 Definitions

Acceptable cell: see definition in 3GPP TS 43.022 [11].

Coverage Class: see definition in 3GPP TS 43.064 [12].

CSG Whitelist: A list provided by NAS containing all the CSG identities and their PLMN IDs of the CSGs to which the subscriber belongs, see 3GPP TS 23.122 [4].

NOTE: This list is known as 'Allowed CSG List' in Rel-8 specifications.

CSG cell: The definition of CSG cell for UTRAN is given in 3GPP TS 25.304 [8]; the definition of CSG cell for E-UTRAN is given in 3GPP TS 36.304 [40].

EC-GSM-IoT: see definition in 3GPP TS 43.064 [12].

EC-GSM-IoT cell: A cell supporting EC-GSM-IoT.

EC operation: See definition in 43.064 [12].

Hybrid cell: The definition of hybrid cell for UTRAN is given in 3GPP TS 25.304 [8]; the definition of hybrid cell for E-UTRAN is given in 3GPP TS 36.304 [40].

Network sharing: network sharing is an optional feature that allows different core network operators to connect to the same shared radio access network (see 3GPP TS 23.251 [45]). When network sharing is in use within a given cell, the network broadcasts within system information the PLMN identities of the PLMNs sharing the cell. A mobile station supporting network sharing uses this information for its PLMN (re)selection processes and indicates the selected PLMN to the BSS.

Power Efficient Operation (PEO): see definition in 3GPP TS 43.064 [12].

Power Saving Mode (PSM): see definition in 3GPP TS 43.064 [12].

Suitable cell: see definition in 3GPP TS 43.022 [11].

Unique Frequency Parameter Set: defined by a single ARFCN or a MA. In case of a radio frequency channel assigned a frequency parameter set consisting of a single ARFCN, the UFPS is defined by that ARFCN. In case of a radio frequency channel assigned a frequency parameter set consisting of a MA, MAIO and HSN, that radio frequency channel belong to the same UFPS as other radio frequency channels assigned the same MA.

1.4 Restrictions

Independently of what is stated elsewhere in this and other 3GPP specifications, mobile station support for PBCCH and PCCCH is optional for A/Gb-mode of operation. The network shall never enable PBCCH and PCCCH.

2 General

The radio sub-system link control aspects that are addressed are as follows:

- Handover;
- RF Power control in *A/Gb mode*, including fast power control for E-TCH and enhanced power control for TCH and O-TCH;
- RF Power control in *Iu mode*, including fast power control for E-TCH and enhanced power control for DBPSCH (in MAC-Dedicated and MAC-DTM states);
- Radio link Failure;
- Cell selection and re-selection in Idle mode, in Group Receive mode, in GPRS mode, in broadcast/multicast receive mode and in EC operation and PEO (see 3GPP TS 43.022);
- Coverage class selection in EC operation;
- CTS mode tasks.

NOTE: A distinction is made between *A/Gb mode* and *Iu mode* only when necessary. Procedures and mechanisms described in this TS apply to both modes of operation unless otherwise stated. In *Iu mode*, unless otherwise stated, DBPSCH covers TCH, PDTCH and FLO.

Handover is required to maintain a call in progress as a MS engaged in a point-to-point call or with access to the uplink of a channel used for a voice group call passes from one cell coverage area to another and may also be employed to meet network management requirements, e.g. relief of congestion.

Handover may occur during a call from one TCH or multiple TCHs (in the case of multislot configuration) to another TCH or multiple TCHs. It may also occur from DCCH to DCCH or from DCCH to one or multiple TCH(s), e.g. during the initial signalling period at call set-up. Additionally in *Iu mode*, handover may occur in MAC-Dedicated and MAC-DTM states:

- on PDTCH or multiple PDTCHs (in the case of multislot configuration) on DBPSCH(s) to another PDTCH or multiple PDTCHs on DBPSCH(s);
- for FLO, from one DBPSCH or multiple DBPSCHs (in the case of multislot configuration) to another DBPSCH or multiple DBPSCHs.

The handover may be either from channel(s) on one cell to other channel(s) on a surrounding cell, or between channels on the same cell which are carried on the same frequency band. Examples are given of handover strategies, however, these will be determined in detail by the network operator.

For a multiband MS, the handover described is also allowed between any channels on different cells which are carried on different frequency bands, e.g. between a GSM 900/TCH and a DCS 1 800/TCH. Handover between two co-located cells, carried on different frequency bands, is considered as inter-cell handover irrespective of the handover procedures used.

For a multi-RAT MS, i.e. an MS supporting multiple radio access technologies, handover is allowed between GSM and other radio access technologies.

NOTE: At handover, the MS will normally not be able to verify the PLMN of the target cell and will thus assume that the same system information apply after the handover unless the network provides new system information.

Adaptive control of the RF transmit power from an MS and optionally from the BSS is implemented in order to optimize the uplink and downlink performance and minimize the effects of co-channel interference in the system.

The criteria for determining radio link failure are specified in order to ensure that calls which fail either from loss of radio coverage or unacceptable interference are satisfactorily handled by the network. Radio link failure may result in either re-establishment or release of the call in progress. For channels used for a voice group call, a radio uplink failure results in the freeing up of the uplink.