INTERNATIONAL STANDARD

ISO 23269-3

First edition 2011-05-01

Ships and marine technology — Breathing apparatus for ships —

Part 3:

Self-contained breathing apparatus (safety equipment) required by the IMO IBC and IGC Codes

Navires et technologie maritime — Appareils respiratoires pour les navires —

Partie 3: Appareils respiratoires autonomes (équipement de sécurité) exigés d'après les Codes IBC et IGC de l'OMI

ISO 23269-3:2011

https://standards.iteh.ai/catalog/standards/iso/126c4c4e-84b7-4b79-a3ba-f1de11c2d790/iso-23269-3-2011



iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 23269-3:2011

https://standards.iteh.ai/catalog/standards/iso/126c4c4e-84b7-4b79-a3ba-f1de11c2d790/iso-23269-3-2011



COPYRIGHT PROTECTED DOCUMENT

© ISO 2011

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 23269-3 was prepared by Technical Committee ISO/TC 8, *Ships and marine technology*, Subcommittee SC 1, *Lifesaving and fire protection*.

ISO 23269 consists of the following parts, under the general title *Ships and marine technology* — *Breathing apparatus for ships*:

- Part 1: Emergency escape breathing devices (EEBD) for shipboard use
- Part 2: Self-contained breathing apparatus for shipboard firefighters
- Part 3: Self-contained breathing apparatus (safety equipment) required by the IMO IBC and IGC Codes
- Part 4: Self-contained breathing apparatus for emergency escape required by the IMO IBC and IGC Codes

Introduction

The IMO IBC Code (for bulk chemicals) and the IMO IGC Code (for gas carriers) developed by the International Maritime Organization require that self-contained breathing apparatus (safety equipment) be carried on board chemical tankers and gas carrier ships. However, these Codes do not technically specify the details of such apparatus; such a specification is necessary to provide a sufficient safety level for users.

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 23269-3:2011

https://standards.iteh.ai/catalog/standards/iso/126c4c4e-84h7-4h79-a3ha-fl.de11c2d790/iso-23269-3-2011

Ships and marine technology — Breathing apparatus for ships —

Part 3:

Self-contained breathing apparatus (safety equipment) required by the IMO IBC and IGC Codes

1 Scope

This part of ISO 23269 provides performance specifications of the self-contained air-breathing apparatus (SCBA) (not using stored oxygen) required by the IMO IBC Code (for bulk chemicals) and the IMO IGC Code (for gas carriers) developed by the International Maritime Organization.

The breathing apparatus manufactured in accordance with this part of ISO 23269 constitutes an element of the set of safety equipment which permits personnel to enter a gas-filled compartment and perform work there. The breathing apparatus is not intended for use in fighting fires or suitable for entry into flames.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies. 3269-32011

IMO IBC Code, International code for the construction and equipment of ships carrying dangerous chemicals in bulk

IMO IGC Code, International code for the construction and equipment of ships carrying liquefied gases in bulk

ISO 15537, Principles for selecting and using test persons for testing anthropometric aspects of industrial products and designs

ISO 23269-2:—¹⁾, Ships and marine technology — Breathing apparatus for ships — Part 2: Self-contained breathing apparatus for shipboard firefighters

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 23269-2 apply.

4 General design requirements

The apparatus shall comply with all of the requirements of Clause 4 of ISO 23269-2:—.

1

¹⁾ To be published.

5 Environmental tests

The apparatus shall comply with all of the requirements of Clause 5 of ISO 23269-2:—.

6 Basic performance tests and requirements

6.1 General

The apparatus shall comply with all of the requirements of Clause 6 of ISO 23269-2:—, except:

- a) 6.9.2 on flammability;
- b) 6.9.3 on resistance to radiant heat.

In addition, the apparatus shall be subjected to the tests specified in 6.2 to 6.4.

6.2 Chemical permeation resistance test

- **6.2.1** The breathing apparatus shall be tested using the principles set forth in ISO 15537. Factors such as the intended user population, critical dimensions of the breathing apparatus, protective clothing likely to be worn with the breathing apparatus, and critical tasks the wearer might perform shall be determined, and shall be described in the test report.
- **6.2.2** A solution of water and non-toxic, coloured dye shall be prepared and placed in a spray bottle. The coloured water shall provide sufficient contrast to indicate penetration of the facepiece of the breathing apparatus by visual inspection of the interior.
- **6.2.3** The test subjects shall individually don a breathing apparatus along with the protective clothing and other related safety equipment. With the test subjects standing upright, the coloured water shall be sprayed on the top and the sides of the breathing apparatus. After spraying the water, there shall be no permeation of water through the facepiece of the breathing device.

6.3 Chemical resistance test of the eyepiece and transparent materials

Apply the following solvents, one at a time using a suitable applicator, to the eyepiece or any transparent part:

- a) trichloroethylene;
- b) benzene;
- c) solvent naphtha;
- d) methanol;
- e) kerosene.

One droplet of each chemical shall be applied to the test specimen, so that the droplet does not rinse. Exposure time shall be until the droplet evaporates or a maximum of 15 min, whichever occurs first. After exposure, the test specimen shall be assessed by visual inspection. No dissolution or deterioration to the extent that the test specimen becomes unusable should be observed, e.g. no holes, leaks, fogging, or hazing are formed.