



Designation: E726 – 01 (Reapproved 2006)

Standard Test Method for Particle Size Distribution of Granular Carriers and Granular Pesticides¹

This standard is issued under the fixed designation E726; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method is used to determine the particle size distribution of granular carriers and granular pesticides.

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.* For specific hazard statements, see Section 6.

2. Referenced Documents

2.1 *ASTM Standards:*²

E11 Specification for Woven Wire Test Sieve Cloth and Test Sieves

E725 Test Method for Sampling Granular Carriers and Granular Pesticides

3. Summary of Test Method

3.1 A known weight of the granular carrier or granular pesticide is placed on the top sieve of a stacked set of U.S. standard sieves and shaken under standard conditions for a specified period of time. The weight percent of the granules retained on each sieve and the bottom pan is determined.

4. Significance and Use

4.1 This procedure was designed principally for clay, corn-cob, nut shell paper, or sand granular carriers and granular pesticide products, but need not be limited to these materials.

¹ This test method is under the jurisdiction of ASTM Committee E35 on Pesticides and Alternative Control Agents and is the direct responsibility of Subcommittee E35.22 on Pesticide Formulations and Delivery Systems.

Current edition approved Nov. 1, 2006. Published November 2006. Originally approved in 1980. Last previous edition approved in 2001 as E726–01. DOI: 10.1520/E0726-01R06.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

There may be more appropriate test methods for other types of granular carriers and products.

5. Apparatus

5.1 *Brushes*; Tyler Part No. 8576 soft brass wire brush, or equivalent, for 100 mesh (150 μ m) and coarser sieves. Tyler nylon bristle brush (Part No. 8577), or equivalent, for screens finer than 100 mesh.

5.2 *Mechanical Sieve Shaker*; a Tyler RoTap sieve shaker, or equivalent, or other agreed upon device.

5.3 *Sieves*; U.S. standard 8-in. (20.3 cm) diameter sieves, or equivalent, conforming to Specification E11.

5.4 *Bottom Receiver Pan* and *Top Sieve Cover*.

5.5 *Interval Timer*; adjustable, with an accuracy of ± 10 s.

5.6 *Balance*; sensitivity of 0.1 g.

6. Hazards

6.1 Before testing, read the precautionary statements on the product label, and the Material Safety Data Sheet, or both. Take proper precautions to prevent skin contact and inhalation of the fines, or the vapors, or both. Take care to prevent contamination of the surrounding area. Always wear the appropriate safety equipment and, where indicated, wear respiratory devices approved by NIOSH for the product being tested.

7. Procedure

7.1 Clean and stack the specified sieves in order of size with the pan on the bottom, and the sieve with the largest mesh on the top.

7.2 Use a representative sample of approximately 100 ± 5 g as defined in Test Method E725.

7.3 Weigh the sample to ± 0.1 g.

7.4 Transfer the whole weighed fraction onto the top sieve, cover and shake for the time given in the product specification or 10 min if time is not specified.

7.5 Remove the sieve assembly from the sieve shaker and, using the brush, quantitatively transfer the granular material on the top sieve to a tared weighing pan and weigh to the nearest