## INTERNATIONAL STANDARD

**ISO/IEC** 11695-1

First edition 2008-11-01

Identification cards — Optical memory cards — Holographic recording method —

Part 1: **Physical characteristics** 

Teh ST Cartes d'identification — Cartes à mémoire optique — Méthode d'enregistrement holographique —

Partie 1: Caractéristiques physiques

ISO/IEC 11695-1:2008 https://standards.iteh.ai/catalog/standards/sist/4089300d-eb6d-4e2f-944d-10078f09378a/iso-iec-11695-1-2008



#### PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/IEC 11695-1:2008 https://standards.iteh.ai/catalog/standards/sist/4089300d-eb6d-4e2f-944d-10078f09378a/iso-iec-11695-1-2008



#### **COPYRIGHT PROTECTED DOCUMENT**

#### © ISO/IEC 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

#### Contents

Page

Forewo	ord	. iv	
Introduction		v	
1	Scope	1	
2	Normative references	1	
3	Terms and definitions	1	
4 4.1 4.1.1 4.1.2 4.1.3 4.1.4 4.2 4.2.1 4.2.2 4.3 4.3.1 4.3.2 4.3.3 4.3.4 4.3.5 4.3.6 4.3.7 4.3.8 4.3.9 4.3.10 4.3.11 4.3.12 4.3.13 4.3.14 4.3.15 4.3.15 4.3.16	Holographic memory cards – physical characteristics  Dimensions  Card height and width  Card thickness  Card corners  Card edges  Construction  Card construction  Cross-section at accessible optical area Physical characteristics  Protective layer(s) ch. STANDARD PREVIEW  Storage layer  Reflective layer  Additions  Bending stiffness  SOJEC 11695-12008  Card warpages://standards/standards/sist/4089300d-eb6d-4e2F944d-  X-rays  Toxicity  Ultraviolet light  Light transmittance  Bending properties  Resistance to chemicals  Atmospheric requirements  Durability  Dimensional stability and warpage with temperature and humidity.	3 3 3 3 3 4 4 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	
	Dimensional stability and warpage with temperature and numidity  Default test environment and conditioning		
Annex	A (informative) Holographic data storage	7	
Bibliog	Bibliography11		

#### **Foreword**

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

ISO/IEC 11695-1 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 17, *Cards and personal identification*.

ISO/IEC 11695 consists of the following parts, under the general title *Identification cards* — *Optical memory cards* — *Holographic recording method*: **STANDARD PREVIEW** 

- Part 1: Physical characteristics (standards.iteh.ai)
- Part 2: Dimensions and location of accessible optical area
- Part 3: Optical properties and characteristics 100/8i09378a/iso-iec-11695-1-2008

#### Introduction

ISO/IEC 11695 is one of a series of International Standards defining the parameters for optical memory cards and the use of such cards for the storage and interchange of digital data.

These International Standards recognize the existence of different methods for recording and reading information on optical memory cards, the characteristics of which are specific to the recording method employed. In general, these different recording methods will not be compatible with each other. Therefore, these International Standards are structured to accommodate the inclusion of existing and future recording methods in a consistent manner.

ISO/IEC 11695 is specific to optical memory cards using the holographic recording method. Characteristics which apply to other specific recording methods are found in separate International Standards.

This part of ISO/IEC 11695 defines the physical characteristics and the extent of compliance with, addition to, and/or deviation from the relevant base document, ISO/IEC 11693.

The International Organization for Standardization (ISO) and International Electrotechnical Commission (IEC) draw attention to the fact that it is claimed that compliance with this document may involve the use of patents.

The ISO and IEC take no position concerning the evidence, validity and scope of these patent rights.

The holders of these patent rights have assured the ISO and IEC that they are willing to negotiate licenses under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of these patent rights are registered with the ISO and IEC. Information may be obtained from:

https://standards.iteh.ai/catalog/standards/sist/4089300d-eb6d-4e2f-944d-

Certego GmbH 10078f09378a/iso-iec-11695-1-2008 Lichtenbergstrasse 8 85748 Garching

85748 Garching Germany

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/IEC 11695-1:2008 https://standards.iteh.ai/catalog/standards/sist/4089300d-eb6d-4e2f-944d-10078f09378a/iso-iec-11695-1-2008

## Identification cards — Optical memory cards — Holographic recording method —

#### Part 1:

#### **Physical characteristics**

#### 1 Scope

This part of ISO/IEC 11695 defines the physical characteristics of optical memory cards using the holographic recording method.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 7810, Identification cards SPhysical characteristics 21)

ISO/IEC 7816-1, Identification cards ISO/IEC 781

10078f09378a/iso-iec-11695-1-2008 ISO/IEC 10373-1, Identification cards — Test methods — Part 1: General characteristics

ISO/IEC 11695-2, Identification cards — Optical memory cards — Holographic recording method — Part 2: Dimensions and location of accessible optical area

ISO/IEC 11695-3 Identification cards — Optical memory cards — Holographic recording method — Part 3: Optical properties and characteristics

#### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 11695-2, ISO/IEC 11695-3 and the following apply.

#### 3.1

#### holographic recording method

writing and/or pre-formatting of digital data on the holographic memory card in the form of holograms

#### 3.2

#### hologram

microscopic structure which can be written by optical energy into an accessible optical area causing diffraction of a read-out beam of certain wavelength by illumination

NOTE 1 A hologram is the representation of a two-dimensional code of digital data on the holographic memory card.

NOTE 2 See Annex A.

#### 3.3

#### amplitude hologram

hologram which modulates the amplitude of a read-out beam in the read-out process

#### 3.4

#### phase hologram

hologram which modulates the phase of a read-out beam in the read-out process

#### 3.5

#### thick hologram

hologram in which the thickness is n times the wavelength of the writing/reading beam, where n > 10

#### 3.6

#### thin hologram

hologram characterized by the thickness of the recording medium containing the hologram, whereby the hologram has the same order as the wavelength of the writing/reading beam

#### 3.7

#### holographic memory card

card containing an accessible optical area to which holograms can be written using external optical energy

#### 3.8

#### accessible optical area

partition of the holographic memory card which is available to be accessed by the read and/or write beam of the holographic read-out and/or recording system used

#### iTeh STANDARD PREVIEW

#### 3.9

#### storage layer

#### (standards.iteh.ai)

specific layer of the holographic memory card, located between the protective layer and the reflective layer, which contains specific materials to permit writing and/or reading back holographic recorded data by optical means

https://standards.iteh.ai/catalog/standards/sist/4089300d-eb6d-4e2f-944d-

#### 10078f09378a/iso-iec-11695-1-2008

#### protective layer

transparent layer of material within the holographic memory card which is placed on top of the storage layer and able to provide protection against scratches, humidity and damage caused by environmental influence

#### 3.11

3.10

#### reflective layer

layer of material within the holographic memory card placed between substrate layer and storage layer to reflect the writing and reading beam so that the holographic memory card can be read out in reflection mode

#### 3.12

#### substrate layer

layer of material of an holographic memory card providing a flat and smooth surface for both the reflective and storage layers attaching the storage medium to the card body, when the substrate layer is not the card body

#### 3.13

#### polarization

property of electromagnetic waves, such as light, that describes the direction of the transverse electric field

NOTE The polarization of a transverse wave describes the direction of oscillation in the plane perpendicular to the direction of travel.

#### 3.14

#### birefringence

decomposition of a ray of light into two rays (the ordinary ray and the extraordinary ray) when it passes through certain types of material, depending on the polarization of the light

NOTE This effect occurs when the structure of the material is anisotropic.

#### 4 Holographic memory cards - physical characteristics

#### 4.1 Dimensions

#### 4.1.1 Card height and width

ISO/IEC 7810 applies.

#### 4.1.2 Card thickness

ISO/IEC 7810 applies.

#### 4.1.3 Card corners

ISO/IEC 7810 applies.

#### 4.1.4 Card edges

ISO/IEC 7810 applies.

#### 4.2 Construction

### 4.2.1 Card construction in the STANDARD PREVIEW

ISO/IEC 7810 applies.

(standards.iteh.ai)


#### 4.2.2 Cross-section at accessible optical area

ISO/IEC 11695-1:2008

See Figure 1. https://standards.iteh.ai/catalog/standards/sist/4089300d-eb6d-4e2f-944d-10078f09378a/iso-iec-11695-1-2008

The holographic memory card contains an accessible optical area which is laminated, bonded, or inserted into the card body.

The accessible optical area is composed of different layers: a substrate layer, a reflective layer, a storage layer and one or more protective layers to protect the sub-layers from damage, e.g. by surface damage, humidity and other environmental influence.



NOTE Drawing not to scale.

Figure 1 — Cross-section of a holographic memory card at the accessible optical area