INTERNATIONAL STANDARD

ISO/IEC 11695-3

First edition
2008-11-01

Identification cards — Optical memory cards — Holographic recording method —

Part 3: Optical properties and characteristics

Cartes d'identification — Cartes à mémoire optique — Méthode d'enregistrement holographique —
Partie 3: Propriétés et caractéristiques optiques

Reference number
ISO/IEC 11695-3:2008(E)

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

ISO/IEC 11695-3 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 17, *Cards and personal identification*.

ISO/IEC 11695 consists of the following parts, under the general title *Identification cards — Optical memory cards — Holographic recording method*:

— *Part 1: Physical characteristics*

— *Part 2: Dimensions and location of accessible optical area*

— *Part 3: Optical properties and characteristics*

Introduction

ISO/IEC 11695 is one of a series of International Standards defining the parameters for optical memory cards and the use of such cards for the storage and interchange of digital data.

These International Standards recognize the existence of different methods for recording and reading information on optical memory cards, the characteristics of which are specific to the recording method employed. In general, these different recording methods will not be compatible with each other. Therefore, these International Standards are structured to accommodate the inclusion of existing and future recording methods in a consistent manner.

ISO/IEC 11695 is specific to optical memory cards using the holographic recording method. Characteristics which apply to other specific recording methods are found in separate International Standards.

This part of ISO/IEC 11695 defines the optical properties and characteristics and the extent of compliance with, addition to, and/or deviation from the relevant base document, ISO/IEC 11693.

The International Organization for Standardization (ISO) and International Electrotechnical Commission (IEC) draw attention to the fact that it is claimed that compliance with this document may involve the use of patents.

The ISO and IEC take no position concerning the evidence, validity and scope of these patent rights.

The holders of these patent rights have assured the ISO and IEC that they are willing to negotiate licenses under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the Statements of the holders of these patent rights are registered with the ISO and IEC. Information may be obtained from:

Certego GmbH
Lichtenbergstrasse 8
85748 Garching
Germany

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Identification cards — Optical memory cards — Holographic recording method —

Part 3:
Optical properties and characteristics

1 Scope

This part of ISO/IEC 11695 specifies the optical properties and characteristics of optical memory cards using the holographic recording method.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 11695-1, *Identification cards — Optical memory cards — Holographic recording method — Part 1: Physical characteristics*

ISO/IEC 11695-2, *Identification cards — Optical memory cards — Holographic recording method — Part 2: Dimensions and location of accessible optical area*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 11695-1, ISO/IEC 11695-2 and the following apply.

3.1
reflectivity
ratio of reflected light to the light incident at a specified wavelength measured at a normal incidence on the holographic memory card

NOTE Reflectivity is generally expressed as a percentage.

3.2
scattering
deviation of reflected radiation from the angle predicted by the law of reflection

NOTE Reflections that undergo scattering are called diffuse reflections. Diffuse reflections are measured by means of an integration sphere, while properly averaging over all angles of illumination and observation.

3.3
spatial resolution
ability of the storage material to distinguish and/or record physical details by electromagnetic means

NOTE The (spatial) resolution is typically expressed in line pairs per millimetre.

3.4
contrast transfer function
CTF
mathematical function that expresses the ability of an optical device to transfer signals faithfully as a function of the spatial or temporal frequency of the signal

NOTE The CTF is the ratio of percentage modulation of a square wave signal leaving to that entering the device over the range of frequencies of interest. The CTF is usually presented as a graph of CTF versus log (frequency).

3.5
diffraction
interference effects occurring when light is incident on a hologram

NOTE The light is reflected or transmitted in discrete directions, called diffraction orders.

3.6
diffraction efficiency
relation of the power of the diffracted light beam (P_{diff}) to the incident power of the read-out beam (P_{inc}):

$$\eta = \frac{P_{diff}}{P_{inc}}$$

NOTE The diffraction efficiency is dependent upon the holographic storage medium. It varies between 0 and 1.

3.7
diffraction grating
device having periodical variations of absorption index and/or refractive index and/or optical path length

3.8
read power
laser power used to read out holograms from the accessible optical area

NOTE Read power is usually expressed in milliwatts.

3.9
write power
laser power required to write information to the accessible optical area at a specified wavelength and beam size

NOTE Write power is usually expressed in milliwatts.

4 Optical properties and characteristics

4.1 Surface roughness/scattering

The substrate shall provide a flat and smooth surface as the carrier for the reflective and optical storage layers. The surface roughness (Ra) shall be less than 100 nm: higher values can cause substantial scattering of the read-out beam. Scattered light shall be less than 10 % for wavelengths between 500 nm and 1 000 nm.

4.2 Reflectivity of blank accessible optical area

The reflective layer enables reading of holographic memory cards in reflection mode. The reflectivity of the blank accessible optical area (not containing holograms) shall be greater than 90 % for wavelengths between 500 nm and 1 000 nm.

4.3 Spatial resolution

The limiting resolution of the holographic memory card is measured by determining the smallest group of bars, both vertically and horizontally, for which the correct number of bars can be recorded and/or seen. By calculating the contrast between the black and white areas at several different frequencies, points of the contrast transfer function (CTF) can be determined with the contrast equation.

$$Contrast = \frac{C_{\max} - C_{\min}}{C_{\max} + C_{\min}}$$

where

$C_{\max}$ is the normalized value of the maximum (for example, the voltage or grey value of the white area);

$C_{\min}$ is the normalized value of the minimum (for example, the voltage or grey value of the black area).

When the system can no longer resolve the bars, the black and white areas have the same value, so *Contrast* = 0. At very low spatial frequencies, $C_{\max}$ = 1 and $C_{\min}$ = 0 so *Contrast* = 1.

For the holographic memory card the minimum *Contrast* shall be 1, up to a density of 1 000 line pairs per millimetre.