
**Information technology — JPEG 2000
image coding system: Interactivity tools,
APIs and protocols**

AMENDMENT 3: JPIP extensions to 3D data

*Technologies de l'information — Système de codage d'images
JPEG 2000: Outils d'interactivité, interfaces de programmes
d'application et protocoles*
(standards.iteh.ai)

AMENDEMENT 3: Extensions JPIP aux données 3D

ISO/IEC 15444-9:2005/Amd 3:2008

<https://standards.iteh.ai/catalog/standards/sist/fe5f9bb2-9f53-46ef-9420-6f8751751dbc/iso-iec-15444-9-2005-amd-3-2008>

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 15444-9:2005/Amd 3:2008](https://standards.iteh.ai/catalog/standards/sist/fe5f9bb2-9f53-46ef-9420-6f8751751dbc/iso-iec-15444-9-2005-amd-3-2008)

<https://standards.iteh.ai/catalog/standards/sist/fe5f9bb2-9f53-46ef-9420-6f8751751dbc/iso-iec-15444-9-2005-amd-3-2008>



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

CONTENTS

	<i>Page</i>
1) Subclause 3.3.....	1
2) Subclause 3.4.....	1
3) Subclause A.3.2.1.....	1
4) Subclause C.4.1.....	1
5) Subclause C.4.1.....	2
6) Subclause C.4.5.....	3
7) Subclauses C.4.6 and C.4.7.....	3
8) Subclause C.4.5.....	4
9) Subclause C.4.7.....	4
10) Subclause C.4.11.....	4
11) Subclause D.2.....	4

iTeh STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/fe5f9bb2-9f53-46ef-9420-6f8751751dbc/iso-iec-15444-9-2005-amd-3-2008>

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 3 to ISO/IEC 15444-9:2005 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*, in conjunction with ITU-T. The identical text is published as ITU-T Rec. T.808 (01/2005)/FDAM 3(E).

[ISO/IEC 15444-9:2005/Amd 3:2008](https://standards.iteh.ai/catalog/standards/sist/fe5f9bb2-9f53-46ef-9420-6f8751751dbc/iso-iec-15444-9-2005-amd-3-2008)

<https://standards.iteh.ai/catalog/standards/sist/fe5f9bb2-9f53-46ef-9420-6f8751751dbc/iso-iec-15444-9-2005-amd-3-2008>

INTERNATIONAL STANDARD
RECOMMENDATION ITU-TInformation technology – JPEG 2000 image coding system:
Interactivity tools, APIs and protocols

Amendment 3

JPIP extensions to 3D data

1) Subclause 3.3

Add the following item:

3.3.23 slice: A subset of voxels in a volumetric image with constant Z coordinates.

2) Subclause 3.4

Add the following items:

fz z-axis frame size for client request view-window
fz' z-axis frame size for suitable codestream resolution
fz'' modified jpx z-axis frame size for suitable resolution
oz z-axis offset for client request view-window
oz' z-axis offset for suitable codestream/component region
oz'' modified z-axis offset for suitable region
sz z-axis size of client request view-window
sz' z-axis size for suitable codestream region
sz'' modified jpx z-axis size for suitable region

3) Subclause A.3.2.1

After the third paragraph, add the following:

For volumetric images encoded in JP3D (Rec. ITU-T T.809 | ISO/IEC 15444-10), the sequence number of precincts within a tile-component is computed as follows: All precincts of the lowest resolution level, i.e., those containing only the [L|X][L|X][L|X] samples are sequenced first, starting from zero, following a raster scan order as defined by 3.11 of Rec. ITU-T T.809 | ISO/IEC 15444-10. The precincts from each successive resolution level are sequenced in turn, again following the raster scan order of 3.11. The precinct with sequence number 0 thus refers to the front most, upper left hand precinct of the lowest resolution sub-band of the image component 0 in tile 0.

4) Subclause C.4.1

Replace the third paragraph with:

Codestream image regions are described using 3 n-dimensional parameters where n is the number of dimensions required to describe this image. The size parameters and offset parameters specify the extent and location of the desired codestream image region with respect to a whole image that has the given frame size. Figure C.1 demonstrates this set-up for regular images with $n = 2$, but the construction carries over naturally to a higher number of dimensions. For the rest of this subclause, we will consider only this case, naming the frame size f_x and f_y , the offset of the region o_x and o_y and its size s_x and s_y as indicated in Figure C.1.

5) Subclause C.4.1

At the end of C.4.1, add the following:

The above considerations for two dimensional images carry over naturally to images of higher dimensionality, e.g., to the case $n = 3$ where a third coordinate is added to each group of parameters. Specifically, the frame size is then represented by three numbers f_x , f_y and f_z , the offset by o_x , o_y and o_z and the region size by s_x , s_y and s_z . In that case, Equation C-1 extends to:

$$ZO_{siz}' = \left\lceil \frac{ZO_{siz}}{2^r} \right\rceil \quad Z_{siz}' = \left\lceil \frac{Z_{siz}}{2^r} \right\rceil$$

where ZO_{siz} and Z_{siz} specify the original image offset and canvas size in the Z direction, respectively. Equation C-2 extends to:

$$o_z' = \left\lceil o_z \cdot \left(\frac{f_z'}{f_z} \right) \right\rceil \quad s_z' = \left\lceil (s_z + o_z) \cdot \frac{f_z'}{f_z} \right\rceil - o_z'$$

For images represented within Rec. ITU-T T.809 | ISO/IEC 15444-10 codestream, ZO_{siz} and Z_{siz} are taken from the relevant NSI marker segment.

In addition, a server may choose to identify a Rec. ITU-T T.801 | ISO/IEC 15444-2 codestream making use of wavelet transformations as a multi-component transformation with a volume image using generated components to represent the third (Z) dimension. The identification by which generated components constitute which slice is then at the discretion of the server, and so is the choice of suitable values for ZO_{siz} and Z_{siz} . In this situation, clients may either choose to use the two-dimensional or three-dimensional request syntax to fetch data from the client. For two-dimensional requests, it is up to the client to identify slices with components and make the necessary requests; for three-dimensional requests, it is the duty of the server to find the relevant components for the requested image volume. In the latter case, servers are not required to honour the comp and mctres fields, see C.4.5 and C.4.11, and their usage is discouraged in this case.

Application Note:

ISO/IEC 15444-9:2005/Amd 3:2008

In case servers have to identify a Rec. ITU-T T.801 | ISO/IEC 15444-2 encoded image with volumetric data, they are recommended to use the following choices for ZO_{siz} and Z_{siz} to provide an efficient and consistent definition of resolution levels in the Z direction:

- ZO_{siz} shall be taken identical to the minimum of all O_{mcc}^i values in all MCC markers within the codestream identified by the request, see Annex A.3.8 of Rec. ITU-T T.801 | ISO/IEC 15444-2. This choice ensures a reasonable definition of the resolution levels in the Z direction compatible to the origin of the wavelet transformation, and eases the extraction of lower-resolution images from the stream.
- Z_{siz} is to be taken identical to the number of slices identified by methods described below plus ZO_{siz} as computed by the procedure above.

It is recommended to use the following procedure to identify the generated components that make up a slice in case a Rec. ITU-T T.801 | ISO/IEC 15444-2 conforming file format is available for the target of the request:

- Identify all compositing layers of the file that use the codestream the request targets at. Each compositing layer in this set defines exactly one slice of the volumetric image. The Z coordinate to be assigned to the first compositing layer in this set is to be ZO_{siz} , as defined above, and all following slices are assigned continuously ascending Z coordinates in the order they appear in the file.
- Within each compositing layer, scan for a channel definition box. If there is a channel definition box, identify the channels that are associated to a colour by testing the *Asoc* field of the *cdef* box for that channel and perform the next step. Otherwise, apply the next step to all channels.
- Identify within the compositing layer the generated components providing the data for the channels found in the step above. For direct mapping, this is a 1:1 relation, but for palette mapped images, the component mapping box must be parsed.

If no Rec. ITU-T T.801 | ISO/IEC 15444-2 conforming file format is available, other metadata outside the scope of this Recommendation | International Standard might be available to identify which generated components define which slice. In this case, servers are expected to use whatever metadata is available and be consistent with the specifications made there.

In case no additional meta-data, neither inside 15444 nor outside of it, is available, the following algorithm can be used as a last resort to come to a reasonable definition of slices:

A codestream is identified as grey scale volume image if each generated component is reconstructed by exactly one transformation stage in the sense of Annex J of Rec. ITU-T T.801 | ISO/IEC 15444-2, and if that type of the transformation stage is a wavelet transformation. A codestream is identified as colour volume image, if each generated component is reconstructed by exactly two transformation stages of which the first one, which is applied to the spatial components of the codestream, is a wavelet transformation, and of which the second one is not a wavelet transformation, but a decorrelation or dependency transformation. All other set-ups cannot be handled.

The Z coordinate of the slice a generated component contributes to is identified as follows: For generated component g, identify the MCC marker MCC^i that describes the wavelet transformation step taken to compute g from the spatial components of the canvas system. According to the above definition, there should be exactly one such marker. If the image is a grey-scale image, find the index j in the output component collection of that marker such that $Wmcc^j$ equals g, i.e., find the output slot in the transformation generating this component. Then generated component g contributes then to the slice with $Z = j + Omcc^i$. This will define a Z coordinate for the component g based on the ordering of the output of the wavelet transformation step.

For colour images, first identify all intermediate input components of the dependency or decorrelation transformation required to reconstruct the generated component g, and find for each of them its Z coordinate as described above. It is required that this Z coordinate does not depend on which of the intermediate components required to reconstruct generated component g has been chosen; otherwise, this algorithm fails.

6) Subclause C.4.5

Insert the following after C.4.4 and update the following subclause numbers accordingly:

C.4.5 Frame size for variable dimension data (fvsiz)

```
fvsiz = "fvsiz" "=" 1#UINT [l] ["round-direction]
round-direction = "round-up" / ("round-down" / "closest")
```

This request takes a variable number of arguments. There shall be as many numerical arguments as there are dimensions in the source codestream. Specifically, if the image is a regular two-dimensional image, this request field is equivalent to the `fsiz` field with the first argument defining `fx` and the second defining `fy`. If the source stream represents volumetric data, there shall be three numerical arguments, specifying the view-window extents `fx`, `fy` and `fz`, in that order.

This field is used to identify the resolution associated with the requested view-window. The numerical arguments specify the desired image resolution, one per dimension. The `round-direction` value specifies how an available codestream image resolution shall be selected for each requested codestream, if the requested image resolution is not available within that codestream. The requested frame size is mapped to a codestream image resolution, following the procedure described in C.4.1, possibly with the addition of coordinate transformations requested via the Codestream Context request field (see C.4.7).

7) Subclauses C.4.6 and C.4.7

Insert the following after C.4.5 and update the following subclause numbers accordingly:

C.4.6 Offset for variable dimension data (rvofff)

```
rvofff = "rvofff" "=" #1UINT
```

This field is used to identify the upper left (front) corner (offset) of the spatial region associated with the requested view-window; if not present, the offset defaults to 0. The actual displacement of a codestream image region from the upper left (front) corner of the image, at the actual codestream image resolution selected by the server, is obtained following the procedure described in C.4.1, possibly with the addition of coordinate transformation requested via a Codestream Context request field (see C.4.7). This field takes a variable number of arguments, there shall be as many arguments to the `rvofff` field as there are dimensions in the source stream. Specifically, for regular two-dimensional images exactly, two arguments are required and this field is equivalent to `rofff`. For volumetric images, exactly three arguments are required, which define `ox`, `oy` and `oz`.

Use of the Offset field for Variable Dimension Data is valid only in conjunction with the Frame Size request field for Variable Dimension Data. If the view-window specified using Region Size and/or Offset turns out to be empty (no area), the server's response should not include any compressed image data. In particular, responses of type "jpp-stream"

or "jpt-stream" should contain no messages which reference precinct, tile or tile-header data-bins. The server may, at its discretion, opt to return main header or metadata-bin messages that would have been returned in response to a request that omitted the Frame Size request field.

C.4.7 Region size for variable dimension data (rvsiz)

```
rvsiz = "rvsiz" "=" #1UINT
```

This field is used to identify the extent (size) of the spatial region associated with the requested view-window; if not present, the region extends to the lower right (back) corner of the image. The actual extent of the view-window, at the actual resolution level selected by the server, are computed following the procedure described in C.4.1. The view-window need not necessarily be fully contained within the image itself, in which case the server simply takes the intersection between the full image region and the requested view-window.

This field takes a variable number of arguments, and there shall be exactly as many arguments as there are dimensions in the target stream. If the view-window specified using Region Size and/or Offset turns out to be empty (no area), the server's response should not include any compressed image data. In particular, responses of type "jpp-stream" or "jpt-stream" should contain no messages which reference precinct, tile or tile-header data-bins. The server may, at its discretion, opt to return main header or metadata-bin messages that would have been returned in response to a request that omitted the Frame Size request for Variable Dimension Data field. In case the image is a regular two-dimensional image, this request takes two arguments, and is identical to the `rsiz` field. For volumetric images, the three arguments are `sx`, `sy` and `sz`, in this order.

8) Subclause C.4.5

At the end of C.4.5, add the following:

Usage of the `comps` field in combination with the Frame, Region or Region Offset request field for Variable Dimension Data with three or more numerical arguments on Rec. ITU-T T.801 | ISO/IEC 15444-2 codestreams is discouraged and servers cannot be expected to handle it.

Full STANDARD PREVIEW
(standards.iteh.ai)

9) Subclause C.4.7

At the end of C.4.7, add the following:

[ISO/IEC 15444-9:2005/Amd 3:2008](https://standards.iteh.ai/catalog/standards/sist/fe5f9bb2-9f53-46ef-9420-68751751d4bc/iso-iec-15444-9-2005-amd-3-2008)

[https://standards.iteh.ai/catalog/standards/sist/fe5f9bb2-9f53-46ef-9420-](https://standards.iteh.ai/catalog/standards/sist/fe5f9bb2-9f53-46ef-9420-68751751d4bc/iso-iec-15444-9-2005-amd-3-2008)

[68751751d4bc/iso-iec-15444-9-2005-amd-3-2008](https://standards.iteh.ai/catalog/standards/sist/fe5f9bb2-9f53-46ef-9420-68751751d4bc/iso-iec-15444-9-2005-amd-3-2008)

The above considerations, especially Equations C-3 and C-4, valid for two-dimensional image data only. They are extended naturally to higher dimensions by duplicating the computations for each additional dimension. Usage of the codestream context field is discouraged if the target of the request contains codestreams with differing numbers of dimensions, and servers cannot be expected to handle this case.

10) Subclause C.4.11

At the end of C.4.11, add the following:

Usage of the `mctres` field in combination with the Frame, Region or Region Offset request field for Variable Dimension Data with three or more numerical arguments on Rec. ITU-T T.801 | ISO/IEC 15444-2 codestreams is discouraged and servers cannot be expected to handle it.

11) Subclause D.2

Add the following subclauses to Annex D and update the following subclause numbers accordingly:

D.2.8 Frame size for variable dimension data (JPIP-fvsiz)

```
JPIP-fvsiz = "JPIP-fvsiz" ":" #1UINT
```

The server should send this response header if the actual frame size differs in any way from that requested via the Frame Size or Frame Size for Variable Dimension Data field. The server may need to modify the frame size because the client requested a frame size that does not exist. It is at the discretion of the server to either return the `JPIP-fsiz` or the `JPIP-fvsiz` response header on two-dimensional data requests, both responses shall be considered equivalent in this case. In all other cases, only the `JPIP-fvsiz` response header shall be used.

D.2.9 Region size for variable dimension data (JPIP-rvsiz)

JPIP-rvsiz = "JPIP-rvsiz" ":" #1UINT

The server should send this response header if the size of the view-window differs in any way from that requested via the Region Size or Region Size for Variable Dimension Data request field. If two-dimensional data had been requested, it is at the discretion of the server to pick either this response header, or the JPIP-rsiz response header, and both shall be considered equivalent by the client. For all other cases, only the JPIP-rvsiz response header shall be used.

D.2.10 Offset for variable dimension data (JPIP-rvoff)

JPIP-rvoff = "JPIP-rvoff" ":" #1UINT

The server should send this response header if the view-window offset differs in any way from that requested via an Offset or Offset for Variable Dimension Data request field. The server may need to modify the offset if it is resizing a requested view-window. For two dimensional data, it is at the discretion of the server to pick either this response header, or the JPIP-roff response header, and the client shall consider both equivalent. For all other data, the JPIP-rvoff response header shall be used.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 15444-9:2005/Amd 3:2008](https://standards.iteh.ai/catalog/standards/sist/fe5f9bb2-9f53-46ef-9420-6f8751751dbc/iso-iec-15444-9-2005-amd-3-2008)

<https://standards.iteh.ai/catalog/standards/sist/fe5f9bb2-9f53-46ef-9420-6f8751751dbc/iso-iec-15444-9-2005-amd-3-2008>