
Document management — Machine-readable paper forms — Optimal design for user friendliness and electronic document management systems (EDMS)

Gestion de document — Formulaires papier exploitables par machine — Conception optimale pour la facilité d'emploi et systèmes de gestion de document électronique (EDMS)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 12029:2010

<https://standards.iteh.ai/catalog/standards/sist/30008e28-3967-4dbf-921b-4f7ba311128e/iso-12029-2010>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 12029:2010

<https://standards.iteh.ai/catalog/standards/sist/30008e28-3967-4dbf-921b-4f7ba311128e/iso-12029-2010>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction.....	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Layout and design	2
5 User guidance	8
6 Post-printing features	13
7 Materials	14
8 Form testing	15
9 Reference criteria for designing forms	15
10 New technology	16
Bibliography	17

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 12029:2010

<https://standards.iteh.ai/catalog/standards/sist/30008e28-3967-4dbf-921b-4f7ba311128e/iso-12029-2010>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12029 was prepared by Technical Committee ISO/TC 171, *Document management applications*, Subcommittee SC 2, *Application issues*.

This first edition cancels and replaces ISO/TS 12029:2007, which has been technically revised.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 12029:2010
<https://standards.iteh.ai/catalog/standards/sist/30008e28-3967-4dbf-921b-4f7ba311128e/iso-12029-2010>

Introduction

This International Standard discusses issues and provides guidance for the design of forms that are used for electronic capture of handwriting information. Features include colour dropouts, type fonts, printing screen tints, line width, data storage and other interrelated issues. It is necessary to balance conflicting requirements of user-friendliness and electronic capture. Making a form appealing by use of colour or graphics could assist users when they complete the form but could also decrease the form's scannability or other automated, related functions. This conflict might require compromise in the design of a form.

While this International Standard focuses on the design and structure of paper-based forms, it is worth noting that the design and structure of electronic based forms can have different characteristics, ensuring usability and readability. The user is advised that use of these specifications when developing paper-based forms while keeping in mind that electronic forms can be easily replicated in an electronic format (with the same content as in the paper-based form), but with differing fonts and spacing.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 12029:2010](https://standards.iteh.ai/catalog/standards/sist/30008e28-3967-4dbf-921b-4f7ba311128e/iso-12029-2010)

<https://standards.iteh.ai/catalog/standards/sist/30008e28-3967-4dbf-921b-4f7ba311128e/iso-12029-2010>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 12029:2010

<https://standards.iteh.ai/catalog/standards/sist/30008e28-3967-4dbf-921b-4f7ba311128e/iso-12029-2010>

Document management — Machine-readable paper forms — Optimal design for user friendliness and electronic document management systems (EDMS)

1 Scope

This International Standard specifies requirements concerning the design of forms for user friendliness, with optimal machine readability for processing by electronic document management systems (EDMS). These requirements are limited to forms using roman characters.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1073-1, *Alphanumeric character sets for optical recognition — Part 1: Character set OCR-A — Shapes and dimensions of the printed image*

ISO 1073-2, *Alphanumeric character sets for optical recognition — Part 2: Character set OCR-B — Shapes and dimensions of the printed image*

ISO 12651-1, *Electronic document management — Vocabulary — Part 1: Electronic document imaging*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 12651-1 and the following apply.

3.1

alphanumeric

pertaining to a character set that contains letters, numbers and other characters, such as punctuation marks and symbols

NOTE Adapted from ISO/IEC 2382-4.

3.2

character pitch

number of characters per unit length of a line of print

3.3

dropout ink

ink of a colour that cannot be detected by a scanner

**3.4
font**

complete set of characters of a given size, weight and style of type, including capitals, small capitals and lower-case characters, together with figures, punctuation marks, ligatures, etc.

NOTE Adapted from ISO/IEC 2382-23.

**3.5
ICR
intelligent character recognition**

advanced optical character recognition (OCR), or rather more specifically, hand-printed recognition system that allows fonts and different styles of handwriting to be learned by a computer during processing to improve accuracy and recognition levels

**3.6
MICR
magnetic ink character recognition**

machine recognition of digits printed with magnetizable ink

**3.7
OMR
optical mark recognition**

machine recognition of a mark such as a tick, cross or spot based on minimum area rather than shape of the mark

[ISO 2033]

iTeh STANDARD PREVIEW
(standards.iteh.ai)

**3.8
recognition zone**

area around a recognition data field that is free of other data

[ISO 12029:2010](#)

<https://standards.iteh.ai/catalog/standards/sist/30008e28-3967-4dbf-921b-4f7ba311128e/iso-12029-2010>

4 Layout and design

4.1 General

The design of a form easiest for a person to complete can be in conflict with the most machine-readable form. For example, in a user-friendly layout, the following items, all interspersed with printed instructions next to specific areas, might be desirable:

- large print,
- colour-coded areas, and
- areas to be completed with both alphabetic and numeric information.

However, in a form designed for an electronic image management system (EIM), strict segregation of spaces for numeric and alphabetic information and instructional text within dropout colour areas can all be essential features. Optimum design can require a compromise between ideal user and scanner requirements. All logically connected information should be placed on the same page.

4.2 Data storage requirement

The designer should be aware of the impact on data storage requirements of line borders, screened tints and logos or other design elements with large areas of reversed print. Reversed print will make heavy demands on data storage. For all designs, particularly those having large areas of reversed print, the amount of data storage required should be determined and compared to the amount of data storage available within the system.

4.3 Page format

On each page of a form, the margin all around should not be less than 10 mm. If the document is bound, padded or has punched holes or die cuts, the margin at that edge should be not less than 25 mm, and holes and die cuts should be restricted to that margin.

Text and entry fields should not be within 6,5 mm of any crease or perforation.

4.4 Typeface and font

4.4.1 Typeface

There are two styles of typeface commonly used on forms, serif and sanserif, as illustrated in Figure 1.



Figure 1 — Comparison of serif and sanserif typefaces

Serif style is designed for ease of legibility, has variable line width within a character and a cross-line finishing a stroke of a letter. Sanserif has uniform line width within a character and no cross-lines. It is the style used in ISO standards.

Serif type will inherently take more data storage capacity in a compressed image than sanserif type because more information has to be recorded for each character. With the most commonly used compression techniques, approximately 10 % more storage is required for a page printed in serif, as compared with one printed in sanserif type.

Sanserif generally requires less horizontal line space and more vertical height than the same point size serif type. Because of its uniform line width, it is preferred for photocopying, microfilming and scanning.

For forms which might be used in optical character recognition (OCR) applications, sanserif typefaces should be used.

For information on a form that is not required to be captured by scanning, the style of typeface used is not important.

4.4.2 Symbols

An OCR program can use a particular symbol to prompt an action. The form designer should be aware of any such symbols and avoid their use other than as a prompt.

4.4.3 Spacing

In typesetting, character spacing can be either fixed or proportional. In fixed typesetting, each character takes up equal horizontal space. Proportional typesetting allows for characters of different width, such as that of “i” compared with “w” and automatically adjusts space between the individual characters to give a more natural appearance.

There should be a clear gap between characters. The recommended minimum gap is not less than the width of the vertical stroke of characters of the font.

The designer should also be concerned with vertical spacing requirements of an OCR system. Although 4,2 mm vertical spacing is usually sufficient for typewritten entries, at least twice that amount of space is necessary for hand-printed entries and for separating entries for OCR.

4.4.4 Character pitch

Form design should allow no more than 0,4 characters per millimetre for character pitch.

4.4.5 Character size

In the printing industry, type size is usually specified in millimetres. In a computer or typewriter, type size is usually indicated in points. Fortunately, the printing industry is familiar with both systems and can easily translate requirements. The point (0,35 mm) is a unit derived from the height of metal slugs, once commonly but now rarely, used to set type. The size of character is not directly related to point size. For a given point size, the actual heights of the same upper-case character can be different for various typefaces. There is also variation in the ratio of heights of lower-case “e” to upper-case characters. This means that for a given point size, even if upper-case characters of two different typefaces have the same height, there is a possibility that this may not be so for lower-case characters. Since it is the size of the lower-case characters that will limit scannability, minimum acceptable point size should be determined by the height of the lower-case “e”. The recommended minimum height of the lower-case “e” is 1,4 mm.

If the EIM system is used as a transfer medium as part of overall processing of the information extracted from a form, the minimum type size used shall allow for any degradation of image quality resulting from subsequent parts of the process.

4.4.6 Weight

The weight of a type font is its relative line thickness, ranging from light to extra bold. Font weight directly affects the number of dots or pixels used to display a character of an electronic image. Different weights can also be used to emphasize or reduce significance of text blocks or captions for the user.

4.4.7 Type family

Design variations on a basic typeface can include italic, condensed, expanded and others. Form designers should try to keep the number of type families used within a form to a minimum to project an uncomplicated appearance that is pleasing to the eye. EIM systems and particularly OCR software can also benefit from limited use of type families.

4.5 Machine-printed stylized information

4.5.1 General

Information may be presented on a form as a bar code or in OCR or MICR characters. These bar codes and stylized character sets are especially designed for automated processing and are machine readable with high accuracy.

Machine reading is not always wholly accurate. The degree of accuracy achievable can be improved if forms have error-checking features built into their design. Whenever possible, forms should be designed to use a second source of information for cross checking. When calculation is involved, both subtotal and entry figures should appear on forms so the processing system can recalculate the subtotal to compare it with the amount read. Other examples of information for cross checking are account number/customer name, version number/issue date.

iTeh STANDARD PREVIEW

(standards.iteh.ai)

ISO 12029:2010
<https://standards.iteh.ai/catalog/standards/sist/30008e28-3967-4dbf-921b-4f7ba311128e/iso-12029-2010>

4.5.2 OCR fonts

OCR fonts such as Farrington 7B, OCR-A and OCR-B are available with numeric only and alphanumeric character sets for automated recognition. Data encoded using OCR fonts shall be printed in accordance with the relevant International Standards listed in Table 1.

Table 1 — OCR font standards

Code types supported	International Standard
OCR-A numeric	ISO 1073-1
OCR-A alphanumeric	ISO 1073-1
OCR-B numeric	ISO 1073-2
OCR-B alphanumeric	ISO 1073-2

OCR characters should be printed by a laser printer at the highest resolution whenever possible. The use of a dot matrix printer will generally give poorer print quality and reduce the accuracy of the OCR reading. Black characters printed on a white or light-coloured background are preferred.

OCR characters may be placed anywhere on the form, however, they should preferably be in a clearly defined recognition zone and printed parallel to the other text. For an example of an OCR font, see Figure 2.

ITh STANDARD PREVIEW
(standards.itech.ai)
A B C D E F G H

Figure 2 — Sample OCR code
ISO 12029:2010
<https://standards.itech.ai/catalog/standards/sist/30008e28-3967-4dbf-921b-4f7ba311128e/iso-12029-2010>

4.5.3 MICR fonts

MICR fonts, shown in Figure 3, are limited, highly stylized character sets that are printed using magnetic ink. Among several fonts available, E-13B and CMC-7 are the fonts frequently used on financial transaction documents such as cheques. E-13B is highly machine readable because of its solid clear character format. CMC-7, on the other hand, is more difficult for optical recognition because the characters are made of discrete, thin vertical lines.

⑆ 255074988 ⑆ 1598300 ⑆ 096 ⑆

Figure 3 — Sample MICR code