
**Gas cylinders — 17E and 25E taper
threads for connection of valves to gas
cylinders —**

**Part 1:
Specifications**

iTeh STANDARD PREVIEW
*Bouteilles à gaz — Filetages coniques 17E et 25E pour le raccordement
des robinets sur les bouteilles à gaz —
(standards.iteh.ai)
Partie 1. Spécifications*

ISO 11363-1:2010

<https://standards.iteh.ai/catalog/standards/sist/e4a5eb59-9ef6-4d05-a7c5-2fd08049ab87/iso-11363-1-2010>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 11363-1:2010

<https://standards.iteh.ai/catalog/standards/sist/e4a5eb59-9ef6-4d05-a7c5-2fd08049ab87/iso-11363-1-2010>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction.....	v
1 Scope	1
2 Terms and definitions	1
2.1 General	1
2.2 Terms relating to cones	2
2.3 Terms relating to diameter	2
2.4 Terms relating to reference	3
3 Requirements	4
3.1 Thread handedness	4
3.2 Taper	4
3.3 Thread profile	4
3.4 Pitch, P	4
3.5 Dimensions	4
4 Thread end finish	7
5 Marking	8
Bibliography	9

iTech STANDARD PREVIEW
(standards.itech.ai)

ISO 11363-1:2010
<https://standards.itech.ai/catalog/standards/sist/e4a5eb59-9ef6-4d05-a7c5-2fd08049ab87/iso-11363-1-2010>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 11363-1 was prepared by Technical Committee ISO/TC 58, *Gas cylinders*, Subcommittee SC 2, *Cylinder fittings*.

This first edition of ISO 11363-1 cancels and replaces ISO 10920:1997 and ISO 11116-1:1999.

ISO 11363 consists of the following parts, under the general title *Gas cylinders — 17E and 25E taper threads for connection of valves to gas cylinders*:

- iTeh STANDARD PREVIEW**
(standards.iteh.ai)
- [ISO 11363-1:2010](https://standards.iteh.ai/catalog/standards/sist/e4a5eb59-9ef6-4d05-a7c5-2fd08049ab87/iso-11363-1-2010)
- *Part 1: Specifications* <https://standards.iteh.ai/catalog/standards/sist/e4a5eb59-9ef6-4d05-a7c5-2fd08049ab87/iso-11363-1-2010>
 - *Part 2: Inspection gauges*

Introduction

Gas cylinders intended to contain compressed, liquefied or dissolved gas under pressure are fitted with accessories to allow release and refilling of gas. Hereinafter, the term “valve” will apply to such accessories.

The connection between cylinder and valve is obtained by assembly of two taper-threads (an external one on the valve stem and an internal one in the cylinder neck), both having the same nominal taper, thread pitch and thread profile.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 11363-1:2010](https://standards.iteh.ai/catalog/standards/sist/e4a5eb59-9ef6-4d05-a7c5-2fd08049ab87/iso-11363-1-2010)

<https://standards.iteh.ai/catalog/standards/sist/e4a5eb59-9ef6-4d05-a7c5-2fd08049ab87/iso-11363-1-2010>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 11363-1:2010](#)

<https://standards.iteh.ai/catalog/standards/sist/e4a5eb59-9ef6-4d05-a7c5-2fd08049ab87/iso-11363-1-2010>

Gas cylinders — 17E and 25E taper threads for connection of valves to gas cylinders —

Part 1: Specifications

1 Scope

This part of ISO 11363 specifies dimensions and tolerances for taper screw threads of nominal diameter 17,4 mm (designated 17E) and 25,8 mm (designated 25E) used for the connection of valves to gas cylinders.

It does not cover the connection requirements for:

- mechanical strength;
- gas tightness;
- capability of repeated assembly and dismantling operations.

Gauge inspection is covered by ISO 11363-2.

<https://standards.iteh.ai/catalog/standards/sist/e4a5eb59-9ef6-4d05-a7c5-2fd08049ab87/iso-11363-1-2010>

2 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

2.1 General

2.1.1

basic profile

theoretical profile, when the profile of the external thread coincides with the profile of the internal thread

2.1.2

design profile

design profile differs from the basic profile due to the radius of the root, necessary for manufacturing and strength requirements

NOTE For such a profile, manufacturing tolerances are taken into account.

2.1.3

length of external thread, l_2

length of full form thread on the valve stem, measured along the cone axis from the reference plane A

NOTE See Figure 1, Table 1 and Table 3.

2.1.4

length of internal thread, L_2

length of full form thread in the cylinder neck, measured along the cone axis from the reference plane F

NOTE See Figure 1, Table 2 and Table 4.

**2.1.5
pitch**

P
distance, measured parallel to the cone surface, between two homologous points of two parallel consecutive flanks of the same thread

NOTE See Figures 2 and 3.

**2.1.6
taper**

ratio of the difference of two diameters corresponding to planes normal to the axis of the reference cone, and the axial distance between the same planes

NOTE Taper can be expressed as a ratio, as an angle or as a percentage.

**2.1.7
thread profile**

thread shape obtained by the intersection of a plane through the thread axis and the threaded surface

**2.1.8
valve stem**

tapered end of the valve body (inlet connection), with a thread formed on the external surface of the truncated cone

NOTE See Figure 1.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

**2.1.9
cylinder neck thread**

tapered axial hole in the cylinder neck, with a thread formed on the internal surface of the truncated cone

ISO 11363-1:2010
<https://standards.iteh.ai/catalog/standards/sist/e4a5eb59-9ef6-4d05-a7c5-2fd08049ab87/iso-11363-1-2010>

NOTE See Figure 1.

2.2 Terms relating to cones

**2.2.1
major cone**

cone bounding the crests of the thread of the valve stem, or the roots of the cylinder neck thread

**2.2.2
minor cone**

cone bounding the roots of the thread, of the valve stem, or the crests of the cylinder neck thread

**2.2.3
pitch cone**

cone passing, coaxially and midway, between the major and minor cones

2.3 Terms relating to diameter

NOTE See Figure 1.

**2.3.1
major diameter, d_{1e}**

diameter of the major cone at the valve stem thread reference plane A (before any chamfer is cut)

**2.3.2
major diameter, D_{1e}**

diameter of the major cone at reference plane G

2.3.3**minor diameter, d_{1i}**

diameter of the minor cone at the valve stem thread reference plane A (before any chamfer is cut)

2.3.4**minor diameter, D_{1i}**

diameter of the minor cone at reference plane G

2.3.5**pitch diameter, d_{1p}**

diameter of the pitch cone at the valve stem thread reference plane A (before any chamfer is cut)

2.3.6**pitch diameter, d_{2p}**

diameter of the pitch cone at reference plane B

2.3.7**pitch diameter, D_{1p}**

diameter of the pitch cone at reference plane G

2.3.8**pitch diameter, D_{2p}**

diameter of the pitch cone at reference plane F (before any chamfer is cut)

2.4 Terms relating to reference

NOTE See Figure 1.

2.4.1**reference length, l_1** <https://standards.iteh.ai/catalog/standards/sist/e4a5eb59-9ef6-4d05-a7c5-26108049ab87/iso-11363-1-2010>
reference dimension being the distance between the parallel reference planes A and B**2.4.2****reference length, L_1**

reference dimension being the distance between the parallel reference planes F and G

2.4.3**reference plane A**reference plane coincident with the small end face of the threaded valve stem and corresponding to diameters d_{1i} , d_{1p} and d_{1e} **2.4.4****reference plane B**reference plane at a distance l_1 from reference plane A and corresponding to diameter d_{2p} **2.4.5****reference plane F**reference plane coincident with the entry section face of the cylinder neck thread and corresponding to pitch diameter D_{2p} **2.4.6****reference plane G**reference plane at a distance L_1 from reference plane F and corresponding to diameter D_{1e} , D_{1p} and D_{1i}