



SLOVENSKI STANDARD

SIST EN 300 369-4 V1.2.4:2005

01-april-2005

8 [[]HJbc`ca fYy`Y`n`]bH[f]fUb]a]glcf]h] Ua]f]G8 BL`E`Dfcl`c`X[[]HJbY`bUfc b]y`_Y`
g[[bU]nUWY`Y`yH`%fB GG`%L`E`8 cdc`b]bUglcf]h]j . `bYXj ci a bUdfYXUU`_]WJf07 HL`E`("`
XY . `5 VglfU`_hb]`dfYg_i`yUb]`b]n`f5 HGL`]b`XcXUtbU]bZ`fa UW`U`nUdfYg_i`yUb`Y`XY`bY`
]nj YXVY`dfcl`c`_U`fD`L`+HL`E`Dfcl`c`Z`fa UgdYWZ`_UW`U`nUi`dcfUvb]`_U`

Integrated Services Digital Network (ISDN); Explicit Call Transfer (ECT) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 4: Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user

[SIST EN 300 369-4 V1.2.4:2005](https://standards.iteh.ai/catalog/standards/sist/138df16b-9d9c-4d58-aceb-4e8616ea129a/sist-en-300-369-4-v1-2-4-2005)

<https://standards.iteh.ai/catalog/standards/sist/138df16b-9d9c-4d58-aceb-4e8616ea129a/sist-en-300-369-4-v1-2-4-2005>

Ta slovenski standard je istoveten z: EN 300 369-4 Version 1.2.4

ICS:

33.080	Digitalno omrežje z integriranimi storitvami (ISDN)	Integrated Services Digital Network (ISDN)
--------	---	--

SIST EN 300 369-4 V1.2.4:2005 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 369-4 V1.2.4:2005

<https://standards.iteh.ai/catalog/standards/sist/138df16b-9d9c-4d58-aeab-4e8616ea129a/sist-en-300-369-4-v1-2-4-2005>

ETSI EN 300 369-4 V1.2.4 (1999-09)

European Standard (Telecommunications series)

**Integrated Services Digital Network (ISDN);
Explicit Call Transfer (ECT) supplementary service;
Digital Subscriber Signalling System No. one (DSS1) protocol;
Part 4: Abstract Test Suite (ATS) and partial Protocol
Implementation eXtra Information for Testing (PIXIT) proforma
specification for the user**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 369-4 V1.2.4:2005](https://standards.iteh.ai/catalog/standards/sist/138df16b-9d9c-4d58-aceb-4e8616ea129a/sist-en-300-369-4-v1-2-4-2005)

<https://standards.iteh.ai/catalog/standards/sist/138df16b-9d9c-4d58-aceb-4e8616ea129a/sist-en-300-369-4-v1-2-4-2005>



Reference

REN/SPS-05116-4 (3f100iqo.PDF)

Keywords

ISDN, DSS1, supplementary service, ECT, ATS, PIXIT, user

ETSI

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C

Association à but non lucratif enregistrée à la
Sous-Prefecture de Grasse (06) N° 7803/88

<https://standards.etsi.org/standards-search/#/standards-search/300-369-4-v1-2-4-2005>

Internet

secretariat@etsi.fr

Individual copies of this ETSI deliverable
can be downloaded from

<http://www.etsi.org>

If you find errors in the present document, send your
comment to: editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1999.
All rights reserved.

Contents

Intellectual Property Rights	5
Foreword	5
1 Scope	6
2 References	6
3 Definitions and abbreviations	7
3.1 Definitions	7
3.2 Abbreviations	7
4 Abstract Test Method	7
5 Untestable test purposes	8
6 ATS conventions	8
6.1 Version of TTCN used	8
6.2 Use of ASN.1	8
6.2.1 Situations where ASN.1 is used	8
6.2.2 Specification of encoding rules	8
7 ATS to TP map	9
8 PCTR conformance	9
9 PIXIT conformance	9
10 ATS conformance	10
Annex A (normative): Protocol Conformance Test Report (PCTR) proforma	11
A.1 Identification summary	11
A.1.1 Protocol conformance test report	11
A.1.2 IUT identification	11
A.1.3 Testing environment	11
A.1.4 Limits and reservations	12
A.1.5 Comments	12
A.2 IUT conformance status	12
A.3 Static conformance summary	12
A.4 Dynamic conformance summary	12
A.5 Static conformance review report	13
A.6 Test campaign report	14
A.7 Observations	15
Annex B (normative): Partial PIXIT proforma	16
B.1 Identification summary	16
B.2 Abstract test suite summary	16
B.3 Test laboratory	16
B.4 Client (of the test laboratory)	17
B.5 System Under Test (SUT)	17
B.6 Protocol information	18
B.6.1 Protocol identification	18
B.6.2 IUT information	18

iTech STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 369-4 V1.2.4:2005](https://standards.iteh.ai/catalog/standards/sist/138df16b-9d9e-4d58-ae6b-4c6616ca129a/sist-en-300-369-4-v1-2-4-2005)

<https://standards.iteh.ai/catalog/standards/sist/138df16b-9d9e-4d58-ae6b-4c6616ca129a/sist-en-300-369-4-v1-2-4-2005>

B.6.2.1	Parameter values	18
B.6.2.2	Sending of messages by IUT.....	19
B.6.2.3	Timer values.....	19
B.6.2.4	Information element codings.....	20
Annex C (normative):	Abstract Test Suite (ATS)	21
C.1	The TTCN Graphical form (TTCN.GR)	21
C.2	The TTCN Machine Processable form (TTCN.MP).....	21
	Bibliography	22
	History.....	23

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 369-4 V1.2.4:2005](https://standards.iteh.ai/catalog/standards/sist/138df16b-9d9c-4d58-aceb-4e8616ea129a/sist-en-300-369-4-v1-2-4-2005)

<https://standards.iteh.ai/catalog/standards/sist/138df16b-9d9c-4d58-aceb-4e8616ea129a/sist-en-300-369-4-v1-2-4-2005>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Signalling Protocols and Switching (SPS).

The present document is part 4 of a multi-part standard covering the Explicit Call Transfer (ECT) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; as described below:

- Part 1: "Protocol specification";
- Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";
- Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";
- Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user";**
- Part 5: "Test Suite Structure and Test Purposes (TSS&TP) specification for the network";
- Part 6: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the network".

National transposition dates

Date of adoption of this EN:	3 September 1999
Date of latest announcement of this EN (doa):	31 December 1999
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2000
Date of withdrawal of any conflicting National Standard (dow):	30 June 2000

1 Scope

This fourth part of EN 300 369 specifies the Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma for the User side of the T reference point or coincident S and T reference point of implementations conforming to the stage three standard for the Explicit Call Transfer (ECT) supplementary service for the pan-European Integrated Services Digital Network (ISDN) by means of the Digital Subscriber Signalling System No. one (DSS1) protocol, EN 300 369-1 [1].

EN 300 369-3 [3] specifies the Test Suite Structure and Test Purposes (TSS&TP) related to this ATS and partial PIXIT proforma specification. Other parts specify the TSS&TP and the ATS and partial PIXIT proforma for the Network side of the T reference point or coincident S and T reference point of implementations conforming to EN 300 369-1 [1].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, subsequent revisions do apply.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- IT-ETSI STANDARD PREVIEW**
(standards.iteh.ai)
- [1] EN 300 369-1 (V1.2): "Integrated Services Digital Network (ISDN); Explicit Call Transfer (ECT) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification". [SIST EN 300 369-4 V1.2.4:2005
https://standards.iteh.ai/catalog/standards/sist/138df16b-9d9c-4d58-aceb-414261040000/en-300-369-1-1999](https://standards.iteh.ai/catalog/standards/sist/138df16b-9d9c-4d58-aceb-414261040000/en-300-369-1-1999)
- [2] EN 300 369-2 (V1.2): "Integrated Services Digital Network (ISDN); Explicit Call Transfer (ECT) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 2: Protocol Implementation Conformance Statement (PICS) proforma specification".
- [3] EN 300 369-3 (V1.2): "Integrated Services Digital Network (ISDN); Explicit Call Transfer (ECT) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 3: Test Suite Structure and Test Purposes (TSS&TP) specification for the user".
- [4] Void.
- [5] EN 300 196-1: "Integrated Services Digital Network (ISDN); Generic functional protocol for the support of supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [6] ISO/IEC 9646: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework" (all parts).
- [7] TR 101 101 (V1.1): "Methods for Testing and Specification (MTS); TTCN interim version including ASN.1 1994 support [ISO/IEC 9646-3] (Second Edition Mock-up for JTC1/SC21 Review)".
- [8] ISO/IEC 8825-1 (1994): "Information technology - ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER)".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ISO/IEC 9646 [6] apply.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ASP	Abstract Service Primitive
ATS	Abstract Test Suite
BER	Basic Encoding Rules
ECT	Explicit Call Transfer
ETS	Executable Test Suite
IUT	Implementation Under Test
LT	Lower Tester
MOT	Means Of Testing
PCO	Point of Control and Observation
PCTR	Protocol Conformance Test Report
PDU	Protocol Data Unit
PICS	Protocol Implementation Conformance Statement
PIXIT	Protocol Implementation eXtra Information for Testing
SUT	System Under Test
TCP	Test Co-ordination Procedures
TP	Test Purpose
TTCN	Tree and Tabular Combined Notation

SIST EN 300 369-4 V1.2.4:2005

<https://standards.iteh.ai/catalog/standards/sist/138df16b-9d9c-4d58-ae6b-33617c249000/en-300-369-4-v1-2-4-2005>

4 Abstract Test Method

The remote test method is applied for the ECT user ATS.

A Point of Control and Observation (PCO) resides at the service access point between layers 2 and 3 in the test system. This PCO is named "L" (for Lower). The L PCO is used to control and observe the behaviour of the Implementation Under Test (IUT) and test case verdicts are assigned depending on the behaviour observed at this PCO.

A second "informal" PCO, called "O" (for Operator) is used to specify control but not observation above the IUT; events at this PCO are never used to generate test case verdicts. Messages sent by the tester at this PCO explicitly indicate to the operator actions which are to be performed on the SUT. This is regarded as a preferred alternative to the use of the implicit send event.




Figure 1: Remote test method with PCO O for test co-ordination

5 Untestable test purposes

There are no untestable test purposes associated with this ATS.

iTeh STANDARD PREVIEW

(standards.iteh.ai)

6 ATS conventions

SIST EN 300 369-4 V1.2.4:2005

6.1 Version of TTCN used

<https://standards.iteh.ai/catalog/standards/sist/138df16b-9d9c-4d58-aceb-4e8616ca129a/sist-en-300-369-4-v1-2-4-2005>

The version of TTCN used is that defined in TR 101 101 [7].

6.2 Use of ASN.1

6.2.1 Situations where ASN.1 is used

ASN.1 has been used for three major reasons:

- 1) types defined in ASN.1 can model problems that "pure" TTCN cannot. For instance, data structures modelling ordered or unordered sequences of data are preferably defined in ASN.1;
- 2) ASN.1 provides a better restriction mechanism for type definitions by using sub-type definitions;
- 3) it is necessary to use ASN.1 to reproduce the type definitions for remote operation components specified in the base standards in ASN.1.

The possibility to use TTCN and ASN.1 in combination is used, i.e. referring to an ASN.1 type from a TTCN type.

6.2.2 Specification of encoding rules

There is a variation in the encoding rules applied to ASN.1 types and constraints specified in this ATS and therefore a mechanism is needed to differentiate the encoding rules. However the mechanism specified in ISO/IEC 9646-3/AM2 [6] and in TR 101 101 [7] does not facilitate definition of the encoding rules as needed for this ATS. A solution is therefore used which is broadly in the spirit of ISO/IEC 9646-3/AM2 [6] in which comment fields have been used as a means of encoding rules.

For ASN.1 used in this ATS, two variations of encoding rules are used. One is the commonly known Basic Encoding Rules (BER) as specified in ISO/IEC 8825-1 [8]. In the second case the encoding is according to ISDN, i.e. the ASN.1 data types are a representation of structures contained within the ISDN specification (basic call, Generic functional protocol or individual supplementary service). For example, if octets of an information element are specified in ASN.1 as a SEQUENCE then this should be encoded in an Executable Test Suite (ETS) as any other ISDN information element specified using tabular TTCN. This ISDN encoding variation is the default encoding rule for this ATS. This means that all ASN.1 constraint tables are encoded using ISDN (non-BER) encoding unless stated otherwise. BER encoding should never be applied to an ASN.1 constraint where BER encoding has not been specified. This encoding rule is sometimes named "Direct Encoding".

For BER encoding, an indication is given in the comments field of the table header. For this ATS such indications appear in the ASN.1 type constraint declaration tables only. In the first line of the table header comment field, the notation "ASN1_Encoding: BER" is used.

NOTE: Within BER, there are a number of variations for the encoding of lengths of fields.

According to EN 300 196-1 [5], an IUT should be able to interpret all length forms within BER for received PDUs. When sending PDUs containing BER encoding, EN 300 196-1 [5] gives guidelines but makes no restrictions on the length forms within BER which an IUT may apply.

In this particular ATS all ASN.1 type constraints which are of type "Component" are to be encoded using BER.

Table 1: ASN.1 type constraint declaration showing use of encoding variation

ASN.1 Type Constraint Declaration	
Constraint Name :	Beg3PTYinv
ASN.1 Type :	Component
Derivation Path :	
Comments :	ASN1_Encoding: BER Receive component: BeginECT_invoke component
Description	
begin3PTY_Components begin3PTY_InvokeComp { invokeID ? , operation_value localValue 4}	
Detailed comments :	

<https://standards.iteh.ai/catalog/standards/sist/138df16b-9d9c-4d58-aceb-4e8616ea129a/sist-en-300-369-4-v1-2-4-2005>

7 ATS to TP map

The identifiers used for the TPs are reused as test case names. Thus there is a straightforward one-to-one mapping.

8 PCTR conformance

A test laboratory, when requested by a client to produce a PCTR, is required, as specified in ISO/IEC 9646-5 [6], to produce a PCTR conformant with the PCTR template given in annex B of ISO/IEC 9646-5 [6].

Furthermore, a test laboratory, offering testing for the ATS specification contained in annex C, when requested by a client to produce a PCTR, is required to produce a PCTR conformant with the PCTR proforma contained in annex A.

A PCTR which conforms to this PCTR proforma specification shall preserve the content and ordering of the clauses contained in annex A. Clause A.6 of the PCTR may contain additional columns. If included, these shall be placed to the right of the existing columns. Text in italics may be retained by the test laboratory.

9 PIXIT conformance

A test realizer, producing an executable test suite for the ATS specification contained in annex C, is required, as specified in ISO/IEC 9646-4 [6], to produce an augmented partial PIXIT proforma conformant with this partial PIXIT proforma specification.