## Draft ETSI EN 300 472 V1.4.1 (2017-01)



# Digital Video Broadcasting (DVB); Specification for conveying ITU-R System B Teletext in DVB bitstreams





Reference REN/JTC-DVB-365

Keywords broadcasting, digital, DVB, MPEG, teletext, TV, video

2

#### ETSI

#### 650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16 Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from: http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <u>https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx</u>

If you find errors in the present document, please send your comment to one of the following services: <u>https://portal.etsi.org/People/CommiteeSupportStaff.aspx</u>

#### **Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI. The content of the PDF version shall not be modified without the written authorization of ETSI. The copyright and the foregoing restriction extend to reproduction in all media.

> © European Telecommunications Standards Institute 2017. © European Broadcasting Union 2017. All rights reserved.

DECT<sup>™</sup>, PLUGTESTS<sup>™</sup>, UMTS<sup>™</sup> and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP<sup>™</sup>** and LTE<sup>™</sup> are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **GSM**® and the GSM logo are Trade Marks registered and owned by the GSM Association.

## Contents

Intell	ectual Property Rights		4
Forev	word		4
Moda	al verbs terminology		5
1	Scope		6
2 2.1 2.2	Normative reference	es	6
3 3.1 3.2	Definitions	viations	7
4 4.0 4.1 4.2 4.3 4.4	Packetization and si Transport Stream (T PES packet format	nto MPEG-2 transport multiplex gnalling S) packet format field lata field	
5	Teletext decoder mod	el	10
Anne	ex A (informative):	PTS transmission	11
Anne	ex B (informative):	Change History	
Histo	ry	field	13

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

4

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Foreword

This draft European Standard (EN) has been produced by Joint Technical Committee (JTC) Broadcast of the European Broadcasting Union (EBU), Comité Européen de Normalisation ELECtrotechnique (CENELEC) and the European Telecommunications Standards Institute (ETSI), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

NOTE: The EBU/ETSI JTC Broadcast was established in 1990 to co-ordinate the drafting of standards in the specific field of broadcasting and related fields. Since 1995 the JTC Broadcast became a tripartite body by including in the Memorandum of Understanding also CENELEC, which is responsible for the standardization of radio and television receivers. The EBU is a professional association of broadcasting organizations whose work includes the co-ordination of its members' activities in the technical, legal, programme-making and programme-exchange domains. The EBU has active members in about 60 countries in the European broadcasting area, its headquarters is in Geneva.

European Broadcasting Union CH-1218 GRAND SACONNEX (Geneva) Switzerland Tel: +41 22 717 21 11 Fax: +41 22 717 24 81

The Digital Video Broadcasting Project (DVB) is an industry-led consortium of broadcasters, manufacturers, network operators, software developers, regulatory bodies, content owners and others committed to designing global standards for the delivery of digital television and data services. DVB fosters market driven solutions that meet the needs and economic circumstances of broadcast industry stakeholders and consumers. DVB standards cover all aspects of digital television from transmission through interfacing, conditional access and interactivity for digital video, audio and data. The consortium came together in 1993 to provide global standardisation, interoperability and future proof specifications.

Proposed national transposition dates		
Date of latest announcement of this EN (doa):	3 months after ETSI publication	
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa	
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa	

## Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the ETSI Drafting Rules (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

FLENSLAND AND States with the states of the

## 1 Scope

The present document specifies the method by which ITU-R System B Teletext (Recommendation ITU-R BT.653 [3]), also known as EBU Teletext (see ETSI EN 300 706 [4]), may be carried in DVB bitstreams. This transport mechanism is intended to satisfy the following requirements:

- to support the transcoding of the Teletext data into the Vertical Blanking Interval (VBI) of analogue video. The transcoded signal should be compatible with existing TV receivers with Teletext decoders;
- the maximum data rate for each Teletext service is equivalent to 16 lines per field so that the service is always suitable for transcoding into the VBI;
- the transmission mechanism should be capable of transmitting subtitles with accurate timing with respect to the video (i.e. to within or near frame accuracy).

A more general data transport mechanism for conveying new types of data services is outside the scope of the present document, but the transport syntax specified here can also be adapted for other data.

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <u>https://docbox.etsi.org/Reference/</u>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ISO/IEC 13818-1: "Information technology -- Generic coding of moving pictures and associated audio information -- Part F: Systems".
- [2] ETSI EN 300 468: "Digital Video Broadcasting (DVB); Specification for Service Information (SI) in DVB systems".
- [3] Recommendation ITU-R BT.653: "Teletext systems".
- [4] ETSI EN 300 706: "Enhanced Teletext specification".

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

[i.1] ISO/IEC 13818-2: "Information technology -- Generic coding of moving pictures and associated audio information -- Part 2: Video".

ISO/IEC 13818-3: "Information technology -- Generic coding of moving pictures and associated [i.2] audio information -- Part 3: Audio".

7

#### 3 Definitions and abbreviations

#### 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

MPEG 2: Refers to ISO/IEC 13818 set of standards.

Systems coding is defined in part 1 [1], video coding is defined in part 2 [i.1], and audio coding is defined NOTE: in part 3 [i.2] of ISO/IEC 13818.

section: syntactic structure used for mapping all service information defined in ETSI EN 300 468 [2] into ISO/IEC 13818-1 [1] Transport Stream (TS) packets

service: sequence of programmes under the control of a broadcaster which can be broadcast as part of a schedule

teletext descriptor: descriptor used in the Program Specific Information (PSI) Program Map Table (PMT) to identify streams which carry EBU teletext data

See ETSI EN 300 468 [2]. NOTE:

#### 3.2 Abbreviations

 
 For the purposes of the present document, the following abbreviations apply:

 DVB
 Digital Video Broadcasting
etallatalogstall hender and shows

DVB	Digital Video Broadcasting
MPEG	Moving Pictures Expert group
PES	Packetized Elementary Stream
PID	Packet IDentifier
PMT	Program Map Table
PSI	Program Specific Information
PTS	Presentation Time Stamp
SI	Service Information
TS	Transport Stream
TV	TeleVision
VBI	Vertical Blanking Interval

#### Insertion of Teletext into MPEG-2 transport multiplex 4

#### 4.0Packetization and signalling

Teletext data shall be conveyed in Packetized Elementary Stream (PES) packets as defined in clause 4.2, carried by Transport Stream (TS) packets as defined in ISO/IEC 13818-1 [1] and according to clause 4.1.

The Packet Identifier (PID) of a Teletext stream associated with a service shall be signalled in the Program Map Table (PMT) of the Program Specific Information (PSI) for that service.

The Teletext data stream shall use stream type value 0x06 (which indicates a PES stream carrying private data).

The appropriate ES info field of the program map section describing Teletext data streams shall contain a Teletext descriptor as defined in ETSI EN 300 468 [2].

A service may include more than one Teletext data stream, provided that each stream has a different value of data\_identifier, and that the streams are distinguishable by their respective Teletext descriptors in the PSI.

The standard TS packet syntax and semantics shall be followed, noting the following constraint:

adaptation\_field\_control only the values "01" and "10" shall be permitted.

## 4.2 PES packet format

The standard PES packet syntax and semantics shall be followed noting the following constraints:

stream_id	shall be set to "1011 1101" meaning "private_stream_1".	
PES_packet_length	shall be set to the value (N $\times$ 184)-6, where N is an integer, so that the PES pac finishes at the end of a Transport packet.	
Data_alignment_indicator	shall be set to "1" indicating that the Teletext access units are aligned with the PES packets.	
PES_header_data_length	shall be set to "0x24".	
stuffing_byte	the PES header shall be followed by as many stuffing bytes as are required to make up the header data length, so that the entire PES header is 45 bytes long.	
PES_packet_data_byte	these bytes shall be coded in accordance with the PES_data_field syntax specified in clause 4.3.	

8

PTS and other optional fields may be present in the PES header, but the header length is always fixed for streams identified in the Program Specific Information (PSI) by the DVB Teletext descriptor (see ETSI EN 300 468 [2]).

NOTE: See annex A.

## 4.3 Syntax for PES data field

#### Table 1: Syntax for PES data field

Syntax 2	No. of bits	Identifier
PES_data_field(){	0	uimsbf
for(i=0;i <n;i++){< td=""><td>8</td><td>umsoi</td></n;i++){<>	8	umsoi
data_unit_id 🛛 👋 🕅	8	uimsbf
data_unit_length	8	uimsbf
data_field()		
}		
}		

#### Data\_field for EBU Teletext

#### Table 2: Syntax for Data\_field for EBU Teletext

Syntax	No. of bits	Identifier
data_field(){		
reserved_future_use	2	bslbf
field_parity	1	bslbf
line_offset	5	uimsbf
framing_code	8	bslbf
magazine_and_packet_address	16	bslbf
data_block	320	bslbf
}		

## 4.4 Semantics for PES data field

**data\_identifier:** this 8-bit field identifies the type of data carried in the PES packet. It shall be coded according to table 3.

#### Table 3: data\_identifier

data_identifier	value
0x00 to 0x0F	reserved for future use
0x10 to 0x1F	EBU data
0x20 to 0x7F	reserved for future use
0x80 to 0xFF	user defined

The data\_identifier shall be set to the same value for each PES packet conveying data in the same Teletext data stream.

data\_unit\_id: this 8-bit field identifies the type of data unit. It shall be coded according to table 4.

data_unit_id	value
0x00 to 0x01	reserved for future use
0x02	EBU Teletext non-subtitle data
0x03	EBU Teletext subtitle data
0x04 to 0x7F	reserved for future use
0x80 to 0xFE	user defined
0xFF	data unit for stuffing

#### Table 4: data unit id

For streams identified in the PSI by the DVB Teletext descriptor (see ETSTEN 300 468 [2]), only values 0x02, 0x03 and 0xFF shall be permitted.

**data\_unit\_length:** this 8-bit field indicates the number of bytes in the data unit following the length field. For data units carrying EBU Teletext data, this field shall always be set to 0x2C.

**reserved\_future\_use:** this field may be used in the future for ETSI defined extensions. As a default reserved\_future\_use bits shall be set to "1".

**field\_parity:** this 1-bit flag specifies the field for which the data is intended; the value "1" indicates the first field of a frame, the value "0" indicates the second field of a frame.

**line\_offset:** this 5-bit field specifies the line number on which the Teletext data packet is intended to be presented if it is transcoded into the VBI. Within a field, the line\_offset numbering shall follow a progressive incremental order except for the undefined line\_offset value "0". The toggling of the field\_parity flag indicates a new field. The line\_offset shall be coded according to table 5.

line_offset	Meaning	
	field_parity = 1	field_parity = 0
0x00	Line number undefined	Line number undefined
0x01 to 0x06	reserved for future use	reserved for future use
0x07	Line number = 7	Line number = 320
0x08	Line number = 8	Line number = 321
:	:	:
0x16	Line number = 22	Line number = 335
0x17 to 0x1F	reserved for future use	reserved for future use

#### Table 5: line offset

Only values 0x00 and 0x07 to 0x16 shall be permitted for EBU Teletext data\_units in streams identified in the PSI by the DVB Teletext descriptor, see ETSI EN 300 468 [2].