

INTERNATIONAL STANDARD

ISO
11600

Second edition
2002-10-01

AMENDMENT 1
2011-07-15

Building construction — Jointing products — Classification and requirements for sealants

AMENDMENT 1

*Construction immobilière — Produits pour joints — Classification et
exigences pour les mastics*
AMENDEMENT 1
(standards.iteh.ai)

[ISO 11600:2002/Amd 1:2011](https://standards.iteh.ai/catalog/standards/sist/4387375d-c974-4bd6-aa24-5af8c31958e9/iso-11600-2002-amd-1-2011)

<https://standards.iteh.ai/catalog/standards/sist/4387375d-c974-4bd6-aa24-5af8c31958e9/iso-11600-2002-amd-1-2011>



Reference number
ISO 11600:2002/Amd.1:2011(E)

© ISO 2011

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 11600:2002/Amd 1:2011](https://standards.iteh.ai/catalog/standards/sist/4387375d-c974-4bd6-aa24-5af8c31958e9/iso-11600-2002-amd-1-2011)
<https://standards.iteh.ai/catalog/standards/sist/4387375d-c974-4bd6-aa24-5af8c31958e9/iso-11600-2002-amd-1-2011>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2011

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

Amendment 1 to ISO 11600:2002 was prepared by Technical Committee ISO/TC 59, *Buildings and civil engineering works*, Subcommittee SC 8, *Sealants*.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 11600:2002/Amd 1:2011](https://standards.iteh.ai/catalog/standards/sist/4387375d-c974-4bd6-aa24-5af8c31958e9/iso-11600-2002-amd-1-2011)

<https://standards.iteh.ai/catalog/standards/sist/4387375d-c974-4bd6-aa24-5af8c31958e9/iso-11600-2002-amd-1-2011>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 11600:2002/Amd 1:2011](https://standards.iteh.ai/catalog/standards/sist/4387375d-c974-4bd6-aa24-5af8c31958e9/iso-11600-2002-amd-1-2011)

<https://standards.iteh.ai/catalog/standards/sist/4387375d-c974-4bd6-aa24-5af8c31958e9/iso-11600-2002-amd-1-2011>

Building construction — Jointing products — Classification and requirements for sealants

AMENDMENT 1

Page 5, Table 3

Replace Table 3 with the following:

Table 3 — Requirements for construction sealants (F)

Properties	Class							Test method
	25LM	25HM	20LM	20HM	12,5E	12,5P	7,5P	
Elastic recovery (%)	≥ 70	≥ 70	≥ 60	≥ 60	≥ 40	< 40	< 40	ISO 7389
Tensile properties								ISO 8339
a) secant tensile modulus at +23 °C (N/mm ²)	≤ 0,4	> 0,4	≤ 0,4	> 0,4	—	—	—	
at -20 °C (N/mm ²)	≤ 0,6	> 0,6	≤ 0,6	> 0,6	—	—	—	
b) elongation at break (%) at +23 °C	—	—	—	—	—	≥ 100	≥ 25	
Tensile properties at maintained extension	nf	nf	nf	nf	nf	—	—	ISO 8340
Adhesion/cohesion properties at variable temperatures	nf	nf	nf	nf	nf	—	—	ISO 9047
Adhesion/cohesion properties at constant temperature	—	—	—	—	—	nf	nf	ISO 9046
Adhesion/cohesion properties at maintained extension after water immersion	nf	nf	nf	nf	nf	—	—	ISO 10590
Adhesion/cohesion properties after water immersion	—	—	—	—	—	≥ 100	≥ 25	ISO 10591
Elongation at break (%) at +23 °C	—	—	—	—	—	—	—	
Loss of volume (%)	≤ 10 see Note 1	≤ 10 see Note 1	≤ 10 see Note 1	≤ 10 see Note 1	≤ 25 see Note 2	≤ 25	≤ 25	ISO 10563
Resistance to flow (mm) (Note 3)	≤ 3	≤ 3	≤ 3	≤ 3	≤ 3	≤ 3	≤ 3	ISO 7390
nf = no failure as defined in Clause 7.								
NOTE 1 A maximum of 25 % for water-borne dispersion sealants.								
NOTE 2 A maximum of 30 % for Class 12,5E water-borne dispersion sealants.								
NOTE 3 Use the U-profile made from anodized aluminum with a nominal width of 20 mm and a nominal depth of 10 mm. Apply test temperatures of (50 ± 2) °C and (5 ± 2) °C. Test to procedure A and procedure B. If the flow exceeds 3 mm, the test may be repeated once.								

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 11600:2002/Amd 1:2011](https://standards.iteh.ai/catalog/standards/sist/4387375d-c974-4bd6-aa24-5af8c31958e9/iso-11600-2002-amd-1-2011)
<https://standards.iteh.ai/catalog/standards/sist/4387375d-c974-4bd6-aa24-5af8c31958e9/iso-11600-2002-amd-1-2011>

ICS 91.100.50

Price based on 1 page