



**SLOVENSKI STANDARD**  
**SIST EN 303 340 V1.1.2:2016**  
**01-december-2016**

---

**Digitalni prizemni radiodifuzijski sprejemniki - Harmonizirani standard, ki zajema bistvene zahteve člena 3.2 direktive 2014/53/EU**

Digital Terrestrial TV Broadcast Receivers - Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

Ta slovenski standard je istoveten z: **ETSI EN 303 340 V1.1.2 (2016-09)**

SIST EN 303 340 V1.1.2:2016  
<https://standards.iteh.ai/catalog/standards/sist/4826277e-cbb9-4b82-9018-8f3f6590393/sist-en-303-340-v1-1-2-2016>

---

**ICS:**

33.160.25      Televizijski sprejemniki      Television receivers

**SIST EN 303 340 V1.1.2:2016**      en

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 303 340 V1.1.2:2016](https://standards.iteh.ai/catalog/standards/sist/482b277e-ebb9-4b82-9018-8ff3f6590393/sist-en-303-340-v1-1-2-2016)

<https://standards.iteh.ai/catalog/standards/sist/482b277e-ebb9-4b82-9018-8ff3f6590393/sist-en-303-340-v1-1-2-2016>

# ETSI EN 303 340 V1.1.2 (2016-09)



## Digital Terrestrial TV Broadcast Receivers; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU

[SIST EN 303 340 V1.1.2:2016](https://standards.iteh.ai/catalog/standards/sist/482b277e-ebb9-4b82-9018-8ff3f6590393/sist-en-303-340-v1-1-2-2016)

<https://standards.iteh.ai/catalog/standards/sist/482b277e-ebb9-4b82-9018-8ff3f6590393/sist-en-303-340-v1-1-2-2016>



## Reference

---

REN/ERM-TG17-14-CR

## Keywords

---

digital, radio, receiver, TV**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 303 340 V1.1.2:2016

<https://standards.iteh.ai/catalog/standards/sist/482b277e-ebb9-4b82-9018-8af3f6590722/ETSI-ERM-TG17-14-CR-V1-1-2-2016>

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	5
Foreword.....	5
Modal verbs terminology.....	5
1 Scope .....	6
2 References .....	6
2.1 Normative references .....	6
2.2 Informative references.....	6
3 Definitions, symbols, and abbreviations .....	7
3.1 Definitions .....	7
3.2 Symbols.....	8
3.3 Abbreviations .....	9
4 Technical requirements specifications .....	9
4.1 Environmental profile.....	9
4.2 Conformance requirements .....	10
4.2.1 DVB-T and DVB-T2 configurations for testing .....	10
4.2.2 Interference and wanted test signals .....	11
4.2.3 Sensitivity .....	11
4.2.3.1 Definition .....	11
4.2.3.2 Method of Measurement .....	11
4.2.3.2.1 Test arrangement description.....	11
4.2.3.2.2 Test procedure .....	11
4.2.3.3 Limits .....	12
4.2.4 Adjacent channel selectivity .....	12
4.2.4.1 Definition .....	12
4.2.4.2 Method of Measurement .....	13
4.2.4.2.1 Test arrangement description.....	13
4.2.4.2.2 Requirements for the ACLR of the interfering signal .....	13
4.2.4.2.3 Test procedure .....	13
4.2.4.3 Limits .....	15
4.2.5 Blocking.....	16
4.2.5.1 Definition .....	16
4.2.5.2 Method of Measurement .....	16
4.2.5.2.1 Test arrangement description.....	16
4.2.5.2.2 Requirements for the ACLR of the interfering signal .....	16
4.2.5.2.3 Test procedure .....	16
4.2.5.3 Limits .....	16
4.2.6 Overloading .....	17
4.2.6.1 Definition .....	17
4.2.6.2 Method of Measurement .....	17
4.2.6.2.1 Test arrangement description.....	17
4.2.6.2.2 Requirements for the ACLR of the interfering signal .....	17
4.2.6.2.3 Test procedure .....	17
4.2.6.3 Limits .....	18
4.2.7 Unwanted emissions in the spurious domain .....	18
4.2.7.1 Definition .....	18
4.2.7.2 Method of Measurement .....	19
4.2.7.3 Limits .....	19
5 Testing for compliance with technical requirements.....	19
5.1 Environmental conditions for testing .....	19
5.2 Interpretation of the measurement results .....	19
<b>Annex A (normative): Relationship between the present document and the essential requirements of Directive 2014/53/EU .....</b>	<b>20</b>

<b>Annex B (informative):</b>	<b>Summary of study work</b> .....	<b>21</b>
B.1	Overview .....	21
B.2	Selection of interferer waveforms .....	21
B.2.1	UE waveform .....	21
B.2.2	BS waveforms .....	22
B.3	Reception conditions for LTE UE 700 MHz interference.....	24
B.3.1	Calculation of maximum coupling gain .....	24
B.3.2	Calculation of maximum received UE interference power .....	25
B.4	Choice of BS interference power in receiver tests .....	25
<b>Annex C (informative):</b>	<b>Measurement records</b> .....	<b>26</b>
<b>Annex D (informative):</b>	<b>Additional information to assist measurements</b> .....	<b>28</b>
D.1	Optional elements of the test arrangement .....	28
D.2	Instrument settings for measuring the power of bursty interference signals.....	28
D.3	Improving ACLR .....	28
D.4	Measuring ACLR .....	29
<b>Annex E (normative):</b>	<b>Applicable tests</b> .....	<b>30</b>
E.1	Applicable tests for different receiver variants .....	30
<b>Annex F (normative):</b>	<b>Requirements for the interfering signal/minimum ACLR</b> .....	<b>31</b>
<b>Annex G (informative):</b>	<b>Change History</b> .....	<b>32</b>
History .....		33

[SIST EN 303 340 V1.1.2:2016](https://standards.iteh.ai/catalog/standards/sist/482b277e-ebb9-4b82-9018-8f3f6590393/sist-en-303-340-v1-1-2-2016)

<https://standards.iteh.ai/catalog/standards/sist/482b277e-ebb9-4b82-9018-8f3f6590393/sist-en-303-340-v1-1-2-2016>

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.11] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.3].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document has a number of interference test data files that are contained in archive en\_303340v010102p0.zip which accompanies the present document.

SIST EN 303 340 V1.1.2:2016

<https://standards.iteh.ai/catalog/standards/sist/482b277e-ebb9-4b82-9018-8f3b590393/sist-en-303-340-v1-1-2-2016>  
**National transposition dates**

Date of latest announcement of this EN (doa):	30 December 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2017
Date of withdrawal of any conflicting National Standard (dow):	30 June 2018

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# 1 Scope

The present document applies to digital terrestrial television broadcast receivers fitted with an external antenna input (tuner port) capable of receiving DVB-T and/or DVB-T2 signals. Receivers without external antenna connectors, receivers with diversity, and receivers intended for mobile or automotive reception are not covered by the present document.

The present document contains the requirements for digital terrestrial television broadcast receivers to meet the essential requirements of article 3.2 of Directive 2014/53/EU [i.3] that radio equipment both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference.

The present document includes considerations of interference from LTE transmissions in the 700 MHz and 800 MHz bands and DTT transmissions in UHF band IV. The requirements of the installation system (antenna, feeder cable, amplifiers, etc.) are not addressed.

**Table 1: Broadcast frequency bands**

Broadcast frequency bands
VHF III
UHF IV and V

There are country specific variations of frequency usage for digital terrestrial television reception and other users such as mobile broadband.

The tests in the present document only apply if the DTT broadcast receiver supports the wanted signal configuration used by the test in question. The applicable tests are summarized in annex E, table E.1.

ITEH STANDARD PREVIEW  
(standards.iteh.ai)

## 2 References

SIST EN 303 340 V1.1.2:2016

<https://standards.iteh.ai/catalog/standards/sist/482b277e-ebb9-4b82-9018-111111111111/sist-en-303-340-v1-1-2-2016>

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] CENELEC EN 55032:2015: "Electromagnetic compatibility of multimedia equipment. Emission requirements".

### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.



- [i.1] Nordig: "NorDig Unified Test Plan for Integrated Receiver Decoders v2.4".
- [i.2] British Broadcasting Corporation and Arqiva, WHP288: "WSD Coexistence Testing at the Building Research Establishment: An Experimental Validation of Ofcom Regulatory Proposals".
- [i.3] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.4] ETSI EN 300 744 (V1.6.1): "Digital Video Broadcasting (DVB); Framing structure, channel coding and modulation for digital terrestrial television".
- [i.5] ETSI EN 302 755 (V1.3.1): "Digital Video Broadcasting (DVB); Frame structure channel coding and modulation for a second generation digital terrestrial television broadcasting system (DVB-T2)".
- [i.6] ETSI TR 100 028-1 (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1".
- [i.7] ETSI TR 100 028-2 (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".
- [i.8] CEPT/ERC/Recommendation 74-01E (2011): "Unwanted emissions in the spurious domain".
- [i.9] ECC Report 186 (2013): "Technical and operational requirements for the operation of white space devices under geo-location approach".
- [i.10] Recommendation ITU-R BT.1729 (2005): "Common 16:9 or 4:3 aspect ratio digital television reference test pattern".
- [i.11] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.  
<https://standards.iteh.ai/catalog/standards/sist/482b277e-ebb9-4b82-9018-81516390393/sist-en-303-340-v1-1-2-2016>
- [i.12] Recommendation ITU-R BT.419-3 (1990): "Directivity and polarization discrimination of antennas in the reception of television broadcasting".

---

## 3 Definitions, symbols, and abbreviations

### 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

**Adjacent Channel Leakage power Ratio (ACLR):** ratio of the on-channel transmit power to the power measured in one of the adjacent channels with no active channel in the adjacent channel

NOTE: In the present document this definition also applies to an unwanted signal at a specified frequency offset in a non-adjacent channel.

**adjacent channel selectivity:** measure of the capability of the receiver to receive a wanted modulated signal without exceeding a given degradation due to the presence of an unwanted signal which differs in frequency from the wanted signal by an amount equal to the adjacent channel separation for which the equipment is intended

NOTE 1: In the present document adjacent channel selectivity is determined by the onset of picture degradation.

NOTE 2: The interference power  $I$  is equal to the licensed power of the interferer. This definition does not have the same meaning as the term "Adjacent Channel Selectivity" (ACS) used in other organizations such as ITU, CEPT, and in co-existence studies. The adjacent channel selectivity in the present document is equivalent to the measured  $I/C$  ratio.

NOTE 3: In the present document this definition also applies to an unwanted signal at a specified frequency offset in a non-adjacent channel.

**blocking or desensitization:** measure of the capability of the receiver to receive a wanted modulated signal without exceeding a given degradation due to the presence of an unwanted signal at any frequency other than those of the spurious responses or of the adjacent channels

NOTE 1: In the present document receiver blocking is determined by the onset of picture degradation.

NOTE 2: The wanted signal level in the blocking tests of the present document is set at the specified receiver sensitivity level plus 6 dB.

**broadcast receiver:** digital terrestrial television broadcast receiver comprising of at least a tuner and demodulator

**broadcast receiver tuner port:** DTT receiver tuner RF input connector

**licensed power:** highest rms power of the active portions of the signal measured over a specific time period

NOTE: In the case of interference power measurements, this is the reference power used for I/C calculations in the present document. Typically for cases of LTE interference, this power is measured with a spectrum analyser in zero span with a gated power measurement function and rms detector over a period equal to an LTE symbol time. Alternatively it can be calculated by measuring the long term rms power and adding the appropriate LAPR from table 5.

**long term rms power:** rms power of the signal measured over a period long enough to smooth out any fluctuations in the signal power over time such as those due to transmission bursts

NOTE: This can be measured on an average power meter with an input filter time constant set high enough to average out fluctuations in the measured signal power or alternatively using a spectrum analyser with settings shown in table D.1.

**onset of picture degradation:** minimum time between successive errors in the displayed video is 15 seconds

**radio equipment:** product or relevant component thereof capable of communication by means of the emission and/or reception of radio waves utilizing the spectrum allocated to terrestrial/space radio communication

NOTE: For the purposes of the present document the radio equipment is a digital terrestrial television broadcast receiver comprising of at least a tuner and demodulator.

**receiver overloading:** interfering signal level expressed in dBm, above which the receiver begins to lose its ability to discriminate against interfering signals at frequencies differing from that of the wanted signal due to the onset of strong non-linear behaviour

NOTE 1: In the present document the overload level is determined by the onset of picture degradation.

NOTE 2: Above the overloading level the receiver will behave in a non-linear way, but does not necessarily fail immediately depending on the receiver and interference characteristics.

**sensitivity:** maximum usable sensitivity is defined as the minimum receiver Radio Frequency (RF) input signal level or field strength able to produce a specified analogue SINAD ratio or Bit Error Ratio (BER), or other specified output performance which depends on this input signal level

NOTE: In the present document receiver sensitivity is determined by the onset of picture degradation.

## 3.2 Symbols

For the purposes of the present document, the following symbols apply:

C	Wanted signal
$G_C$	Coupling Gain
I	Interferer signal
$I_{lic}$	Licensed power
$I_{rms}$	Long term rms power
$P_{RX\_UE}$	Received UE interference power
$P_{UE}$	UE transmitted power

### 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ACE	Active Constellation Extension
ACLR	Adjacent Channel Leakage power Ratio
ACS	Adjacent Channel Selectivity
AGC	Automatic Gain Control
BER	Bit Error Ratio
BS	Base Station for mobile communications
CEPT	European Conference of Postal and Telecommunications Administrations
DTG	UK Digital TV Group
DTT	Digital Terrestrial Television
DVB-T	Digital Video Broadcast Terrestrial - first generation [i.4]
DVB-T2	Digital Video Broadcast Terrestrial - second generation [i.5]
FEC	Forward Error Correction
FEF	Future Extension Frame
FFT	Fast Fourier Transform
HEM	High Efficiency Mode
ISSY	Input Stream SYNchronizer
QAM	Quadrature Amplitude Modulation
LAPR	Licensed to Average Power Ratio

NOTE: This is the ratio of the licensed power (described above) to the long term rms power (described above) of the signal.

LDPC	Low Density Parity Check (codes)
LTE	Long Term Evolution
PAPR	Peak to Average Power Ratio
PLP	Physical Layer Pipe
64-QAM	64-ary Quadrature Amplitude Modulation
256-QAM	256-ary Quadrature Amplitude Modulation
RF	Radio Frequency
SINAD	(Signal + Noise + Distortion)/(Noise + Distortion) ratio
SISO	Single Input Single Output (meaning one transmitting and one receiving antenna)
TFS	Time-Frequency Slicing
UE	User Equipment for mobile communications

NOTE: Example handsets, dongles, etc.

UHF	Ultra High Frequency
VHF	Very High Frequency

---

## 4 Technical requirements specifications

### 4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the manufacturer. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared operational environmental profile.

NOTE: The applicability of the different tests as defined in annex E may vary depending upon the selected country profile.

## 4.2 Conformance requirements

### 4.2.1 DVB-T and DVB-T2 configurations for testing

Representative DVB-T and DVB-T2 configurations used for conformance specification and testing are shown in tables 2 and 3. These are used in the Nordig specification test plan [i.1].

**Table 2: DVB-T configuration**

Parameter	Value for "7 MHz" VHF tests	Value for "8 MHz" UHF tests
Bandwidth	6,66 MHz	7,61 MHz
FFT size	8K	8K
Modulation	64-QAM	64-QAM
Hierarchy	Non-Hierarchical	Non-Hierarchical
Guard interval	1/4	1/4
Code rate	2/3	2/3
Channel Bandwidth	7 MHz	8 MHz

**Table 3: DVB-T2 configuration**

Parameter	Value for "7 MHz" VHF tests	Value for "8 MHz" UHF tests
Bandwidth	6,66 MHz	7,77 MHz
FFT	32k	32k
Carrier mode	Normal	Extended
SISO/MISO	SISO	SISO
Guard Interval	1/16	1/16
Version	1.2.1	1.2.1
Number of symbols/frame ( $L_f$ )	42	62
Pilot pattern	PP4	PP4
TFS	No	No
FEF	Not used	Not used
Auxiliary streams	Not used	Not used
Subslices / T2 frame	1	1
Frames / Superframe	2	2
L1 post FEC type	16k LDPC (see note 1)	16k LDPC (see note 1)
L1 repetition	0	0
L1 post extension	No	No
L1 post modulation	64 QAM	64-QAM
L1 post scrambling	None	None
L1_ACE_MAX	0 (see note 2)	0 (see note 2)
L1 bias balancing cells	No	No
PAPR	L1-ACE & TR (see note 3)	L1-ACE & TR (see note 3)
PAPR: $V_{clip}$	3,1 V (see note 1)	3,1 V (see note 1)
PAPR: Number of iterations	10 (see note 1)	10 (see note 1)
TS bit rate (Mbit/s)	31,146	36,552
Input mode	Mode A (single PLP mode)	Mode A (single PLP mode)
Number of PLPs	1	1
PLP type	Data type 1	Data type 1
Constellation rotation	Yes	Yes
PLP FEC type	64k LDPC	64k LDPC
FEC Frame length	64 800 (see note 4)	64 800 (see note 4)
Baseband Mode	High efficiency mode (HEM)	High efficiency mode (HEM)
ISSY	None	None
In band signalling	Disabled	Disabled
Null packet deletion	Disabled	Disabled
Time interleaver length	3	3
Frame interval	1	1
Time interleaver type	0	0
T2 frames / Interleaver frame	1 (see note 5)	1 (see note 5)