



Designation: D6572 – 06

# Standard Test Methods for Determining Dispersive Characteristics of Clayey Soils by the Crumb Test<sup>1</sup>

This standard is issued under the fixed designation D6572; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

## 1. Scope

1.1 These test methods provide a qualitative indication of the natural dispersive characteristics of clayey soils.

1.2 These test methods are not applicable for soils with less than 12 % fraction finer than 0.005 mm and with a plasticity index less than or equal to 8.

1.3 The crumb test method has some limitations in its usefulness as an indicator of dispersive clay. A dispersive soil may sometimes give a nondispersive reaction in the crumb test. Soils containing kaolinite with known field dispersion problems have shown nondispersive reactions in the crumb test (1)<sup>2</sup>. However, if the crumb test indicates dispersion, the soil is probably dispersive.

1.4 Oven-dried soil should not be used to prepare crumb test specimens, as irreversible changes could occur to the soil pore-water physicochemical properties responsible for dispersion (2).

1.5 The crumb test method, while a good quick indication of dispersive clay, should usually be run in conjunction with a pinhole test and a double hydrometer test, Test Methods D4647 and D4221, respectively.

NOTE 1—In some cases, the results of the pinhole, crumb, and double-hydrometer test methods may disagree. Crumb test methods are a better indicator of dispersive clays than of nondispersive clays (3).

1.6 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.7 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

<sup>1</sup> These test methods are under the jurisdiction of ASTM Committee D18 on Soil and Rock and are the direct responsibility of Subcommittee D18.06 on Physical-Chemical Interactions of Soil and Rock

Current edition approved Nov. 1, 2006. Published December 2006. DOI: 10.1520/D6572-06.

<sup>2</sup> The boldface numbers in parentheses refer to the list of references at the end of this standard.

## 2. Referenced Documents

### 2.1 ASTM Standards:<sup>3</sup>

D653 Terminology Relating to Soil, Rock, and Contained Fluids

D1193 Specification for Reagent Water

D2216 Test Methods for Laboratory Determination of Water (Moisture) Content of Soil and Rock by Mass

D3740 Practice for Minimum Requirements for Agencies Engaged in Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction

D4221 Test Method for Dispersive Characteristics of Clay Soil by Double Hydrometer

D4318 Test Methods for Liquid Limit, Plastic Limit, and Plasticity Index of Soils

D4647 Test Method for Identification and Classification of Dispersive Clay Soils by the Pinhole Test

D6026 Practice for Using Significant Digits in Geotechnical Data

E1 Specification for ASTM Liquid-in-Glass Thermometers

E11 Specification for Woven Wire Test Sieve Cloth and Test Sieves

## 3. Terminology

### 3.1 Definitions:

3.1.1 *dispersive clays*—soils that disperse (deflocculate) easily and rapidly without significant mechanical assistance in water of low-salt concentration.

3.1.1.1 *Discussion*—Such soils usually have a high proportion of their adsorptive capacity saturated with sodium cations although adsorbed lithium and magnesium may also play a role (4). Such soils also generally have a high shrink-swell potential, have low resistance to erosion, and have low permeability in an intact state.

3.2 For definitions of other terms used in these test methods, refer to Terminology D653.

<sup>3</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

#### 4. Summary of Test Method

4.1 A cube of remolded soil approximately 15 mm ( $\frac{5}{8}$  in.) on each side (about the size of a single die in a pair of dice) or a natural soil crumb of approximately similar volume is placed on the bottom of a white porcelain dish containing 250 mL of distilled water.

4.2 Temperature of the water is recorded and visual determinations of dispersion grade are made and recorded at 2 min, 1 h, and 6 h. Determination of grade is based on the formation, extent, and turbidity of a dense “cloud” or halo of colloidal-sized particles extending from the soil crumb.

4.3 Determinations consist of: Grade 1 (Nondispersive), Grade 2 (Intermediate), Grade 3 (Dispersive), and Grade 4 (Highly Dispersive).

#### 5. Significance and Use

5.1 The crumb test method provides a simple, quick method for field or laboratory identification of a dispersive clay soil. The internal erosion failures of a number of homogeneous earth dams, erosion along channel or canal banks, and rainfall erosion of earthen structures have been attributed to colloidal erosion along cracks or other flow channels formed in masses of dispersive clay (5).

5.2 The crumb test method, as originally developed by Emerson (6), was called the aggregate coherence test and had seven different categories of soil-water reactions. Sherard (5) later simplified the test by combining some soil-water reactions so that only four categories, or grades, of soil dispersion are observed during the test. The crumb test is a relatively accurate positive indicator of the presence of dispersive properties in a soil. The crumb test, however, is not a completely reliable negative indicator that soils are not dispersive. The crumb test, can seldom be relied upon as a sole test method for determining the presence of dispersive clays. The double-hydrometer test (Test Method D4221) and pinhole test (Test Method D4647) are test methods that provide valuable additional insight into the probable dispersive behavior of clay soils.

NOTE 2—The quality of the result produced by these test methods is dependent on the competence of the personnel performing it, and the suitability of the equipment and facilities used. Agencies that meet the criteria of Practice D3740 are generally considered capable of competent and objective testing. Users of these test methods are cautioned that compliance with Practice D3740 does not in itself ensure reliable testing. Reliable testing depends on several factors; Practice D3740 provides a means of evaluating some of those factors.

#### 6. Interferences

6.1 Oven-dried soil shall not be used in performing the crumb test as irreversible changes could occur to the soil pore-water physicochemical properties responsible for dispersion (2).

6.2 Using other than Type IV water in accordance with Specification D1193, can interfere with dispersion of the colloidal clay particles.

6.3 Carefully place the cube or crumb directly on the bottom of the dish when submerging the crumb. Dropping the crumb

from the water surface can cause excessive slaking and may result in erroneous interpretation of the dispersion grade.

6.4 Jarring or moving the soil specimen or porcelain dish once the test method has begun can cause excessive turbidity and may result in erroneous interpretation of the dispersion grade.

6.5 The use of natural, irregular-shaped soil crumbs may result in a specimen that is not representative of the total sample. Therefore, several crumb test specimens should be selected to ensure that representative test results are obtained. The total number of test specimens should be determined during the test program and will depend on the degree of agreement of individual test results.

6.6 These test methods are not applicable to soils less than 12 % fraction finer than 0.005 mm and with a plasticity index less than or equal to 8, refer to Test Method D4318.

#### 7. Apparatus

7.1 *Specimen Container*—Dish, porcelain, evaporating, 300-mL capacity.

NOTE 3—Plastic bowls or cups can also be used but they should be white or clear to help in distinguishing the colloidal cloud. The container should be at least 85 mm (3 in.) across the bottom if flat-bottomed.

7.2 *Thermometer*—0 to 50°C range, 0.1°C divisions, conforming to the requirements of Specification E1.

7.3 *Sieve*, 4.75-mm (No. 4) and 2-mm (No. 10) sieve, in accordance with Specification E11.

#### 8. Reagents and Materials

8.1 *Purity of Water*—Type IV of Specification D1193 with a pH between 5.5 and 7.0 shall be used for conducting the test method and preparing remolded specimens. Distilled water is preferred.

#### 9. Sampling, Test Specimens, and Test Units

9.1 *Sampling*—Obtain a representative soil sample of  $-4.75$ -mm (No. 4) soil. Depending on the percentage of coarse sand in the material, approximately 25 to 75 g of material is needed to perform a crumb test method and approximately 400 to 500 g of material is needed to perform the crumb, pinhole, and double-hydrometer tests.

NOTE 4—Do not use oven-dried material for the crumb test method because irreversible changes may occur to the soil pore-water physicochemical properties responsible for dispersion. Soil at natural moisture or at specified compaction moisture is preferred.

9.1.1 Water content of the sample prior to specimen preparation should be determined using either natural, air-dried, or water content as specified in Test Method D2216."

##### 9.2 Test Specimens:

9.2.1 Test specimens may be from natural, irregularly shaped soil crumbs (Test Method A) or may be remolded from material passing a 2-mm (No. 10) sieve (Test Method B). Material for the crumb test method should be selected as soon as possible after obtaining the soil sample.

##### 9.2.2 Test Method A—Natural Soil Crumbs: