

ISO/IEC JTC 1

Secretariat: **ANSI**

Voting begins on:
2009-01-21

Voting terminates on:
2009-03-21

**Information technology — Coding of
audio-visual objects —**

**Part 10:
Advanced Video Coding**

AMENDMENT 1: Multiview Video Coding

iTeh STANDARD PREVIEW

(standards.itih.ai) *Technologies de l'information — Codage des objets audiovisuels —
Partie 10: Codage visuel avancé*

ISO/IEC 14496-10:2008/FDAM1
AMENDEMENT 1: Codage vidéo multivues
<https://standards.itih.ai/catalog/standards/sist/065880a8-43b3-44be-9fba-fb838991ff3/iso-iec-14496-10-2008-fdam-1>

Please see the administrative notes on page iii

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



Reference number
ISO/IEC 14496-10:2008/FDAM 1:2009(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[ISO/IEC 14496-10:2008/FDAM 1](https://standards.iteh.ai/catalog/standards/sist/065880a8-43b3-44be-9fba-fb838991ff3/iso-iec-14496-10-2008-fdam-1)

<https://standards.iteh.ai/catalog/standards/sist/065880a8-43b3-44be-9fba-fb838991ff3/iso-iec-14496-10-2008-fdam-1>

Copyright notice

This ISO document is a Draft International Standard and is copyright-protected by ISO. Except as permitted under the applicable laws of the user's country, neither this ISO draft nor any extract from it may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission being secured.

Requests for permission to reproduce should be addressed to either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Reproduction may be subject to royalty payments or a licensing agreement.

Violators may be prosecuted.

In accordance with the provisions of Council Resolution 21/1986, this document is **circulated in the English language only**.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 14496-10:2008/FDAM 1](https://standards.iteh.ai/catalog/standards/sist/065880a8-43b3-44be-9fba-fb838991ffe3/iso-iec-14496-10-2008-fdam-1)

<https://standards.iteh.ai/catalog/standards/sist/065880a8-43b3-44be-9fba-fb838991ffe3/iso-iec-14496-10-2008-fdam-1>

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 1 to ISO/IEC 14496-10:2008 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information* in collaboration with ITU-T.

INTERNATIONAL STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 14496-10:2008/FDAM 1](https://standards.iteh.ai/catalog/standards/sist/065880a8-43f3-44be-9fba-fb838991ff3/iso-iec-14496-10-2008-fdam-1)
<https://standards.iteh.ai/catalog/standards/sist/065880a8-43f3-44be-9fba-fb838991ff3/iso-iec-14496-10-2008-fdam-1>

Information technology — Coding of audio-visual objects —

Part 10: Advanced Video Coding

AMENDMENT 1: Multiview Video Coding

In 0.6, add the following paragraph after the paragraph that starts with “Scalable video coding”:

Multiview video coding is specified in Annex H allowing the construction of bitstreams that represent multiple views. Similar to scalable video coding, bitstreams that represent multiple views may also contain sub-bitstreams that conform to this Specification. For temporal bitstream scalability, i.e., the presence of a sub-bitstream with a smaller temporal sampling rate than the bitstream, complete access units are removed from the bitstream when deriving the sub-bitstream. In this case, high-level syntax and inter prediction reference pictures in the bitstream are constructed accordingly. For view bitstream scalability, i.e. the presence of a sub-bitstream with fewer views than the bitstream, NAL units are removed from the bitstream when deriving the sub-bitstream. In this case, inter-view prediction, i.e., the prediction of one view signal by data of another view signal, is typically used for efficient coding.

[ISO/IEC 14496-10:2008/FDAM 1](https://standards.iteh.ai/catalog/standards/sist/065880a8-43b3-44be-9fba-58389173/iso-iec-14496-10-2008-fdam-1)

[https://standards.iteh.ai/catalog/standards/sist/065880a8-43b3-44be-9fba-](https://standards.iteh.ai/catalog/standards/sist/065880a8-43b3-44be-9fba-58389173/iso-iec-14496-10-2008-fdam-1)

In 0.7, add the following paragraph after the paragraph that starts with “Annex G specifies”:

Annex H specifies multiview video coding (MVC). The reader is referred to Annex H for the entire decoding process for MVC, which is specified there with references being made to clauses 2-9 and Annexes A-E. Subclause H.10 specifies one profile for MVC (Multiview High).

In 7.3.1, NAL unit syntax, replace the following row of the syntax table:

nal_unit_header_svc_extension() /* specified in Annex G */	All	
--	-----	--

with:

svc_extension_flag	All	u(1)
if(svc_extension_flag)		
nal_unit_header_svc_extension() /* specified in Annex G */	All	
else		
nal_unit_header_mvc_extension() /* specified in Annex H */		

In 7.3.2.1.1, Sequence parameter set data syntax, replace the following rows of the syntax table:

reserved_zero_4bits /* equal to 0 */	0	u(4)
level_idc	0	u(8)
seq_parameter_set_id	0	ue(v)
if(profile_idc == 100 profile_idc == 110 profile_idc == 122 profile_idc == 244 profile_idc == 44 profile_idc == 83 profile_idc == 86) {		

with:

constraint_set4_flag	0	u(1)
reserved_zero_3bits /* equal to 0 */	0	u(3)
level_idc	0	u(8)
seq_parameter_set_id	0	ue(v)
if(profile_idc == 100 profile_idc == 110 profile_idc == 122 profile_idc == 244 profile_idc == 44 profile_idc == 83 profile_idc == 86 profile_idc == 118) {		

Add a new subclause 7.3.2.1.3 as follows:

iTeH STANDARD PREVIEW
(standards.iteh.ai)

7.3.2.1.3 Subset sequence parameter set RBSP syntax

ISO/IEC 14496-10:2008/FDAM 1

	C	Descriptor
subset_seq_parameter_set_rbsp() {		
seq_parameter_set_data()	0	
if(profile_idc == 83 profile_idc == 86) {		
seq_parameter_set_svc_extension() /* specified in Annex G */	0	
svc_vui_parameters_present_flag	0	u(1)
if(svc_vui_parameters_present_flag == 1)		
svc_vui_parameters_extension() /* specified in Annex G */	0	
} else if(profile_idc == 118) {		
bit_equal_to_one /* equal to 1 */	0	f(1)
seq_parameter_set_mvc_extension() /* specified in Annex H */	0	
mvc_vui_parameters_present_flag	0	u(1)
if(mvc_vui_parameters_present_flag == 1)		
mvc_vui_parameters_extension() /* specified in Annex H */	0	
}		
additional_extension2_flag	0	u(1)
if(additional_extension2_flag == 1)		
while(more_rbsp_data())		
additional_extension2_data_flag	0	u(1)
rbsp_trailing_bits()		
}		

Add a new subclause 7.3.2.12 as follows:

7.3.2.12 Prefix NAL unit RBSP syntax

	C	Descriptor
prefix_nal_unit_rbsp() {		
if(svc_extension_flag)		
prefix_nal_unit_svc() /* specified in Annex G */	2	
}		

Add a new subclause 7.3.2.13 as follows:

7.3.2.13 Slice layer extension RBSP syntax

	C	Descriptor
slice_layer_extension_rbsp() {		
if(svc_extension_flag)		
slice_header_in_scalable_extension() /* specified in Annex G */	2	
if(!slice_skip_flag)		
slice_data_in_scalable_extension() /* specified in Annex G */	2 3 4	
} else {		
slice_header()	2	
slice_data()	2 3 4	
}		
rbsp_slice_trailing_bits()	2	
}		

In 7.3.3, Slice header syntax, replace the condition:

```
if( nal_unit_type == 5 )
```

with:

```
if( IdrPicFlag )
```

In 7.3.3, Slice header syntax, replace the following row of the syntax table:

ref_pic_list_modification()	2	
------------------------------	---	--

with:

if(nal_unit_type == 20)		
ref_pic_list_mvc_modification() /* specified in Annex H */	2	
else		
ref_pic_list_modification()	2	

In 7.4.1, NAL unit semantics, make the following changes:

Replace the following paragraph:

For coded video sequences conforming to one or more of the profiles specified in Annex A that are decoded using the decoding process specified in clauses 2-9, VCL and non-VCL NAL units are specified in Table 7-1 in the column labelled “Annex A NAL unit type class”. For coded video sequences conforming to one or more of the profiles specified in Annex G that are decoded using the decoding process specified in Annex G, VCL and non-VCL NAL units are specified in Table 7-1 in the column labelled “Annex G NAL unit type class”. The entry “suffix dependent” for nal_unit_type equal to 14 is specified as follows.

with:

For coded video sequences conforming to one or more of the profiles specified in Annex A that are decoded using the decoding process specified in clauses 2-9, VCL and non-VCL NAL units are specified in Table 7-1 in the column labelled “Annex A NAL unit type class”. For coded video sequences conforming to one or more of the profiles specified in Annex G that are decoded using the decoding process specified in Annex G or specified in Annex H that are decoded using the decoding process specified in Annex H, VCL and non-VCL NAL units are specified in Table 7-1 in the column labelled “Annex G and Annex H NAL unit type class”. The entry “suffix dependent” for nal_unit_type equal to 14 is specified as follows.

Replace Table 7-1 with:

Table 7-1 – NAL unit type codes, syntax element categories, and NAL unit type classes

nal_unit_type	Content of NAL unit and RBSP syntax structure	C	Annex A NAL unit type class	Annex G and Annex H NAL unit type class
0	Unspecified		non-VCL	non-VCL
1	Coded slice of a non-IDR picture slice_layer_without_partitioning_rbsp()	2, 3, 4	VCL	VCL
2	Coded slice data partition A slice_data_partition_a_layer_rbsp()	2	VCL	not applicable
3	Coded slice data partition B slice_data_partition_b_layer_rbsp()	3	VCL	not applicable
4	Coded slice data partition C slice_data_partition_c_layer_rbsp()	4	VCL	not applicable
5	Coded slice of an IDR picture slice_layer_without_partitioning_rbsp()	2, 3	VCL	VCL
6	Supplemental enhancement information (SEI) sei_rbsp()	5	non-VCL	non-VCL
7	Sequence parameter set seq_parameter_set_rbsp()	0	non-VCL	non-VCL
8	Picture parameter set pic_parameter_set_rbsp()	1	non-VCL	non-VCL
9	Access unit delimiter access_unit_delimiter_rbsp()	6	non-VCL	non-VCL
10	End of sequence end_of_seq_rbsp()	7	non-VCL	non-VCL
11	End of stream end_of_stream_rbsp()	8	non-VCL	non-VCL
12	Filler data filler_data_rbsp()	9	non-VCL	non-VCL
13	Sequence parameter set extension seq_parameter_set_extension_rbsp()	10	non-VCL	non-VCL
14	Prefix NAL unit prefix_nal_unit_rbsp()	2	non-VCL	suffix dependent
15	Subset sequence parameter set subset_seq_parameter_set_rbsp()	0	non-VCL	non-VCL
16..18	Reserved		non-VCL	non-VCL
19	Coded slice of an auxiliary coded picture without partitioning slice_layer_without_partitioning_rbsp()	2, 3, 4	non-VCL	non-VCL
20	Coded slice extension slice_layer_extension_rbsp()	2, 3, 4	non-VCL	VCL
21..23	Reserved		non-VCL	non-VCL
24..31	Unspecified		non-VCL	non-VCL

Before the paragraph that begins with “**rbbsp_byte[i]**”, insert the following paragraph:

svc_extension_flag indicates whether a **nal_unit_header_svc_extension()** or **nal_unit_header_mvc_extension()** will follow next in the syntax structure.

The value of **svc_extension_flag** shall be equal to 1 for coded video sequences conforming to one or more profiles specified in Annex G. Decoders conforming to one or more profiles specified in Annex G shall ignore NAL units for which **nal_unit_type** is equal to 14 or 20 and for which **svc_extension_flag** is equal to 0.

The value of **svc_extension_flag** shall be equal to 0 for coded video sequences conforming to one or more profiles specified in Annex H. Decoders conforming to one or more profiles specified in Annex H shall ignore NAL units for which **nal_unit_type** is equal to 14 or 20 and for which **svc_extension_flag** is equal to 1.

In 7.4.2.1.1, *Sequence parameter set data semantics*, replace the semantics for **reserved_zero_4bits** with the following:

constraint_set4_flag shall be equal to 0. Decoders shall ignore the value of **constraint_set4_flag**.

reserved_zero_3bits shall be equal to 0. Other values of **reserved_zero_3bits** may be specified in the future by ITU-T | ISO/IEC. Decoders shall ignore the value of **reserved_zero_3bits**.

iTeh STANDARD PREVIEW

Add a new subclause 7.4.2.1.3 as follows: standards.iteh.ai

7.4.2.1.3 Subset sequence parameter set RBSP semantics

svc_vui_parameters_present_flag equal to 0 indicates that the syntax structure **svc_vui_parameters_extension()** is not present. **svc_vui_parameters_present_flag** equal to 1 indicates that the syntax structure **svc_vui_parameters_extension()** is present.

bit_equal_to_one shall be equal to 1.

mvc_vui_parameters_present_flag equal to 0 indicates that the syntax structure **mvc_vui_parameters_extension()** is not present. **mvc_vui_parameters_present_flag** equal to 1 indicates that the syntax structure **mvc_vui_parameters_extension()** is present.

additional_extension2_flag equal to 0 specifies that the syntax elements **additional_extension2_data_flag** are not present within the subset sequence parameter set RBSP syntax structure. **additional_extension2_flag** shall be equal to 0 in bitstreams conforming to this Recommendation | International Standard. The value of 1 for **additional_extension2_flag** is reserved for future use by ITU-T | ISO/IEC. Decoders shall ignore all data that follow the value 1 for **additional_extension2_flag** in a subset sequence parameter set NAL unit.

additional_extension2_data_flag may have any value.

Add a new subclause 7.4.2.12 as follows:

7.4.2.12 Prefix NAL unit RBSP semantics

The content of the prefix NAL unit RBSP is dependent on the value of **svc_extension_flag**.

Add a new subclause 7.4.2.13 as follows:

7.4.2.13 Slice layer extension RBSP semantics

The content of the slice layer extension RBSP is dependent on the value of `svc_extension_flag`.

Coded slice extension NAL units with `svc_extension_flag` equal to 1 are also referred to as coded slice in scalable extension NAL units and coded slice extension NAL units with `svc_extension_flag` equal to 0 are also referred to as coded slice MVC extension NAL units.

In C, Hypothetical reference decoder, replace:

For each picture in the bitstream, the variable `OutputFlag` for the decoded picture and, when applicable, the reference base picture is set as follows.

- If the coded video sequence containing the picture conforms to one or more of the profiles specified in Annex A and the decoding process specified in clauses 2-9 is used), `OutputFlag` is set equal to 1.
- Otherwise (the coded video sequence containing the picture conforms to a profile specified in Annex G and the decoding process specified in Annex G is used), the following applies:
 - For a reference base picture, `OutputFlag` is set equal to 0.
 - For a decoded picture, `OutputFlag` is set equal to the value of the `output_flag` syntax element of the target layer representation.

The operation of the CPB is specified in subclause C.1. The instantaneous decoder operation is specified in clauses 2-9 when decoding a coded video sequence conforming to one or more of the profiles specified in Annex A, or specified in Annex G when decoding a coded video sequence conforming to one or more of the profiles specified in Annex G. The operation of the DPB is specified in subclause C.2. The output cropping is specified in subclause C.2.2.

HSS and HRD information concerning the number of enumerated delivery schedules and their associated bit rates and buffer sizes is specified in subclauses E.1.1, E.1.2, E.2.1 and E.2.2. The HRD is initialised as specified by the buffering period SEI message as specified in subclauses D.1.1 and D.2.1. The removal timing of access units from the CPB and output timing from the DPB are specified in the picture timing SEI message as specified in subclauses D.1.2 and D.2.2. All timing information relating to a specific access unit shall arrive prior to the CPB removal time of the access unit.

with:

For each picture in the bitstream, the variable `OutputFlag` for the decoded picture and, when applicable, the reference base picture, is set as follows.

- If the coded video sequence containing the picture conforms to one or more of the profiles specified in Annex A and the decoding process specified in clauses 2-9 is used), `OutputFlag` is set equal to 1.
- Otherwise if the coded video sequence containing the picture conforms to a profile specified in Annex G and the decoding process specified in Annex G is used, the following applies:
 - For a reference base picture, `OutputFlag` is set equal to 0.
 - For a decoded picture, `OutputFlag` is set equal to the value of the `output_flag` syntax element of the target layer representation.

- Otherwise (the coded video sequence containing the picture conforms to a profile specified in Annex H and the decoding process specified in Annex H is used), the following applies:
 - For the decoded view components of the target output views, OutputFlag is set equal to 1.
 - For the decoded view components of other views, OutputFlag is set to 0.

The operation of the CPB is specified in subclause C.1. The instantaneous decoder operation is specified in clauses 2-9 when decoding a coded video sequence conforming to one or more of the profiles specified in Annex A, or specified in Annex G when decoding a coded video sequence conforming to one or more of the profiles specified in Annex G, or specified in Annex H when decoding a coded video sequence conforming to one or more of the profiles specified in Annex H. The operation of the DPB is specified in subclause C.2. The output cropping is specified in subclause C.2.2.

HSS and HRD information concerning the number of enumerated delivery schedules and their associated bit rates and buffer sizes is specified in subclauses E.1.1, E.1.2, E.2.1 and E.2.2 when decoding a coded video sequence conforming to one or more of the profiles specified in Annex A using the decoding process specified in clauses 2-9, or specified in subclauses G.14.1 and G.14.2 when decoding a coded video sequence conforming to one or more of the profiles specified in Annex G using the decoding process specified in Annex G, or specified in subclauses H.14.1 and H.14.2 when decoding a coded video sequence conforming to one or more of the profiles specified in Annex H using the decoding process specified in Annex H. The HRD is initialised as specified by the buffering period SEI message as specified in subclauses D.1.1 and D.2.1. The removal timing of access units from the CPB and output timing from the DPB are specified in the picture timing SEI message as specified in subclauses D.1.2 and D.2.2. All timing information relating to a specific access unit shall arrive prior to the CPB removal time of the access unit.

iTeh STANDARD PREVIEW

In C.2, Operation of the decoded picture buffer (DPB), add the following text after the sentence, “When decoding a coded video sequence conforming to one or more of the profiles specified in Annex G”:

ISO/IEC 14496-10:2008/FDAM 1

When decoding a coded video sequence conforming to one or more of the profiles specified in Annex H using the decoding process specified in Annex H, each of the frame buffers may contain a decoded frame view component, a decoded complementary field view component pair, or a single (non-paired) decoded field view component that is marked as “used for reference” (reference pictures) or is held for future output (reordered or delayed pictures).

In C.2.1, Decoding of gaps in frame_num and storage of “non-existing” frames, add the following paragraph at the start of the subclause:

When decoding a coded video sequence conforming to a profile specified in Annex H using the decoding process specified in Annex H, the following process in this subclause is repeatedly invoked for each view in increasing order of view order index, with “picture” being replaced by “view component”, “frame” being replaced by “frame view component”, and “field” being replaced by “field view component”. During the invocation of the process for a particular view, only view components of the particular view may be removed from the DPB.

In C.2.2, Picture decoding and output, make the following changes:

Add the following text at the start of the subclause:

When the coded video sequence containing the picture conforms to a profile specified in Annex H and the decoding process specified in Annex H is used, the following applies:

- When at least one view component of picture *n* has OutputFlag equal to 1, it is considered that picture *n* has OutputFlag equal to 1.
- When at least one view component of picture *n* is output, it is considered that picture *n* is output.
- When at least one view component of picture *n* is stored in DPB, it is considered that picture *n* is stored in the DPB.

Replace:

NOTE – When the current picture is a reference picture it will be stored in the DPB.

with:

NOTE – When the current picture or a view component of the current picture has *nal_ref_idc* greater than 0, it will be stored in the DPB.

Replace:

When output, the picture shall be cropped using the cropping rectangle specified in the active sequence parameter set for the picture.

with:

When the coded video sequence containing the picture conforms to a profile specified in Annex H and the decoding process specified in Annex H is used, and picture *n* is output, the view components of all the target output views in picture *n* are output at the same time instant and in increasing order of VOIdx.

When output, the picture or a view component of the picture shall be cropped, using the cropping rectangle specified in the active sequence parameter set for the picture or the view component.

In C.2.3 Removal of pictures from the DPB before possible insertion of the current picture, make the following changes:

Add the following at the start of the subclause:

When decoding a coded video sequence conforming to a profile specified in Annex H using the decoding process specified in Annex H, the following process in this subclause is repeatedly invoked for each view in view decoding order, with “picture” being replaced by “view component”, “frame” being replaced by “frame view component”, and “field” being replaced by “field view component”. During the invocation of the process for a particular view, only view components of the particular view may be removed from the DPB.

Replace:

All reference pictures in the DPB are marked as “unused for reference” as specified in subclause 8.2.5.1 when decoding a coded video sequence conforming to one or more of the profiles specified in Annex A using the decoding process specified in clauses 2-9, or as specified in subclause G.8.2.4 when decoding a coded video sequence conforming to one or more of the profiles specified in Annex G using the decoding process specified in Annex G.

with:

All reference pictures in the DPB are marked as “unused for reference” as specified in subclause 8.2.5.1 when decoding a coded video sequence conforming to one or more of the profiles specified in Annex A using the decoding process specified in clauses 2-9, or as specified in subclause G.8.2.4 when decoding a coded video sequence conforming to one or more of the profiles specified in Annex G using the decoding process specified in Annex G, or as specified in subclause H.8.3 when decoding a coded video sequence conforming to one or more of the profiles specified in Annex H using the decoding process specified in Annex H.

Replace:

Otherwise (the slice header of the current picture does not include `memory_management_control_operation` equal to 5), the decoded reference picture marking process specified in subclause 8.2.5 is invoked when decoding a coded video sequence conforming to one or more of the profiles specified in Annex A using the decoding process specified in clauses 2-9, or the decoded reference picture marking process specified in subclause G.8.2.4 is invoked when decoding a coded video sequence conforming to one or more of the profiles specified in Annex G using the decoding process specified in Annex G.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

with:

Otherwise (the slice header of the current picture does not include `memory_management_control_operation` equal to 5), the decoded reference picture marking process specified in subclause 8.2.5 is invoked when decoding a coded video sequence conforming to one or more of the profiles specified in Annex A using the decoding process specified in clauses 2-9, or the decoded reference picture marking process specified in subclause G.8.2.4 is invoked when decoding a coded video sequence conforming to one or more of the profiles specified in Annex G using the decoding process specified in Annex G, or the decoded reference picture marking process specified in subclause H.8.3 is involved when decoding a coded video sequence conforming to one or more of the profiles specified in Annex H using the decoding process specified in Annex H.

In C.2.4 Current decoded picture marking and storage, add the following at the start of the subclause:

When decoding a coded video sequence conforming to a profile specified in Annex H using the decoding process specified in Annex H, the following process in this subclause is repeatedly invoked for each view in increasing order of view order index, with “picture” being replaced by “view component”, “frame” being replaced by “frame view component”, and “field” being replaced by “field view component”. During the invocation of the process for a particular view, only view components of the particular view may be removed from the DPB.

In C.3, Bitstream Conformance, make the following changes:

Replace:

The nominal removal times of pictures from the CPB (starting from the second picture in decoding order), shall satisfy the constraints on $t_{r,n}(n)$ and $t_r(n)$ expressed in subclauses A.3.1 through A.3.3 for the profile and level specified in the bitstream when decoding a coded video sequence conforming to one or more of the profiles

specified in Annex A using the decoding process specified in clauses 2-9, and they shall satisfy the constraints on $t_{r,n}(n)$ and $t_r(n)$ expressed in subclauses G.10.2.1 and G.10.2.2 for profile and level specified in the bitstream when decoding a coded video sequence conforming to one or more of the profiles specified in Annex G using the decoding process specified in Annex G.

with:

The nominal removal times of pictures from the CPB (starting from the second picture in decoding order), shall satisfy the constraints on $t_{r,n}(n)$ and $t_r(n)$ expressed in subclauses A.3.1 through A.3.3 for the profile and level specified in the bitstream when decoding a coded video sequence conforming to one or more of the profiles specified in Annex A using the decoding process specified in clauses 2-9, and they shall satisfy the constraints on $t_{r,n}(n)$ and $t_r(n)$ expressed in subclauses G.10.2.1 and G.10.2.2 for profile and level specified in the bitstream when decoding a coded video sequence conforming to one or more of the profiles specified in Annex G using the decoding process specified in Annex G, and they shall satisfy the constraints on $t_{r,n}(n)$ and $t_r(n)$ expressed in subclause H.10.2 for the profile and level specified in the bitstream when decoding a coded video sequence conforming to one or more of the profiles specified in Annex H using the decoding process specified in Annex H.

Replace:

The value of $\Delta_{t_{o,dpb}}(n)$ as given by Equation C-13, which is the difference between the output time of a picture and that of the first picture following it in output order and having OutputFlag equal to 1, shall satisfy the constraint expressed in subclause A.3.1 for the profile and level specified in the bitstream when decoding a coded video sequence conforming to one or more of the profiles specified in Annex A using the decoding process specified in clauses 2-9, and it shall satisfy the constraint expressed in subclause G.10.2.1 for profile and level specified in the bitstream when decoding a coded video sequence conforming to one or more of the profiles specified in Annex G using the decoding process specified in Annex G.

[ISO/IEC 14496-10:2008/FDAM 1](https://standards.iteh.ai/catalog/standards/sist/065880a8-43f3-44be-9fba-fb838991ff3/iso-iec-14496-10-2008-fdam-1)

with: <https://standards.iteh.ai/catalog/standards/sist/065880a8-43f3-44be-9fba-fb838991ff3/iso-iec-14496-10-2008-fdam-1>

The value of $\Delta_{t_{o,dpb}}(n)$ as given by Equation C-13, which is the difference between the output time of a picture and that of the first picture following it in output order and having OutputFlag equal to 1, shall satisfy the constraint expressed in subclause A.3.1 for the profile and level specified in the bitstream when decoding a coded video sequence conforming to one or more of the profiles specified in Annex A using the decoding process specified in clauses 2-9, and it shall satisfy the constraint expressed in subclause G.10.2.1 for profile and level specified in the bitstream when decoding a coded video sequence conforming to one or more of the profiles specified in Annex G using the decoding process specified in Annex G, and it shall satisfy the constraints expressed in subclauses H.10.2 for the profile and level specified in the bitstream when decoding a coded video sequence conforming to one or more of the profiles specified in Annex H using the decoding process specified in Annex H.

In C.4.1, Operation of the output order DPB, add the following text after the sentence starting with, "When decoding a coded video sequence conforming to one or more of the profiles specified in Annex G":

When decoding a coded video sequence conforming to one or more of the profiles specified in Annex H using the decoding process specified in Annex H, each of the frame buffers may contain a decoded frame view component, a decoded complementary field view component pair, or a single (non-paired) decoded field view component that is marked as "used for reference" (reference pictures) or is held for future output (reordered or delayed pictures).