

SLOVENSKI STANDARD
oSIST prEN 300 338-7 V1.0.0:2021
01-september-2021

Tehnične karakteristike in merilne metode za naprave, ki generirajo, oddajajo in sprejemajo digitalni selektivni klic (DSC) v pomorski mobilni storitvi, ki deluje v območju MF, MF/HF oziroma VHF - 7. del: Izvedba upravljanja z opozorili na mostu (BAM) v radijski opremi DSC

Technical characteristics and methods of measurement for equipment for generation, transmission and reception of Digital Selective Calling (DSC) in the maritime MF, MF/HF and/or VHF mobile service - Part 7: Implementation of Bridge Alert Management (BAM) in DSC radio equipment

Free STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/463ae524-abc2-4536-b88c-46355aecd507/osist-pren-300-338-7-v1-0-0-2021>

Ta slovenski standard je istoveten z: ETSI EN 300 338-7 V1.0.0 (2021-07)

ICS:

33.060.20	Sprejemna in oddajna oprema	Receiving and transmitting equipment
47.020.70	Navigacijska in krmilna oprema	Navigation and control equipment

oSIST prEN 300 338-7 V1.0.0:2021 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN 300 338-7 V1.0.0:2021](https://standards.iteh.ai/catalog/standards/sist/463ae524-abc2-4536-b88c-46355aecd507/osist-pren-300-338-7-v1-0-0-2021)

<https://standards.iteh.ai/catalog/standards/sist/463ae524-abc2-4536-b88c-46355aecd507/osist-pren-300-338-7-v1-0-0-2021>

Draft **ETSI EN 300 338-7** V1.0.0 (2021-07)



**Technical characteristics and methods of measurement
for equipment for generation, transmission
and reception of Digital Selective Calling (DSC)
in the maritime MF, MF/HF and/or VHF mobile service;
Part 7: Implementation of Bridge Alert Management (BAM)
in DSC radio equipment**

Reference

DEN/ERM-TGMAR-087-7

Keywords

DSC, GMDSS, maritime, radio, SAR

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.
All rights reserved.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	6
3 Definition of terms, symbols and abbreviations.....	7
3.1 Terms.....	7
3.2 Symbols.....	8
3.3 Abbreviations	8
4 General requirements	9
4.1 Bridge alert management implementation.....	9
4.1.1 Requirements	9
4.1.2 Methods of test and required test results.....	9
4.2 Audible signals for BAM alerts vs audible indications	9
4.2.1 General.....	9
4.2.2 Requirements	10
4.2.3 Methods of test and required test results.....	10
4.3 Interfaces	10
4.3.1 General requirements.....	10
4.3.2 Construction requirements	11
4.3.2.1 Physical connection.....	11
4.3.2.2 Ethernet protocols	11
4.3.3 Required sentences to support on the interface.....	11
4.3.4 Methods of test and required test results.....	12
5 Bridge Alert Management	12
5.1 Classification of BAM alerts	12
5.2 Mapping DSC alarms to BAM alerts	12
5.2.1 Requirements for BAM alerts defined in the present document.....	12
5.2.2 Requirements for manufacturer defined BAM alerts.....	13
5.2.3 Methods of test and required results	14
5.3 Unacknowledged BAM warnings	15
5.3.1 Requirements	15
5.3.2 Methods of test and required results	15
6 Detailed requirements for BAM alerts and alert communication.....	15
6.1 Alert communication.....	15
6.1.1 Requirements	15
6.1.2 Method of test and required results.....	16
6.2 Handling DSC alerts of types "distress" and "distress relay" in received distress automated procedure and of category "urgency" in received non-distress automated procedure.....	16
6.2.1 Typical alert flow.....	16
6.2.2 Requirements	17
6.2.3 Methods of test and required results	19
6.2.3.1 Distress and Distress Relay.....	19
6.2.3.2 Urgency.....	20
6.3 Handling DSC alerts in received non-distress automated procedure other than category urgency	21
6.3.1 Typical alert flow.....	21
6.3.2 Requirements	21
6.3.3 Methods of test and required results	22
6.4 Handling other alerts related to DSC communication equipment	23
6.4.1 Typical alert flow.....	23
6.4.2 No position data received by DSC equipment	25

6.4.2.1	Requirements	25
6.4.2.2	Methods of test and required results	25
6.4.3	Antenna Tuner Error or other detected antenna failures (optional)	26
6.4.3.1	Requirements	26
6.4.3.2	Methods of test and required results	27
6.4.4	Transmission power error or otherwise inhibited transmission (optional).....	28
6.4.4.1	Requirements	28
6.4.4.2	Methods of test and required results	28
Annex A (normative): Audible indications and BAM alert audible signals		30
A.1	Aural specifications	30
Annex B (informative): Guidelines for designing DSC radios to the BAM concept		32
B.1	Introduction	32
History		35

iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN 300 338-7 V1.0.0:2021](https://standards.iteh.ai/catalog/standards/sist/463ae524-abc2-4536-b88c-46355aecd507/osist-pren-300-338-7-v1-0-0-2021)

<https://standards.iteh.ai/catalog/standards/sist/463ae524-abc2-4536-b88c-46355aecd507/osist-pren-300-338-7-v1-0-0-2021>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

ITih STANDARD PREVIEW
(standards.iteh.ai)

Foreword

oSIST prEN 300 338-7 V1.0.0:2021

This draft European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document is part 7 of a multi-part deliverable. Full details of the entire series can be found in ETSI EN 300 338-1 [i.1].

Proposed national transposition dates

Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document specifies the minimum requirements for GMDSS radiocommunication system using Digital Selective Calling (DSC) Class A, with the capability to operate on a SOLAS bridge with the application of SOLAS regulation V/15 [i.5] and thus implementing the BAM concept defined by IMO in MSC.302(87) [8].

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Recommendation ITU-R M.493-15: "Digital selective-calling system for use in the maritime mobile service".
- [2] ETSI EN 300 338-2: "Technical characteristics and methods of measurement for equipment for generation, transmission and reception of Digital Selective Calling (DSC) in the maritime MF, MF/HF and/or VHF mobile service; Part 2: Class A DSC".
- [3] IEC 62923-1 (Ed. 1) (2018): "Maritime navigation and radiocommunication equipment and systems - Bridge alert management - Part 1: Operational and performance requirements, methods of testing and required test results".
- [4] IEC 61162-1 (Ed. 5) (2016): "Maritime navigation and radiocommunication equipment and systems - Digital interfaces - Part 1: Single talker and multiple listeners".
- [5] IEC 61162-2: "Maritime navigation and radiocommunication equipment and systems - Digital interfaces - Part 2: Single talker and multiple listeners, high-speed transmission".
- [6] IEC 61162-450 (Ed. 2) (2018): "Maritime navigation and radiocommunication equipment and systems - Digital interfaces - Part 450: Multiple talkers and multiple listeners - Ethernet interconnection".
- [7] IEC 62923-2 (Ed. 1) (2018): "Maritime navigation and radiocommunication equipment and systems - Bridge alert management - Part 2: Alert and cluster identifiers and other additional features".
- [8] IMO Resolution MSC.302(87): "Adoption of performance standards for bridge alert management".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EN 300 338-1: "Technical characteristics and methods of measurement for equipment for generation, transmission and reception of Digital Selective Calling (DSC) in the maritime MF, MF/HF and/or VHF mobile service; Part 1: Common requirements".
- [i.2] IEC 62940:2016: "Maritime navigation and radiocommunication equipment and systems - Integrated communication system (ICS) - Operational and performance requirements, methods of testing and required test results".
- [i.3] IEC 61097-3 (Ed. 2) (2017): "Global maritime distress and safety system (GMDSS) - Part 3: Digital selective calling (DSC) equipment - Operational and performance requirements, methods of testing and required results".
- [i.4] ETSI EN 300 338-8: "Technical characteristics and methods of measurement for equipment for generation, transmission and reception of Digital Selective Calling (DSC) in the maritime MF, MF/HF and/or VHF mobile service; Part 8: Enabling DSC radio equipment with remote control capabilities".
- [i.5] SOLAS: "International Convention for the Safety Of Life At Sea", 1974 (as amended).
- [i.6] IMO Resolution A.1021(26) (2009): "Code on alerts and indicators".

3 Definition of terms, symbols and abbreviations

3.1 Terms

iTeh STANDARD PREVIEW
(standards.iteh.ai)

For the purposes of the present document, the terms given in ETSI EN 300 338-1 [i.1] and the following apply:

acknowledge: BAM alert acknowledge [oSIST prEN 300 338-7 V1.0.0:2021](https://standards.iteh.ai/catalog/standards/sist/463ae524-abc2-4536-b88c-46355aeed507/osist-pr-en-300-338-7-v1-0-0-2021)

audible indication: sound from the EUT that is not associated with raising a BAM alert of priority alarm or warning in the list of active alerts of the EUT

NOTE: BAM alerts of priority caution and emergency alarm do not have a BAM audible signal, nor have states to handle acknowledgement or silencing.

EXAMPLE 1: A sound indicating a change of control position.

EXAMPLE 2: Table 7.1.1 of IMO Resolution A.1021(26):2009, "Code on Alerts and Indicators" [i.6].

BAM alert: announcement of abnormal situations and conditions requiring attention

NOTE: BAM alerts are divided in four priorities: emergency alarms, alarms, warnings and cautions.

distress event: unique distress situation identified by two (VHF) or three (MF/HF) parameters of the distress information; the MMSI of the vessel in distress and the nature of distress and on MF/HF the mode of subsequent communication

DSC acknowledge: DSC procedure acknowledge

DSC alarm: event in DSC equipment as specified in ETSI EN 300 338-2 [2]

DSC distress acknowledgement: distress DSC message of type Alert Acknowledgement

DSC distress alert: distress DSC message of type Alert

DSC distress relay: distress DSC message of type Relay

DSC urgency message: non-distress DSC message of category Urgency

non-distress DSC message: DSC messages or DSC acknowledgements that do not have the format specifier or category of "distress"

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

A	Assembly
BAM	Bridge Alert Management
CAM	Central Alert Management
DSC	Digital Selective Calling
ED	Edition
EN	European Norm
ETSI	European Telecommunications Standards Institute
EUT	Equipment Under Test
GMDSS	Global Maritime Distress and Safety System
HF	High Frequency
HMI	Human Machine Interface
ICS	Integrated Communication System
ID	Identity
IEC	International Electrotechnical Commission
IMO	International Maritime Organization
IP	Internet Protocol
ITU	International Telecommunications Union
ITU-R	ITU - Radiocommunications sector
MF	Medium Frequency
MMSI	Maritime Mobile Service Identity
MSC	Marine Safety Committee
N	North/Northern latitude
NM	Nautical Mile
OOW	Officer Of the Watch
RX	Receive(d)/Receiving
S	South/Southern latitude
SAR	Search And Rescue
SFI	System Function ID
SNMP	Simple Network Management Protocol
SOLAS	International convention on the Safety Of Life At Sea 1974
STF	Specialist Task Force
TAG	Transport Annotate and Group
TCP	Transmission Control Protocol
TX	Transmit(ted)/Transmitting
UDP	User Datagram Protocol
VHF	Very High Frequency

4 General requirements

4.1 Bridge alert management implementation

4.1.1 Requirements

Compliance with the BAM concept, including the interfaces required for BAM, is a functional and conceptual extension to, not a substitution of, facilities as required in ETSI EN 300 338-2 [2]. Compliance with ETSI EN 300 338-2 [2] is required unless the present document requires otherwise. According to MSC.302(87) [8] and IEC 62923-1 [3], in case of conflict between the alert requirements of ETSI EN 300 338-2 [2] and the present document, the requirements and tests of the present document and of MSC.302(87) [8], IEC 62923-1 [3] and IEC 62923-2 [7] shall take precedence.

According to the BAM concept it is necessary to prioritize BAM alerts and the priorities shall be determined by the DSC equipment. The BAM concept poses requirements on the alert definition concept, alert properties and the Human Machine Interface (HMI). For guidance see IEC 62923-1 [3], Annex E.

Further a signalling interface and a protocol are defined for interfacing equipment to a CAM system or to other BAM compliant equipment according to IEC 62923-1 [3], IEC 61162-1 [4] and IEC 62923-2 [7]. The present document adopts the signalling protocol and allows, within limits, for DSC alarms from radio equipment to be part of the BAM concept or otherwise facilitates these.

The EUT shall comply with the requirements of ETSI EN 300 338-2 [2], IEC 62923-1 [3] and IEC 62923-2 [7].

Informative guidance on implementing Bridge Alert Management can be found in Annex B to the present document.

4.1.2 Methods of test and required test results

It shall be confirmed that the EUT complies with the tests in ETSI EN 300 338-2 [2], IEC 62923-1 [3] and IEC 62923-2 [7].

<https://standards.iteh.ai/catalog/standards/sist/463ae524-abc2-4536-b88c-46355eccd505/sist-prn300-338-7-v1-0-0-2021>

<https://standards.iteh.ai/catalog/standards/sist/463ae524-abc2-4536-b88c-46355eccd505/sist-prn300-338-7-v1-0-0-2021>

4.2 Audible signals for BAM alerts vs audible indications

4.2.1 General

BAM alerts are alerts falling into the concept of Bridge Alert Management (BAM) (see MSC.302(87) [8] and IEC 62923-1 [3]). BAM applies to all alerts presented on, or transferred to, the bridge of a vessel (the concept can also be applied in other areas). The visual and audible announcements of BAM alerts are always handled on the EUT, and, within limitations, additionally on the CAM system. The latter of which is not covered in the present document (see IEC 62923-1 [3] and IEC 62923-2 [7]).

The BAM concept provides amongst others human machine interface requirements and provides a standardized method to disseminate the information to the CAM system, thus requiring the support of the alert signalling interface and protocol as defined in IEC 61162-1 [4] and IEC 62923-1 [3].

BAM alerts are distinct from matters such as DSC aural alarms. For the purpose of the present document the audible presentation and handling of DSC aurals defined in Recommendation ITU-R M.493-15 [1] and ETSI EN 300 338-2 [2] includes:

- audible signals. An audible signal is intended to recognize the existence and priority of a BAM alert and to identify the equipment where an audible BAM alert can be handled. In the present document some audible signals are directly based on DSC aurals, see Annex A and Table A.1;
- sound in the time allotted for speech output. Speech output is intended to recognize the specific BAM alert. Some DSC aurals are allowed or required for this purpose, see Annex A and Table A.1; and
- audible indications (see also IEC 62923-1 [3]). Most DSC aurals are audible indications for the purpose of the present document. The audible indications that occur together with a caution are listed in Annex A and Table A.1.

Audible indications indicating DSC aural alarms or other situations may be applied in the EUT for functionality that does not warrant a BAM alert, for example a tone for pressing the dedicated distress button, or for situations that do not warrant an audible BAM alert, for example when the corresponding BAM alerts raised are only characterized as a caution (thus without audible signal). Situations where ITU has defined sounds that need to be detached from alert management altogether are therefore not defined in the present document.

Audible indications (mandatory or manufacturer specific) may be applied subject to the requirements defined in clause 4.2.2.

4.2.2 Requirements

BAM alerts of priority warning and alarm shall not be accompanied with an audible indication (only the audible presentation defined in IEC 62923-1 [3] is allowed).

All sounds provided by the EUT that are not required by the present document as (part of the) audible presentation of a BAM alert (i.e. an audible signal for a BAM alert and the signal in the time for 'speech output') are audible indications.

When an audible indication is provided, it shall:

- not be possible to be confused with a BAM alert;
- not be startling;
- be less disturbing than BAM alerts; and
- be either:
 - momentary or temporary without user interaction, or
 - stop after a defined user action on the equipment, which action is not related to alert management (this user action shall not involve the alert acknowledgement or silencing features). See also clause A.1.

4.2.3 Methods of test and required test results

It shall be confirmed by inspection of the EUT that BAM alerts of priority warning and alarm are not accompanied with an audible indication, thus only the audible presentation defined in IEC 62923-1 [3] shall occur.

It shall be confirmed by inspection of the EUT that when an audible indication is provided, e.g. along with a caution raised or detached from alert management, the audible indication:

- cannot be confused with a BAM alert;
- is not startling;
- is less disturbing than BAM alerts; and
- is either:
 - momentary or temporary without user interaction, or
 - stops after a defined user action on the equipment, which action is not related to alert management (this user action shall not involve the alert acknowledgement or silencing features). See also clause A.1.

4.3 Interfaces

4.3.1 General requirements

Data interfaces for Bridge Alert Management purposes for the connection with a CAM system, and optionally other BAM compliant equipment, shall be provided and shall comply with at least one of IEC 61162-1 [4], IEC 61162-2 [5] or IEC 61162-450 [6]. The manufacturer shall specify which alternative(s) (defined in IEC 61162-1 [4], IEC 61162-2 [5] and IEC 61162-450 [6]) the physical interface(s) of the EUT supports.