
**Methods of evaluation of the battery life
of a battery-powered watch**

*Méthodes d'évaluation de l'autonomie de fonctionnement d'une montre
à pile*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 12819:2009

<https://standards.iteh.ai/catalog/standards/sist/c7dd3ce4-43eb-47cb-b161-7e0ea65fe40a/iso-12819-2009>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 12819:2009

<https://standards.iteh.ai/catalog/standards/sist/c7dd3ce4-43eb-47cb-b161-7e0ea65fe40a/iso-12819-2009>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

| | |
|---|----------|
| Foreword..... | iv |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 1 |
| 4 General | 2 |
| 4.1 Parameters | 2 |
| 4.2 Types of battery life | 2 |
| 4.3 Operating mode | 2 |
| 4.4 Environmental conditions | 2 |
| 5 Current consumption of a watch | 2 |
| 5.1 Mean current consumed (I_m) | 2 |
| 5.2 Capacity of the battery (C) | 2 |
| 5.3 Self-discharge currents (I_{as}, I_{ad}) | 3 |
| 5.4 Current consumption of additional functions (I_f) | 3 |
| 6 Calculation of battery life | 4 |
| 6.1 Practical battery life (AP): method I | 4 |
| 6.2 Theoretical battery life (AT) | 4 |
| 7 Labelling | 4 |
| Annex A (normative) Self-discharge currents | 5 |
| Annex B (normative) Practical battery life (AP) | 6 |

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12819 was prepared by Technical Committee ISO/TC 114, *Horology*.

This second edition cancels and replaces the first edition (ISO 12819:1999), and Technical Corrigendum ISO 12819:1999/Cor.1:1999, which have been technically revised.

ISO 12819:2009
<https://standards.iteh.ai/catalog/standards/sist/c7dd3ce4-43eb-47cb-b161-7e0ea65fe40a/iso-12819-2009>

Methods of evaluation of the battery life of a battery-powered watch

1 Scope

This International Standard specifies two methods for determining the battery life of a battery-powered watch and specifies the labelling to be used by the manufacturers or the distributors to inform the users.

According to the available information, either the theoretical battery life or the practical battery life must be calculated using the equations given in this International Standard.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6426-2, *Horological vocabulary — Part 2: Technical and commercial definitions*

IEC 60086-3, *Primary batteries — Part 3: Watch batteries*

<https://standards.iteh.ai/catalog/standards/sist/c7dd3ce4-43eb-47cb-b161-7e0ea65fe40a/iso-12819-2009>

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 6426-2 and the following apply.

3.1

battery life

operating duration of a battery-powered watch, as determined by the characteristics of the battery and the movement

NOTE The battery life starts when the battery is inserted and starts powering the movement of the watch and lasts until the point when the voltage falls below the level required for operation and the watch stops.

3.2

practical battery life

AP

calculation of the battery life, taking in account the self-discharge current of the battery during storage and operation

3.3

theoretical battery life

AT

calculation of the battery life assuming an ideal battery with no self-discharge of current

4 General

4.1 Parameters

The following parameters influence the calculation:

- the type of battery used;
- the type of movement used;
- the operating and environmental conditions.

4.2 Types of battery life

This International Standard considers two types of battery life, the practical battery life and the theoretical battery life.

4.3 Operating mode

The operating mode may be normal or economic. Some watches have a device that permits the reduction of the power consumption during storage. The operating modes shall be described on the documents supplied with the watch.

4.4 Environmental conditions

The values below are valid for normal environmental conditions as follows:

- a temperature of (28 ± 2) °C;

- a relative humidity of (50 ± 10) %

ITeH STANDARD PREVIEW
(standards.iteh.ai)
ISO 12819:2009
standards.iteh.ai/catalog/standards/sist/c7dd3ce4-43eb-47cb-b161-7e0ea65fe40a/iso-12819-2009

5 Current consumption of a watch

5.1 Mean current consumed (I_m)

The mean current, I_m , is the average of currents consumed by the oscillator and the display of time of day function(s) excluding all additional functions. The mean current is expressed in microamperes (μ A).

For a movement with an analogical display, the consumption shall be measured over a large number of pulses of the motor.

For a movement with a digital display, the consumption shall be measured when a mean number of digits is operating.

5.2 Capacity of the battery (C)

The capacity of the battery used to determine the battery life of a watch shall conform to the value specified by the manufacturer of batteries and controlled by the watch manufacturer, in accordance with IEC 60086-3. The capacity, C , is expressed in milliampere hours (mAh).

5.3 Self-discharge currents (I_{as} , I_{ad})

5.3.1 Self-discharge current in storage (I_{as})

When a battery is stored, it sustains an annual loss which affects capacity. Loss of capacity depends on the type of battery and the storage temperature and humidity. It is equivalent to the mean self-discharge current in storage, I_{as} , expressed in microamperes according to Equation (1):

$$I_{as} = \frac{\Delta C_s}{8,76} \quad (1)$$

NOTE The value 8,76 is the ratio between the number of hours in the year (8 760) and the conversion rate from milliamperes to microamperes (1 000).

The value ΔC_s is usually supplied by the battery manufacturer. In the case of lack of information, the values given in Annex A shall be used. ΔC_s is expressed in milliamperere hours (mAh).

5.3.2 Self-discharge current in use (I_{ad})

When the same battery discharges, the average self-discharge current, I_{ad} , expressed in microamperes, may be different. It is determined by Equation (2):

$$I_{ad} = K \cdot I_{as} \quad (2)$$

NOTE The value K depends on the type and size of the battery as well as the operating conditions (e.g. temperature).

The value K is usually supplied by the battery manufacturer. In the case of lack of information, the values given in Annex A shall be used.

5.4 Current consumption of additional functions (I_f)

The mean current, I_f , consumed over a day by an additional function is calculated by Equation (3):

$$I_f = \frac{i_f \cdot t}{86\,400} \quad (3)$$

where

I_f is the mean current expressed in microamperes (μA);

i_f is the additional current consumption due to the function, expressed in microamperes (μA);

t is the time of use of the function in one day, expressed in seconds (s).

The usual values of t for additional functions used for the determination of I_f are those, expressed in seconds, that are usually mentioned in the user's instructions for each product. In the absence of these values, in most cases the values given in Table A.1 are conventionally selected.

NOTE The values are approximate and may change over a wide range from one user to another. They are of interest only for comparison between products.

6 Calculation of battery life

6.1 Practical battery life (AP): method I

The practical battery life, AP , expressed in years, is determined by Equation (4), based on a linear decrease of the battery capacity:

$$AP = \frac{C - (n \cdot \Delta C_s)}{8,76(I_m + I_{ad} + \sum I_f)} \quad (4)$$

where n is the storage duration of the battery, expressed in years, from its manufacture until it is placed in the watch.

For comparison between products, the watch manufacturer shall use, at his own discretion, the values $n = 1$ or $n = 0,5$.

For the battery life indication, the watch manufacturer shall take into consideration the intrinsic battery life, of which indicative values are given in B.3.

Another method of calculation for the practical battery life (method II) is described in B.4.

6.2 Theoretical battery life (AT)

The theoretical battery life, AT , expressed in years, is determined by Equation (5):

$$AT = \frac{C}{8,76(I_m + \sum I_f)} \quad (5)$$

iTech STANDARD PREVIEW
(standards.iteh.ai)
ISO 12819:2009
<https://standards.iteh.ai/catalog/standards/sist/c7dd3ce4-43eb-47cb-b161-7e0ea65fe40a/iso-12819-2009>

7 Labelling

The indication of the practical, AP , or of the theoretical, AT , battery life of a watch shall be expressed in years and, if necessary, this value shall be rounded to the half year immediately below the calculated value. However, if this value is below 2 years, it shall be expressed in months.

The following wording shall be used in the documents supplied with the watch:

“The practical (or theoretical) battery life of this watch, determined in accordance with the method specified in ISO 12819, with a (producer, capacity) battery, reference, is ... years (or months).”

Annex A (normative)

Self-discharge currents

A.1 General

The following numerical values for calculating factors ΔC_s and K (see 5.3) shall be used when information is not supplied by the battery manufacturer.

A.2 Values for ΔC_s

$\Delta C_s = 0,05C$ for silver oxide batteries;

$\Delta C_s = 0,02C$ for lithium batteries;

where C is the nominal capacity of the battery.

The factors 0,05 and 0,02 express the agreed yearly loss of capacity according to the type of battery.

A.3 Values for K

$K = 1$ for an unworn watch or one that is stored at a temperature $< 23\text{ }^\circ\text{C}$;

$K = 2$ for a worn watch, i.e. one that is subjected to temperatures between $28\text{ }^\circ\text{C}$ and $30\text{ }^\circ\text{C}$.

A.4 Daily use of the additional functions; agreed values

Table A.1 — Agreed values

| Function | Daily use t_s |
|---|-----------------|
| A) Display lighting | 20 |
| B) Alarm strike | 20 |
| C) Hour strike | 12 |
| D) Timer strike | 20 |
| E) Function strike | 12 |
| F) Chronograph | 3 600 |
| G) Calculator | 1 800 |
| H) Electronic hand-setting (alarm or time zone) | 20 |