
**Cylindrical shank twist drills — Long
series**

Forets à queue cylindrique — Série longue

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 494:2009

<https://standards.iteh.ai/catalog/standards/sist/98625980-8908-424b-92e2-f93f24b7e2a9/iso-494-2009>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 494:2009

<https://standards.iteh.ai/catalog/standards/sist/98625980-8908-424b-92e2-f93f24b7e2a9/iso-494-2009>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 494 was prepared by Technical Committee ISO/TC 29, *Small tools*, Subcommittee SC 2, *High speed steel cutting tools and their attachments*.

This second edition cancels and replaces the first edition (ISO 494:1975), of which it constitutes a minor revision. In particular, the dimensions in inches have been deleted.

ISO 494:2009

<https://standards.itech.ai/catalog/standards/sist/98625980-8908-424b-92e2-f93f24b7e2a9/iso-494-2009>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 494:2009

<https://standards.iteh.ai/catalog/standards/sist/98625980-8908-424b-92e2-f93f24b7e2a9/iso-494-2009>

Cylindrical shank twist drills — Long series

1 Scope

This International Standard specifies the dimensions of cylindrical shank twist drills, having working lengths in the long series.

The cylindrical shank jobber and stub series drills and Morse taper shank drills are given in ISO 235.


2 Dimensions

2.1 General

All dimensions and tolerances are given in millimetres.

2.2 General dimensions

The dimensions of cylindrical shank twist drills shall be in accordance with the dimensions shown in Figure 1 and given in Table 1.



Key

1 recess optional

Figure 1 — Dimensions of cylindrical shank twist drill

Table 1 — Dimensions of cylindrical shank twist drill

d_1 h8	l_1	l_2	d_1 h8	l_1	l_2	d_1 h8	l_1	l_2	d_1 h8	l_1	l_2
1,00	33	56	6,10	97	148	11,20	128	195	19,75	166	254
1,10	37	60	6,20			11,30			20,00		
1,20	41	65	6,30			11,40			20,25		
1,30			6,40			11,50			20,50		
1,40	45	70	6,50			11,60			20,75	171	261
1,50			6,60			11,70			21,00		
1,60	50	76	6,70			11,80			21,25	176	268
1,70			6,80	11,90	21,50						
1,80	53	80	6,90	12,00	21,75						
1,90			7,00	12,10	22,00						
2,00			7,10	12,20	22,25						
2,10	56	85	7,20	12,30	22,50	180	275				
2,20			7,30	12,40	22,75						
2,30	59	90	7,40	12,50	23,00						
2,40			7,50	12,60	23,25						
2,50	62	95	7,60	12,70	23,50	185	282				
2,60			7,70	12,80	23,75						
2,70	66	100	7,80	12,90	24,00						
2,80			7,90	13,00	24,25						
2,90			8,00	13,10	24,50						
3,00	69	106	8,10	13,20	24,75			190	290		
3,10			8,20	13,30	25,00						
3,20			8,30	13,40	25,25						
3,30	73	112	8,40	13,50	25,50	195	298				
3,40			8,50	13,60	25,75						
3,50			8,60	13,70	26,00						
3,60	78	119	8,70	13,80	26,25			201	307		
3,70			8,80	13,90	26,50						
3,80			8,90	14,00	26,75						
3,90	82	126	9,00	14,25	27,00			207	316		
4,00			9,10	14,50	27,25						
4,10			9,20	14,75	27,50						
4,20	87	132	9,30	15,00	27,75	214	316				
4,30			9,40	15,25	28,00						
4,40			9,50	15,50	28,25						
4,50	91	139	9,60	15,75	28,50	216	325				
4,60			9,70	16,00	28,75						
4,70			9,80	16,25	29,00						
4,80	96	146	9,90	16,50	29,25			222	334		
4,90			10,00	16,75	29,50						
5,00			10,10	17,00	29,75						
5,10	100	153	10,20	17,25	30,00			228	343		
5,20			10,30	17,50	30,25						
5,30			10,40	17,75	30,50						
5,40	104	160	10,50	18,00	30,75	234	352				
5,50			10,60	18,25	31,00						
5,60			10,70	18,50	31,25						
5,70	108	167	10,80	18,75	31,50	240	361				
5,80			10,90	19,00	31,75						
5,90			11,00	19,25	32,00						
6,00	11,10	19,50	32,25								

2.3 Lengths set out as functions of diameter steps

The lengths set out as functions of diameter steps shall be as given in Table 2.

Table 2 — Lengths set out as functions of diameter steps

Diameter ranges d_1		Corresponding lengths	
Over	Up to and including	l_1	l_2
0,95	1,06	33	56
1,06	1,18	37	60
1,18	1,32	41	65
1,32	1,50	45	70
1,50	1,70	50	76
1,70	1,90	53	80
1,90	2,12	56	85
2,12	2,36	59	90
2,36	2,65	62	95
2,65	3,00	66	100
3,00	3,35	69	106
3,35	3,75	73	112
3,75	4,25	78	119
4,25	4,75	82	126
4,75	5,30	87	132
5,30	6,00	91	139
6,00	6,70	97	148
6,70	7,50	102	156
7,50	8,50	109	165
8,50	9,50	115	175
9,50	10,60	121	184
10,60	11,80	128	195
11,80	13,20	134	205
13,20	14,00	140	214
14,00	15,00	144	220
15,00	16,00	149	227
16,00	17,00	154	235
17,00	18,00	158	241
18,00	19,00	162	247
19,00	20,00	166	254
20,00	21,20	171	261
21,20	22,40	176	268
22,40	23,60	180	275
23,60	25,00	185	282
25,00	26,50	190	290
26,50	28,00	195	298
28,00	30,00	201	307
30,00	31,50	207	316

NOTE For tolerance on lengths, lengths l_1 and l_2 may vary, within one diameter step, between the minimum and maximum limits corresponding respectively to the figures given for the nearest lower or upper step.

EXAMPLE For diameter $d_1 = 4$ mm, length l_1 may vary between 73 mm and 82 mm from the nominal value 78 mm and length l_2 may vary between 112 mm and 126 mm from the nominal value 119 mm.

3 Cutting length

The cutting length shall be at the manufacturer's discretion. Unless otherwise specified, these drills shall be right-hand cutting.

4 Shank

The cylindrical shank twist drills shall be manufactured without tenon drive.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 494:2009

<https://standards.iteh.ai/catalog/standards/sist/98625980-8908-424b-92e2-f93f24b7e2a9/iso-494-2009>

Bibliography

- [1] ISO 235, *Parallel shank jobber and stub series drills and Morse taper shank drills*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 494:2009

<https://standards.iteh.ai/catalog/standards/sist/98625980-8908-424b-92e2-f93f24b7e2a9/iso-494-2009>