
**Information technology — Conformance
testing methodology for biometric data
interchange formats defined in
ISO/IEC 19794 —**

**Part 5:
Face image data**

iTeh STANDARD PREVIEW

(standards.iteh.int)
*Technologies de l'information — Méthodologie d'essai de conformité
pour les formats d'échange de données biométriques définis dans
l'ISO/CEI 19794 —*

ISO/IEC 29109-5:2011
Partie 5: Données d'image de la face
[https://standards.iteh.int/catalog/standards/sist/22cd5e11-bd1b-451b-881d-
db5ee915400d/iso-iec-29109-5-2011](https://standards.iteh.int/catalog/standards/sist/22cd5e11-bd1b-451b-881d-db5ee915400d/iso-iec-29109-5-2011)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 29109-5:2011](https://standards.iteh.ai/catalog/standards/sist/22cd3e11-bd3b-43f3-881d-db5ee915400d/iso-iec-29109-5-2011)

<https://standards.iteh.ai/catalog/standards/sist/22cd3e11-bd3b-43f3-881d-db5ee915400d/iso-iec-29109-5-2011>



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2011

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Conformance	1
3 Normative references	2
4 Terms and definitions	2
5 Symbols and abbreviated terms	2
6 Conformance testing methodology	2
6.1 Overview	2
6.2 Table of requirements in the base standard	2
6.3 ISO/IEC 19794-5:2005 Level 1 and 2 test assertions	9
Bibliography	25

Tables**iTeh STANDARD PREVIEW****(standards.iteh.ai)**

Table 1 — Requirements of the Base Standard (ISO/IEC 19794-5:2005)	2
Table 2 — Conformance Test Assertions for ISO/IEC 19794-5:2005 Generic All Type Images	11
Table 3 — Conformance Test Assertions for ISO/IEC 19794-5:2005 Basic Type Images	15
Table 4 — Conformance Test Assertions for ISO/IEC 19794-5:2005 Full Frontal Images	18
Table 5 — Conformance Test Assertions for ISO/IEC 19794-5:2005 Token Frontal Images	21

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 29109-5 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 37, *Biometrics*.

ISO/IEC 29109 consists of the following parts, under the general title *Information technology — Conformance testing methodology for biometric data interchange formats defined in ISO/IEC 19794*:

- *Part 1: Generalized conformance testing methodology*
- *Part 2: Finger minutiae data*
- *Part 4: Finger image data*
- *Part 5: Face image data*
- *Part 6: Iris image data*
- *Part 7: Signature/sign time series data*
- *Part 8: Finger pattern skeletal data*
- *Part 9: Vascular image data*
- *Part 10: Hand geometry silhouette data*

The following part is under preparation:

- *Part 14: DNA data*

Finger pattern spectral data, signature/sign processed dynamic data, and voice data will form the subjects of future parts.

Introduction

ISO/IEC 19794-5:2005 specifies a data record interchange format for storing, recording, and transmitting one or more face images within a Common Biometric Exchange Formats Framework (CBEFF) data structure. Each image is accompanied by subject-specific and image-specific metadata contained in a header record. This part of ISO/IEC 29109 establishes tests for checking the correctness of the binary record.

The objective of ISO/IEC 19794-5:2005 cannot be completely achieved until biometric products can be tested to determine whether they conform to those specifications. Conforming implementations are a necessary prerequisite for achieving interoperability among implementations; therefore there is a need for a standardized conformance testing methodology, test assertions, and test procedures as applicable to specific modalities addressed by each part of ISO/IEC 19794. The test assertions will cover as much as practical of the ISO/IEC 19794 requirements (covering the most critical features), so that the conformity results produced by the test suites will reflect the real degree of conformity of the implementations to ISO/IEC 19794 data interchange format records. This is the motivation for the development of this conformance testing methodology.

This part of ISO/IEC 29109 supports those applications that require use of face image data according to ISO/IEC 19794-5:2005. It defines a testing methodology to assure conformance of a vendor's application or service to the base ISO/IEC 19794-5:2005 specification. Thus this part of ISO/IEC 29109 is intended to:

- establish elements of the Conformance Testing Methodology framework that are specific to the Face Image-based Data Record requirements of ISO/IEC 19794-5:2005 conformance testing,
- define requirements and guidelines for specifying conformance test suites and related test methods for measuring conformity of products and services to the Face Image-based Data Record requirements of ISO/IEC 19794-5:2005, and
- define test procedures to be followed before, during, and after conformance testing.

This part of ISO/IEC 29109 is applicable to the development and use of conformity test method specifications, conformity test suites for ISO/IEC 19794-5:2005 records, and conformance testing programs for ISO/IEC 19794-5:2005 conformant products. It is intended primarily for use by testing organizations, but can be applied by developers and users of test method specifications and test method implementations.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/IEC 29109-5:2011

<https://standards.iteh.ai/catalog/standards/sist/22cd3e11-bdf3-43f3-881d-db5ee915400d/iso-iec-29109-5-2011>

Information technology — Conformance testing methodology for biometric data interchange formats defined in ISO/IEC 19794 —

Part 5: Face image data

1 Scope

This part of ISO/IEC 29109 specifies elements of conformance testing methodology, test assertions, and test procedures as applicable to the ISO/IEC 19794-5:2005 biometric data interchange format standard for face image data.

This part of ISO/IEC 29109 establishes

- test assertions of the structure of the face image data format as specified in ISO/IEC 19794-5:2005 (Type A Level 1 as defined in ISO/IEC 29109-1:2009),
- test assertions of internal consistency by checking the types of values that can be contained within each field (Type A Level 2 as defined in ISO/IEC 29109-1:2009),
- tests of semantic assertions (Type A Level 3 as defined in ISO/IEC 29109-1:2009).

This part of ISO/IEC 29109 does not establish

- tests of conformance of CBEFF structures required by ISO/IEC 19794-5:2005,
- tests of consistency with the input biometric data record (Level 3),
- tests of conformance of the image data to the quality-related specifications of ISO/IEC 19794-5:2005,
- tests of conformance of the image data blocks to the respective JPEG or JPEG 2000 standards,
- tests of other characteristics of biometric products or other types of testing of biometric products (e.g. acceptance, performance, robustness, security),
- tests of conformance of 3D face records defined in ISO/IEC 19794-5:2005/Amd.2.

2 Conformance

Biometric data interchange format conformance tests conform to this part of ISO/IEC 29109 if they satisfy all of the normative requirements related to Clause 6. Specifically, they shall use the test methodology specified in Clauses 6, 7 and 8 of ISO/IEC 29109-1:2009, and all Level 1 and Level 2 tests shall use the assertions defined in Table 2 in this part of ISO/IEC 29109.

Implementations of ISO/IEC 19794-5:2005 tested according to the methodology specified shall be able to claim conformance only to those Biometric Data Record (BDR) requirements specified in ISO/IEC 19794-5:2005 that are tested by the test methods established by this methodology.

Implementations of ISO/IEC 19794-5:2005 do not necessarily need to conform to all possible aspects of ISO/IEC 19794-5:2005, but only to those ISO/IEC 19794-5:2005 requirements that are claimed to be

supported by the implementation in an Implementation Conformance Statement, filled out in accordance with Clause 8 of ISO/IEC 29109-1:2009 and Table 1 in this part of ISO/IEC 29109.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 19794-5:2005, *Information technology — Biometric data interchange formats — Part 5: Face image data*

ISO/IEC 29109-1:2009, *Information technology — Conformance testing methodology for biometric data interchange formats defined in ISO/IEC 19794 — Part 1: Generalized conformance testing methodology*

4 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 29109-1 apply.

5 Symbols and abbreviated terms

For the purposes of this document, the symbols and abbreviated terms given in ISO/IEC 29109-1 apply.

6 Conformance testing methodology

iTech STANDARD PREVIEW
(standards.iteh.ai)

6.1 Overview

<https://standards.iteh.ai/catalog/standards/sist/22cd3e11-bd3b-43f3-881d-325975409200/iso-iec-29109-5-2011>

The testing methodology specified in Clauses 6.7 and 8 of ISO/IEC 29109-1:2009 apply. The content of the tables below is based on the conformance testing methodology outlined in ISO/IEC 29109-1 and shall only be used in the context of that testing methodology.

6.2 Table of requirements in the base standard

The normative requirements of ISO/IEC 19794-5:2005 are listed in Table 1. The supplier of the IUT can explain which optional components of the standard are supported and the testing laboratory can note the results of the test.

Under subformat applicability the columns labelled B, F and T indicate the Basic, Full Frontal and Token Frontal image types.

Table 1 — Requirements of the Base Standard (ISO/IEC 19794-5:2005)

Requirement ID	Ref. in Base Std	Requirement Summary	Level	Status	Subformat Applicability			IUT Support	Supported Range	Test Result
					B	F	T			
R-1	5.2.1	Within the record format and all well-defined data blocks therein, all multi-byte quantities are [implied shall] stored in Big-Endian format. That is, the more significant bytes of any multi-byte quantity are stored at lower addresses in memory than less significant bytes. For example, the value 1025 (2 to the 10th power plus one) would be stored as first byte=00000100 and second byte=00000001.	1	M	Y	Y	Y			
R-2	5.2.2	Numeric Values All numeric values are fixed-length unsigned integer quantities, unless otherwise specified.	1	M	Y	Y	Y			
R-3	5.4.1	Format Identifier The (4 byte) Format Identifier shall consist of three ASCII characters "FAC" followed by a zero byte as a NULL string terminator to identify the record format as the face record format.	1	M	Y	Y	Y			

Requirement ID	Ref. in Base Std	Requirement Summary	Level	Status	Subformat Applicability			IUT Support	Supported Range	Test Result
					B	F	T			
R-4	5.4.2	Version Number The (4 byte) Version Number block shall consist of three ASCII numerals followed by a zero byte as a NULL string terminator. The first and second character will represent the major version number and the third character will represent the minor revision number. The version number of this specification shall be 0x30313000; "010" – Version 1 revision 0.	1	M	Y	Y	Y			
R-5	5.4.3	Length of Record The (4 byte) Record Length Block shall be the combined length in bytes for the record. This is the entire length of the record including the Facial Record Header and Facial Record Data.	2	M	Y	Y	Y			
R-6	5.4.4	Number of Facial Images The (2 byte) Number of Facial Images block shall be the number of facial images included in the record.	2	M	Y	Y	Y			
R-7	5.5	The Facial Information block The (20 byte) Facial Information block is intended to describe discrete properties of the individual discernable from the image, one is included for each facial image included in the record. The structure of this block is shown in [ISO/IEC 19794-5:2005] Figure 2. Zero or more Facial Feature blocks, one Image Information block, and one Image Data block follow this block.	2	M-2	Y	Y	Y			
R-8	5.5.1	Facial Record Data Length The (4 byte) Facial Record Data Length field denotes the sum of the lengths of the Facial Information block, the Feature Point block(s), the Image Information block, and the Image Data block. The minimum value of the Facial Record Data Length is 32 bytes plus the size of the Image Data block (in bytes).	2	M	Y	Y	Y			
R-9	5.5.2	Number of Feature Points The (2 byte) Number of Feature Points block shall be the number of Feature Point blocks that follow the Facial Information block. The Feature Point block is defined in [ISO/IEC 19794-5:2005] clause 5.6.	2	M	Y	Y	Y			
R-10	5.5.3	Gender The (1 byte) Gender block shall be specified in accordance with [ISO/IEC 19794-5:2005] Table 3.	1	M	Y	Y	Y			
R-11	5.5.4	Eye Colour The (1 byte) Eye Colour field shall represent the colour of irises of the eyes according to [ISO/IEC 19794-5:2005] Table 4. If the eyes are different colours, then right eye colour is to be encoded.	1	M	Y	Y	Y			
R-12	5.5.5	Hair Colour The (1 byte) Hair Colour field shall represent the colour of the hair according to the [ISO/IEC 19794-5:2005] Table 5.	1	M	Y	Y	Y			
R-13	5.5.6	Property Mask The (3 byte) Property Mask is a bit mask of 3 bytes and each bit of the mask position listed in [ISO/IEC 19794-5:2005] Table 6 shall be set to 1 if the corresponding property is present, and set to 0 if absent. The mask position starts from 0 at the lowest bit. The lowest bit set to 0 shall indicate that properties are not specified; the lowest bit set to 1 shall indicate that all listed properties have been considered and that a zero value of any property bit indicates an absence of that property. Note that a Blink flag set to "1" will indicate non-compliance with the Frontal, Full Frontal, and Token image types.	2	M	Y	Y	Y			
R-14	5.5.7	Expression The (2 byte) Expression field shall represent the expression of the face according to [ISO/IEC 19794-5:2005] Table 7.	1	M	Y	Y	Y			
R-15	5.5.8	Pose Angle The (3 multi-byte) Pose Angle field (B _y , B _p , B _r) shall represent the estimate or measure pose of the subject in the image. Each byte in the field respectively represents pose angles of yaw, pitch and roll in that order. The pose angle is given by Tait-Bryan angles. • Yaw angle: Rotation about the vertical (y) axis. • Pitch angle: Rotation about the horizontal side-to-side (x) horizontal axis. • Roll angle: Rotation about the horizontal back to front (z) axis. The angles are defined relative to the frontal view of the subject, which has angles (0,0,0) as shown in [ISO/IEC 19794-5:2005] Figure 4. The examples are shown in [ISO/IEC 19794-5:2005] Figure 5. As order of the successive rotation around the different axes does matter, the encoded rotation angle shall correspond to an order of	3C	O-1	Y	Y	Y			

Requirement ID	Ref. in Base Std	Requirement Summary	Level	Status	Subformat Applicability			IUT Support	Supported Range	Test Result
					B	F	T			
		<p>execution starting from the frontal view. This order shall be given by Roll (about the front axis), then Pitch (about the horizontal axis) and finally Yaw (about the vertical axis). The (first executed) Roll transformation will therefore always be in the image (x,y) plane.</p> <p>From the point of view of executing a transformation from the observed view to a frontal view, the transformation order will therefore be Yaw, Pitch, and then Roll. Note however that the encoded angle is from the frontal view to the observed view.</p>								
R-16	5.5.8.1	<p>Pose Angle – Yaw</p> <p>The yaw angle Y is the rotation in degrees about the y-axis (vertical axis) shown in [ISO/IEC 19794-5:2005] Figure 4. Frontal faces have a yaw angle of 0 degrees. Positive angles represent faces looking to their left (a counter-clockwise rotation around the y-axis).</p> <p>The encoding B_Y of the yaw angle Y shall be in degrees as a byte (1 byte) with values from –180 to 180 modulo 2.</p> <p>If $180 \geq Y \geq 0$ then $B_Y = Y/2 + 1$. The remainder is discarded.</p> <p>If $-180 \leq Y < 0$ then $B_Y = 181 + Y/2$. The remainder is discarded.</p> <p>The maximum value of B_Y is 181. If the pose angle is not specified, the value of B_Y shall be 0.</p>	1	M	Y	Y	Y			
R-17	5.5.8.2	<p>Pose Angle – Pitch</p> <p>The pitch angle is the rotation in degrees about the x-axis (horizontal axis) shown in [ISO/IEC 19794-5:2005] Figure 4. Frontal faces have a pitch angle of 0 degrees. Positive angles represent faces looking down (a counterclockwise rotation around the x-axis).</p> <p>The encoding B_P of the yaw angle P shall be in degrees as a byte (1 byte) with values from –180 to 180 modulo 2.</p> <ul style="list-style-type: none"> · If $180 \geq P \geq 0$ and then $B_P = P/2 + 1$. The remainder is discarded. · If $-180 \leq P < 0$ and then $B_P = 181 + P/2$. The remainder is discarded. <p>The maximum value of B_P is 181. If the pitch angle is not specified, the value of B_P shall be 0.</p>	1	M	Y	Y	Y			
R-18	5.5.8.3	<p>Pose Angle – Roll</p> <p>The roll angle is the rotation in degrees about the z-axis (the horizontal axis from front to back) shown in [ISO/IEC 19794-5:2005] Figure 4. Frontal faces have a roll angle of 0 degrees. Positive angles represent faces tilted toward their right shoulder (counter-clockwise rotation around the z-axis).</p> <p>The encoding B_R of the yaw angle R shall be in degrees as a byte (1 byte) with values from –180 to 180 modulo 2.</p> <ul style="list-style-type: none"> · If $180 \geq R \geq 0$ and then $B_R = R/2 + 1$. The remainder is discarded. · If $-180 \leq R < 0$ and then $B_R = 181 + R/2$. The remainder is discarded. <p>The maximum value of B_R is 181. If the roll angle is not specified, the value of B_R shall be 0.</p>	1	M	Y	Y	Y			
R-19	5.5.9	<p>Pose Angle Uncertainty</p> <p>The (3 multi-byte) Pose Angle Uncertainty (U_Y, U_P, U_R) represents the expected degree of accuracy of the pose angle yaw, pitch, and roll. Each byte in the field respectively represents the uncertainty of yaw, pitch and roll in that order. The uncertainty is allowed to represent experimental uncertainty specified by each vendor.</p> <p>The encoding of Pose Angle Uncertainty is given by bytes (U_Y, U_P, U_R) where each byte U_k in the field (k=Y,P,R) represents 1 degree of uncertainty with minimum and maximum values of 1 and 181 where U_k=(uncertainty+1). The more uncertain, the value of the uncertainty U_k shall become larger. If the uncertainty is not specified, then the values of U_Y, U_P and U_R shall be set to zero (0).</p>	1	M	Y	Y	Y			
R-20	5.6	<p>The Feature Point Block</p> <p>The optional (8 byte) Feature Point block specifies the type, code and position of a Feature Point in the facial image. The number of Feature Point blocks shall be specified in the Number of Feature Points field of the Facial Information Block. The structure of this block is shown in [ISO/IEC 19794-5:2005] Table 8.</p>	1	M	N	Y	Y			
R-21	5.6.1	<p>Feature Point Type</p> <p>The (1 byte) Feature Point Type field represents the type of the Feature Point stored in the Feature Point block. This field shall be set to 0x01 to denote that the position of the Feature Point is represented by the coordinate of the image. All other field values are reserved for future definition of Feature Point types.</p>	1	M	N	Y	Y			

Requirement ID	Ref. in Base Std	Requirement Summary	Level	Status	Subformat Applicability			IUT Support	Supported Range	Test Result
					B	F	T			
R-22	5.6.2	<p>Feature Point Code</p> <p>The (1 byte) Feature Point Code field shall specify the Feature Point that is stored in the Feature Point block. The codes of the Feature Points in [ISO/IEC 19794-5:2005] clause 5.6.3, taken from the MPEG4 standard and defined as MPEG4 Feature Points, or the additional eye and nostril Feature Points in [ISO/IEC 19794-5:2005] clause 5.6.4 shall be stored in this block.</p> <p>Each Feature Point code is represented by a notation A.B using a major (A) and a minor (B) value. The encoding of the Feature Point code is given by the (1 byte) value of $A*16 + B$.</p>	1	M	N	Y	Y			
R-23	5.6.3	<p>MPEG4 Feature Points</p> <p>[ISO/IEC 19794-5:2005] Figure 6 denotes the Feature Point codes associated with Feature Points as given by Annex C of ISO/IEC 14496-2</p>	3C	O-1	N	Y	Y			
R-24	5.6.4	<p>Eye and nostril centre Feature Points</p> <p>The eye centre Feature Points 12.1 (left) and 12.2 (right) are defined to be the horizontal and vertical midpoints of the eye corners (3.7, 3.11) and (3.8, 3.12) respectively. The left nostril centre Feature Point 12.3 is defined to be the midpoint of the nose Feature Points (9.1, 9.15) in the horizontal direction and (9.3,9.15) in the vertical direction. Similarly, the right nostril centre Feature Point 12.4 is defined to be the midpoint of the nose Feature Points (9.2, 9.15) in the horizontal direction and (9.3,9.15) in the vertical direction. Both the eye centre and nostril centre Feature Points are shown in [ISO/IEC 19794-5:2005] Figure 7 and values given in [ISO/IEC 19794-5:2005] Table 9.</p>	3C	O-1	N	Y	Y			
R-25	5.7	<p>The Image Information Block</p> <p>The (16 byte) Image Information block is intended to describe digital properties of the facial image, one is included for each facial image included in the record. The structure of this block is shown in [ISO/IEC 19794-5:2005] Figure 2. One Image Data block shall follow this block.</p>	2	M-2	Y	Y	Y			
R-26	5.7.1	<p>Face Image Type</p> <p>The Face Image Type field shall represent the type of the facial image stored in the Image Data Block according to [ISO/IEC 19794-5:2005] Table 10. Note that all Frontal Image Types are either Full Frontal or Token Frontal. Therefore a separate Frontal Value is not required. The Basic Face Image Type is defined in [ISO/IEC 19794-5:2005] clause 6. The Frontal, Frontal/Full and Frontal/Token Face Image Types are defined in [ISO/IEC 19794-5:2005] clauses 7, 8, and 9 respectively. Face Image Types use the notion of inheritance. For example, the Frontal Face Image Type inherits all of the requirements of the Basic Face Image Type - the Frontal Face Image type obeys all normative requirements of the Basic Face Image Type. The inheritance structure of currently defined image types is shown in [ISO/IEC 19794-5:2005] Figure 8.</p>	1	M	Y	Y	Y			
R-27	5.7.2	<p>Image Data Type</p> <p>The (1 byte) Image Data Type field denotes the encoding type of the Image Data block. Either JPEG (ISO/IEC 10918-1 and ITU-T Rec. T.81) or JPEG2000 (ISO/IEC 15444-1) shall be specified. Note that a "Unspecified" Value cannot be encoded.</p>	2	M	Y	Y	Y			
R-28	5.7.3	<p>Width</p> <p>The (2-byte) Width field shall specify the number of pixels in the horizontal direction.</p>	2	M	Y	Y	Y			
R-29	5.7.4	<p>Height</p> <p>The (2-byte) Height field shall specify the number of pixels in the vertical direction.</p>	2	M	Y	Y	Y			
R-30	5.7.5	<p>Image Colour Space</p> <p>The (1 byte) Image Colour Space field indicates the colour space used in the encoded Image Data block according to the values in [ISO/IEC 19794-5:2005] Table 12. The values of 128-255 are vendor specific. Application developers may obtain the values for these codes from the vendor.</p>	2	M	Y	Y	Y			
R-31	5.7.6	<p>Source Type</p> <p>The (1 byte) Source Type field denotes the classification of the source of the captured image and is given in [ISO/IEC 19794-5:2005] Table 13.</p>	1	M	Y	Y	Y			
R-32	5.7.7	<p>Device Type</p> <p>The (2 byte) Device Type field denotes the vendor specific capture device type ID. A value of all zeros will be acceptable and will indicate that the capture device type ID is unspecified. Application developers may obtain the values for these codes from the vendor.</p>	1	M	Y	Y	Y			

Requirement ID	Ref. in Base Std	Requirement Summary	Level	Status	Subformat Applicability			IUT Support	Supported Range	Test Result
					B	F	T			
R-33	5.7.8	Quality The (2 byte) Quality field shall be reserved for future definition to represent a quality of the facial image. This field shall be set to the value 0 indicating "unspecified".	1	M	Y	Y	Y			
R-34	5.8.1	Data structure The (variable byte) Image Data block shall be the image data encoded by either the JPEG or JPEG2000 standards.	2	M	Y	Y	Y			
Basic Face Image Type										
R-35	6.2	Image data encoding requirements for the Basic Face Image Type One of two possible encodings is to be used for all image types (Basic) 1) The JPEG Sequential baseline (ISO/IEC 10918-1) mode of operation and encoded in the JFIF file format (the JPEG file format) 2) The JPEG-2000 Part-1 Code Stream Format (ISO/IEC 15444-1) and encoded in the JP2 file format (the JPEG2000 file format).	2	M	Y	Y	Y			
R-36	6.4.1	Facial Header [for the Basic Face Image Type] The Format Identifier, Version Number, Length of Record, and Number of Faces fields shall be specified.	1	M	Y	Y	Y			
R-37	6.4.2	Facial Information [for the Basic Face Image Type] The Block Length and Number of Feature Points fields shall be specified.	1	M	Y	Y	Y			
R-38	6.4.3	Image Information [for the Basic Face Image Type] The Face Image Type field shall be specified with value 0x00.	1	M	Y	Y	Y			
R-39	6.4.3	The Image Data Type, Width, and Height fields shall be specified.	1	M	Y	Y	Y			
The Frontal Face Image Type										
R-40	7.2.2	Pose Thus, the full-face frontal pose shall be used. Rotation of the head shall be less than $\pm 5^\circ$ from frontal in pitch and yaw (see 5.5.8). Pose variations that lead to an in-plane rotation of the head can be more easily compensated by automated face recognition systems. Therefore, the rotation of the head shall be less than $\pm 8^\circ$ from frontal in roll (see 5.5.8). [ISO/IEC 19794-5:2005] Figure Cor.1.1 shows an example of $\pm 8^\circ$ rotation in roll. The best practice recommendation as outlined in A.2.2 is that the rotation of the head should be less than $\pm 5^\circ$ from frontal in roll. This constraint refers to the pose of the subject associated with the face image format data for all applications that call for this format to be used. [NOTE: This text is from ISO/IEC 19794-5:2005 TECHNICAL CORRIGENDUM 2 Published 2008-07-01]	3C	O-1	N	Y	Y			
R-41	7.2.4	Assistance in positioning the face In no cases will any other face be captured in the Frontal image. See informative annex A.2 for best practices on this topic.	3C	O-1	N	Y	Y			
R-42	7.2.5	Shoulders Shoulders shall be "square on" to the camera. "Portrait style" photographs where the subject is looking over one shoulder are not acceptable.	3C	O-1	N	Y	Y			
R-43	7.2.7	Subject and scene lighting Lighting shall be equally distributed on the face.	3C	O-1	N	Y	Y			
R-44	7.2.7	There shall be no significant direction of the light from the point of view of the photographer, as further described in [ISO/IEC 19794-5:2005] clauses 7.2.8 and 7.2.9	3C	O-1	N	Y	Y			
R-45	7.2.8	Shadows over the face The region of the face, from the crown (as defined in section 4.6) to the base of the chin, and from ear-to-ear, shall be clearly visible and free of shadows.	3C	O-1	N	Y	Y			
R-46	7.2.8	Special care shall be taken in cases when veils, scarves or headdresses cannot be removed for religious reasons to ensure these coverings do not obscure any facial features and do not generate shadow. In all other cases head coverings shall be absent .	3C	O-1	N	Y	Y			
R-47	7.2.9	Shadows in eye-sockets There shall be no dark shadows in the eye-sockets due to the brow.	3C	O-1	N	Y	Y			
R-48	7.2.9	The iris and pupil of the eyes shall be clearly visible.	3C	O-1	N	Y	Y			
R-49	7.2.10	Hot Spots Care shall be taken to avoid "hot spots" (bright areas of light shining on the face). These artefacts are typically caused when one, high intensity, focused light source is used for illumination.	3C	O-1	N	Y	Y			