



SLOVENSKI STANDARD
oSIST prEN 302 217-2 V3.2.0:2019
01-maj-2019

Fiksni radijski sistemi - Karakteristike in zahteve za opremo in antene tipa točka-točka - 2. del: Digitalni sistemi, ki delujejo v frekvenčnih pasovih od 1 GHz do 86 GHz - Harmonizirani standard za dostop do radijskega spektra

Fixed Radio Systems - Characteristics and requirements for point-to-point equipment and antennas - Part 2: Digital systems operating in frequency bands from 1 GHz to 86 GHz - Harmonised Standard for access to radio spectrum

(standards.iteh.ai)

[SIST EN 302 217-2 V3.2.2:2020](https://standards.iteh.ai/catalog/standards/sist/19ff3b9f-282d-43a2-b42a-b5bdd6fdae20/sist-en-302-217-2-v3-2-2-2020)

<https://standards.iteh.ai/catalog/standards/sist/19ff3b9f-282d-43a2-b42a-b5bdd6fdae20/sist-en-302-217-2-v3-2-2-2020>

Ta slovenski standard je istoveten z: ETSI EN 302 217-2 V3.2.0 (2019-03)

ICS:

33.060.30	Radiorelejni in fiksni satelitski komunikacijski sistemi	Radio relay and fixed satellite communications systems
33.120.40	Antene	Aerials

oSIST prEN 302 217-2 V3.2.0:2019 **en**

Draft **ETSI EN 302 217-2** V3.2.0 (2019-03)



**Fixed Radio Systems;
Characteristics and requirements for
point-to-point equipment and antennas;
Part 2: Digital systems operating in frequency bands
from 1 GHz to 86 GHz;
Harmonised Standard for access to radio spectrum**

Reference

REN/ATTM-0438

Keywords

antenna, DFRS, digital, DRRS, FWA, point-to-point, radio, regulation, transmission

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARDS PREVIEW
(standards.iteh.ai)

Important notice

SIST EN 302 217-2 V3.2.2:2020
The present document can be downloaded from:

<http://www.etsi.org/standards-search>

<https://standards.iteh.ai/catalog/standards/sist-en-302-217-2-v3-2-2-2020>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	9
Foreword.....	9
Modal verbs terminology.....	10
Introduction	10
1 Scope	11
2 References	11
2.1 Normative references	11
2.2 Informative references.....	12
3 Definition of terms, symbols and abbreviations.....	15
3.1 Terms.....	15
3.2 Symbols.....	15
3.3 Abbreviations	15
4 Technical requirements specifications	15
4.1 Framework for categorisation of system	15
4.1.0 Generality	15
4.1.1 Introduction and equipment flexibility	15
4.1.2 Operating frequency bands and channel arrangements.....	17
4.1.3 Spectral efficiency classes	17
4.1.4 System alternatives	18
4.1.5 Channel arrangements and utilization.....	18
4.1.6 Specific Requirements for frequency bands	19
4.1.7 Minimum RIC density for spectral efficiency class selection.....	20
4.1.8 Payload flexibility.....	20
4.1.9 System identification and traffic loading.....	21
4.1.10 Environmental profile	22
4.2 Transmitter requirements	22
4.2.0 General: system loading.....	22
4.2.1 Transmitter power and power environmental variation	23
4.2.1.1 Maximum power and EIRP.....	23
4.2.1.2 Combined TX power output and EIRP limits	23
4.2.1.3 Output power environmental variation.....	24
4.2.2 Transmitter power and frequency control.....	24
4.2.2.1 Power Control (ATPC and RTPC).....	24
4.2.2.1.0 General background.....	24
4.2.2.1.1 Automatic Transmit Power Control (ATPC).....	24
4.2.2.1.2 Remote Transmit Power Control (RTPC)	24
4.2.2.2 Remote Frequency Control (RFC)	24
4.2.3 Radio Frequency (RF) spectrum mask.....	25
4.2.3.1 Limits background	25
4.2.3.2 Limits	28
4.2.4 Discrete CW components exceeding the spectrum mask limit	41
4.2.4.1 Discrete CW components at the symbol rate	41
4.2.4.2 Other discrete CW components exceeding the spectrum mask limit	41
4.2.5 Unwanted emissions in the <i>spurious domain</i> - external.....	42
4.2.6 Dynamic Change of Modulation Order	43
4.2.7 Frequency tolerance	43
4.2.8 Emission limitations outside the allocated band	44
4.3 Receiver requirements	44
4.3.0 General: System loading	44
4.3.1 Unwanted emissions in the <i>spurious domain</i> - external.....	44
4.3.2 BER as a function of receiver input signal level RSL	44
4.3.3 Receiver selectivity.....	45
4.3.3.1 Introduction.....	45
4.3.3.2 Co-channel "external", first and second adjacent channel interference sensitivity	45

4.3.3.2.1	Requirements basic.....	45
4.3.3.2.2	Limits for co-channel and first adjacent channel.....	46
4.3.3.2.3	Limits for second adjacent channel interference.....	46
4.3.3.3	CW spurious interference (blocking & spurious response rejection).....	47
4.4	Antenna Characteristics.....	48
4.4.1	Integral antennas or dedicated antennas.....	48
4.4.1.1	Introduction.....	48
4.4.1.2	Radiation Pattern Envelope (Off-axis EIRP density).....	48
4.4.1.3	Antenna gain.....	48
4.4.1.4	Antenna Cross-Polar Discrimination (XPD).....	48
4.4.2	Guidelines for <i>stand-alone</i> antennas.....	48
5	Testing for compliance with technical requirements.....	49
5.1	Environmental and other conditions for testing.....	49
5.1.1	Environmental conditions.....	49
5.1.2	Other basic conditions.....	49
5.2	Test methods for the transmitter.....	50
5.2.0	General test summary.....	50
5.2.1	Transmitter power and power environmental variation.....	51
5.2.1.1	Transmitter power and EIRP.....	51
5.2.1.2	Combined TX power output and EIRP limits.....	52
5.2.1.3	Output power environmental variation.....	52
5.2.2	Transmitter power and frequency control.....	52
5.2.2.1	Transmitter Power Control (ATPC and RTPC).....	52
5.2.2.1.1	ATPC.....	52
5.2.2.1.2	RTPC.....	52
5.2.2.2	Remote Frequency Control (RFC).....	52
5.2.3	RF spectrum mask.....	53
5.2.4	Discrete CW components exceeding the spectrum mask limit.....	53
5.2.5	Unwanted emissions in the spurious domain - external.....	53
5.2.6	Dynamic Change of Modulation Order.....	53
5.2.7	Radio frequency tolerance.....	54
5.3	Test methods for the receiver.....	54
5.3.0	General test summary.....	54
5.3.1	Unwanted emissions in the spurious domain - external.....	55
5.3.2	BER as a function of receiver input signal level (RSL).....	55
5.3.3	Receiver selectivity.....	56
5.3.3.1	Void.....	56
5.3.3.2	Co-channel "external", first and second adjacent channel interference sensitivity.....	56
5.3.3.2.1	Co-channel and first adjacent channel.....	56
5.3.3.2.2	Second adjacent channel.....	56
5.3.3.3	CW spurious interference.....	56
5.4	Antenna test methods for systems with integral or dedicated antenna.....	56
5.4.0	General test summary.....	56
5.4.1	Radiation Pattern Envelope (Off-axis EIRP density).....	57
5.4.2	Antenna gain.....	57
5.4.3	Antenna Cross-Polar Discrimination (XPD).....	57
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU.....	58
Annex B (normative):	Frequency bands from 1,4 GHz to 2,6 GHz.....	60
B.1	Introduction.....	60
B.2	General characteristics.....	60
B.2.1	Frequency characteristics and channel arrangements.....	60
B.2.2	Transmission capacities.....	60
B.3	Transmitter.....	61
B.3.1	General requirements.....	61
B.3.2	RF spectrum masks options.....	62
B.4	Receiver.....	62

B.4.1	General requirements	62
B.4.2	BER as a function of receiver input signal level (RSL)	62
B.4.3	Co-channel "external" and adjacent channels interference sensitivity	63
Annex C (normative): Frequency bands from 3,5 GHz to 11 GHz (channel separation up to 30 MHz and 56/60 MHz)		65
C.1	Introduction	65
C.2	General characteristics	65
C.2.1	Frequency characteristics and channel arrangements	65
C.2.2	Transmission capacities	66
C.3	Transmitter	67
C.3.1	General requirements	67
C.3.2	RF spectrum masks	67
C.4	Receiver	67
C.4.1	General requirements	67
C.4.2	BER as a function of Receiver input Signal Level (RSL)	67
C.4.3	Co-channel "external" and adjacent channel interference sensitivity	69
Annex D (normative): Frequency bands from 4 GHz to 11 GHz (channel separation 40 MHz)		70
D.1	Introduction	70
D.2	General characteristics	70
D.2.1	Frequency characteristics and channel arrangements	70
D.2.2	Transmission capacities	70
D.3	Transmitter	71
D.3.1	General requirements	71
D.3.2	RF spectrum masks	71
D.4	Receiver	72
D.4.1	General requirements	72
D.4.2	BER as a function of Receiver input Signal Level (RSL)	72
D.4.3	Co-channel "external" and adjacent channel interference sensitivity	73
Annex E (normative): Frequency bands 13 GHz, 15 GHz and 18 GHz.....		74
E.1	Introduction	74
E.2	General characteristics	74
E.2.1	Frequency characteristics and channel arrangements	74
E.2.2	Transmission capacities	75
E.3	Transmitter	75
E.3.1	General requirements	75
E.3.2	RF spectrum masks	75
E.4	Receiver	76
E.4.1	General requirements	76
E.4.2	BER as a function of Receiver input Signal Level (RSL)	76
E.4.3	Co-channel "external" and adjacent channel interference sensitivity	79
Annex F (normative): Frequency bands from 23 GHz to 42 GHz		80
F.1	Introduction	80
F.2	General characteristics	80
F.2.1	Frequency characteristics and channel arrangements	80
F.2.2	Transmission capacities	81
F.3	Transmitter	81
F.3.1	General requirements	81
F.3.2	RF spectrum masks	82

F.4	Receiver.....	82
F.4.1	General requirements	82
F.4.2	BER as a function of Receiver input Signal Level (RSL)	82
F.4.3	Co-channel "external" and adjacent channel interference sensitivity	85
Annex G (normative): Frequency bands from 50 GHz to 55 GHz		86
G.1	Introduction	86
G.2	General characteristics	86
G.2.1	Frequency characteristics and channel arrangements	86
G.2.2	Transmission capacities.....	87
G.3	Transmitter	87
G.3.1	General requirements	87
G.3.2	RF spectrum masks	87
G.4	Receiver.....	87
G.4.1	General requirements	87
G.4.2	BER as a function of Receiver input Signal Level (RSL)	88
G.4.3	Co-channel "external" and adjacent channel interference sensitivity	88
Annex H (normative): Frequency band 57 GHz to 66 GHz		89
H.1	Introduction	89
H.2	General characteristics	89
H.2.1	Frequency characteristics and channel arrangements.....	89
H.2.2	Transmission capacities.....	89
H.3	Transmitter	90
H.3.1	General requirements	90
H.3.2	Combined TX power output and EIRP limits.....	90
H.3.2.1	Maximum power and EIRP	90
H.3.2.2	Equipment without ATPC as permanent feature	91
H.3.2.3	Equipment implementing ATPC as permanent feature.....	91
H.3.3	RF spectrum masks	94
H.3.4	Emissions outside the 57 GHz to 66 GHz range	94
H.4	Receiver.....	94
H.4.1	General requirements	94
H.4.2	BER as a function of Receiver input Signal Level (RSL)	94
H.4.3	Co-channel "external" and adjacent channel interference sensitivity	95
H.5	Minimum antenna gain.....	96
Annex I (normative): Frequency band 64 GHz to 66 GHz		97
I.1	Introduction	97
I.2	General characteristics	97
I.2.1	Frequency characteristics and channel arrangements.....	97
I.2.2	Transmission capacities.....	98
I.2.2.1	Channel arrangement based on $N \times 50$ MHz.....	98
I.2.2.2	Channel arrangement based on $N \times 30$ MHz.....	98
I.3	Transmitter	99
I.3.1	General requirements	99
I.3.2	Combined TX power and EIRP limits.....	99
I.3.2.1	Generality	99
I.3.2.2	Equipment without ATPC as permanent feature	99
I.3.2.3	Equipment implementing ATPC as permanent feature.....	100
I.3.3	RF spectrum mask	103
I.3.4	Emissions outside the 64 GHz to 66 GHz range	103
I.4	Receiver.....	103
I.4.1	General requirements	103

I.4.2	BER as a function of Receiver input Signal Level (RSL)	103
I.4.2.1	Channel arrangement based on $N \times 50$ MHz	103
I.4.2.2	Channel arrangement based on $N \times 30$ MHz	103
I.4.3	Co-channel "external" and adjacent channel interference sensitivity	104
I.4.3.1	Channel arrangement based on $N \times 50$ MHz	104
I.4.3.2	Channel arrangement based on $N \times 30$ MHz	105
I.5	Minimum antenna gain.....	105
Annex J (normative): Frequency bands from 71 GHz to 86 GHz		106
J.1	Introduction	106
J.2	General characteristics	106
J.2.1	Frequency characteristics and channel arrangements	106
J.2.2	Transmission capacities.....	107
J.3	Transmitter	108
J.3.1	General requirements	108
J.3.2	Combined maximum transmitter power and EIRP.....	108
J.3.2.1	Generality	108
J.3.2.2	Equipment without ATPC as permanent feature	108
J.3.2.3	Equipment implementing ATPC as permanent feature.....	109
J.3.3	RF spectrum masks	111
J.3.4	Emissions outside the 71 GHz to 76 GHz and 81 GHz to 86 GHz ranges	111
J.3.4.1	General requirement	111
J.3.4.2	Requirement for emissions above 86 GHz band edge	111
J.3.4.3	Conformance statement (see note).....	112
J.4	Receiver.....	113
J.4.1	General requirements	113
J.4.2	BER as a function of Receiver input Signal Level (RSL)	113
J.4.3	Co-channel "external" and adjacent channel interference sensitivity.....	115
J.5	Minimum antenna gain.....	117
Annex K:	Void	118
Annex L:	Void	119
Annex M:	Void	120
Annex N (normative):	Definition of equivalent data rates for packet data, PDH/SDH and other signals on the traffic interface.....	121
N.1	Introduction	121
N.2	General characteristics	121
N.2.1	Frequency characteristics and channel arrangements.....	121
N.2.2	Transmission capacities.....	121
N.3	System parameters.....	124
N.3.0	Introduction	124
N.3.1	Transmitter	124
N.3.2	Receiver.....	124
N.3.3	FER as a function of BER	124
Annex O (normative): Test report in relation to flexible systems applications		126
O.1	Wide radio-frequency band covering units	126
O.2	Multirate/multiple modulation format equipment.....	128
O.2.0	Introduction	128
O.2.1	Generic required tests in the test report.....	129
O.2.2	Reduced set of required tests in the test report.....	129
O.2.2.0	Introduction.....	129

O.2.2.1	Reduced transmitter tests	129
O.2.2.2	Reduced receiver tests	130
O.2.3	Bandwidth adaptive test set requirements	131
O.3	BER and C/I measurement in <i>multi-channels</i> systems (including <i>channels-aggregation</i>) when common SDH or Ethernet single/multiple-interfaces payload is provided.....	131
O.3.0	Introduction	131
O.3.1	Case 1: multi-interfaces/two-channels systems where each interface payload is transmitted on one channel only	132
O.3.2	Case 2: single interface or multi-interfaces/two-channels system where each payload interface is transmitted equally split on both channels	132
O.4	Test provisions for <i>channels-aggregation</i> equipment.....	134
O.4.1	General requirements and test method	134
O.4.2	Limits combination for <i>single-port</i> case.....	136
Annex P (informative):	Technical background for receiver selectivity and C/I interference sensitivity evaluation.....	139
P.1	Receiver selectivity	139
P.1.1	Introduction	139
P.1.2	Graphical representation of WBSEL.....	140
P.2	C/I interference sensitivity	141
P.2.1	Introduction	141
P.2.2	Ideal selectivity and best case C/I value for 2nd adjacent CS	142
Annex Q (informative):	Guidelines for using stand-alone antennas.....	145
Annex R (informative):	Test interpretation and measurement uncertainty	146
Annex S (informative):	Bibliography.....	147
Annex T (informative):	Change history	148
History		149

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Access, Terminals, Transmission and Multiplexing (ATTM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.62] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 2 of a multi-part deliverable covering Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas. Full details of the entire series can be found in ETSI EN 302 217-1 [4].

National transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Major changes with respect to previously published versions are summarized in annex T.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The ETSI EN 302 217 series has been produced in order to rationalize a large number of previous ETSI ENs dealing with equipment and antennas for Point-to-Point (P-P) Fixed Service applications. For more details, see foreword in ETSI EN 302 217-1 [4].

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 302 217-2 V3.2.2:2020](#)

<https://standards.iteh.ai/catalog/standards/sist/f9ff3b9f-282d-43a2-b42a-b5bdd6fdae20/sist-en-302-217-2-v3-2-2-2020>

1 Scope

The present document specifies technical characteristics and methods of measurements for Point-to-point (P-P) Digital Fixed Radio Systems (DFRS) operating in frequency bands allocated to Fixed Service (FS) from 1 GHz to 86 GHz, corresponding to the appropriate frequency bands from 1,4 GHz to 86 GHz as described in annex B to annex J.

Systems in the scope of the present document are generally intended to operate in full frequency division duplex (FDD) and covers also unidirectional applications. Time division duplex (TDD) applications, when possibly applicable in a specific band, are explicitly mentioned as appropriate in annex B through annex J.

The present document covers requirements to demonstrate that radio equipment both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference

NOTE: The relationship between the present document and the essential requirements of article 3.2 of Directive 2014/53/EU [i.1] is given in annex A.

2 References

2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 301 126-1 (V1.1.2) (09-1999): "Fixed Radio Systems; Conformance testing; Part 1: Point-to-point equipment - Definitions, general requirements and test procedures".
- [2] ETSI EN 301 126-3-1 (V1.1.2) (12-2002): "Fixed Radio Systems; Conformance testing; Part 3-1: Point-to-Point antennas; Definitions, general requirements and test procedures".
- [3] ETSI EN 301 390 (V1.3.1) (08-2013): "Fixed Radio Systems; Point-to-point and Multipoint Systems; Unwanted emissions in the spurious domain and receiver immunity limits at equipment/antenna port of Digital Fixed Radio Systems".
- [4] ETSI EN 302 217-1 (V3.2.0) (02-2019): "Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas; Part 1: Overview, common characteristics and system-independent requirements".
- [5] ETSI EN 302 217-4 (V2.1.1) (05-2017): "Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas; Part 4: Antennas".
- [6] Recommendation ITU-T O.151 (10-1992) / Corrigendum 1 (05-2002): "Error performance measuring equipment operating at the primary rate and above".
- [7] Recommendation ITU-T O.181 (05-2002): "Equipment to assess error performance on STM-N interfaces".
- [8] Recommendation ITU-T O.191 (02-2000): "Equipment to measure the cell transfer performance of ATM connections".
- [9] IEEE 802.3™-2012: "IEEE Standard for Ethernet".
- [10] ITU Radio Regulations (2016).

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] ETSI EG 203 336 (V1.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.3] CEPT/ERC/REC 74-01 (Cardiff 2011): "Unwanted emissions in the spurious domain".
- [i.4] CEPT/ERC/REC (01)02 (2010): "Preferred channel arrangement for digital fixed service systems operating in the frequency band 31.8 - 33.4 GHz".
- [i.5] CEPT/ERC/REC 12-02 (2007): "Harmonized radio frequency channel arrangements for analogue and digital terrestrial fixed systems operating in the band 12.75 GHz to 13.25 GHz".
- [i.6] CEPT/ERC/REC 12-03: "Harmonized radio frequency channel arrangements for digital terrestrial fixed systems operating in the band 17.7 GHz to 19.7 GHz".
- [i.7] CEPT/ERC/REC 12-05 (2007): "Harmonized radio frequency channel arrangements for digital terrestrial fixed systems operating in the band 10.0 - 10.68 GHz".
- [i.8] CEPT/ERC/REC 12-06 (2010): "Harmonized radio frequency channel arrangements for digital terrestrial fixed systems operating in the band 10.7 GHz to 11.7 GHz".
- [i.9] CEPT/ERC/REC 12-07: "Harmonized radio frequency channel arrangements for digital terrestrial fixed systems operating in the band 14.5 - 14.62 GHz paired with 15.23 - 15.35 GHz".
- [i.10] CEPT/ERC/REC 12-08: "Harmonized radio frequency channel arrangements and block allocations for low, medium and high capacity systems in the band 3600 MHz to 4200 MHz".
- [i.11] CEPT/ERC/REC 12-11 (2015): "Radio frequency channel arrangement for fixed service systems operating in the bands 48.5-50.2 GHz and 50.9-52.6 GHz".
- [i.12] CEPT/ERC/REC 12-12 (2015): "Radio frequency channel arrangement for fixed service systems operating in the band 55.78-57.0 GHz".
- [i.13] CEPT/ERC/REC 14-01 (2014): "Radio-frequency channel arrangements for high capacity analogue and digital radio-relay systems operating in the band 5925 MHz - 6425 MHz".
- [i.14] CEPT/ERC/REC 14-02 (2014): "Radio-frequency channel arrangements for medium and high capacity analogue or high capacity digital radio-relay systems operating in the band 6425 MHz - 7125 MHz".
- [i.15] CEPT/ERC/REC 14-03: "Harmonized radio frequency channel arrangements for low and medium capacity systems in the band 3400 MHz to 3600 MHz".
- [i.16] CEPT/ERC/REC T/R 12-01 (2010): "Preferred channel arrangements for fixed service systems operating in the band 37-39.5 GHz".
- [i.17] CEPT/ERC/REC T/R 13-01 (2010): "Preferred channel arrangements for fixed services systems operating in the frequency range 1-2.3 GHz".

- [i.18] CEPT/ERC/REC T/R 13-02 (2010): "Preferred channel arrangements for fixed services systems in the frequency range 22.0 - 29.5 GHz".
- [i.19] CEPT ECC/REC (01)04 (2014): "Recommended guidelines for the accommodation and assignment of Fixed Multimedia Wireless Systems (MWS) and Point-to-point (P-P) Fixed Wireless Systems in the frequency band 40.5-43.5 GHz".
- [i.20] ECC Report 198: "Adaptive modulation and ATPC operations in fixed point-to-point systems - Guideline on coordination procedures".
- [i.21] CEPT ECC/REC (02)02 (2010): "Channel arrangement for digital fixed service systems (point-to-point and point-to-multipoint) operating in the frequency band 31 - 31.3 GHz".
- [i.22] CEPT ECC/REC (02)06 (2011): "Preferred channel arrangements for digital fixed service systems operating in the frequency range 7125-8500 MHz".
- [i.23] CEPT ECC/REC (05)02 (2009): "Use of the 64 - 66 GHz frequency band for Fixed Service".
- [i.24] CEPT ECC/REC(05)07 (2013): "Radio frequency channel arrangements for fixed service systems operating in the bands 71-76 GHz and 81-86 GHz".
- [i.25] CEPT ECC/REC(09)01: "Use of the 57 - 64 GHz frequency band for point-to-point Fixed Wireless Systems".
- [i.26] CEPT ECC/REC(14)06 (2015): "Implementation of Fixed Service Point-to-Point narrow channels (3.5 MHz, 1.75 MHz, 0.5 MHz, 0.25 MHz, 0.025 MHz) in the guard bands and centre gaps of the lower 6 GHz (5925 to 6425 MHz) and upper 6 GHz (6425 to 7125 MHz) bands".
- [i.27] ETSI TR 100 028 (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.28] ETSI TR 101 506 (V2.1.1): "Fixed Radio Systems; Generic definitions, terminology and applicability of essential requirements covering article 3.2 of Directive 2014/53/EU to Fixed Radio Systems".
- [i.29] ETSI TR 101 854: "Fixed Radio Systems; Point-to-point equipment; Derivation of receiver interference parameters useful for planning fixed service point-to-point systems operating different equipment classes and/or capacities".
- [i.30] ETSI TR 102 215: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Recommended approach, and possible limits for measurement uncertainty for the measurement of radiated electromagnetic fields above 1 GHz".
- [i.31] ETSI TR 102 243-1: "Fixed Radio Systems; Representative values for transmitter power and antenna gain to support inter- and intra-compatibility and sharing analysis; Part 1: Digital point-to-point systems".
- [i.32] ETSI TR 102 565: "Fixed Radio Systems (FRS); Point-to-point systems; Requirements and bit rates of PtP Fixed Radio Systems with packet data interfaces, effects of flexible system parameters, use of mixed interfaces and implications on IP/ATM networks".
- [i.33] ETSI TR 103 103: "Fixed Radio Systems; Point-to-point systems; ATPC, RTPC, Adaptive Modulation (mixed-mode) and Bandwidth Adaptive functionalities; Technical background and impact on deployment, link design and coordination".
- [i.34] Recommendation ITU-R F.382-8: "Radio-frequency channel arrangements for fixed wireless systems operating in the 2 and 4 GHz bands".
- [i.35] Recommendation ITU-R F.383-9: "Radio-frequency channel arrangements for high capacity fixed wireless systems operating in the lower 6 GHz (5 925 to 6 425 MHz) band".
- [i.36] Recommendation ITU-R F.384-11: "Radio-frequency channel arrangements for medium and high capacity digital fixed wireless systems operating in the 6 425-7 125 MHz band".
- [i.37] Recommendation ITU-R F.385-10: "Radio-frequency channel arrangements for fixed wireless systems operating in the 7 110-7 900 MHz band".