



**IMT cellular networks;
Harmonised Standard for access to radio spectrum;
Part 23: Active Antenna System (AAS) Base Station (BS);
Release 15**

[ETSI EN 301 908-23 V15.1.1 \(2023-09\)](#)

<https://standards.iteh.ai/catalog/standards/sist/b6317d65-9632-4725-b38ad46730625630/etsi-en-301-908-23-v15-1-1-2023-09>

Reference
DEN/MSG-TFES-13-23

Keywords
3G, 3GPP, 4G, 5G, antenna, base station, cellular, digital, E-UTRA, IMT, IMT-2000, IMT-Advanced, LTE, LTE-Advanced, mobile, NR, radio, regulation, UMTS, UTRA, WCDMA

ETSI
650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:
<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:
<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2023.
All rights reserved.

Contents

Intellectual Property Rights	10
Foreword.....	10
Modal verbs terminology.....	11
Introduction	11
1 Scope	12
2 References	14
2.1 Normative references	14
2.2 Informative references.....	15
3 Definition of terms, symbols and abbreviations.....	17
3.1 Terms.....	17
3.2 Symbols	21
3.3 Abbreviations	23
4 Technical requirements specifications	24
4.1 Environmental profile.....	24
4.2 Requirement set applicability	24
4.3 Conformance requirements	25
4.3.1 Introduction.....	25
4.3.1.1 General	25
4.3.1.2 Conducted transmitter requirements	27
4.3.1.3 Conducted receiver requirements	28
4.3.1.4 Conducted requirements for BS capable of multi-band operation	28
4.3.1.5 Radiated transmitter requirements	29
4.3.1.6 Radiated receiver requirements	29
4.3.1.7 Radiated requirements for BS capable of multi-band operation	30
4.3.2 Operating Band Unwanted Emissions (OBUE).....	30
4.3.2.1 Definition and applicability.....	30
4.3.2.2 Limits	31
4.3.2.2.1 Limits for <i>MSR operation</i>	31
4.3.2.2.2 Limits for <i>single RAT E-UTRA operation</i>	47
4.3.2.3 Conformance	62
4.3.3 Spectrum Emission Mask (SEM).....	62
4.3.3.1 Definition and applicability.....	62
4.3.3.2 Limits	62
4.3.3.3 Conformance	67
4.3.4 Adjacent Channel Leakage power Ratio (ACLR)	67
4.3.4.1 Definition and applicability.....	67
4.3.4.2 Limits	68
4.3.4.2.1 General	68
4.3.4.2.2 Absolute limits	68
4.3.4.2.3 Relative limits for <i>MSR operation</i>	68
4.3.4.2.4 Relative limits for <i>single RAT UTRA FDD operation</i>	73
4.3.4.2.5 Relative limits for <i>E-UTRA operation</i>	74
4.3.4.3 Conformance	76
4.3.5 Transmitter spurious emissions.....	76
4.3.5.1 Definition and applicability.....	76
4.3.5.2 Limits	77
4.3.5.2.1 General spurious emissions limits	77
4.3.5.2.2 Limits for protection of the <i>BS receiver</i>	78
4.3.5.2.3 Limits for co-existence with other systems	79
4.3.5.2.4 Additional limits	81
4.3.5.3 Conformance	82
4.3.6 Base station maximum output power.....	82
4.3.6.1 Definition and applicability.....	82
4.3.6.2 Limits	82

4.3.6.3	Conformance	82
4.3.7	Transmit intermodulation	83
4.3.7.1	Definition and applicability.....	83
4.3.7.2	Limits	83
4.3.7.2.1	Limits for <i>MSR operation</i>	83
4.3.7.2.2	Limits for Single RAT UTRA operation.....	84
4.3.7.2.3	Limits for Single RAT E-UTRA operation	85
4.3.7.3	Conformance	86
4.3.8	Receiver spurious emissions	86
4.3.8.1	Definition and applicability.....	86
4.3.8.2	Limits	87
4.3.8.2.1	General limits	87
4.3.8.3	Conformance	87
4.3.9	Blocking.....	87
4.3.9.1	Definition and applicability.....	87
4.3.9.2	Limits	87
4.3.9.2.1	Limits for <i>MSR operation</i>	87
4.3.9.2.2	Limits for <i>single RAT UTRA operation</i>	88
4.3.9.2.3	Limits for <i>single RAT E-UTRA operation</i>	91
4.3.9.3	Conformance	94
4.3.10	Receiver intermodulation.....	94
4.3.10.1	Definition and applicability.....	94
4.3.10.2	Limits	94
4.3.10.2.1	Limits for <i>MSR operation</i>	94
4.3.10.2.2	Limits for single RAT UTRA operation.....	97
4.3.10.2.3	Limits for single RAT E-UTRA operation	98
4.3.10.3	Conformance	101
4.3.11	Adjacent Channel Selectivity (ACS), general blocking and narrowband blocking	101
4.3.11.1	Definition and applicability.....	101
4.3.11.2	Limits	102
4.3.11.2.1	Limits for <i>MSR operation</i>	102
4.3.11.2.2	Limits for <i>single RAT UTRA operation</i>	104
4.3.11.2.3	Limits for <i>single RAT E-UTRA operation</i>	104
4.3.11.3	Conformance	106
4.3.12	Reference sensitivity level	107
4.3.12.1	Definition and applicability.....	107
4.3.12.2	Limits	107
4.3.12.2.1	Limits for UTRA FDD operation	107
4.3.12.2.2	Limits for E-UTRA operation	107
4.3.12.2.3	Limits for NR operation	108
4.3.12.3	Conformance	109
4.3.13	OTA Operating Band Unwanted Emissions (OTA OBUE).....	109
4.3.13.1	Definition and applicability.....	109
4.3.13.2	Limits	109
4.3.13.2.1	Limits for <i>MSR operation</i>	109
4.3.13.2.2	Limits for <i>single RAT E-UTRA operation</i>	125
4.3.13.3	Conformance	139
4.3.14	OTA Spectrum Emission Mask (OTA SEM)	140
4.3.14.1	Definition and applicability.....	140
4.3.14.2	Limits	140
4.3.14.3	Conformance	144
4.3.15	OTA Adjacent Channel Leakage power Ratio (OTA ACLR)	145
4.3.15.1	Definition and applicability.....	145
4.3.15.2	Limits	145
4.3.15.2.1	General	145
4.3.15.2.2	Absolute limits	145
4.3.15.2.3	Relative limits.....	146
4.3.15.3	Conformance	154
4.3.16	OTA transmitter spurious emissions.....	154
4.3.16.1	Definition and applicability.....	154
4.3.16.2	Limits	155
4.3.16.2.1	General spurious emissions limits	155

4.3.16.2.2	Limits for protection of the <i>BS receiver</i>	156
4.3.16.2.3	Limits for co-existence with other systems	156
4.3.16.2.4	Additional limits	160
4.3.16.3	Conformance	160
4.3.17	Radiated transmit power	160
4.3.17.1	Definition and applicability.....	160
4.3.17.2	Limits	161
4.3.17.3	Conformance	161
4.3.18	OTA Maximum output power	161
4.3.18.1	Definition and applicability.....	161
4.3.18.2	Limits	161
4.3.18.3	Conformance	161
4.3.19	OTA transmitter intermodulation	161
4.3.19.1	Definition and applicability.....	161
4.3.19.2	Limits	162
4.3.19.2.1	Limits for <i>MSR operation</i>	162
4.3.19.2.2	Limits for single RAT UTRA operation.....	163
4.3.19.2.3	Limits for single RAT E-UTRA operation.....	164
4.3.19.3	Conformance	164
4.3.20	OTA receiver spurious emissions	164
4.3.20.1	Definition and applicability.....	164
4.3.20.2	Limits	165
4.3.20.3	Conformance	165
4.3.21	OTA blocking	165
4.3.21.1	Definition and applicability.....	165
4.3.21.2	Limits	166
4.3.21.2.1	Limits for <i>MSR operation</i>	166
4.3.21.2.2	Limits for <i>Single RAT UTRA operation</i>	166
4.3.21.2.3	Limits for <i>single RAT E-UTRA operation</i>	167
4.3.21.3	Conformance	168
4.3.22	OTA receiver intermodulation	169
4.3.22.1	Definition and applicability.....	169
4.3.22.2	Limits	169
4.3.22.2.1	https://limits for <i>MSR operation</i>	169
4.3.22.2.2	Limits for single RAT UTRA operation.....	172
4.3.22.2.3	Limits for single RAT E-UTRA operation.....	174
4.3.22.3	Conformance	178
4.3.23	OTA Adjacent Channel Selectivity (OTA ACS), general blocking and narrowband blocking	178
4.3.23.1	Definition and applicability.....	178
4.3.23.2	Limits	179
4.3.23.2.1	Limits for <i>MSR operation</i>	179
4.3.23.2.2	Limits for Single RAT UTRA FDD operation	181
4.3.23.2.3	Limits for single RAT E-UTRA operation	182
4.3.23.3	Conformance	184
4.3.24	OTA Sensitivity	184
4.3.24.1	Definition and applicability.....	184
4.3.24.2	Limits	184
4.3.24.2.1	Limits for UTRA operation	184
4.3.24.2.2	Limits for E-UTRA operation	185
4.3.24.2.3	Limits for NR operation	185
4.3.24.3	Conformance	185
4.3.25	OTA Reference sensitivity level	186
4.3.25.1	Definition and applicability.....	186
4.3.25.2	Limits	186
4.3.25.2.1	Limits for UTRA FDD operation	186
4.3.25.2.2	Limits for E-UTRA operation	186
4.3.25.2.3	Limits for NR operation	187
4.3.25.3	Conformance	188
5	Testing for compliance with technical requirements.....	188
5.1	Environmental conditions for testing	188
5.2	Interpretation of the measurement results	189

5.3	Essential radio test suites.....	189
5.3.1	Introduction.....	189
5.3.2	<i>Operating band unwanted emissions</i>	189
5.3.2.1	General.....	189
5.3.2.2	Initial conditions	189
5.3.2.3	Procedure	189
5.3.2.4	Test requirement	190
5.3.3	Spectrum Emission Mask (SEM).....	190
5.3.3.1	General.....	190
5.3.3.2	Initial conditions	190
5.3.3.3	Procedure	191
5.3.3.4	Test requirement	191
5.3.4	Adjacent Channel Leakage power Ratio (ACLR)	191
5.3.4.1	General.....	191
5.3.4.2	Initial conditions	191
5.3.4.2.1	General test conditions	191
5.3.4.2.2	MSR	192
5.3.4.2.3	UTRA FDD	192
5.3.4.2.4	E-UTRA	192
5.3.4.3	Procedure	192
5.3.4.3.1	General procedure	192
5.3.4.3.2	MSR	192
5.3.4.3.3	UTRA FDD	193
5.3.4.3.4	E-UTRA	193
5.3.5	Transmitter spurious emissions.....	193
5.3.5.1	General.....	193
5.3.5.2	Initial conditions	194
5.3.5.3	Procedure	194
5.3.5.4	Test requirement	195
5.3.6	Base station output power.....	195
5.3.6.1	General.....	195
5.3.6.2	Initial conditions	195
5.3.6.3	Procedure	195
5.3.6.4	<i>ETSI EN 301 908-23 V15.1.1 (2023-09)</i> h Test requirement	195
5.3.7	Transmit intermodulation	196
5.3.7.1	General.....	196
5.3.7.2	Initial conditions	196
5.3.7.3	Procedure	196
5.3.7.3.1	Procedure for co-location requirement	196
5.3.7.3.2	Procedure for intra-system requirement	198
5.3.7.4	Test requirement	199
5.3.8	Receiver spurious emissions.....	199
5.3.8.1	General.....	199
5.3.8.2	Initial conditions	199
5.3.8.3	Procedure	199
5.3.8.4	Test requirement	199
5.3.9	Blocking.....	200
5.3.9.1	General.....	200
5.3.9.2	Initial conditions	200
5.3.9.3	Procedure	200
5.3.9.3.1	General procedure	200
5.3.9.3.2	<i>MSR operation</i>	200
5.3.9.3.3	Single RAT UTRA FDD operation	201
5.3.9.3.4	<i>Single RAT E-UTRA operation</i>	201
5.3.9.4	Test requirement	201
5.3.10	Receiver intermodulation characteristics	202
5.3.10.1	General.....	202
5.3.10.2	Initial conditions	202
5.3.10.3	Procedure	202
5.3.10.3.1	General procedure	202
5.3.10.3.2	MSR procedure.....	202
5.3.10.3.3	Procedure for single RAT UTRA FDD operation	203

5.3.10.3.4	Procedure for <i>single RAT E-UTRA operation</i>	203
5.3.10.4	Test requirement	203
5.3.11	Adjacent Channel Selectivity (ACS), general blocking and narrowband blocking	203
5.3.11.1	General.....	203
5.3.11.2	Initial conditions	203
5.3.11.3	Procedure	204
5.3.11.3.1	General procedure	204
5.3.11.3.2	<i>MSR operation</i>	204
5.3.11.3.3	Single RAT UTRA FDD operation	205
5.3.11.3.4	<i>Single RAT E-UTRA operation</i>	205
5.3.11.4	Test requirement	206
5.3.12	Reference sensitivity level	206
5.3.12.1	General.....	206
5.3.12.2	Initial conditions	206
5.3.12.3	Procedure	206
5.3.12.4	Test requirement	206
5.3.13	OTA operating band unwanted emissions	207
5.3.13.1	General.....	207
5.3.13.2	Initial conditions	207
5.3.13.3	Procedure	207
5.3.13.4	Test requirement	208
5.3.14	OTA Spectrum Emission Mask (OTA SEM)	208
5.3.14.1	General.....	208
5.3.14.2	Initial conditions	208
5.3.14.3	Procedure	208
5.3.14.4	Test requirement	209
5.3.15	OTA Adjacent Channel Leakage power Ratio (OTA ACLR)	209
5.3.15.1	General.....	209
5.3.15.2	Initial conditions	209
5.3.15.2.1	General test conditions	209
5.3.15.2.2	<i>MSR</i>	210
5.3.15.2.3	UTRA FDD	210
5.3.15.2.4	E-UTRA	210
5.3.15.2.5	https://standards.itieh.ai/catalog/standards/sist/b631/d65-9632-4725-h38a-	210
5.3.15.3	Procedure https://standards.itieh.ai/catalog/standards/sist/b631/d65-9632-4725-h38a-	210
5.3.15.3.1	General procedure	210
5.3.15.3.2	<i>MSR</i>	211
5.3.15.3.3	UTRA FDD	211
5.3.15.3.4	E-UTRA	211
5.3.15.4	Test requirement	212
5.3.16	OTA transmitter spurious emissions.....	212
5.3.16.1	General.....	212
5.3.16.2	General spurious emissions.....	212
5.3.16.2.1	General	212
5.3.16.2.2	Initial conditions.....	212
5.3.16.2.3	Procedure.....	213
5.3.16.2.4	Test requirement.....	214
5.3.16.3	Protection of the <i>BS receiver</i>	214
5.3.16.3.1	General	214
5.3.16.3.2	Initial conditions.....	214
5.3.16.3.3	Procedure.....	214
5.3.16.3.4	Test requirement.....	215
5.3.16.4	Co-existence with other systems.....	215
5.3.16.4.1	General	215
5.3.16.4.2	Initial conditions.....	215
5.3.16.4.3	Procedure.....	216
5.3.16.4.4	Test requirement.....	217
5.3.17	Radiated transmit power	217
5.3.17.1	General	217
5.3.17.2	Initial conditions	217
5.3.17.3	Procedure	217
5.3.17.4	Test requirement	218

5.3.18	OTA Maximum output power	218
5.3.18.1	General	218
5.3.18.2	Initial conditions	218
5.3.18.3	Procedure	218
5.3.18.4	Test requirement	219
5.3.19	OTA transmitter intermodulation	219
5.3.19.1	General	219
5.3.19.2	Initial conditions	219
5.3.19.3	Procedure	220
5.3.19.4	Test requirement	222
5.3.20	OTA receiver spurious emissions	222
5.3.20.1	General	222
5.3.20.2	Initial conditions	222
5.3.20.3	Procedure	222
5.3.20.4	Test requirement	223
5.3.21	OTA blocking	223
5.3.21.1	General	223
5.3.21.2	Initial conditions	223
5.3.21.3	Procedure	224
5.3.21.3.1	General procedure	224
5.3.21.3.2	<i>MSR operation</i>	224
5.3.21.3.3	Single RAT UTRA FDD operation	224
5.3.21.3.4	<i>Single RAT E-UTRA operation</i>	225
5.3.21.4	Test requirement	225
5.3.22	OTA receiver intermodulation	225
5.3.22.1	General	225
5.3.22.2	Initial conditions	226
5.3.22.3	Procedure	226
5.3.22.3.1	General procedure	226
5.3.22.3.2	<i>MSR operation</i>	226
5.3.22.3.3	Single RAT UTRA FDD operation	227
5.3.22.3.4	<i>Single RAT E-UTRA operation</i>	227
5.3.22.4	Test requirement	227
5.3.23	OTA Adjacent Channel Selectivity (OTA ACS)	227
5.3.23.1	General	227
5.3.23.2	Initial conditions	228
5.3.23.3	Procedure	228
5.3.23.3.1	General procedure	228
5.3.23.3.2	<i>MSR operation</i>	228
5.3.23.3.3	Single RAT UTRA FDD operation	229
5.3.23.3.4	<i>Single RAT E-UTRA operation</i>	229
5.3.23.4	Test requirement	230
5.3.24	OTA sensitivity	230
5.3.24.1	General	230
5.3.24.2	Initial conditions	230
5.3.24.3	Procedure	231
5.3.24.4	Test requirement	231
5.3.25	OTA reference sensitivity level	231
5.3.25.1	General	231
5.3.25.2	Initial conditions	231
5.3.25.3	Procedure	232
5.3.25.4	Test requirement	232
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	233
Annex B (informative):	Maximum Measurement Uncertainty	235
Annex C (normative):	Base Station configurations for conducted testing	238
C.1	Transmit configurations	238
C.2	Receive configurations	238

C.3	Power supply options	239
C.4	BS with integrated Iuant BS modem.....	239
Annex D (normative):	Base Station configurations for radiated testing.....	240
D.1	Transmit configurations	240
D.2	Receive configurations	241
D.3	Power supply options	242
D.4	BS with integrated Iuant BS modem.....	242
Annex E (informative):	Checklist	243
Annex F (informative):	Bibliography	244
Annex G (informative):	Change history	245
History		246

i T h A N D A R D P R E (s t a n d a r d s . i t)

h t t p s : / / s t a n d a r d s . i t e h . a
d 4 6 7 3 0 6 2 5 6 3 0 / e t s i - e i

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the **GSM** logo are trademarks registered and owned by the **GSM Association**.

Foreword

(standards.iteh.ai)

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG). https://standards.iteh.ai/catalog/standards/sist/b6317d65-9632-4725-b38a-446730625630/etsi_en_301_908_23_v15_1_1_2023_09

For non-EU countries the present document may be used for regulatory (Type Approval) purposes.

The present document has been prepared under Commission's standardisation request C(2015) 5376 final [i.1] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document is part 23 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.6].

National transposition dates	
Date of adoption of this EN:	4 September 2023
Date of latest announcement of this EN (doa):	31 December 2023
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2024
Date of withdrawal of any conflicting National Standard (dow):	30 June 2025

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document is part of a set of standards developed by ETSI that are designed to fit in a modular structure to cover radio equipment within the scope of the Radio Equipment Directive [i.2]. The present document is produced following the guidance in ETSI EG 203 336 [i.3] as applicable.

i T h A N D A R D P R E
(s t a n d a r d s . i t)

h t t p s : / / s t a n d a r d s . i t e h . a
d 4 6 7 3 0 6 2 5 6 3 0 / e t s i - e i
E T S I E N 3 0 1 9 0 8 - 2

1 Scope

The present document specifies technical characteristics and methods of measurements for types of radio equipment:

- AAS BS supporting Single-RAT UTRA FDD.
- AAS BS supporting Single-RAT E-UTRA.
- AAS BS supporting Multi-Standard Radio (UTRA-FDD, E-UTRA, NR).

In the present document, the term "requirements for single RAT operation" refers to requirements that are derived from the ETSI TS 125 141 [7] or ETSI TS 136 141 [11] specifications baseline. The term "requirements for MSR operation" refers to requirements derived from the ETSI TS 137 141 [6] specification baseline (including NR operation as part of MSR).

These radio equipment types are capable of operating in whole or any part of the frequency band(s) given in table 1-1.

Table 1-1: AAS BS operating bands

Band designation for operation as:		Band Category	Direction of transmission	AAS BS operating bands	Relevant EC/ECC decision
Single-RAT E-UTRA or MSR (note 1)	Single-RAT UTRA				
1	I	BC1	Transmit	2 110 MHz to 2 170 MHz	[i.20] and [i.21]
			Receive	1 920 MHz to 1 980 MHz	
3	III	BC2	Transmit	1 805 MHz to 1 880 MHz	[i.18] and [i.19]
			Receive	1 710 MHz to 1 785 MHz	
7	VII	BC1	Transmit	2 620 MHz to 2 690 MHz	[i.23] and [i.24]
			Receive	2 500 MHz to 2 570 MHz	
8	VIII	BC2	Transmit	925 MHz to 960 MHz	[i.18] and [i.19]
			Receive	880 MHz to 915 MHz	
20	XX	BC1	Transmit	791 MHz to 821 MHz	[i.13] and [i.14]
			Receive	832 MHz to 862 MHz	
22	XXII	BC1	Transmit	3 510 MHz to 3 590 MHz	[i.8] and [i.25]
			Receive	3 410 MHz to 3 490 MHz	
28	NA	BC1 (notes 2 and 3)	Transmit	758 MHz to 803 MHz	[i.11] and [i.12]
			Receive	703 MHz to 748 MHz	
31	NA	BC1 (note 2)	Transmit	462,5 MHz to 467,5 MHz	[i.10]
			Receive	452,5 MHz to 457,5 MHz	
32	XXXII	BC1 (note 7)	Transmit	1 452 MHz to 1 496 MHz	[i.15] and [i.16]
			Receive	N/A	
33	NA	BC3	Transmit and Receive	1 900 MHz to 1 920 MHz	[i.19]
34	NA	BC3	Transmit and Receive	2 010 MHz to 2 025 MHz	[i.19]
38	NA	BC3	Transmit and Receive	2 570 MHz to 2 620 MHz	[i.23] and [i.24]
40	NA	BC3	Transmit and Receive	2 300 MHz to 2 400 MHz	[i.22]
41	NA	BC3 (note 4)	Transmit and Receive	2 496 MHz to 2 690 MHz	[i.23] and [i.24]
42	NA	BC3	Transmit and Receive	3 400 MHz to 3 600 MHz	[i.8] and [i.25]
43	NA	BC3	Transmit and Receive	3 600 MHz to 3 800 MHz	[i.8] and [i.25]
50	NA	BC3 (note 7)	Transmit and Receive	1 432 MHz to 1 517 MHz	[i.15], [i.16] and [i.17]
51	NA	BC3 (note 7)	Transmit and Receive	1 427 MHz to 1 432 MHz	[i.15] and [i.16]
65	NA	BC1 (notes 2 and 8)	Transmit	2 110 MHz to 2 200 MHz	[i.20], [i.21] and [i.26]
			Receive	1 920 MHz to 2 010 MHz	

Band designation for operation as:		Band Category	Direction of transmission	AAS BS <i>operating bands</i>	Relevant EC/ECC decision
Single-RAT E-UTRA or MSR (note 1)	Single-RAT UTRA				
67	NA	BC1 (notes 2 and 7)	Transmit	738 MHz to 758 MHz	[i.11] and [i.12]
			Receive	N/A	
68	NA	BC1 (note 10)	Transmit	753 MHz to 783 MHz	[i.11] and [i.12]
			Receive	698 MHz to 728 MHz	
69	NA	BC1 (notes 2 and 7)	Transmit	2 570 MHz to 2 620 MHz	[i.23] and [i.24]
			Receive	N/A	
72	NA	BC1 (note 2)	Transmit	461 MHz to 466 MHz	[i.10]
			Receive	451 MHz to 456 MHz	
75	NA	BC1 (notes 2 and 7)	Transmit	1 432 MHz to 1 517 MHz	[i.15], [i.16] and [i.17]
			Receive	N/A	
76	NA	BC1 (notes 2 and 7)	Transmit	1 427 MHz to 1 432 MHz	[i.15] and [i.16]
			Receive	N/A	
77	NA	BC3 (notes 5 and 9)	Transmit and Receive	3 300 MHz to 4 200 MHz	[i.8] and [i.25]
78	NA	BC3 (notes 6 and 9)	Transmit and Receive	3 300 MHz to 3 800 MHz	[i.8] and [i.25]
87	NA	BC1 (note 10)	Transmit	420 MHz to 425 MHz	[i.10]
			Receive	410 MHz to 415 MHz	
88	NA	BC1 (note 10)	Transmit	422 MHz to 427 MHz	[i.10]
			Receive	412 MHz to 417 MHz	

NOTE 1: The band designations given are the MSR BS band designations. The relation between the band designations for MSR BS and the designations for NR, E-UTRA and UTRA are given in table 4.4-1 of ETSI TS 137 141 [6].

NOTE 2: The band is for NR and/or E-UTRA only.

NOTE 3: In Europe, according to [i.13] and [i.14], radio equipment in band 28 operates between 758 MHz and 791 MHz for the transmitter ($F_{DL_low} = 758$ MHz and $F_{DL_high} = 791$ MHz) and between 703 MHz and 736 MHz for the receiver ($F_{UL_low} = 703$ MHz and $F_{UL_high} = 736$ MHz).

NOTE 4: In Europe according to [i.22] and [i.23], radio equipment in band 41 operates between 2 570 MHz and 2 620 MHz ($F_{DL_low} = 2 570$ MHz and $F_{DL_high} = 2 620$ MHz).

NOTE 5: In Europe, according to [i.24] and [i.8], radio equipment in band n77 operates between 3 400 MHz and 3 800 MHz ($F_{DL_low} = 3 400$ MHz and $F_{DL_high} = 3 800$ MHz).

NOTE 6: In Europe, according to [i.24] and [i.8], radio equipment in band n78 operates between 3 400 MHz and 3 800 MHz ($F_{DL_low} = 3 400$ MHz and $F_{DL_high} = 3 800$ MHz).

NOTE 7: Radio equipment in bands 32, 50, 51, 67, 69, 75 and 76 only operates in transmit mode (downlink only). Only transmitter requirements are applicable.

NOTE 8: This band includes two frequency ranges that are harmonised in Europe:

- (a) According to [i.21] and [i.22], radio equipment in band n65 operates between 2 110 MHz and 2 170 MHz for the transmitter ($F_{DL_low} = 2 110$ MHz and $F_{DL_high} = 2 170$ MHz), and between 1 920 MHz and 1 980 MHz for the receiver ($F_{UL_low} = 1 920$ MHz and $F_{UL_high} = 1 980$ MHz).
- (b) Based on [i.26], radio equipment in band n65 operates between 2 170 MHz and 2 200 MHz for the transmitter ($F_{DL_low} = 2 170$ MHz and $F_{DL_high} = 2 200$ MHz) and between 1 980 MHz and 2 010 MHz for the receiver ($F_{UL_low} = 1 980$ MHz and $F_{UL_high} = 2 010$ MHz) as the Complementary Ground Component (CGC) of a Mobile-satellite service by reference to the present document.

NOTE 9: The band is for NR only.

NOTE 10: The band is for E-UTRA only.

NOTE 1: For BS capable of multi-band operation, the supported *operating bands* may belong to different Band Categories.

NOTE 2: AAS BS does not support GSM/EDGE, but BC2 is still applicable for protection of/against GSM/EDGE operation in BC2 *operating bands*.

NOTE 3: AAS BS does not support Narrow-Band Internet of Things (NB-IoT) in band, NB-IoT guard band, or standalone NB-IoT operation, but NB-IoT limits are still applicable for AAS BS protection of/against NB-IoT operation in *operating bands*.

NOTE 4: AAS BS does not support band 46 operation, but band 46 limits are still applicable for AAS BS protection of/against devices operating in band 46.

NOTE 5: The band categories for BS are defined in clause 4.4 of ETSI TS 137 141 [6] and are listed in table 1-1.

AAS BS supports *carrier aggregation* as defined in tables 4.2.1-3 to 4.2.1-6 in ETSI EN 301 908-14 [5], or tables 4.2.1-2 to 4.2.1-7 in ETSI EN 301 908-18 [4], except for the CA combinations involving band 46.

The present document covers conducted and radiated requirements for AAS BS capable of single-RAT UTRA, single-RAT E-UTRA and MSR multi-RAT operation (UTRA, E-UTRA, NR) in 3GPP™ Release 15. Additionally, it includes for selected AAS BS *operating bands* from 3GPP Release 16.

NOTE 6: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.2] is given in annex A.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] [ETSI TS 137 105 \(V15.18.0\) \(04-2023\)](#): "Universal Mobile Telecommunications System (UMTS); LTE; 5G; Active Antenna System (AAS) Base Station (BS) transmission and reception (3GPP TS 37.105 version 15.18.0 Release 15)".
- [2] [ETSI TS 137 145-1 \(V15.14.0\) \(07-2022\)](#): "Universal Mobile Telecommunications System (UMTS); LTE; 5G; Active Antenna System (AAS) Base Station (BS) conformance testing; Part 1: conducted conformance testing (3GPP TS 37.145-1 version 15.14.0 Release 15)".
- [3] [ETSI TS 137 145-2 \(V15.15.0\) \(07-2022\)](#): "Universal Mobile Telecommunications System (UMTS); LTE; 5G; Active Antenna System (AAS) Base Station (BS) conformance testing; Part 2: radiated conformance testing (3GPP TS 37.145-2 version 15.15.0 Release 15)".
- [4] [ETSI EN 301 908-18 \(V15.1.1\) \(09-2021\)](#): "IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 18: E-UTRA, UTRA and GSM/EDGE Multi-Standard Radio (MSR) Base Station (BS) Release 15".
- [5] [ETSI EN 301 908-14 \(V15.1.1\) \(09-2021\)](#): "IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 14: Evolved Universal Terrestrial Radio Access (E-UTRA) Base Stations (BS) Release 15".
- [6] [ETSI TS 137 141 \(V15.20.0\) \(01-2023\)](#): "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE; 5G; NR, E-UTRA, UTRA and GSM/EDGE; Multi-Standard Radio (MSR) Base Station (BS) conformance testing (3GPP TS 37.141 version 15.20.0 Release 15)".
- [7] [ETSI TS 125 141 \(V15.4.0\) \(04-2019\)](#): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) conformance testing (FDD) (3GPP TS 25.141 version 15.4.0 Release 15)".
- [8] [ETSI TS 145 004 \(V15.0.0\) \(07-2018\)](#): "Digital cellular telecommunications system (Phase 2+) (GSM); GSM/ EDGE Modulation (3GPP TS 45.004 version 15.0.0 Release 15)".
- [9] [ETSI TS 136 104 \(V15.15.0\) \(04-2022\)](#): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception (3GPP TS 36.104 version 15.15.0 Release 15)".

- [10] [ETSI TS 125 104 \(V15.5.0\) \(04-2019\)](#): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) radio transmission and reception (FDD) (3GPP TS 25.104 version 15.5.0 Release 15)".
- [11] [ETSI TS 136 141 \(V15.18.0\) \(04-2023\)](#): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) conformance testing (3GPP TS 36.141 version 15.18.0 Release 15)".
- [12] [ETSI TS 138 141-1 \(V15.14.0\) \(01-2023\)](#): "5G; NR; Base Station (BS) conformance testing Part 1: Conducted conformance testing (3GPP TS 38.141-1 version 15.14.0 Release 15)".
- [13] [ETSI TS 138 104 \(V15.18.0\) \(10-2022\)](#): "5G; NR; Base Station (BS) radio transmission and reception (3GPP TS 38.104 version 15.18.0 Release 15)".
- [14] [ETSI EN 301 908-24 \(V15.1.1\) \(09-2023\)](#): "IMT cellular networks; Harmonised Standard for access to radio spectrum Part 24: New Radio (NR) Base Stations (BS); Release 15".
- [15] [ETSI TS 138 141-2 \(V15.17.0\) \(05-2023\)](#): "5G; NR; Base Station (BS) conformance testing Part 2: Radiated conformance testing (3GPP TS 38.141-2 version 15.17.0 Release 15)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] [Commission implementing decision C\(2015\) 5376 final of 4.8.2015](#) on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.2] [Directive 2014/53/EU](#) of the European parliament and of the council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.3] ETSI EG 203 336 (V1.2.1) (05-2020): "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.4] Recommendation ITU-R SM.329-12 (09-2012): "Unwanted emissions in the spurious domain".
- [i.5] ETSI TR 100 028 (parts 1 and 2) (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.6] ETSI EN 301 908-1 (V15.1.1) (09-2021): "IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 1: Introduction and common requirements Release 15".
- [i.7] ETSI TR 103 877: "Task Force for European Standards for IMT-2000 (MSG); Technical Parameter selection in ETSI EN 301 908 Base Station (BS) Harmonised Standards".
- [i.8] [Commission implementing Decision \(EU\) 2019/235 of 24 January 2019](#) on amending Decision 2008/411/EC as regards an update of relevant technical conditions applicable to the 3400-3800 MHz frequency band.
- [i.9] ETSI TS 103 807 (V1.1.1) (10-2021): "Mobile Standards Group (MSG); IMT Cellular Networks Base Stations (BS) Additional Regulatory Requirements".