



**IMT cellular networks;  
Harmonised Standard for access to radio spectrum;  
Part 23: Active Antenna System (AAS) Base Station (BS);  
Release 15**

[ETSI EN 301 908-23 V15.0.0 \(2022-12\)](#)

<https://standards.iteh.ai/catalog/standards/sist/b6317d65-9632-4725-b38ad46730625630/etsi-en-301-908-23-v15-0-0-2022-12>

---

**Reference**DEN/MSG-TFES-13-23

---

**Keywords**3G, 3GPP, 4G, 5G, antenna, base station, cellular,  
digital, E-UTRA, IMT, IMT-2000, IMT-Advanced,  
LTE, LTE-Advanced, mobile, NR, radio, regulation,  
UMTS, UTRA, WCDMA

---

**ETSI**650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at  
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our  
Coordinated Vulnerability Disclosure Program:  
<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.  
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.  
The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.  
All rights reserved.

# Contents

Intellectual Property Rights .....	10
Foreword.....	10
Modal verbs terminology.....	11
Introduction .....	11
1    Scope .....	12
2    References .....	14
2.1    Normative references .....	14
2.2    Informative references.....	15
3    Definition of terms, symbols and abbreviations.....	17
3.1    Terms.....	17
3.2    Symbols.....	21
3.3    Abbreviations .....	23
4    Technical requirements specifications .....	24
4.1    Environmental profile.....	24
4.2    Requirement set applicability .....	24
4.3    Conformance requirements .....	25
4.3.1    Introduction.....	25
4.3.1.1    General .....	25
4.3.1.2    Conducted transmitter requirements .....	28
4.3.1.3    Conducted receiver requirements .....	28
4.3.1.4    Conducted requirements for BS capable of multi-band operation .....	29
4.3.1.5    Radiated transmitter requirements .....	29
4.3.1.6    Radiated receiver requirements.....	30
4.3.1.7    Radiated requirements for BS capable of multi-band operation .....	30
4.3.2    Operating Band Unwanted Emissions (OBUE).....	31
4.3.2.1    Definition and applicability.....	31
4.3.2.2    Limits .....	31
4.3.2.2.1    Limits for <i>MSR operation</i> .....	31
4.3.2.2.2    Limits for <i>single RAT E-UTRA operation</i> .....	46
4.3.2.3    Conformance .....	60
4.3.3    Spectrum Emission Mask (SEM).....	60
4.3.3.1    Definition and applicability.....	60
4.3.3.2    Limits .....	61
4.3.3.3    Conformance .....	66
4.3.4    Adjacent Channel Leakage power Ratio (ACLR) .....	66
4.3.4.1    Definition and applicability.....	66
4.3.4.2    Limits .....	66
4.3.4.2.1    General .....	66
4.3.4.2.2    Absolute limits .....	66
4.3.4.2.3    Relative limits for <i>MSR operation</i> .....	67
4.3.4.2.4    Relative limits for <i>single RAT UTRA FDD operation</i> .....	72
4.3.4.2.5    Relative limits for <i>E-UTRA operation</i> .....	73
4.3.4.3    Conformance .....	75
4.3.5    Transmitter spurious emissions.....	75
4.3.5.1    Definition and applicability.....	75
4.3.5.2    Limits .....	76
4.3.5.2.1    General spurious emissions limits .....	76
4.3.5.2.2    Limits for protection of the <i>BS receiver</i> .....	77
4.3.5.2.3    Limits for co-existence with other systems .....	77
4.3.5.2.4    Additional limits .....	80
4.3.5.3    Conformance .....	80
4.3.6    Base station maximum output power.....	80
4.3.6.1    Definition and applicability.....	80
4.3.6.2    Limits .....	80

4.3.6.3	Conformance .....	81
4.3.7	Transmit intermodulation .....	81
4.3.7.1	Definition and applicability.....	81
4.3.7.2	Limits .....	81
4.3.7.2.1	Limits for <i>MSR operation</i> .....	81
4.3.7.2.2	Limits for Single RAT UTRA operation.....	83
4.3.7.2.3	Limits for Single RAT E-UTRA operation .....	84
4.3.7.3	Conformance .....	84
4.3.8	Receiver spurious emissions .....	85
4.3.8.1	Definition and applicability.....	85
4.3.8.2	Limits .....	85
4.3.8.2.1	General limits .....	85
4.3.8.3	Conformance .....	86
4.3.9	Blocking.....	86
4.3.9.1	Definition and applicability.....	86
4.3.9.2	Limits .....	86
4.3.9.2.1	Limits for <i>MSR operation</i> .....	86
4.3.9.2.2	Limits for <i>single RAT UTRA operation</i> .....	87
4.3.9.2.3	Limits for <i>single RAT E-UTRA operation</i> .....	90
4.3.9.3	Conformance .....	92
4.3.10	Receiver intermodulation.....	92
4.3.10.1	Definition and applicability.....	92
4.3.10.2	Limits .....	92
4.3.10.2.1	Limits for <i>MSR operation</i> .....	92
4.3.10.2.2	Limits for single RAT UTRA operation.....	96
4.3.10.2.3	Limits for single RAT E-UTRA operation .....	96
4.3.10.3	Conformance .....	100
4.3.11	Adjacent Channel Selectivity (ACS), general blocking and narrowband blocking .....	100
4.3.11.1	Definition and applicability.....	100
4.3.11.2	Limits .....	101
4.3.11.2.1	Limits for <i>MSR operation</i> .....	101
4.3.11.2.2	Limits for <i>single RAT UTRA operation</i> .....	103
4.3.11.2.3	Limits for <i>single RAT E-UTRA operation</i> .....	104
4.3.11.3	Conformance .....	106
4.3.12	Reference sensitivity level .....	106
4.3.12.1	Definition and applicability.....	106
4.3.12.2	Limits .....	106
4.3.12.2.1	Limits for UTRA FDD operation .....	106
4.3.12.2.2	Limits for E-UTRA operation .....	107
4.3.12.2.3	Limits for NR operation .....	108
4.3.12.3	Conformance .....	109
4.3.13	OTA Operating Band Unwanted Emissions (OTA OBUE).....	109
4.3.13.1	Definition and applicability.....	109
4.3.13.2	Limits .....	109
4.3.13.2.1	Limits for <i>MSR operation</i> .....	109
4.3.13.2.2	Limits for <i>single RAT E-UTRA operation</i> .....	125
4.3.13.3	Conformance .....	139
4.3.14	OTA Spectrum Emission Mask (OTA SEM) .....	139
4.3.14.1	Definition and applicability.....	139
4.3.14.2	Limits .....	139
4.3.14.3	Conformance .....	143
4.3.15	OTA Adjacent Channel Leakage power Ratio (OTA ACLR) .....	144
4.3.15.1	Definition and applicability.....	144
4.3.15.2	Limits .....	144
4.3.15.2.1	General .....	144
4.3.15.2.2	Absolute limits .....	144
4.3.15.2.3	Relative limits.....	145
4.3.15.3	Conformance .....	153
4.3.16	OTA transmitter spurious emissions.....	153
4.3.16.1	Definition and applicability.....	153
4.3.16.2	Limits .....	154
4.3.16.2.1	General spurious emissions limits .....	154

4.3.16.2.2	Limits for protection of the <i>BS receiver</i> .....	155
4.3.16.2.3	Limits for co-existence with other systems .....	155
4.3.16.2.4	Additional limits .....	158
4.3.16.3	Conformance .....	159
4.3.17	Radiated transmit power .....	159
4.3.17.1	Definition and applicability.....	159
4.3.17.2	Limits .....	159
4.3.17.3	Conformance .....	159
4.3.18	OTA Maximum output power .....	160
4.3.18.1	Definition and applicability.....	160
4.3.18.2	Limits .....	160
4.3.18.3	Conformance .....	160
4.3.19	OTA transmitter intermodulation .....	160
4.3.19.1	Definition and applicability.....	160
4.3.19.2	Limits .....	160
4.3.19.2.1	Limits for <i>MSR operation</i> .....	160
4.3.19.2.2	Limits for single RAT UTRA operation.....	162
4.3.19.2.3	Limits for single RAT E-UTRA operation.....	163
4.3.19.3	Conformance .....	163
4.3.20	OTA receiver spurious emissions .....	163
4.3.20.1	Definition and applicability.....	163
4.3.20.2	Limits .....	164
4.3.20.3	Conformance .....	164
4.3.21	OTA blocking .....	164
4.3.21.1	Definition and applicability.....	164
4.3.21.2	Limits .....	165
4.3.21.2.1	Limits for <i>MSR operation</i> .....	165
4.3.21.2.2	Limits for <i>Single RAT UTRA operation</i> .....	165
4.3.21.2.3	Limits for <i>single RAT E-UTRA operation</i> .....	166
4.3.21.3	Conformance .....	167
4.3.22	OTA receiver intermodulation .....	168
4.3.22.1	Definition and applicability.....	168
4.3.22.2	Limits .....	168
4.3.22.2.1	https://standards.etsi.org/standards/sist/b631/d632-4725-h38a- Limits for <i>MSR operation</i> .....	168
4.3.22.2.2	Limits for single RAT UTRA operation.....	172
4.3.22.2.3	Limits for single RAT E-UTRA operation.....	174
4.3.22.3	Conformance .....	178
4.3.23	OTA Adjacent Channel Selectivity (OTA ACS), general blocking and narrowband blocking .....	178
4.3.23.1	Definition and applicability.....	178
4.3.23.2	Limits .....	179
4.3.23.2.1	Limits for <i>MSR operation</i> .....	179
4.3.23.2.2	Limits for Single RAT UTRA FDD operation .....	182
4.3.23.2.3	Limits for single RAT E-UTRA operation .....	182
4.3.23.3	Conformance .....	185
4.3.24	OTA Sensitivity .....	185
4.3.24.1	Definition and applicability.....	185
4.3.24.2	Limits .....	185
4.3.24.2.1	Limits for UTRA operation .....	185
4.3.24.2.2	Limits for E-UTRA operation .....	185
4.3.24.2.3	Limits for NR operation .....	186
4.3.24.3	Conformance .....	186
4.3.25	OTA Reference sensitivity level .....	186
4.3.25.1	Definition and applicability.....	186
4.3.25.2	Limits .....	187
4.3.25.2.1	Limits for UTRA FDD operation .....	187
4.3.25.2.2	Limits for E-UTRA operation .....	187
4.3.25.2.3	Limits for NR operation .....	188
4.3.25.3	Conformance .....	189
5	Testing for compliance with technical requirements.....	189
5.1	Environmental conditions for testing .....	189
5.2	Interpretation of the measurement results .....	189

5.3	Essential radio test suites.....	189
5.3.1	Introduction.....	189
5.3.2	<i>Operating band unwanted emissions</i> .....	190
5.3.2.1	General.....	190
5.3.2.2	Initial conditions .....	190
5.3.2.3	Procedure .....	190
5.3.2.4	Test requirement .....	191
5.3.3	Spectrum Emission Mask (SEM).....	191
5.3.3.1	General.....	191
5.3.3.2	Initial conditions .....	191
5.3.3.3	Procedure .....	191
5.3.3.4	Test requirement .....	192
5.3.4	Adjacent Channel Leakage power Ratio (ACLR) .....	192
5.3.4.1	General.....	192
5.3.4.2	Initial conditions .....	192
5.3.4.2.1	General test conditions .....	192
5.3.4.2.2	MSR .....	192
5.3.4.2.3	UTRA FDD .....	192
5.3.4.2.4	E-UTRA .....	192
5.3.4.3	Procedure .....	193
5.3.4.3.1	General procedure .....	193
5.3.4.3.2	MSR .....	193
5.3.4.3.3	UTRA FDD .....	193
5.3.4.3.4	E-UTRA .....	194
5.3.5	Transmitter spurious emissions.....	194
5.3.2.1	General.....	194
5.3.5.2	Initial conditions .....	194
5.3.5.3	Procedure .....	195
5.3.5.4	Test requirement .....	195
5.3.6	Base station output power.....	195
5.3.6.1	General.....	195
5.3.6.2	Initial conditions .....	195
5.3.6.3	Procedure .....	196
5.3.6.4	<i>ETSI EN 301 908-23 V15.0.0 (2022-12)</i> h Test requirement .....	196
5.3.7	Transmit intermodulation .....	196
5.3.7.1	General.....	196
5.3.7.2	Initial conditions .....	196
5.3.7.3	Procedure .....	197
5.3.7.3.1	Procedure for co-location requirement .....	197
5.3.7.3.2	Procedure for intra-system requirement .....	199
5.3.7.4	Test requirement .....	200
5.3.8	Receiver spurious emissions.....	200
5.3.8.1	General.....	200
5.3.8.2	Initial conditions .....	200
5.3.8.3	Procedure .....	200
5.3.8.4	Test requirement .....	200
5.3.9	Blocking.....	200
5.3.9.1	General.....	200
5.3.9.2	Initial conditions .....	201
5.3.9.3	Procedure .....	201
5.3.9.3.1	General procedure .....	201
5.3.9.3.2	<i>MSR operation</i> .....	201
5.3.9.3.3	Single RAT UTRA FDD operation .....	202
5.3.9.3.4	<i>Single RATE-UTRA operation</i> .....	202
5.3.9.4	Test requirement .....	202
5.3.10	Receiver intermodulation characteristics .....	202
5.3.10.1	General.....	202
5.3.10.2	Initial conditions .....	203
5.3.10.3	Procedure .....	203
5.3.10.3.1	General procedure .....	203
5.3.10.3.2	MSR procedure.....	203
5.3.10.3.3	Procedure for single RAT UTRA FDD operation .....	203

5.3.10.3.4	Procedure for <i>single RAT E-UTRA operation</i> .....	204
5.3.10.4	Test requirement .....	204
5.3.11	Adjacent Channel Selectivity (ACS), general blocking and narrowband blocking .....	204
5.3.11.1	General.....	204
5.3.11.2	Initial conditions .....	204
5.3.11.3	Procedure .....	205
5.3.11.3.1	General procedure .....	205
5.3.11.3.2	<i>MSR operation</i> .....	205
5.3.11.3.3	Single RAT UTRA FDD operation .....	206
5.3.11.3.4	<i>Single RAT E-UTRA operation</i> .....	206
5.3.11.4	Test requirement .....	207
5.3.12	Reference sensitivity level .....	207
5.3.12.1	General.....	207
5.3.12.2	Initial conditions .....	207
5.3.12.3	Procedure .....	207
5.3.12.4	Test requirement .....	207
5.3.13	OTA operating band unwanted emissions .....	208
5.3.13.1	General.....	208
5.3.13.2	Initial conditions .....	208
5.3.13.3	Procedure .....	208
5.3.13.4	Test requirement .....	209
5.3.14	OTA Spectrum Emission Mask (OTA SEM) .....	209
5.3.14.1	General.....	209
5.3.14.2	Initial conditions .....	209
5.3.14.3	Procedure .....	209
5.3.14.4	Test requirement .....	210
5.3.15	OTA Adjacent Channel Leakage power Ratio (OTA ACLR) .....	210
5.3.15.1	General.....	210
5.3.15.2	Initial conditions .....	210
5.3.15.2.1	General test conditions .....	210
5.3.15.2.2	<i>MSR</i> .....	210
5.3.15.2.3	UTRA FDD .....	211
5.3.15.2.4	E-UTRA .....	211
5.3.15.2.5	<a href="https://standards.itieh.ai/catalog/standards/sist/b6317/d65-9632-4725-h38a-">https://standards.itieh.ai/catalog/standards/sist/b6317/d65-9632-4725-h38a-</a> .....	211
5.3.15.3	Procedure <a href="https://standards.itieh.ai/catalog/standards/sist/b6317/d65-9632-4725-h38a-">https://standards.itieh.ai/catalog/standards/sist/b6317/d65-9632-4725-h38a-</a> .....	211
5.3.15.3.1	General procedure .....	211
5.3.15.3.2	<i>MSR</i> .....	212
5.3.15.3.3	UTRA FDD .....	212
5.3.15.3.4	E-UTRA .....	212
5.3.15.4	Test requirement .....	213
5.3.16	OTA transmitter spurious emissions.....	213
5.3.16.1	General.....	213
5.3.16.2	General spurious emissions.....	213
5.3.16.2.1	General .....	213
5.3.16.2.2	Initial conditions.....	213
5.3.16.2.3	Procedure.....	213
5.3.16.2.4	Test requirement.....	215
5.3.16.3	Protection of the <i>BS receiver</i> .....	215
5.3.16.3.1	General .....	215
5.3.16.3.2	Initial conditions.....	215
5.3.16.3.3	Procedure.....	215
5.3.16.3.4	Test requirement.....	216
5.3.16.4	Co-existence with other systems.....	216
5.3.16.4.1	General .....	216
5.3.16.4.2	Initial conditions.....	216
5.3.16.4.3	Procedure.....	217
5.3.16.4.4	Test requirement.....	218
5.3.17	Radiated transmit power .....	218
5.3.17.1	General .....	218
5.3.17.2	Initial conditions .....	218
5.3.17.3	Procedure .....	218
5.3.17.4	Test requirement .....	219

5.3.18	OTA Maximum output power .....	219
5.3.18.1	General .....	219
5.3.18.2	Initial conditions .....	219
5.3.18.3	Procedure .....	219
5.3.18.4	Test requirement .....	220
5.3.19	OTA transmitter intermodulation .....	220
5.3.19.1	General .....	220
5.3.19.2	Initial conditions .....	220
5.3.19.3	Procedure .....	220
5.3.19.4	Test requirement .....	223
5.3.20	OTA receiver spurious emissions .....	223
5.3.20.1	General .....	223
5.3.20.2	Initial conditions .....	223
5.3.20.3	Procedure .....	223
5.3.20.4	Test requirement .....	224
5.3.21	OTA blocking .....	224
5.3.21.1	General .....	224
5.3.21.2	Initial conditions .....	224
5.3.21.3	Procedure .....	224
5.3.21.3.1	General procedure .....	224
5.3.21.3.2	<i>MSR operation</i> .....	225
5.3.21.3.3	Single RAT UTRA FDD operation .....	225
5.3.21.3.4	<i>Single RAT E-UTRA operation</i> .....	226
5.3.21.4	Test requirement .....	226
5.3.22	OTA receiver intermodulation .....	226
5.3.22.1	General .....	226
5.3.22.2	Initial conditions .....	226
5.3.22.3	Procedure .....	227
5.3.22.3.1	General procedure .....	227
5.3.22.3.2	<i>MSR operation</i> .....	227
5.3.22.3.3	Single RAT UTRA FDD operation .....	227
5.3.22.3.4	<i>Single RAT E-UTRA operation</i> .....	228
5.3.22.4	Test requirement .....	228
5.3.23	OTA Adjacent Channel Selectivity (OTA ACS) <small>(ETSI EN 301 908-23 V15.0.0 (2022-12))</small> .....	228
5.3.23.1	General .....	228
5.3.23.2	Initial conditions .....	228
5.3.23.3	Procedure .....	229
5.3.23.3.1	General procedure .....	229
5.3.23.3.2	<i>MSR operation</i> .....	229
5.3.23.3.3	Single RAT UTRA FDD operation .....	230
5.3.23.3.4	<i>Single RAT E-UTRA operation</i> .....	230
5.3.23.4	Test requirement .....	231
5.3.24	OTA sensitivity .....	231
5.3.24.1	General .....	231
5.3.24.2	Initial conditions .....	231
5.3.24.3	Procedure .....	231
5.3.24.4	Test requirement .....	232
5.3.25	OTA reference sensitivity level .....	232
5.3.25.1	General .....	232
5.3.25.2	Initial conditions .....	232
5.3.25.3	Procedure .....	232
5.3.25.4	Test requirement .....	233
<b>Annex A (informative):</b>	<b>Relationship between the present document and the essential requirements of Directive 2014/53/EU .....</b>	<b>234</b>
<b>Annex B (informative):</b>	<b>Maximum Measurement Uncertainty .....</b>	<b>236</b>
<b>Annex C (normative):</b>	<b>Base Station configurations for conducted testing .....</b>	<b>239</b>
C.1	Transmit configurations .....	239
C.2	Receive configurations .....	239

C.3	Power supply options .....	240
C.4	BS with integrated Iuant BS modem.....	240
<b>Annex D (normative):</b>	<b>Base Station configurations for radiated testing.....</b>	<b>241</b>
D.1	Transmit configurations .....	241
D.2	Receive configurations .....	242
D.3	Power supply options .....	243
D.4	BS with integrated Iuant BS modem.....	243
<b>Annex E (informative):</b>	<b>Checklist .....</b>	<b>244</b>
<b>Annex F (informative):</b>	<b>Bibliography .....</b>	<b>245</b>
<b>Annex G (informative):</b>	<b>Change history .....</b>	<b>246</b>
History .....		247

# i T h A N D A R D P R E ( s t a n d a r d s . i t )

h t t p s : / / s t a n d a r d s . i t e h . a  
d 4 6 7 3 0 6 2 5 6 3 0 / e t s i - e i

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™, PLUGTESTS™, UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the **GSM** logo are trademarks registered and owned by the **GSM Association**.

## Foreword

(standards.etsi.ai)

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure. [d46730625630/etsi-en-301-908-23-v15-0-0-2022-12](#)

For non-EU countries the present document may be used for regulatory (Type Approval) purposes.

The present document has been prepared under Commission's standardisation request C(2015) 5376 final [i.1] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document is part 23 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.6].

<b>Proposed national transposition dates</b>	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

## Introduction

The present document is part of a set of standards developed by ETSI that are designed to fit in a modular structure to cover radio equipment within the scope of the Radio Equipment Directive [i.2]. The present document is produced following the guidance in ETSI EG 203 336 [i.3] as applicable.

i T h   A N D A R D   P R E  
( s t a n d a r d s . i t )

h t t p s : / / s t a n d a r d s . i t e h . a  
d 4 6 7 3 0 6 2 5 6 3 0 / e t s i - e i

# 1 Scope

The present document specifies technical characteristics and methods of measurements for types of radio equipment:

- AAS BS supporting Single-RAT UTRA FDD.
- AAS BS supporting Single-RAT E-UTRA.
- AAS BS supporting Multi-Standard Radio (UTRA-FDD, E-UTRA, NR).

In the present document, the term "requirements for single RAT operation" refers to requirements that are derived from the ETSI TS 125 141 [7] or ETSI TS 136 141 [11] specifications baseline. The term "requirements for MSR operation" refers to requirements derived from the ETSI TS 137 141 [6] specification baseline (including NR operation as part of MSR).

These radio equipment types are capable of operating in whole or any part of the frequency band(s) given in table 1-1.

**Table 1-1: AAS BS operating bands**

Band designation for operation as:		Band Category	Direction of transmission	AAS BS operating bands	Relevant EC/ECC decision
Single-RAT E-UTRA or MSR (note 1)	Single-RAT UTRA				
1	I	BC1	Transmit	2 110 MHz to 2 170 MHz	[i.20] and [i.21]
			Receive	1 920 MHz to 1 980 MHz	
3	III	BC2	Transmit	1 805 MHz to 1 880 MHz	[i.18] and [i.19]
			Receive	1 710 MHz to 1 785 MHz	
7	VII	BC1	Transmit	2 620 MHz to 2 690 MHz	[i.23] and [i.24]
			Receive	2 500 MHz to 2 570 MHz	
8	VIII	BC2	Transmit	925 MHz to 960 MHz	[i.18] and [i.19]
			Receive	880 MHz to 915 MHz	
20	XX	BC1	Transmit	791 MHz to 821 MHz	[i.13] and [i.14]
			Receive	832 MHz to 862 MHz	
22	XXII	BC1	Transmit	3 510 MHz to 3 590 MHz	[i.8] and [i.25]
			Receive	3 410 MHz to 3 490 MHz	
28	NA	BC1 (notes 2 and 3)	Transmit	758 MHz to 803 MHz	[i.11] and [i.12]
			Receive	703 MHz to 748 MHz	
31	NA	BC1 (note 2)	Transmit	462,5 MHz to 467,5 MHz	[i.10]
			Receive	452,5 MHz to 457,5 MHz	
32	XXXII	BC1 (note 7)	Transmit	1 452 MHz to 1 496 MHz	[i.15] and [i.16]
			Receive	N/A	
33	NA	BC3	Transmit and Receive	1 900 MHz to 1 920 MHz	[i.19]
34	NA	BC3	Transmit and Receive	2 010 MHz to 2 025 MHz	[i.19]
38	NA	BC3	Transmit and Receive	2 570 MHz to 2 620 MHz	[i.23] and [i.24]
40	NA	BC3	Transmit and Receive	2 300 MHz to 2 400 MHz	[i.22]
41	NA	BC3 (note 4)	Transmit and Receive	2 496 MHz to 2 690 MHz	[i.23] and [i.24]
42	NA	BC3	Transmit and Receive	3 400 MHz to 3 600 MHz	[i.8] and [i.25]
43	NA	BC3	Transmit and Receive	3 600 MHz to 3 800 MHz	[i.8] and [i.25]
50	NA	BC3 (note 7)	Transmit and Receive	1 432 MHz to 1 517 MHz	[i.15], [i.16] and [i.17]
51	NA	BC3 (note 7)	Transmit and Receive	1 427 MHz to 1 432 MHz	[i.15] and [i.16]
65	NA	BC1 (notes 2 and 8)	Transmit	2 110 MHz to 2 200 MHz	[i.20], [i.21] and [i.26]
			Receive	1 920 MHz to 2 010 MHz	

Band designation for operation as:		Band Category	Direction of transmission	AAS BS <i>operating bands</i>	Relevant EC/ECC decision
Single-RAT E-UTRA or MSR (note 1)	Single-RAT UTRA				
67	NA	BC1 (notes 2 and 7)	Transmit	738 MHz to 758 MHz	[i.11] and [i.12]
			Receive	N/A	
68	NA	BC1 (note 10)	Transmit	753 MHz to 783 MHz	[i.11] and [i.12]
			Receive	698 MHz to 728 MHz	
69	NA	BC1 (notes 2 and 7)	Transmit	2 570 MHz to 2 620 MHz	[i.23] and [i.24]
			Receive	N/A	
72	NA	BC1 (note 2)	Transmit	461 MHz to 466 MHz	[i.10]
			Receive	451 MHz to 456 MHz	
75	NA	BC1 (notes 2 and 7)	Transmit	1 432 MHz to 1 517 MHz	[i.15], [i.16] and [i.17]
			Receive	N/A	
76	NA	BC1 (notes 2 and 7)	Transmit	1 427 MHz to 1 432 MHz	[i.15] and [i.16]
			Receive	N/A	
77	NA	BC3 (notes 5 and 9)	Transmit and Receive	3 300 MHz to 4 200 MHz	[i.8] and [i.25]
78	NA	BC3 (notes 6 and 9)	Transmit and Receive	3 300 MHz to 3 800 MHz	[i.8] and [i.25]
87	NA	BC1 (note 10)	Transmit	420 MHz to 425 MHz	[i.10]
			Receive	410 MHz to 415 MHz	
88	NA	BC1 (note 10)	Transmit	422 MHz to 427 MHz	[i.10]
			Receive	412 MHz to 417 MHz	

NOTE 1: The band designations given are the MSR BS band designations. The relation between the band designations for MSR BS and the designations for NR, E-UTRA and UTRA are given in table 4.4-1 of ETSI TS 137 141 [6].

NOTE 2: The band is for NR and/or E-UTRA only.

NOTE 3: In Europe, according to [i.13] and [i.14], radio equipment in band 28 operates between 758 MHz and 791 MHz for the transmitter ( $F_{DL\_low} = 758$  MHz and  $F_{DL\_high} = 791$  MHz) and between 703 MHz and 736 MHz for the receiver ( $F_{UL\_low} = 703$  MHz and  $F_{UL\_high} = 736$  MHz).

NOTE 4: In Europe according to [i.22] and [i.23], radio equipment in band 41 operates between 2 570 MHz and 2 620 MHz ( $F_{DL\_low} = 2 570$  MHz and  $F_{DL\_high} = 2 620$  MHz).

NOTE 5: In Europe, according to [i.24] and [i.8], radio equipment in band n77 operates between 3 400 MHz and 3 800 MHz ( $F_{DL\_low} = 3 400$  MHz and  $F_{DL\_high} = 3 800$  MHz).

NOTE 6: In Europe, according to [i.24] and [i.8], radio equipment in band n78 operates between 3 400 MHz and 3 800 MHz ( $F_{DL\_low} = 3 400$  MHz and  $F_{DL\_high} = 3 800$  MHz).

NOTE 7: Radio equipment in bands 32, 50, 51, 67, 69, 75 and 76 only operates in transmit mode (downlink only). Only transmitter requirements are applicable.

NOTE 8: This band includes two frequency ranges that are harmonised in Europe:

- (a) According to [i.21] and [i.22], radio equipment in band n65 operates between 2 110 MHz and 2 170 MHz for the transmitter ( $F_{DL\_low} = 2 110$  MHz and  $F_{DL\_high} = 2 170$  MHz), and between 1 920 MHz and 1 980 MHz for the receiver ( $F_{UL\_low} = 1 920$  MHz and  $F_{UL\_high} = 1 980$  MHz).
- (b) Based on [i.26], radio equipment in band n65 operates between 2 170 MHz and 2 200 MHz for the transmitter ( $F_{DL\_low} = 2 170$  MHz and  $F_{DL\_high} = 2 200$  MHz) and between 1 980 MHz and 2 010 MHz for the receiver ( $F_{UL\_low} = 1 980$  MHz and  $F_{UL\_high} = 2 010$  MHz) as the Complementary Ground Component (CGC) of a Mobile-satellite service by reference to the present document.

NOTE 9: The band is for NR only.

NOTE 10: The band is for E-UTRA only.

NOTE 1: For BS capable of multi-band operation, the supported *operating bands* may belong to different Band Categories.

NOTE 2: AAS BS does not support GSM/EDGE, but BC2 is still applicable for protection of/against GSM/EDGE operation in BC2 *operating bands*.

NOTE 3: AAS BS does not support Narrow-Band Internet of Things (NB-IoT) in band, NB-IoT guard band, or standalone NB-IoT operation, but NB-IoT limits are still applicable for AAS BS protection of/against NB-IoT operation in *operating bands*.

NOTE 4: AAS BS does not support band 46 operation, but band 46 limits are still applicable for AAS BS protection of/against devices operating in band 46.

NOTE 5: The band categories for BS are defined in clause 4.4 of ETSI TS 137 141 [6] and are listed in table 1-1.

AAS BS supports *carrier aggregation* as defined in tables 4.2.1-3 to 4.2.1-6 in ETSI EN 301 908-14 [5], or tables 4.2.1-2 to 4.2.1-7 in ETSI EN 301 908-18 [4], except for the CA combinations involving band 46.

The present document covers conducted and radiated requirements for AAS BS capable of single-RAT UTRA, single-RAT E-UTRA and MSR multi-RAT operation (UTRA, E-UTRA, NR) in 3GPP™ Release 15. Additionally, it includes for selected AAS BS *operating bands* from 3GPP Release 16.

NOTE 6: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.2] is given in annex A.

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 137 105 (V15.17.0) (06-2022): "Universal Mobile Telecommunications System (UMTS); LTE; 5G; Active Antenna System (AAS) Base Station (BS) transmission and reception (3GPP TS 37.105 version 15.17.0 Release 15)".
- [2] ETSI TS 137 145-1 (V15.14.0) (06-2022): "Universal Mobile Telecommunications System (UMTS); LTE; 5G; Active Antenna System (AAS) Base Station (BS) conformance testing; Part 1: conducted conformance testing (3GPP TS 37.145-1 version 15.14.0 Release 15)".
- [3] ETSI TS 137 145-2 (V15.15.0) (06-2022): "Universal Mobile Telecommunications System (UMTS); LTE; 5G; Active Antenna System (AAS) Base Station (BS) conformance testing; Part 2: radiated conformance testing (3GPP TS 37.145-2 version 15.15.0 Release 15)".
- [4] ETSI EN 301 908-18 (V15.1.1) (09-2021): "IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 18: E-UTRA, UTRA and GSM/EDGE Multi-Standard Radio (MSR) Base Station (BS); Release 15".
- [5] ETSI EN 301 908-14 (V15.1.1) (09-2021): "IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 14: Evolved Universal Terrestrial Radio Access (E-UTRA) Base Stations (BS); Release 15".
- [6] ETSI TS 137 141 (V15.18.0) (10-2019): "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE; 5G; NR, E-UTRA, UTRA and GSM/EDGE; Multi-Standard Radio (MSR) Base Station (BS) conformance testing (3GPP TS 37.141 version 15.18.0 Release 15)".
- [7] ETSI TS 125 141 (V15.4.0) (04-2019): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) conformance testing (FDD) (3GPP TS 25.141 version 15.4.0 Release 15)".
- [8] ETSI TS 145 004 (V15.0.0) (07-2018): "Digital cellular telecommunications system (Phase 2+) (GSM); GSM/ EDGE Modulation (3GPP TS 45.004 version 15.0.0 Release 15)".
- [9] ETSI TS 136 104 (V15.15.0) (04-2022): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception (3GPP TS 36.104 version 15.15.0 Release 15)".

- [10] ETSI TS 125 104 (V15.5.0) (04-2019): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) radio transmission and reception (FDD) (3GPP TS 25.104 version 15.5.0 Release 15)".
- [11] ETSI TS 136 141 (V15.16.0) (04-2022): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) conformance testing (3GPP TS 36.141 version 15.16.0 Release 15)".
- [12] ETSI TS 138 141-1 (V15.12.0) (04-2022): "5G; NR; Base Station (BS) conformance testing Part 1: Conducted conformance testing (3GPP TS 38.141-1 version 15.12.0 Release 15)".
- [13] ETSI TS 138 104 (V15.17.0) (08-2022): "5G; NR; Base Station (BS) radio transmission and reception (3GPP TS 38.104 version 15.7.0 Release 15)".
- [14] ETSI EN 301 908-24 (V15.0.0) (12-2022): "IMT cellular networks; Harmonised Standard for access to radio spectrum Part 24: New Radio (NR) Base Stations (BS); Release 15".
- [15] ETSI TS 138 141-2 (V15.14.0) (08-2022): "5G; NR; Base Station (BS) conformance testing Part 2: Radiated conformance testing (3GPP TS 38.141-2 version 15.14.0 Release 15)".

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Commission implementing decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.  
<https://standards.etsi.org/standardisation-request/2019-06-15-0001263904.html#2022-12>
- [i.2] Directive 2014/53/EU of the European parliament and of the council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.3] ETSI EG 203 336 (V1.2.1) (05-2020): "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.4] Recommendation ITU-R SM.329-12 (09-2012): "Unwanted emissions in the spurious domain".
- [i.5] ETSI TR 100 028 (parts 1 and 2) (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1".
- [i.6] ETSI EN 301 908-1 (V15.1.1) (09-2021): "IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 1: Introduction and common requirements Release 15".
- [i.7] ETSI TR 103 877 (V1.1.1): "Task Force for European Standards for IMT-2000 (MSG); Technical Parameter selection in ETSI EN 301 908 Base Station (BS) Harmonised Standards".
- [i.8] Commission implementing Decision (EU) 2019/235 of 24 January 2019 on amending Decision 2008/411/EC as regards an update of relevant technical conditions applicable to the 3 400-3800 MHz frequency band.
- [i.9] ETSI TS 103 807 (V1.1.1) (10-2021): "Mobile Standards Group (MSG); IMT Cellular Networks Base Stations (BS) Additional Regulatory Requirements".