



# SLOVENSKI STANDARD

## SIST EN 301 908-2 V11.1.2:2017

01-oktober-2017

---

**Celična omrežja IMT - Harmonizirani standard, ki zajema bistvene zahteve člena 3.2 direktive 2014/53/EU - 2. del: CDMA z neposrednim razprševanjem ("Direct Spread") (UTRA FDD) (UE)**

IMT cellular networks - Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU - Part 2: CDMA Direct Spread (UTRA FDD) User Equipment (UE)

### iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 908-2 V11.1.2:2017](https://standards.iteh.ai/catalog/standards/sist/d9841abb-a8a1-482fb4f0-49f245d79705/sist-en-301-908-2-v11-1-2-2017)

<https://standards.iteh.ai/catalog/standards/sist/d9841abb-a8a1-482fb4f0-49f245d79705/sist-en-301-908-2-v11-1-2-2017>

**Ta slovenski standard je istoveten z: ETSI EN 301 908-2 V11.1.2 (2017-08)**

---

#### **ICS:**

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.070.99	Druge mobilne storitve	Other mobile services

**SIST EN 301 908-2 V11.1.2:2017**      **en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 301 908-2 V11.1.2:2017](https://standards.iteh.ai/catalog/standards/sist/d9841abb-a8a1-482f-b4f0-49f245d79705/sist-en-301-908-2-v11-1-2-2017)

<https://standards.iteh.ai/catalog/standards/sist/d9841abb-a8a1-482f-b4f0-49f245d79705/sist-en-301-908-2-v11-1-2-2017>

# ETSI EN 301 908-2 V11.1.2 (2017-08)



**IMT cellular networks;**  
**Harmonised Standard covering the essential requirements**  
**of article 3.2 of Directive 2014/53/EU;**  
**Part 2: CDMA Direct Spread (UTRA FDD)**  
**User Equipment (UE)**

SIST EN 301 908-2 V11.1.2:2017  
<https://standards.etsi.org/standards-search/standards-search/482fb4f0-49f245d79705/sist-en-301-908-2-v11-1-2-2017>

## Reference

---

REN/MSG-TFES-11-02-RED-C1

## Keywords

---

3G, 3GPP, cellular, digital, IMT, mobile, radio,  
regulation, UMTS, UTRA, WCDMA

**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 301 908-2 V11.1.2:2017

<https://standards.iteh.ai/catalog/standards/sist/d9841abb-a8a1-482fb4f0-49d245d79705/sist-en-301-908-2-v11-1-2-2017>

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M** logo is protected for the benefit of its Members.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	7
Foreword.....	7
Modal verbs terminology.....	7
Introduction .....	8
1 Scope .....	9
2 References .....	10
2.1 Normative references .....	10
2.2 Informative references.....	10
3 Definitions, symbols and abbreviations .....	11
3.1 Definitions.....	11
3.2 Symbols.....	12
3.3 Abbreviations .....	13
4 Technical requirements specifications .....	14
4.1 Environmental profile.....	14
4.2 Conformance requirements .....	14
4.2.0 General.....	14
4.2.1 Introduction.....	14
4.2.2 Transmitter maximum output power.....	15
4.2.2.1 Transmitter maximum output power.....	15
4.2.2.1.1 Definition.....	15
4.2.2.1.2 Limits .....	15
4.2.2.1.3 Conformance .....	16
4.2.2.2 Transmitter maximum output power for DC-HSUPA .....	16
4.2.2.2.1 Definition for DC-HSUPA.....	16
4.2.2.2.2 Limits for DC-HSUPA.....	16
4.2.2.2.3 Conformance .....	16
4.2.2.3 Transmitter maximum output power for UL OLTD .....	16
4.2.2.3.1 Definition for UL OLTD .....	16
4.2.2.3.2 Limits for UL OLTD .....	16
4.2.2.3.3 Conformance .....	17
4.2.3 Transmitter spectrum emission mask.....	17
4.2.3.1 Transmitter spectrum emission mask .....	17
4.2.3.1.1 Definition.....	17
4.2.3.1.2 Limits .....	17
4.2.3.1.3 Conformance .....	18
4.2.3.2 Transmitter spectrum emission mask for DC-HSUPA .....	18
4.2.3.2.1 Definition for DC-HSUPA.....	18
4.2.3.2.2 Limits for DC-HSUPA .....	18
4.2.3.2.3 Conformance .....	18
4.2.3.3 Transmitter spectrum emission mask for UL OLTD .....	19
4.2.3.3.1 Definition for UL OLTD .....	19
4.2.3.3.2 Limits for UL OLTD .....	19
4.2.3.3.3 Conformance .....	19
4.2.3.4 Transmitter spectrum emission mask for UL CLTD Activation state 1 .....	19
4.2.3.4.1 Definition for UL CLTD Activation state 1 .....	19
4.2.3.4.2 Limits for UL CLTD Activation state 1 .....	19
4.2.3.4.3 Conformance .....	20
4.2.4 Transmitter spurious emissions.....	20
4.2.4.1 Transmitter spurious emissions.....	20
4.2.4.1.1 Definition.....	20
4.2.4.1.2 Limits .....	20
4.2.4.1.3 Conformance .....	22
4.2.4.2 Transmitter spurious emissions for DC-HSUPA .....	22
4.2.4.2.1 Definition for DC-HSUPA .....	22

4.2.4.2.2	Limits for DC-HSUPA .....	22
4.2.4.2.3	Conformance .....	24
4.2.5	Transmitter minimum output power .....	25
4.2.5.1	Transmitter minimum output power.....	25
4.2.5.1.1	Definition.....	25
4.2.5.1.2	Limits .....	25
4.2.5.1.3	Conformance .....	25
4.2.5.2	Transmitter minimum output power for DC-HSUPA .....	25
4.2.5.2.1	Definition for DC-HSUPA .....	25
4.2.5.2.2	Limits for DC-HSUPA .....	25
4.2.5.2.3	Conformance .....	25
4.2.5.3	Transmitter minimum output power for UL CLTD Activation state 1 .....	25
4.2.5.3.1	Definition for UL CLTD Activation state 1 .....	25
4.2.5.3.2	Limits for UL CLTD Activation state 1 .....	25
4.2.5.3.3	Conformance .....	25
4.2.6	Receiver Adjacent Channel Selectivity (ACS) .....	26
4.2.6.1	Definition .....	26
4.2.6.2	Limits .....	26
4.2.6.3	Conformance.....	26
4.2.7	Receiver blocking characteristics .....	26
4.2.7.1	Definition .....	26
4.2.7.2	Limits .....	26
4.2.7.3	Conformance.....	28
4.2.8	Receiver spurious response.....	28
4.2.8.1	Definition .....	28
4.2.8.2	Limits .....	28
4.2.8.3	Conformance.....	29
4.2.9	Receiver intermodulation characteristics .....	29
4.2.9.1	Definition .....	29
4.2.9.2	Limits .....	29
4.2.9.3	Conformance.....	30
4.2.10	Receiver spurious emissions .....	30
4.2.10.1	Definition.....	30
4.2.10.2	Limits .....	30
4.2.10.3	Conformance.....	31
4.2.11	Out-of-synchronization handling of output power.....	31
4.2.11.1	Definition .....	31
4.2.11.2	Limits .....	31
4.2.11.3	Conformance.....	33
4.2.12	Transmitter Adjacent Channel Leakage power Ratio (ACLR) .....	33
4.2.12.1	Transmitter adjacent channel leakage power ratio (ACLR).....	33
4.2.12.1.1	Definition.....	33
4.2.12.1.2	Limits .....	33
4.2.12.1.3	Conformance .....	33
4.2.12.2	Adjacent channel leakage power ratio for DC-HSUPA .....	33
4.2.12.2.1	Definition for DC-HSUPA .....	33
4.2.12.2.2	Limits for DC-HSUPA .....	33
4.2.12.2.3	Conformance .....	34
4.2.12.3	Adjacent channel leakage power ratio for UL OLTD .....	34
4.2.12.3.1	Definition for UL OLTD .....	34
4.2.12.3.2	Limits for UL OLTD .....	34
4.2.12.3.3	Conformance .....	34
4.2.12.4	Adjacent channel leakage power ratio for UL CLTD Activation state 1 .....	34
4.2.12.4.1	Definition for UL CLTD Activation state 1 .....	34
4.2.12.4.2	Limits for UL CLTD Activation state 1 .....	34
4.2.12.4.3	Conformance .....	35
4.2.13	Receiver Reference Sensitivity level .....	35
4.2.13.0	General .....	35
4.2.13.1	Definition .....	35
4.2.13.2	Limits .....	35
4.2.13.3	Conformance.....	35

5	Testing for compliance with technical requirements.....	35
5.1	Environmental conditions for testing .....	35
5.2	Interpretation of the measurement results .....	36
5.3	Essential radio test suites.....	37
5.3.0	General.....	37
5.3.1	Transmitter maximum output power.....	37
5.3.1.1	Method of test .....	37
5.3.1.1.1	UTRA .....	37
5.3.1.1.1A	DC-HSUPA .....	38
5.3.1.1.1B	UL OLTD .....	38
5.3.1.2	Test requirements.....	39
5.3.2	Transmitter spectrum emission mask.....	39
5.3.2.1	Method of test .....	39
5.3.2.1.1	UEs not supporting HSDPA and/or E-DCH.....	39
5.3.2.1.1A	UEs supporting HSDPA and/or E-DCH.....	40
5.3.2.1.1B	DC-HSUPA .....	40
5.3.2.1.1C	UL OLTD .....	41
5.3.2.1.1D	UL CLTD Activation state 1 .....	42
5.3.2.2	Test requirements.....	42
5.3.3	Transmitter spurious emissions.....	42
5.3.3.1	Method of test .....	42
5.3.3.1.1	UTRA .....	42
5.3.3.1.1A	DC-HSUPA .....	43
5.3.3.2	Test requirements.....	43
5.3.4	Transmitter minimum output power .....	44
5.3.4.1	Method of test .....	44
5.3.4.1.1	UTRA .....	44
5.3.4.1.1A	DC-HSUPA .....	44
5.3.4.1.1B	UL CLTD Activation state 1 .....	45
5.3.4.2	Test requirements.....	45
5.3.5	Receiver Adjacent Channel Selectivity (ACS) .....	45
5.3.5.1	Method of test .....	45
5.3.5.1.1	Initial conditions.....	45
5.3.5.1.2	Procedure.....	46
5.3.5.2	Test requirements.....	46
5.3.6	Receiver blocking characteristics .....	46
5.3.6.1	Method of test .....	46
5.3.6.1.1	Initial requirements.....	46
5.3.6.1.2	Procedure.....	46
5.3.6.2	Test requirements.....	46
5.3.7	Receiver spurious response.....	47
5.3.7.1	Method of test .....	47
5.3.7.1.1	Initial conditions.....	47
5.3.7.1.2	Procedure.....	47
5.3.7.2	Test requirements.....	47
5.3.8	Receiver Intermodulation characteristics .....	47
5.3.8.1	Method of test .....	47
5.3.8.1.1	Initial conditions.....	47
5.3.8.1.2	Procedure.....	48
5.3.8.2	Test requirements.....	48
5.3.9	Receiver spurious emissions .....	48
5.3.9.1	Method of test .....	48
5.3.9.1.1	Initial conditions.....	48
5.3.9.1.2	Procedure.....	48
5.3.9.2	Test requirements.....	48
5.3.10	Out-of-synchronization handling of output power.....	48
5.3.10.1	Method of test .....	48
5.3.10.1.1	Initial conditions.....	48
5.3.10.1.2	Procedure.....	49
5.3.10.2	Test requirements.....	49
5.3.11	Transmitter adjacent channel leakage power ratio.....	49
5.3.11.1	Method of test .....	49

5.3.11.1.1	UEs not supporting HSDPA and/or E-DCH.....	49
5.3.11.1.1A	UEs supporting HSDPA and/or E-DCH.....	50
5.3.11.1.1B	DC-HSUPA.....	50
5.3.11.1.1C	UL OLTD.....	51
5.3.11.1.1D	UL CLTD Activation state 1.....	51
5.3.11.2	Test requirements.....	52
5.3.12	Receiver Reference Sensitivity level.....	52
5.3.12.1	Method of test.....	52
5.3.12.1.1	Initial conditions.....	52
5.3.12.1.2	Procedure.....	52
5.3.12.2	Test requirements.....	52
<b>Annex A (informative):</b>	<b>Relationship between the present document and the essential requirements of Directive 2014/53/EU.....</b>	<b>53</b>
<b>Annex B (normative):</b>	<b>Environmental profile.....</b>	<b>54</b>
B.1	General.....	54
B.1.1	Introduction.....	54
B.1.2	Temperature.....	54
B.1.3	Voltage.....	54
B.1.4	Test environment.....	54
<b>Annex C (informative):</b>	<b>Bibliography.....</b>	<b>55</b>
<b>Annex D (informative):</b>	<b>Change history.....</b>	<b>56</b>
History.....		57

**ITeH STANDARD PREVIEW**  
(standards.iteh.ai)

[SIST EN 301 908-2 V11.1.2:2017](https://standards.iteh.ai/catalog/standards/sist/d9841abb-a8a1-482fb4f0-49f245d79705/sist-en-301-908-2-v11-1-2-2017)

<https://standards.iteh.ai/catalog/standards/sist/d9841abb-a8a1-482fb4f0-49f245d79705/sist-en-301-908-2-v11-1-2-2017>



---

## Intellectual Property Rights

### Essential patents

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

### Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

## Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.9] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2]. <https://standards.iteh.ai/catalog/standards/sist/d9841abb-a8a1-482fb4f0-49f245d79705/sist-en-301-908-2-v11-1-2-2017>

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A-1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 2 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.10].

National transposition dates	
Date of latest announcement of this EN (doa):	30 November 2017
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 May 2018
Date of withdrawal of any conflicting National Standard (dow):	31 May 2019

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

## Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the Radio Equipment Directive [i.2]. The present document is produced following the guidance in ETSI EG 203 336 [i.3] as applicable.

### **iTeh STANDARD PREVIEW (standards.iteh.ai)**

[SIST EN 301 908-2 V11.1.2:2017](https://standards.iteh.ai/catalog/standards/sist/d9841abb-a8a1-482f-b4f0-49f245d79705/sist-en-301-908-2-v11-1-2-2017)

<https://standards.iteh.ai/catalog/standards/sist/d9841abb-a8a1-482f-b4f0-49f245d79705/sist-en-301-908-2-v11-1-2-2017>

# 1 Scope

The present document applies to the following radio equipment type:

- User Equipment for IMT-2000 CDMA Direct Spread (UTRA FDD).

These radio equipment types are capable of operating in all or any part of the frequency bands given in table 1-1.

**Table 1-1: UTRA FDD operating bands**

UTRA FDD Band	Direction of transmission	UTRA FDD operating bands
I	Transmit	1 920 MHz to 1 980 MHz
	Receive	2 110 MHz to 2 170 MHz
III	Transmit	1 710 MHz to 1 785 MHz
	Receive	1 805 MHz to 1 880 MHz
VII	Transmit	2 500 MHz to 2 570 MHz
	Receive	2 620 MHz to 2 690 MHz
VIII	Transmit	880 MHz to 915 MHz
	Receive	925 MHz to 960 MHz
XV	Transmit	1 900 MHz to 1 920 MHz
	Receive	2 600 MHz to 2 620 MHz
XVI	Transmit	2 010 MHz to 2 025 MHz
	Receive	2 585 MHz to 2 600 MHz
XX	Transmit	832 MHz to 862 MHz
	Receive	791 MHz to 821 MHz
XXII	Transmit	3 410 MHz to 3 490 MHz
	Receive	3 510 MHz to 3 590 MHz

The present document covers requirements for UTRA FDD User Equipment from 3GPP™ Releases 99, 4, 5, 6, 7, 8, 9, 10 and 11 defined in ETSI TS 125 101 [4]. This include the requirements for UE operating bands from 3GPP™ Release 12 defined in ETSI TS 125 101 [4]. In addition, the present document covers requirements for UTRA FDD User Equipment in the operating bands specified in ETSI TS 102 735 [i.4].

NOTE: For Band XX:

- for user equipment designed to be mobile or nomadic, the requirements in the present document measured at the antenna port also show conformity to the corresponding requirement defined as TRP (Total Radiated Power), as described in Commission Decision 2010/267/EU [i.6], ECC Decision (09)03 [i.7] and CEPT Report 30 [i.8];
- for user equipment designed to be fixed or installed, the present document does not address the requirements described in Commission Decision 2010/267/EU [i.6], ECC Decision (09)03 [i.7] and CEPT Report 30 [i.8].

The present document contains requirements to demonstrate that radio equipment both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference.

The present document covers the essential requirements of article 3.2 of Directive 2014/53/EU [i.2] under the conditions identified in annex A.

## 2 References

### 2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 134 121-1 (V12.1.0) (10-2015): "Universal Mobile Telecommunications System (UMTS); User Equipment (UE) conformance specification; Radio transmission and reception (FDD); Part 1: Conformance specification (3GPP TS 34.121-1 version 12.1.0 Release 12)".
- [2] ETSI TS 134 108 (V12.1.0) (10-2015): "Universal Mobile Telecommunications System (UMTS); LTE; Common test environments for User Equipment (UE); Conformance testing (3GPP TS 34.108 version 12.1.0 Release 12)".
- [3] ETSI TS 134 109 (V12.0.0) (09-2014): "Universal Mobile Telecommunications System (UMTS); Terminal logical test interface; Special conformance testing functions (3GPP TS 34.109 version 12.0.0 Release 12)".
- [4] ETSI TS 125 101 (V11.11.0) (01-2015): "Universal Mobile Telecommunications System (UMTS); User Equipment (UE) radio transmission and reception (FDD) (3GPP TS 25.101 version 11.11.0 Release 11)".
- [5] IEC 60068-2-1 (03-2007): "Environmental testing - Part 2-1: Tests - Test A: Cold".
- [6] IEC 60068-2-2 (07-2007): "Environmental testing - Part 2-2: Tests - Test B: Dry heat".
- [7] ETSI TS 125 214 (V11.12.0) (07-2015): "Universal Mobile Telecommunications System (UMTS); Physical layer procedures (FDD) (3GPP TS 25.214 version 11.12.0 Release 11)".
- [8] ETSI TS 145 004 (V11.0.0) (10-2012): "Digital cellular telecommunications system (Phase 2+); Modulation (3GPP TS 45.004 version 11.0.0 Release 11)".

### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Void.
- [i.2] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.3] ETSI EG 203 336 (V1.1.1) (08-2015): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".

- [i.4] ETSI TS 102 735 (V7.1.0): "Universal Mobile Telecommunications System (UMTS); Band-specific requirements for UMTS Frequency Division Duplex (FDD) operation in the bands 1 900 MHz to 1 920 MHz paired with 2 600 MHz to 2 620 MHz and 2 010 MHz to 2 025 MHz paired with 2 585 MHz to 2 600 MHz".
- [i.5] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.6] Commission Decision 2010/267/EU of 6 May 2010 on harmonised technical conditions of use in the 790-862 MHz frequency band for terrestrial systems capable of providing electronic communications services in the European Union.
- [i.7] ECC Decision (09)03 of 30 October 2009 on harmonised conditions for mobile/fixed communications networks (MFCN) operating in the band 790 - 862 MHz.
- [i.8] CEPT Report 30 of 30 October 2009 to the European Commission in response to the Mandate on "The identification of common and minimal (least restrictive) technical conditions for 790 - 862 MHz for the digital dividend in the European Union".
- [i.9] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.10] ETSI EN 301 908-1 (V11.1.1): "IMT cellular networks; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU; Part 1: Introduction and common requirements".

## iTeh STANDARD PREVIEW

### 3 Definitions, symbols and abbreviations

#### 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

**chip rate:** rate of "chips" (modulated symbols after spreading) per second

NOTE: The UTRA FDD chip rate is 3,84 Mchip/s.

**data rate:** rate of the user information, which is transmitted over the Air Interface

EXAMPLE: Output rate of the voice codec.

**enhanced performance receiver type 1 for DCH:** receiver with performance requirements which are optional for the UE and utilize receiver diversity during DCH reception

**environmental profile:** range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

**maximum output power:** measure of the maximum power the UE can transmit (i.e. the actual power as would be measured assuming no measurement error) in a bandwidth of at least  $(1 + \alpha)$  times the chip rate of the radio access mode

NOTE: The period of measurement is assumed to be at least one timeslot.

**mean power:** power (transmitted or received) in a bandwidth of at least  $(1 + \alpha)$  times the chip rate of the radio access mode, when applied to a WCDMA modulated signal

NOTE: The period of measurement is assumed to be at least one timeslot unless otherwise stated.

**node B:** logical node responsible for radio transmission/reception in one or more cells to/from the User Equipment

**nominal maximum output power:** nominal power defined by the UE power class

**operating band:** frequency range that is defined with a specific set of technical requirements, in which UTRA FDD operates

NOTE: Operating bands for UTRA are designated with Roman numerals, while the corresponding operating bands for E-UTRA are designated with Arabic numerals.

**power spectral density:** function of power versus frequency and when integrated across a given bandwidth, the function represents the mean power in such a bandwidth

NOTE 1: When the mean power is normalized to (divided by) the chip-rate it represents the mean energy per chip. Some signals are directly defined in terms of energy per chip, (DPCH\_Ec, Ec, OCNS\_Ec and S-CCPCH\_Ec) and others defined in terms of PSD ( $I_o$ ,  $I_{oc}$ ,  $I_{or}$  and  $\hat{I}_{or}$ ). There also exist quantities that are a ratio of energy per chip to PSD (DPCH\_Ec/ $I_{or}$ , Ec/ $I_{or}$ , etc.). This is the common practice of relating energy magnitudes in communication systems.

NOTE 2: It can be seen that if both energy magnitudes in the ratio are divided by time, the ratio is converted from an energy ratio to a power ratio, which is more useful from a measurement point of view. It follows that an energy per chip of X dBm/3,84 MHz can be expressed as a mean power per chip of X dBm. Similarly, a signal PSD of Y dBm/3,84 MHz can be expressed as a signal power of Y dBm.

NOTE 3: The units of Power Spectral Density (PSD) are extensively used in the present document.

**RRC filtered mean power:** mean power as measured through a root raised cosine filter with roll-off factor  $\alpha$  and a bandwidth equal to the chip rate of the radio access mode

NOTE: The RRC filtered mean power of a perfectly modulated WCDMA signal is 0,246 dB lower than the mean power of the same signal.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

### 3.2 Symbols

For the purposes of the present document, the following symbols apply:

$\alpha$	Roll-off factor of the root raised cosine filter, $\alpha = 0,22$
DPCH_Ec	Average energy per PN chip for DPCH
$E_c$	Average energy per PN chip
$F_{uw}$	Frequency of unwanted signal

NOTE: This is specified in bracket in terms of an absolute frequency(s) or a frequency offset from the assigned channel frequency.

$\langle \text{REF } \hat{I}_{or} \rangle$	Reference $\hat{I}_{or}$ $I_o$ The total received power spectral density, including signal and interference, as measured at the UE antenna connector
$I_{oc}$	Power spectral density (integrated in a noise bandwidth equal to the chip rate and normalized to the chip rate) of a band limited white noise source (simulating interference from cells, which are not defined in a test procedure) as measured at the UE antenna connector
$I_{or}$	Total transmit power spectral density (integrated in a bandwidth of $(1 + \alpha)$ times the chip rate and normalized to the chip rate) of the downlink signal at the Node B antenna connector
$\hat{I}_{or}$	Received power spectral density (integrated in a bandwidth of $(1 + \alpha)$ times the chip rate and normalized to the chip rate) of the downlink signal as measured at the UE antenna connector
$\beta_c$	Gain factor for DPCCCH
$\beta_d$	Gain factor for DPDCH
$\beta_{hs}$	Gain factor for HS-DPCCCH
$\beta_{ec}$	Gain factor for E-DPCCCH
$\beta_{ed}$	Gain factor for E-DPDCH

### 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

4C-HSDPA	4 Carrier HSDPA
<REFSENS>	Reference sensitivity
AC	Access Channel
ACLR	Adjacent Channel Leakage power Ratio
ACS	Adjacent Channel Selectivity
BER	Bit Error Ratio
CA	Carrier Aggregation
CDMA	Code Division Multiple Access
CEPT	European Conference of Postal and Telecommunications administrations
CLTD	Closed Loop Transmit Diversity
CW	Continuous Wave

NOTE: Unmodulated signal.

DB-DC-HSDPA	Dual Band Dual Cell HSDPA
DCH	Dedicated Channel

NOTE: Which is mapped into Dedicated Physical Channel.

DC-HSUPA	Dual Cell HSUPA
DL	Downlink
DPCCH	Dedicated Physical Control CHannel
DPCH	Dedicated Physical CHannel
DPDCH	Dedicated Physical Data CHannel
E-DCH	Enhanced Dedicated CHannel
E-DPCCH	Enhanced DPCCH
E-DPDCH	Enhanced DPDCH
E-UTRA	Evolved Universal Terrestrial Radio Access
EC	European Commission
ECC	Electronic Communications Committee
EFTA	European Free Trade Association
EMC	ElectroMagnetic Compatibility
ERM	Electromagnetic compatibility and Radio spectrum Matters
EU	European Union
EUT	Equipment Under Test
FDD	Frequency Division Duplex
FRC	Fixed Reference Channel
GMSK	Gaussian Minimum Shift Keying
GSM	Global System for Mobile
HSDPA	High Speed Downlink Packet Access
HS-DPCCH	High Speed DPCCH
HSUPA	High Speed Uplink Packet Access
IEC	International Electrotechnical Commission
IMT	International Mobile Telecommunications
LTE	Long Term Evolution
MPR	Maximum Power Reduction
MSG	Mobile Standards Group
OCNS	Orthogonal Channel Noise Simulator

NOTE: A mechanism used to simulate the users or control signals on the other orthogonal channels of a downlink.

OLTD	Open Loop Transmit Diversity
PCH	Paging Channel
PN	PseudoNoise
PSD	Power Spectral Density
QPSK	Quadrature Phase Shift Keying
RF	Radio Frequency
RRC	Root Raised Cosine