

---

---

**Fuel cell road vehicles — Maximum  
speed measurement**

*Véhicules routiers à pile à combustible — Mesure de la vitesse  
maximale*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/TR 11954:2008](https://standards.iteh.ai/catalog/standards/sist/3a30ad15-0993-4863-a6c3-32de68e91fd5/iso-tr-11954-2008)

<https://standards.iteh.ai/catalog/standards/sist/3a30ad15-0993-4863-a6c3-32de68e91fd5/iso-tr-11954-2008>



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO/TR 11954:2008

<https://standards.iteh.ai/catalog/standards/sist/3a30ad15-0993-4863-a6c3-32de68e91fd5/iso-tr-11954-2008>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In exceptional circumstances, when a technical committee has collected data of a different kind from that which is normally published as an International Standard ("state of the art", for example), it may decide by a simple majority vote of its participating members to publish a Technical Report. A Technical Report is entirely informative in nature and does not have to be reviewed until the data it provides are considered to be no longer valid or useful.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any of all such patent rights.

ISO/TR 11954 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 21, *Electrically propelled road vehicles*.

<https://standards.iteh.ai/catalog/standards/sist/3a30ad15-0993-4863-a6c3-32de68e91fd5/iso-tr-11954-2008>

## Introduction

Fuel cell vehicles (FCV) include the following types:

- pure fuel cell vehicles (PFCV), in which the fuel cell system is the only on-board energy source for propulsion and auxiliary systems,
- fuel cell hybrid electric vehicles (FCHEV), in which the fuel cell system is integrated with an on-board rechargeable energy storage system (RESS) for electric energy supply to propulsion and auxiliary systems.

FCHEV design options include the following:

- a) externally chargeable or non-externally chargeable;
- b) rechargeable energy storage system (RESS): battery or capacitor;
- c) driver-selected operating modes: if FCHEV has no driver-selected operating mode, it has only an FCHEV mode.

Table 1 shows the classification of FCHEV.

STANDARD PREVIEW  
(standards.iteh.ai)

Table 1 — FCHEV classification

	Chargeability	Operating mode
<b>FCHEV</b>	externally chargeable	FCHEV mode
		EV mode
	non-externally chargeable	FCHEV mode
		EV mode

This Technical Report is applicable to PFCV and to non-externally chargeable FCHEV with FCHEV mode only (see shaded boxes in Table 1).

# Fuel cell road vehicles — Maximum speed measurement

## 1 Scope

This Technical Report describes test procedures for measuring the maximum road speed of fuel cell passenger cars and light duty trucks which use compressed hydrogen and which are not externally chargeable, in accordance with national or regional standards or legal requirements.

## 2 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

### 2.1

#### rechargeable energy storage system

##### RESS

system that stores energy for delivery of electric energy and that is rechargeable

EXAMPLE Batteries, capacitors.

### 2.2

#### RESS state of charge

[ISO/TR 11954:2008](#)

#### RESS SOC

residual capacity of RESS available to be discharged

NOTE RESS state of charge is normally expressed as a percentage of full charge.

### 2.3

#### fuel cell hybrid electric vehicle operation mode

##### FCHEV operation mode

mode of an FCHEV in which both RESS and fuel cell system are used sequentially or simultaneously for vehicle propulsion

NOTE The fuel cell system can also charge the RESS during propulsion or standstill.

### 2.4

#### maximum speed

highest average speed that the vehicle can maintain throughout a specified test

### 2.5

#### test mass

mass of a vehicle prepared for a defined test procedure

### 3 Parameters, units and accuracy of measurements

Table 2 shows parameters and their units and accuracy.

**Table 2 — Parameters, units and accuracy of measurements**

Parameter	Unit	Accuracy
Time	s	± 0,1 s
Distance	m	± 0,1 %
Air temperature	°C or K	± 1 °C or ± 1 °K
Air pressure	kPa	± 1 kPa
Speed	km/h	± 1 % or ± 0,1 km/h whichever is greater
Mass	kg	± 0,5 %

### 4 Descriptions

#### 4.1 General

The maximum speed of the vehicle should be measured in accordance with the descriptions in this clause.

#### 4.2 Preparation of the vehicle

The configuration of the vehicle and its attitude should be as determined by the manufacturer. In addition, the vehicle should be clean, the windows and air entries should be closed and only the accessories necessary for the operation of the vehicle for the purposes of the test should be in use. The viscosity of the oils for the mechanical moving parts and the tyre pressures (for operation under full load at maximum speed) should conform to the specifications of the vehicle manufacturer.

The running in of the transmission and tyres should be carried out in accordance with the manufacturer's instructions.

The fuel used should be the commercial grade for the type of vehicle tested or, in the event of a dispute, one of those prescribed in ISO/TS 14687-2.

#### 4.3 Track characteristics

##### 4.3.1 General

The measurements should be taken on a straight track (see 4.3.2) and/or a loop track (see 4.3.3). The surface of the track should be hard, smooth, clean and dry, and should give good adhesion.

##### 4.3.2 Measurement on straight track

###### 4.3.2.1 Lengths

The length,  $L$ , in metres, should be selected in relation to the precision of the apparatus and the method used for measuring the time,  $t$ , of the run, in seconds, so that the actual speed can be determined to within ± 1 %. The length of the measuring zone should be at least 1 000 m. The length actually used for the measurement should be recorded in the test report.

#### 4.3.2.2 Stabilizing zone

The stabilizing zone should be of the same nature as the measuring zone, approximately straight and of sufficient length for the vehicle to have stabilized at its maximum speed by the time the vehicle reaches the measuring zone.

#### 4.3.2.3 Slopes

##### 4.3.2.3.1 Longitudinal

In the stabilizing and the measuring zones, the longitudinal slope should not exceed 0,5 %.

##### 4.3.2.3.2 Transverse

Transverse slope should not exceed 3 % in the measuring zone.

#### 4.3.2.4 Section of loop track

A section of loop track may be regarded as "straight" if

- the descriptions of 4.3.1 to 4.3.2.3.1 are satisfied, and
- the centrifugal inertia reaction is less than 20 % of the initial mass of the vehicle and is compensated by the transverse slope of the track.

#### 4.3.3 Measurement on loop track

##### 4.3.3.1 Lengths

The length of the loop should be not less than 2 000 m. To calculate the maximum speed, the length of run should be the distance actually covered by the vehicle.

The loop track should be a convex curve and may vary from a perfect circle to straight sections linked by approximately circular sections. The radius of curves should be not less than 200 m. The effects of centrifugal force should be compensated by the transverse profile of the curves in such a way that the vehicle holds a normal line without any action on the steering wheel.

##### 4.3.3.2 Correction factor for loop track

A correction factor determined experimentally by the procedure given in UNECE R 68, Annex 3, or by national or regional standards, or legal requirements, may be applied for loop track. This correction factor should be subject to confirmation by the administrative service at the time of approval by the technical service responsible for the tests. The factor may in no case entail a correction exceeding 5 %. However, for vehicles equipped with a speed regulator, the factor should not be applied if the regulator is in operation during the test.

## 4.4 Atmospheric conditions

### 4.4.1 Air density

The air density at the time of the test, calculated by Equation (1), should not vary by more than 7,5 % from the air density in the reference conditions.

The air density in test conditions,  $d_r$ , should be calculated as follows:

$$d_r = d_0 \times \frac{H_T}{H_0} \times \frac{T_0}{T_T} \quad (1)$$

where

$d_0$  is the air density in reference conditions;

$H_T$  is the pressure during the test;

$T_T$  is the absolute temperature during the test, in kelvins;

$H_0$  is the pressure at reference conditions [ $H_0 = 100$  kPa];

$T_0$  is the temperature at reference conditions [ $T_0 = 293$  K (20 °C)].

In addition, the atmospheric pressure during the tests should be at least 91 kPa and temperature should be at least 278 K (5 °C).

STANDARD PREVIEW  
(standards.iteh.ai)

### 4.4.2 Wind

The average wind speed measured at a height of 1 m above the ground should be less than 3 m/s. Gusts should be less than 5 m/s.

ISO/TR 11954:2008

32de68e91fd5/iso-tr-11954-2008

### 4.4.3 Relative humidity

The relative humidity should be less than 95 % and the track should be dry.

## 4.5 Test method

### 4.5.1 Warming up

Immediately before the test, the parts of the vehicle that might affect the measurement should be in the stable temperature conditions specified by the manufacturer.

During measurement, the gear ratio used should be that in which the vehicle is able to reach its maximum steady speed. The accelerator should be fully depressed.

### 4.5.2 RESS state of charge preconditioning

RESS SOC should be conditioned in accordance with the vehicle manufacturer's procedure.



### 4.5.3 Test procedures for maximum speed measurement on a straight track

#### 4.5.3.1 Standard test procedure (Two direction test)

In order to reduce the influence of factors such as road slope and wind direction/speed, the test should be executed in both directions of the test track in direct sequence, taking care to use the same stretch of the track.

The time,  $t_i$ , taken to cover the measured length,  $L$ , should be recorded. It should be checked that the speed does not vary by more than 2 % at any moment during the run.

This procedure should be carried out at least three times in each direction. The variation between the extreme values of the six " $t_i$ " values recorded should not exceed 3 %.

Time,  $t$ , expressed in seconds, should be determined by Equation (2):

$$t = \frac{1}{6} \sum_{i=1}^6 t_i \quad (2)$$

and the test speed,  $V$ , expressed in kilometres per hour, should be determined by Equation (3):

$$V = \frac{3,6L}{t} \quad (3)$$

#### 4.5.3.2 Single direction test

Testing in one direction only should be permissible if, in view of the characteristics of the circuit, it is not possible for the vehicle to reach its maximum speed in both directions.

In this case, the characteristics of the track should be as set out in 4.3.1 and 4.3.2. In addition:

- the variation in altitude should not exceed 1 m between any two points;
- the run should be repeated five times in immediate succession;
- the axial wind component speed should not exceed 2 m/s.

The maximum speed,  $V_i$ , should be determined by the correction formula in Equation (4), taking into account wind speed:

$$V_i = V_r \pm (V_v \times f) \quad (4)$$

where

$V_r$  is the maximum speed measured for each run ( $V_r = 3,6L/t$ );

$v$  is the axial wind component, in metres per second;

$V_v$  is the axial wind component, in kilometres per hour ( $V_v = 3,6v$ );

$f$  is the correction factor ( $f = 0,6$ ).

NOTE See UNECE R 68 for further details about the correction factor.