

INTERNATIONAL STANDARD

ISO
20898

First edition
2008-11-15

Industrial trucks — Electrical requirements

Chariots de manutention — Exigences électriques

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 20898:2008](#)

<https://standards.iteh.ai/catalog/standards/iso/7d44d1be-2594-4468-80a4-0f22da263759/iso-20898-2008>



Reference number
ISO 20898:2008(E)

© ISO 2008

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh Standards

(<https://standards.iteh.ai>)

Document Preview

[ISO 20898:2008](#)

<https://standards.iteh.ai/catalog/standards/iso/7d44d1be-2594-4468-80a4-0f22da263759/iso-20898-2008>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 List of hazards	3
5 Requirements	5
5.1 Electrical requirements for battery powered trucks	5
5.2 Electrical requirements for internal combustion trucks	11
6 Verification of battery powered trucks	12
6.1 Insulation resistance testing (routine test)	12
6.2 Type testing	13
7 Information for use	16
7.1 Minimum markings for electric trucks	16
7.2 Charging area	17
7.3 Minimum marking internal combustion trucks	18
Bibliography	19

ITEH Standards

Document Preview

ISO 20898:2008

<https://standards.iteh.ai/catalog/standards/iso/7d44d1be-2594-4468-80a4-0f22da263759/iso-20898-2008>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 20898 was prepared by Technical Committee ISO/TC 110, *Industrial trucks*, Subcommittee SC 2, *Safety of powered industrial trucks*.

iTeh Standards (<https://standards.iteh.ai>) Document Preview

[ISO 20898:2008](#)

<https://standards.iteh.ai/catalog/standards/iso/7d44d1be-2594-4468-80a4-0f22da263759/iso-20898-2008>

Industrial trucks — Electrical requirements

1 Scope

This International Standard specifies the electrical requirements for the design and manufacture of self-propelled industrial trucks including masted and variable reach rough terrain trucks (see ISO 5053:1987, 3.1.3.1.8), and tow tractors with a rated drawbar pull up to and including 20 000 N. This International Standard applies to trucks with battery voltages in accordance with ISO 1044. For additional requirements of trucks with mains power, see IEC 60204-1.

This International Standard does not apply to

- trucks used in potentially explosive atmospheres, or
- issues related to electromagnetic compatibility.

This International Standard does not repeat all the technical rules which are state of the art and which are applicable to the material used to construct the industrial truck, for which reference can be made to ISO 12100-2.

ISO 12100-2: (https://standards.iteh.ai)

2 Normative references Document Preview

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1044, Industrial trucks — Lead-acid traction batteries for electric trucks — Preferred voltages

ISO 12100-2, *Safety of machinery — Basic concepts, general principles for design — Part 2: Technical principles*

ISO 14121-1. Safety of machinery — Risk assessment — Part 1: Principles

ISO 13849-1, *Safety of machinery — Safety-related parts of control systems — Part 1: General principles for design*

EN 50272-3. Safety requirements for secondary batteries and battery installations — Part 3: Traction batteries

IEC 60204-1:2005, *Safety of machinery — Electrical equipment of machines — Part 1: General Requirements*

IEC 60947-5-1, Low-voltage switchgear and control gear — Part 5-1: Control circuit devices and switching elements — Electromechanical control circuit devices

IEC 60384-14, *Fixed capacitors for use in electronic equipment — Part 14: Sectional specification: Fixed capacitors for electromagnetic interference suppression and connection to the supply mains*

IEC 60529, Degrees of protection provided by enclosures (IP Code)

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

arcing part

mechanical device that interrupts current during operation

3.2

auxiliary circuit

electrical circuit that controls lights, fans and other accessories

3.3

battery compartment

compartment on the truck that houses the battery

3.4

battery enclosure

container or tray that houses the individual cells

3.5

control circuit

electrical circuitry that controls truck movement

3.6

deactivate

make inactive or ineffective.

3.7

direct contact

contact of person with live parts

3.8

electrical enclosure

compartment on a truck that houses uninsulated live electrical components

[ISO 20898:2008](https://standards.iteh.ai)

<https://standards.iteh.ai/iso-20898-2008>

3.9

electrical or electronic steering

system where input is not mechanically connected to output

3.10

exposed conductive part

conductive part of electrical equipment, which can be touched and which is not normally live, but which may become live under fault condition

3.11

frame fault

accidental connection of a live part to the truck structure

3.12

indirect contact

contact of persons with exposed conductive parts which have become live under fault conditions

3.13

live part

conductor or conductive part intended to be energized in normal use

3.14**nominal current**

current in amperes that the electrical system is able to carry continuously without exceeding the allowable temperature indicated

3.15**nominal voltage (of the truck system)**

total number of battery cells connected in series in the truck's system multiplied by the nominal cell voltage

3.16**power circuit**

electrical circuitry that supplies the motors which cause truck movement, i.e. traction, steering and lifting

3.17**rated operating current**

I_e

value of current which is determined by the conditions of use of the contactor

3.18**rated thermal current**

I_{th}

value of current which determines the temperature rise conditions of the main circuit in the absence of any closing or opening operation of the contacts

3.19**risk of fire**

any device that has a surface temperature greater than 175 °C or that emits sparks outside of its enclosure

iTeh Standards

(<https://standards.iteh.ai>)

Document Preview

3.20**routine test**

test required for all production trucks

3.21**type test**

[ISO 20898:2008](#)

<http://www.iteh.ai/iso-20898-2008-1/iso-14121-1/iso-14121-5/7344111-2594-4468-80-4-022da263759/iso-20898-2008>

4 List of hazards

Table 1 contains all the significant hazards, hazardous situations and events, as far as they are dealt with in this International Standard, from ISO 14121-1:2007, Annex A and referenced in brackets, and are applicable in the situations described and could involve risks to persons if not addressed. The corresponding requirements offer guidance to limit the risk or reduce the hazard in each situation.

Table 1 — List of significant hazards, hazardous situations and hazardous events

Hazard		Corresponding requirements	
1	Mechanical hazards	5.1.11	Slack chains
	Crushing hazard (1.1)	5.1.12	Low voltage
	— between truck components	5.1.14	Controls — General
	— between truck and obstacles	5.1.15	Controls — Travel
	Impact by collision (20)	5.1.16	Controls — Load handling
	— when driven by the operator	5.1.17	Controls — Steering
	Loss of stability (18)	5.1.18	Contactors
	— from excess speed	7.1	Minimum marking electric trucks
	— from faulty battery mass	7.3	Minimum marking IC trucks
2	Electrical hazards	5.1.1	Traction batteries
	Electric shock (2.1)	5.1.2	Battery leads
	Overloading	5.1.3	Battery connectors
	— all voltages	5.1.4	Battery charging
		5.1.5	Emergency switching off requirements
		5.1.6	Design construction
		5.1.8	Wiring and wire construction
		5.1.9	Electrical shock protection
		5.1.13	Overcurrent protective devices
		5.2.1	Battery
		5.2.2	Circuit protection
		5.2.3	Control systems
		5.2.4	Wiring and wire construction
		5.2.5	Electrical shock protection
		6.2.1	Abnormal operation
	120 V < voltages \leq 240 V	5.1.1	Traction batteries
		5.1.7	Trucks with nominal voltage exceeding 120 V dc
3	Thermal hazards	6.2.2	Temperature
7	Material/substance hazards	5.1.1	Traction batteries
	Battery electrolyte	5.1.2	Battery leads
	Fire or explosion hazard (all voltages)	5.1.3	Battery connectors
		5.1.4	Battery charging
		5.1.5	Emergency switching off requirements
		5.1.6	Design construction
		6.1	Insulation resistance testing
		6.2.1	Abnormal operation

Table 1 (continued)

Hazard		Corresponding requirements	
		6.2.3	Arc rupture
		6.2.5	Connector testing
		6.2.6	Contactor testing
	120 V < voltages ≤ 240 V	5.2.8	Trucks with nominal voltage exceeding 120 V dc
		7.1	Minimum marking electric trucks
		7.3	Minimum marking IC trucks
4.5	Ergonomic hazards (8)	7.1	Minimum marking electric trucks
4.5.1	Human error (8.6)	7.3	Minimum marking IC trucks
4.6	Hazards due to functional disorders (10)	5.2.13 5.2.15	Low voltage Controls — General
4.6.1	Failure of energy supply	5.2.16	Controls — Travels
4.6.2	Failure of control system	5.2.17	Controls — Load handling
4.6.3	Loss of machine stability	5.2.18	Control — Steering
		5.2.19	Contactors
		5.3.2	Circuit protection
		5.3.3	Control systems

(https://standards.iteh.ai)

5 Requirements

Document Preview

5.1 Electrical requirements for battery powered trucks

ISO 20898:2008

<http://standards.iteh.ai/standards/iso/7d44d1be-2594-4468-80a4-0f22da263759/iso-20898-2008>

5.1.1.1 All trucks shall be equipped with an insulated battery.

5.1.1.2 Cells assembled in metal containers shall be insulated from each other.

5.1.1.3 The cell connections shall be such that the potential between any two adjacent cells cannot be more than 24 V dc nominal.

5.1.1.4 For battery terminals, measures shall be taken to reduce risk of a connection coming loose causing arcing or overheating.

5.1.1.5 On trucks equipped with an on-board battery charger, the battery terminals shall be protected by insulating boots or covers.

Exception No. 1: A terminal that is intentionally connected to ground on the truck frame need not be provided with a boot or cover.

Exception No. 2: This requirement does not apply to on-board battery chargers complying with 5.1.1.6 equipped with a ground-fault circuit interrupter or an isolated output.

5.1.1.6 When trucks are fitted with on-board chargers the requirements in IEC 60204-1:2005, 6.3 up to and including 6.3.2, 7.2.1 and 8 up to and including 8.2 shall apply. The enclosure containing equipment connected to the mains supply shall be IPxxB of IEC 60529. However, for top surfaces the degree of protection shall be at least IPxxD.

5.1.1.7 For batteries with nominal voltages exceeding 120 V dc, the battery enclosure shall be lockable or facilities shall be provided so that the battery compartment can be secured to prevent unauthorized access to the battery if a lockable cover is not present on the battery enclosure.

5.1.1.8 For batteries with nominal voltages exceeding 120 V dc the following protective measures against indirect contact can be selected:

- a) protective electrical insulation or;
- b) protection by earth - free equipotential bonding or;
- c) protection by automatic disconnection or signalling.

5.1.1.9 A battery enclosure where the battery nominal voltage exceeds 120 V dc shall be:

- a) metal and lined with a material bonded to the metal that is impervious to the electrolyte or,
- b) constructed of an insulating material.

5.1.2 Battery leads

5.1.2.1 A battery lead for battery nominal voltage up to and including 120 V dc shall be:

- a) acceptable for application due to cross section of wires and thickness of insulation (see IEC 60227-1 and IEC 60245-1);
- b) insulated with a suitable material rated for the temperatures and voltages of the truck;
- c) resistant to the electrolyte;
- d) able to withstand flexing, handling, and impact at temperatures referenced in 5.1.3.2;
- e) average insulation thickness shall not be less than 1,5 mm for a wire less than or equal to 35 mm² and shall not be less than 2 mm for a wire greater than 35 mm².

5.1.2.2 A battery lead where the battery nominal voltage exceeds 120 V dc shall meet the requirements of IEC 60204-1:2005.

5.1.3 Battery connectors

5.1.3.1 If a battery connector is installed, one part of the connector shall be permanently mounted to either the truck or the battery enclosure. The length of the cable attached to the free part of the connector shall be as short as practicable, without interfering with the connector mating, operational efficiency or disconnecting operations and without placing stress on terminals and leads. (See 5.1.2.)

5.1.3.2 The battery connector shall be rated for the voltage of the battery and be designed for use in the application and shall be resistant to battery electrolyte and battery gases. Connectors shall have a minimum temperature rating of -20 °C to +90 °C and comply with the tests defined in 6.2.5.

5.1.3.3 The connector shall be designed so that opposite polarities can not be coupled together. Different operating voltages shall be indicated either by colour or by a coding device to prevent charger/battery/truck mismatch.

5.1.3.4 The half-connector connected permanently to the battery shall be protected against the accidental contact of persons with energized parts. Live parts shall be recessed from the face of the connectors. For battery voltage greater than 60 V dc, protection shall be IP2X or higher, in accordance with IEC 60529.

5.1.3.5 When the two half-connectors are coupled their enclosure shall provide a degree of protection IP23, in accordance with IEC 60529.