Designation: F1548 – 01 (Reapproved 2006)

An American National Standard

Standard Specification for Performance of Fittings for Use with Gasketed Mechanical Couplings Used in Piping Applications¹

This standard is issued under the fixed designation F1548; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification defines classification, materials, test requirements, inspection certification, marking and packaging of fittings for use with gasketed mechanical couplings complying to Specification F1476.

2. Referenced Documents

2.1 ASTM Standards:²

Note 1—See Table 1 for equivalency listing of applicable, equivalent specifications.

A47/A47M Specification for Ferritic Malleable Iron Castings

A48/A48M Specification for Gray Iron Castings

A53/A53M Specification for Pipe, Steel, Black and Hot-Dipped, Zinc-Coated, Welded and Seamless

A153/A153M Specification for Zinc Coating (Hot-Dip) on

Iron and Steel Hardware

A216/A216M Specification for Steel Castings, Carbon,
Suitable for Fusion Welding, for High-Temperature Ser-

vice
A234/A234M Specification for Piping Fittings of Wrought

Carbon Steel and Alloy Steel for Moderate and High

A312/A312M Specification for Seamless, Welded, and Heavily Cold Worked Austenitic Stainless Steel Pipes

A395/A395M Specification for Ferritic Ductile Iron Pressure-Retaining Castings for Use at Elevated Temperatures

A403/A403M Specification for Wrought Austenitic Stainless Steel Piping Fittings

A536 Specification for Ductile Iron Castings

TABLE 1 Specification Equivalency Table

Spec. Ref.	U.S. Designation	British	ISO
Number	ASTM	Standard	Standard
1	A47/A47M	6681	5922
2	A48/A48M	1452	_
3	A53/A53M	3601	_
4	A153/A153M	729	1459, 1460, 1461
5	A216/A216M	3100	_
6	A234/A234M	1640 Pt. 1	_
7	A312/A312M	3605	_
8	A395/A395M	_	_
9	A403/A403M	1640 Pt. 2	_
10	A536	4772	2531, 4179, 8179
11	A743/A743M	3100	_
12	B26/B26M	1490	3522, 7722
13	B75	2871	_
14	B210	1471	209
15	B369	3071	_
16	B580	_	_
17 1	B584	1400	_
18	B633	1706	2081
	ANSI		
	710.		
19	B 36.10	3600	4200
20	B 36.19	3600	4200
2006)	Z 540.1	5781	_
	ANSI/AWWA		
1547 5100			
22	C151/A21.51	4772	2531, 4179, 8179
23	C606-87	_	_

A743/A743M Specification for Castings, Iron-Chromium, Iron-Chromium-Nickel, Corrosion Resistant, for General Application

B26/B26M Specification for Aluminum-Alloy Sand Castings

B75 Specification for Seamless Copper Tube

B210 Specification for Aluminum and Aluminum-Alloy Drawn Seamless Tubes

B369 Specification for Copper-Nickel Alloy Castings

B580 Specification for Anodic Oxide Coatings on Aluminum

B584 Specification for Copper Alloy Sand Castings for General Applications

¹ This practice is under the jurisdiction of ASTM Committee F25 on Ships and Marine Technology and is the direct responsibility of Subcommittee F25.11 on Machinery and Piping Systems.

Current edition approved Dec. 1, 2006. Published January 2007. Originally approved in 1994. Last previous edition approved in 2001 as F1548-01. DOI: 10.1520/F1548-01R06.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

- B633 Specification for Electrodeposited Coatings of Zinc on Iron and Steel
- F1476 Specification for Performance of Gasketed Mechanical Couplings for Use in Piping Applications
- 2.2 ANSI Standards:³
- B 36.10 Welded and Seamless Wrought Steel Pipe
- B 36.19 Stainless Steel Pipe
- Z 540.1 Calibration Laboratories in Measuring Test Equipment
- 2.3 ANSI/AWWA Standards:³
- C151/A21.51 Ductile-Iron Pipe, Centrifugally Cast in Metal Molds or Sand-Lined Molds, for Water and Other Liquids
- C606–87 Grooved and Shouldered Joints
- 2.4 British Standards:⁴
- BS 729 Specification for Hot Dip Galvanized Coatings on Iron and Steel Articles
- BS 1400 Specification for Copper Alloy Ingots and Copper Alloy and High Conductivity Copper Castings
- BS 1452 Specification for Flake Graphite Cast Iron
- BS 1471 Specification for Wrought Aluminum and Aluminum Alloys for General Engineering Purposes—Drawn Tube
- BS 1490 Specification for Aluminum and Aluminum Alloy Ingots and Castings for General Engineering Purposes
- BS 1640 Pt. 1 Wrought Carbon and Ferritic Alloy Steel Fittings
- BS 1640 Pt. 2 Wrought and Cast Austenitic Chromium—Nickel Steel Fittings
- BS 1706 Method for Specifying Electroplated Coatings of Zinc and Cadmium on Iron and Steel
- BS 2871 Specification for Copper and Copper Alloys— Tubes
- BS 3071 Specification for Nickel—Copper Alloy Castings
- BS 3100 Specification for Steel Castings for General Engineering Purposes
- BS 3600 Specification for Dimensions of Steel Pipe for the Petroleum Industry
- BS 3601 Specification for Carbon Steel Pipes and Tubes with Specified Room Temperature Properties for Pressure Purposes
- BS 3605 Austenitic Stainless Steel Pipes and Tubes for Pressure Purposes
- BS 4772 Specification for Ductile Iron Pipes and Fittings
- BS 5781 Measurement and Calibration System
- BS 6681 Specification for Malleable Cast Iron
- 2.5 International Standards Organization:⁵
- 209 Composition of Wrought Products of Aluminum and Aluminum Alloys . . . Chemical Composition (Percent)
- 1459 Metallic Coatings—Protection Against Corrosion by Hot Dip Galvanizing—Guiding Principles
- 1460 Metallic Coatings—Hot Dip Galvanized Coatings on Ferrous Materials—Determination of the Mass Per Unit
- ³ Available from American National Standards Institute (ANSI), 25 W. 43rd St., 4th Floor, New York, NY 10036, http://www.ansi.org.
- ⁴ Available from British Standards Institute (BSI), 389 Chiswick High Rd., London W4 4AL, U.K., http://www.bsi-global.com.
- ⁵ Available from International Organization for Standardization (ISO), 1 rue de Varembé, Case postale 56, CH-1211, Geneva 20, Switzerland, http://www.iso.ch.

- Area—Gravimetric Method
- 1461 Metallic Coatings—Hot Dipped Galvanized Coatings on Fabricated Ferrous Products—Requirements
- 2081 Metallic Coatings—Electroplated Coatings of Zinc on Iron or Steel
- 2531 Ductile Iron Pipes, Fittings and Accessories for Pressure Pipe Lines
- 3522 Cast Aluminum Alloys—Chemical Composition and Mechanical Properties
- 4179 Ductile Iron Pipes for Pressure and Non-Pressure Pipelines—Centrifugal Cement Mortar Lining—General Requirements
- 4200 Plain End Steel Tubes, Welded and Seamless— General Tables of Dimensions and Masses Per Unit Length
- 5922 Malleable Cast Iron
- 7722 Aluminum Alloy Castings Produced by Gravity, Sand, or Chill Casting, or by Related Processes—General Conditions for Inspection and Delivery
- 8179 Ductile Iron Pipes—External Zinc Coating

3. Terminology

- 3.1 Definitions:
- 3.1.1 *fabricated fitting*—a fitting constructed by welding together sections of pipe or tube.
- 3.1.2 *fitting*—a device used in a piping system to change pipe direction, size, split or combine flows, or adapt to other joining methods.
- 3.1.3 *grooved end*—type of fitting or pipe end having a groove for use with grooved mechanical couplings (Type I) as defined in F1476.
- 3.1.4 *pipe*—hollow tubular product conforming to Table 1 Specification Reference Nos. 19, 20, 22 and 13, Nominal Dimensions, or O.D. tube.
- 3.1.5 *plain end*—type of fitting or pipe end for use with a gasketed mechanical coupling (Type II) that is plain end as defined in Specification F1476.
- 3.1.6 *tangent*—a section of straight pipe or tube integral to or welded to the end(s) of a fitting.
- 3.1.7 *wrought fitting*—a fitting made by shaping or shaping and welding.

4. Classification

- 4.1 These fittings are classified into the following design types:
 - 4.1.1 Type I—Grooved end.
 - 4.1.2 Type II—Plain end.

5. Ordering Information

- 5.1 Orders for fittings under this specification shall include the following:
- 5.1.1 Specification designation, title, number and year of issue.
 - 5.1.2 Quantity.
- 5.1.3 Size and appropriate suffix (Example 8 in. IPS, 76.1 mm O.D.).
 - 5.1.4 Fitting description (90° Elbow, Tee, Cross, etc.).