



Designation: D1882 – 96(Reapproved 2006)

Standard Test Method for Effect of Cooling System Chemical Solutions on Organic Finishes for Automotive Vehicles¹

This standard is issued under the fixed designation D1882; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method determines the effect of cooling system chemical solutions on organic finishes used on motor vehicles. Cooling system chemicals include: coolants or corrosion inhibitors, or both, cooling system cleaners or flushes, or both, and stop leak additives.

NOTE 1—This test method is a modification of Practice D1540.

1.2 The values stated in SI units are to be regarded as the standard. The values stated in parentheses are for information only.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*²

D609 Practice for Preparation of Cold-Rolled Steel Panels for Testing Paint, Varnish, Conversion Coatings, and Related Coating Products

D1176 Practice for Sampling and Preparing Aqueous Solutions of Engine Coolants or Antirusts for Testing Purposes

D1540 Method of Test for Effect of Chemical Agents on Organic Finishes Used in the Transportation Industry (Withdrawn 1992)³

3. Summary of Test Method

3.1 Concentrated or diluted cooling system chemical solutions are brought into contact with organic finishes typical of

¹ This test method is under the jurisdiction of ASTM Committee D15 on Engine Coolants and Related Fluids and is the direct responsibility of Subcommittee D15.03 on Physical Properties.

Current edition approved Nov. 1, 2006. Published January 2007. Originally approved in 1961. Last previous edition approved in 2001 as D1882 – 96(2001). DOI: 10.1520/D1882-96R06.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The last approved version of this historical standard is referenced on www.astm.org.

those used on automobiles for 1 h at room temperature. The surface of the finish then is inspected visually for any of the surface changes mentioned in Section 4.

4. Significance and Use

4.1 This test method will distinguish between cooling system chemical solutions that do or do not have a tendency to change the surface appearance when applied to organic finishes used on vehicles. Such changes may be manifested by discoloration, loss of gloss, softening, swelling, or other similar phenomena.

5. Materials

5.1 *Test Panels*—Steel panels, approximately 100 by 150 mm (4 by 6 in.) shall be prepared in accordance with the Methods of Preparation of Practice D609. The surface of the test panels shall be roughened to 0.25 to 0.50 μm (10 to 20 $\mu\text{in.}$) prior to applying the organic finish. These panels shall be coated with an organic finish of the type used on vehicles such as clear coated and non-clear coated thermoset urethane and acrylic urethane finishes. Other finishes may be used upon agreement between the customer and supplier.

6. Test Solution

6.1 The coolant to be tested shall be either a concentrate or a dilution. Sufficient ASTM Type IV water shall be added to yield a solution of 50 % concentration by volume in accordance with Test Method D1176, section on Preparation of Solutions Requiring Inclusion of Separated Solids and Liquids. Any separated solids or liquids shall be included in the test material.

6.2 Other cooling system chemicals shall be tested both without dilution and at a typical use concentration as indicated by instructions on the label. Any separated solids or liquids shall be included in the test material.

7. Procedure

7.1 Conduct the test at $25 \pm 5^\circ\text{C}$ without humidity control.

7.2 Select a test panel prepared in accordance with Section 5. Place sufficient test solution on the surface of the test panel to form spots approximately 25 mm (1 in.) in diameter.