



**SLOVENSKI STANDARD**  
**SIST EN 301 489-15 V2.2.1:2019**  
**01-junij-2019**

---

**Standard elektromagnetne združljivosti (EMC) za radijsko opremo in storitve - 15. del: Posebni pogoji za komercialno dostopno amatersko radijsko opremo - Harmonizirani standard, ki zajema bistvene zahteve člena 3.1(b) direktive 2014/53/EU**

ElectroMagnetic Compatibility (EMC) standard for radio equipment and services - Part 15: Specific conditions for commercially available amateur radio equipment - Harmonised Standard covering the essential requirements of article 3.1(b) of Directive 2014/53/EU

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 301 489-15 V2.2.1:2019](https://standards.iteh.ai/catalog/standards/sist/05abce75-bc02-4c11-888b-1aed6eae3c3e/sist-en-301-489-15-v2-2-1-2019)  
<https://standards.iteh.ai/catalog/standards/sist/05abce75-bc02-4c11-888b-1aed6eae3c3e/sist-en-301-489-15-v2-2-1-2019>

**Ta slovenski standard je istoveten z: ETSI EN 301 489-15 V2.2.1 (2019-04)**

---

**ICS:**

|           |   |  |
|-----------|---|--|
| 33.060.20 | Sprejemna in oddajna oprema             | Receiving and transmitting equipment     |
| 33.100.01 | Elektromagnetna združljivost na splošno | Electromagnetic compatibility in general |

**SIST EN 301 489-15 V2.2.1:2019**      **en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 301 489-15 V2.2.1:2019](https://standards.iteh.ai/catalog/standards/sist/05abce75-bc02-4c11-888b-1aed6eae3c3e/sist-en-301-489-15-v2-2-1-2019)

<https://standards.iteh.ai/catalog/standards/sist/05abce75-bc02-4c11-888b-1aed6eae3c3e/sist-en-301-489-15-v2-2-1-2019>

# ETSI EN 301 489-15 V2.2.1 (2019-04)



**ElectroMagnetic Compatibility (EMC)  
standard for radio equipment and services;  
Part 15: Specific conditions for commercially available  
amateur radio equipment;  
Harmonised Standard covering the essential requirements  
of article 3.1(b) of Directive 2014/53/EU**

---

**Reference**

REN/ERM-EMC-372

---

**Keywords**

amateur, EMC, harmonised standard, radio

**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

---

**Important notice**

<https://standards.iteh.ai/catalog/standards/sist/05abce75-bc02-4c11-888b-1ac0c5a3a3/sist-011-489-15-v2-2-1-2019>  
The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

# Contents

|   |    |
|---|----|
| Intellectual Property Rights .....  | 5  |
| Foreword.....   | 5  |
| Modal verbs terminology.....  | 5  |
| 1 Scope .....   | 6  |
| 2 References .....  | 6  |
| 2.1 Normative references .....  | 6  |
| 2.2 Informative references.....   | 6  |
| 3 Definitions, symbols and abbreviations .....  | 7  |
| 3.1 Definitions .....   | 7  |
| 3.2 Symbols.....  | 7  |
| 3.3 Abbreviations .....   | 7  |
| 4 Test conditions .....   | 8  |
| 4.1 General .....   | 8  |
| 4.2 Arrangements for test signals .....   | 8  |
| 4.2.1 Arrangements for test signals at the input of transmitters.....                                     | 8  |
| 4.2.2 Arrangements for test signals at the output of transmitters.....                                    | 9  |
| 4.2.3 Arrangements for test signals at the input of receivers .....                                       | 9  |
| 4.2.4 Arrangements for test signals at the output of receivers .....                                      | 9  |
| 4.2.5 Arrangements for testing transmitter and receiver together (as a system) .....                      | 9  |
| 4.3 RF exclusion band of radio communications equipment.....  | 9  |
| 4.3.1 Exclusion band for receivers or the receiver part of transceivers .....                             | 9  |
| 4.3.2 Exclusion band for transmitters or the transmitter part of transceivers.....                        | 10 |
| 4.3.2.1 Exclusion band for EMC emission measurements .....  | 10 |
| 4.3.2.2 Exclusion band for immunity tests.....  | 10 |
| 4.4 Narrowband responses of receivers or receivers which are part of transceivers .....                   | 10 |
| 4.5 Normal test modulation .....  | 10 |
| 4.5.1 Transmitters .....  | 10 |
| 4.5.2 Receivers .....   | 11 |
| 4.5.3 RF amplifiers and transverters .....  | 11 |
| 5 Performance assessment.....   | 12 |
| 5.1 General .....   | 12 |
| 5.2 Equipment which can provide a continuous communications link .....                                    | 12 |
| 5.3 Equipment which does not provide a continuous communications link.....                                | 12 |
| 5.4 Ancillary equipment .....   | 12 |
| 5.5 Equipment classification .....  | 12 |
| 6 Performance criteria .....  | 13 |
| 6.0 Introduction .....  | 13 |
| 6.1 Performance criteria for primary user functions.....  | 13 |
| 6.1.0 Introduction.....   | 13 |
| 6.1.1 General performance criteria (primary user functions).....  | 14 |
| 6.1.2 Performance criteria A for continuous phenomena (primary user functions).....                       | 14 |
| 6.1.3 Performance criteria B for transient phenomena and short voltage dips (primary user functions)..... | 15 |
| 6.1.4 Performance criteria C for long voltage dips and interruptions (primary user functions).....        | 15 |
| 6.2 Performance criteria for secondary user functions .....   | 16 |
| 6.3 Performance criteria for equipment which does not provide a continuous communication link.....        | 16 |
| 6.4 Performance criteria for ancillary equipment tested on a stand alone basis .....                      | 16 |
| 7 Applicability overview tables.....  | 16 |
| 7.1 EMC Emission .....  | 16 |
| 7.1.1 General.....  | 16 |
| 7.1.2 Special conditions .....  | 17 |
| 7.2 Immunity .....  | 17 |
| 7.2.1 General.....  | 17 |

|                               |   |           |
|-------------------------------|---|-----------|
| 7.2.2                         | Special conditions .....  | 17        |
| <b>Annex A (informative):</b> | <b>Relationship between the present document and the essential requirements of Directive 2014/53/EU .....</b> | <b>18</b> |
| <b>Annex B (informative):</b> | <b>Examples of amateur radio equipment within the scope of the present document .....</b>                     | <b>20</b> |
| B.1                           | Amateur radio equipment which is commercially available .....   | 20        |
| <b>Annex C (informative):</b> | <b>Change history .....</b>   | <b>21</b> |
| History .....                 |   | 22        |

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 489-15 V2.2.1:2019](https://standards.iteh.ai/catalog/standards/sist/05abce75-bc02-4c11-888b-1aed6eae3c3e/sist-en-301-489-15-v2-2-1-2019)

<https://standards.iteh.ai/catalog/standards/sist/05abce75-bc02-4c11-888b-1aed6eae3c3e/sist-en-301-489-15-v2-2-1-2019>

## Intellectual Property Rights

### Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

### Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

## Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.4] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1]. <https://standards.iteh.ai/catalog/standards/sist/05abce75-bc02-4c11-888b-1aed6eae3c3e/sist-en-301-489-15-v2-2-1-2019>

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 15 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

| National transposition dates   |                 |
|--|-----------------|
| Date of adoption of this EN:   | 6 June 2017     |
| Date of latest announcement of this EN (doa):  | 31 July 2019    |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 31 January 2020 |
| Date of withdrawal of any conflicting National Standard (dow):                         | 31 January 2021 |

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

# 1 Scope

The present document, together with ETSI EN 301 489-1 [1], covers the assessment of commercially available amateur radio equipment, and associated ancillary equipment, in respect of ElectroMagnetic Compatibility (EMC).

Technical specifications related to the antenna port and emissions from the enclosure port of commercially available amateur radio equipment are not included in the present document. Such technical specifications are found in the relevant product standard ETSI EN 301 783 [i.2] for the effective use of the radio spectrum.

The present document specifies the applicable EMC tests, the methods of measurement, the limits and the performance criteria for radio equipment intended for use by radio amateurs within the meaning of article 1, definition 53 of the Radio Regulations [i.3] and associated ancillary equipment, which is commercially available.

Examples of amateur radio equipment covered by the present document are given in annex B.

The provisions of the present document apply to amateur radio equipment manufactured commercially either as ready-to-use equipment, modules, or components having an intrinsic functionality for the customer.

The expression "amateur radio equipment" in the context of the present document is taken to mean "commercially available amateur radio equipment" only.

In case of differences (for instance concerning special conditions, definitions, abbreviations) between the present document and ETSI EN 301 489-1 [1], the provisions of the present document take precedence.

The environment classification and the emission and immunity requirements used in the present document are as stated in ETSI EN 301 489-1 [1], except for any special conditions included in the present document. The applicable environments referred to in ETSI EN 301 489-1 [1] where equipment covered by the scope of the present document may be used, are to be declared by the manufacturer.

STANDARD PREVIEW  
(standards.iteh.ai)

---

## 2 References

SIST EN 301 489-15 V2.2.1:2019

<https://standards.iteh.ai/catalog/standards/sist/05abce75-bc02-4c11-888b-1aed6eae3c3e/sist-en-301-489-15-v2-2-1-2019>

### 2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 301 489-1 (V2.2.0) (03-2017): "ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements; Harmonised Standard covering the essential requirements of article 3.1(b) of Directive 2014/53/EU and the essential requirements of article 6 of Directive 2014/30/EU".

### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.



The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] ETSI EN 301 783 (V2.1.1) (01-2016): "Commercially available amateur radio equipment; Harmonised standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU".
- [i.3] ITU Radio Regulations (Edition of 2016).
- [i.4] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.

## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in ETSI EN 301 489-1 [1] and the following apply:

**maximum usable sensitivity:** minimum receiver Radio Frequency (RF) input signal level or field strength able to produce a specified analogue SINAD ratio or Bit Error Ratio (BER), or other specified output performance which depends on this input signal level

**multimode equipment:** amateur radio equipment capable of being used in several modes of operation, such as AM, FM, SSB

<https://standards.iteh.ai/catalog/standards/sist/05abce75-bc02-4c11-888b-1aed6eae3c3e/sist-en-301-489-15-v2-2-1-2019>

### 3.2 Symbols

For the purposes of the present document, the symbols given in ETSI EN 301 489-1 [1] and the following apply:

|                |   |
|----------------|---|
| F <sub>b</sub> | skirt bandwidth   |
| F <sub>c</sub> | centre frequency of the transmitter necessary bandwidth |
| F <sub>n</sub> | necessary bandwidth                                     |

### 3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI EN 301 489-1 [1] and the following apply:

|        |  |
|--------|--|
| AM     | Amplitude Modulation   |
| BER    | Bit Error Ratio  |
| DSB-SC | Double SideBand-Suppressed Carrier                             |
| EMC    | ElectroMagnetic Compatibility                                  |
| ESD    | ElectroStatic Discharge  |
| EUT    | Equipment Under Test   |
| FM     | Frequency Modulation   |
| HF     | High Frequency   |
| PEP    | Peak Envelope Power  |
| RF     | Radio Frequency  |
| SINAD  | Ratio of (Signal + Noise + Distortion) to (Noise + Distortion) |
| SSB    | Single SideBand  |
| UHF    | Ultra High Frequency   |
| VHF    | Very High Frequency  |

## 4 Test conditions

### 4.1 General

For the purposes of the present document, the test conditions of ETSI EN 301 489-1 [1], clause 4 shall apply as appropriate. Further product related test conditions for amateur radio and ancillary equipment are specified in the present document.

For emission and immunity tests, the test modulation, test arrangements, etc., as specified in the present document, clauses 4.1 to 4.5 of the present document shall apply.

The general test conditions for amateur radio equipment are as follows:

- transmitters and amplifiers shall be tested in stand-by (if applicable) and in transmit mode of operation;
- transceivers and transverters shall be tested in receive, stand-by, and transmit mode of operation;
- if integral antenna equipment provides an internal antenna connector for testing purposes, then the tests can be made via that connector.

The manufacturer shall recommend a power supply (e.g. an AC/DC power adapter) for use in conjunction with the equipment under test (EUT), to ensure satisfactory operation of the combination during the EMC tests. When a range of different types of power supply units can be used with several types of that manufacturer's radio equipment, then each type of power supply unit shall be tested with the radio providing the highest RF output Peak Envelope Power (PEP). These power supply units shall then be listed as preferred items for future generations of that manufacturer's radio equipment.

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

The EMC tests shall be performed with the EUT set to the following operation frequencies:

- single-band equipment:
  - test with the operation frequency set to the centre of the operation frequency band;
- double-band equipment:
  - test with the operation frequency set in sequence to the centre of each operation frequency band;
- HF multiband equipment or VHF/UHF multiband equipment:
  - test with the operation frequency set in sequence to the centre of the lowest, middle, and highest HF operation frequency band;
- HF/VHF, HF/UHF or HF/VHF/UHF combined equipment:
  - test with the operation frequency set in sequence to the centre of the lowest HF band, the middle HF band, the highest HF band, the lowest VHF/UHF band, the middle VHF/UHF band, and the centre of the highest VHF/UHF band.

### 4.2 Arrangements for test signals

#### 4.2.1 Arrangements for test signals at the input of transmitters

The provisions of ETSI EN 301 489-1 [1], clause 4.2.1 shall apply with the following modifications.

If possible, the transmitter should be modulated with a suitable signal, from an internal or external signal source. If it is not appropriate to get a modulated RF signal from the transmitter, then the tests may be performed using its unmodulated carrier.

It shall be possible to verify that a communications link is established and maintained.

## 4.2.2 Arrangements for test signals at the output of transmitters

The provisions of ETSI EN 301 489-1 [1], clause 4.2.2 shall apply with the following modifications.

The transmitter under test shall be modulated such that the maximum PEP output is achieved, either by single or multiple tones, or by a suitable bit stream, or in case of transmitters for other than analogue voice or data transmission, by a test modulation representative of normal use (see also clause 4.5). The manufacturer shall declare the normal test modulation.

Where thermal limitations prevent continuous transmission under such conditions, the tests may be performed using gated methods. Under these circumstances, the test method used shall be recorded in the test report.

## 4.2.3 Arrangements for test signals at the input of receivers

The provisions of ETSI EN 301 489-1 [1], clause 4.2.3 shall apply with the following modifications.

The receiver shall be provided with a wanted RF input signal chosen according to clause 4.2.3 of ETSI EN 301 489-1 [1] set to its operation frequency, and modulated with a suitable modulation signal fitting the communication system characteristics (see clause 4.5.2). If it is not appropriate to provide the receiver with a modulated wanted RF input signal, the test may be performed using an unmodulated wanted RF input signal.

If possible, the wanted RF input signal to establish a communications link shall be presented to the antenna connector by a coaxial cable. The wanted RF input signal shall be set to a nominal value of 60 dB (or a lower value as declared by the manufacturer) above the maximum usable sensitivity of the EUT, as declared by the manufacturer in the product documentation.

It shall be possible to verify that a communications link is established and maintained.

## 4.2.4 Arrangements for test signals at the output of receivers

The provisions of ETSI EN 301 489-1 [1], clause 4.2.4 shall apply.

## 4.2.5 Arrangements for testing transmitter and receiver together (as a system)

The provisions of ETSI EN 301 489-1 [1], clause 4.2.5 shall apply with the following modification.

These arrangements are only applicable for duplex transceivers. The wanted RF input signal, coupled to the receiver, shall be modulated with a suitable test signal (see clause 4.5.3). The transmitter shall be operated at its maximum PEP RF output, modulated with the test signal, coupled to the transmitter from the output of the receiver (repeater mode).

## 4.3 RF exclusion band of radio communications equipment

### 4.3.1 Exclusion band for receivers or the receiver part of transceivers

The exclusion band for a receiver and the receiver part of a transceiver is determined by the characteristics of the equipment.

For receivers operating on a fixed single frequency, the exclusion band extends from -5 % to +5 % of that fixed single operation frequency.

For receivers operating or capable of operating, on a number of spot frequencies in a narrow operating frequency band which is less than 20 % of the centre frequency of the operating band, the exclusion band extends from -5 % of the lowest frequency of the narrow operating frequency band to +5 % of the highest frequency of that band.

For receivers operating, or capable of operating on a number of spot frequencies over a wide frequency band, the exclusion band for each of the wanted RF signal test frequencies shall extend from -5 % to +5 % of each wanted RF signal test frequency.