



**Smart Cards;  
UICC-Terminal interface;  
Physical and logical characteristics  
(Release 14)**

iTeh Standards PREVIEW  
(standards.iteh.ai)  
<https://standards.iteh.ai/catalog/standards/sist/eb67512b-ec1f-4882-ab78-11017a0b026e/etsi-ts-102-221-v14.0.0-2017-02>

## Reference

---

RTS/SCP-T102221ve00

## Keywords

---

smart card

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**Important notice**

---

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at  
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.  
**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	12
Foreword.....	12
Modal verbs terminology.....	12
Introduction .....	13
1 Scope .....	14
2 References .....	14
2.1 Normative references .....	14
2.2 Informative references.....	15
3 Definitions, symbols, abbreviations and coding conventions .....	16
3.1 Definitions.....	16
3.2 Symbols.....	18
3.3 Abbreviations .....	18
3.4 Coding conventions .....	20
4 Physical characteristics.....	21
4.0 UICC Form Factors .....	21
4.0.0 Generic requirements.....	21
4.0.1 ID-1 UICC .....	21
4.0.2 Plug-in UICC.....	21
4.0.3 Mini-UICC.....	22
4.0.4 4FF.....	23
4.1 ID-1 UICC.....	24
4.2 Plug-in UICC.....	24
4.3 Mini-UICC .....	24
4.4 Environmental conditions for card operation and storage .....	24
4.4.0 Standard UICC environmental conditions.....	24
4.4.1 Specific UICC environmental conditions .....	24
4.4.1.0 Specific UICC environmental conditions indication.....	24
4.4.1.1 Temperature range for specific UICC environmental conditions.....	25
4.4.1.2 High humidity .....	25
4.5 Contacts.....	25
4.5.1 Provision of contacts.....	25
4.5.1.1 Terminal.....	25
4.5.1.2 UICC.....	25
4.5.2 Contact activation and deactivation .....	25
4.5.2.1 Contacts assigned by the present document .....	25
4.5.2.2 Optional contacts.....	26
4.5.3 Inactive contacts .....	26
4.5.4 Contact pressure.....	26
5 Electrical specifications of the UICC - Terminal interface .....	26
5.0 General requirements .....	26
5.1 Class A operating conditions.....	27
5.1.1 Supply voltage Vcc (contact C1) .....	27
5.1.2 Reset (RST) (contact C2).....	27
5.1.3 Programming voltage Vpp (contact C6) .....	27
5.1.4 Clock CLK (contact C3).....	28
5.1.5 I/O (contact C7) .....	28
5.2 Class B operating conditions .....	28
5.2.1 Supply voltage Vcc (contact C1) .....	28
5.2.2 Reset (RST) (contact C2).....	29
5.2.3 Clock CLK (contact C3).....	29
5.2.4 I/O (contact C7) .....	30
5.3 Class C operating conditions .....	30
5.3.1 Supply voltage Vcc (contact C1) .....	30

5.3.2	Reset (RST) (contact C2).....	31
5.3.3	Clock CLK (contact C3).....	31
5.3.4	I/O (contact C7).....	31
6	Initial communication establishment procedures.....	32
6.1	UICC activation and deactivation.....	32
6.2	Supply voltage switching.....	32
6.2.0	UICC activation voltage.....	32
6.2.1	Supply voltage classes.....	32
6.2.2	Power consumption of the UICC during ATR.....	32
6.2.3	Application related electrical parameters.....	32
6.3	Answer To Reset content.....	33
6.3.0	Introduction.....	33
6.3.1	Coding of historical bytes.....	34
6.3.2	Speed enhancement.....	34
6.3.3	Global Interface bytes.....	34
6.4	PPS procedure.....	35
6.5	Reset procedures.....	35
6.5.1	Cold reset.....	35
6.5.2	Warm reset.....	35
6.5.3	Reaction to resets.....	36
6.6	Clock stop mode.....	36
6.7	Bit/character duration and sampling time.....	36
6.8	Error handling.....	36
6.9	Compatibility.....	37
7	Transmission protocols.....	37
7.0	Introduction.....	37
7.1	Physical layer.....	38
7.2	Data link layer.....	38
7.2.0	Introduction.....	38
7.2.1	Character frame.....	38
7.2.1.0	Structure, coding and timing.....	38
7.2.1.1	Low impedance I/O line behaviour.....	39
7.2.2	Transmission protocol T = 0.....	39
7.2.2.0	Introduction.....	39
7.2.2.1	Timing and specific options for characters in T = 0.....	39
7.2.2.2	Command header.....	40
7.2.2.3	Command processing.....	40
7.2.2.3.0	General description.....	40
7.2.2.3.1	Procedure bytes.....	40
7.2.2.3.2	Status bytes.....	40
7.2.2.4	Error detection and correction.....	41
7.2.3	Transmission protocol T = 1.....	41
7.2.3.0	Introduction.....	41
7.2.3.1	Timing and specific options for blocks sent with T = 1.....	41
7.2.3.1.0	Introduction.....	41
7.2.3.1.1	Information field size.....	41
7.2.3.1.2	Character waiting integer.....	41
7.2.3.1.3	Character waiting time.....	41
7.2.3.1.4	Block waiting time.....	42
7.2.3.1.5	Block guard time.....	42
7.2.3.1.6	Waiting time extension.....	42
7.2.3.1.7	Error detection code.....	42
7.2.3.2	Block frame structure.....	42
7.2.3.2.0	Overall structure.....	42
7.2.3.2.1	Prologue field.....	43
7.2.3.2.2	Epilogue field.....	44
7.2.3.2.3	Block notations.....	45
7.2.3.3	Error free operation.....	45
7.2.3.4	Error handling for T = 1.....	46
7.2.3.4.0	General description.....	46

7.2.3.4.1	Protocol initialization .....	46
7.2.3.4.2	Block dependent errors.....	46
7.2.3.5	Chaining.....	47
7.2.3.5.0	Chaining Mechanism.....	47
7.2.3.5.1	Rules for chaining.....	47
7.3	Transport layer .....	47
7.3.0	Introduction.....	47
7.3.1	Transportation of an APDU using T = 0.....	47
7.3.1.0	Introduction.....	47
7.3.1.1	Mapping of APDUs to TPDUs.....	48
7.3.1.1.0	General behaviour .....	48
7.3.1.1.1	Case 1 .....	48
7.3.1.1.2	Case 2 .....	49
7.3.1.1.3	Case 3 .....	49
7.3.1.1.4	Case 4 .....	50
7.3.1.1.5	Use of procedure bytes '61xx' and '6Cxx'.....	51
7.3.2	Transportation of a APDU using T = 1.....	52
7.3.2.0	General mechanism.....	52
7.3.2.1	Case 1.....	52
7.3.2.2	Case 2.....	52
7.3.2.3	Case 3.....	53
7.3.2.4	Case 4.....	53
7.4	Application layer .....	53
7.4.0	Overall description.....	53
7.4.1	Exchange of APDUs.....	54
7.4.2	CAT layer .....	54
7.4.2.0	Overview.....	54
7.4.2.1	Proactive command.....	54
7.4.2.2	ENVELOPE Commands.....	55
7.4.3	Application execution.....	55
8	Application and file structure.....	56
8.1	UICC application structure.....	56
8.2	File types .....	56
8.2.0	Introduction.....	56
8.2.1	Dedicated files .....	57
8.2.2	Elementary files .....	57
8.2.2.1	Transparent EF.....	57
8.2.2.2	Linear fixed EF .....	57
8.2.2.3	Cyclic EF .....	57
8.2.2.4	BER-TLV structure EF .....	58
8.3	File referencing .....	58
8.4	Methods for selecting a file .....	58
8.4.0	Default state after UICC activation and ATR.....	58
8.4.1	SELECT by File Identifier referencing.....	59
8.4.2	SELECT by path referencing.....	60
8.4.3	Short File Identifier (SFI) .....	61
8.5	Application characteristics .....	61
8.5.0	Application selection types.....	61
8.5.1	Explicit application selection.....	61
8.5.1.1	SELECT by DF name .....	61
8.5.1.2	SELECT by partial DF name .....	62
8.5.2	Application session activation .....	62
8.5.3	Application session termination.....	62
8.5.4	Application session reset .....	63
8.5.5	Void.....	63
8.6	Reservation of file Ids .....	63
8.7	Logical channels.....	64
8.8	Shareable versus not-shareable files.....	65
8.9	Secure channels.....	65
9	Security features.....	66

9.0	Introduction .....	66
9.1	Supported security features .....	66
9.2	Security architecture.....	66
9.2.0	Overview and basic rules .....	66
9.2.1	Security attributes .....	67
9.2.2	Access mode .....	67
9.2.3	Security condition .....	67
9.2.4	Access rules .....	67
9.2.5	Compact format .....	68
9.2.6	Expanded format.....	68
9.2.7	Access rule referencing.....	68
9.3	Security environment .....	69
9.3.0	Description.....	69
9.3.1	Definition of the security environment .....	70
9.3.2	Logical Channels and Security Environment.....	70
9.4	PIN definitions .....	71
9.4.0	Introduction.....	71
9.4.1	Universal PIN .....	71
9.4.2	Application PIN .....	71
9.4.3	Local PIN.....	71
9.4.4	PINs and logical channels.....	71
9.5	PIN and key reference relationship .....	72
9.5.0	Introduction.....	72
9.5.1	Access condition mapping .....	72
9.5.2	PIN status indication .....	73
10	Structure of commands and responses .....	74
10.1	Command APDU .....	74
10.1.0	Structure and case .....	74
10.1.1	Coding of Class Byte .....	75
10.1.2	Coding of Instruction Byte .....	76
10.1.3	Coding of parameter bytes .....	77
10.1.4	Coding of Lc byte .....	77
10.1.5	Coding of data part .....	77
10.1.6	Coding of Le byte .....	77
10.2	Response APDU .....	77
10.2.0	Structure.....	77
10.2.1	Status conditions returned by the UICC .....	77
10.2.1.0	Introduction.....	77
10.2.1.1	Normal processing .....	78
10.2.1.2	Postponed processing .....	78
10.2.1.3	Warnings .....	78
10.2.1.4	Execution errors .....	78
10.2.1.5	Checking errors .....	79
10.2.1.5.0	Base checking errors.....	79
10.2.1.5.1	Functions in CLA not supported .....	79
10.2.1.5.2	Command not allowed.....	79
10.2.1.5.3	Wrong parameters .....	79
10.2.1.6	Application errors .....	80
10.2.2	Status words of the commands .....	81
10.3	Logical channels.....	83
11	Commands.....	83
11.1	Generic commands .....	83
11.1.0	Introduction.....	83
11.1.1	SELECT.....	83
11.1.1.1	Functional description.....	83
11.1.1.2	Command parameters and data .....	83
11.1.1.3	Response Data.....	84
11.1.1.3.0	Base coding .....	84
11.1.1.3.1	Response for MF, DF or ADF .....	85
11.1.1.3.2	Response for an EF.....	85

11.1.1.4	File control parameters.....	85
11.1.1.4.1	File size.....	85
11.1.1.4.2	Total file size.....	86
11.1.1.4.3	File Descriptor.....	86
11.1.1.4.4	File identifier.....	87
11.1.1.4.5	DF name.....	87
11.1.1.4.6	Proprietary information.....	87
11.1.1.4.7	Security attributes.....	91
11.1.1.4.8	Short file identifier.....	93
11.1.1.4.9	Life cycle status integer.....	93
11.1.1.4.10	PIN status template DO.....	93
11.1.2	STATUS.....	94
11.1.2.1	Functional description.....	94
11.1.2.2	Command parameters.....	94
11.1.3	READ BINARY.....	95
11.1.3.1	Functional description.....	95
11.1.3.2	Command parameters.....	95
11.1.4	UPDATE BINARY.....	95
11.1.4.1	Functional parameters.....	95
11.1.4.2	Command parameters and data.....	96
11.1.5	READ RECORD.....	96
11.1.5.1	Functional description.....	96
11.1.5.2	Command parameters.....	97
11.1.6	UPDATE RECORD.....	97
11.1.6.1	Functional description.....	97
11.1.6.2	Command parameters and data.....	98
11.1.7	SEARCH RECORD.....	98
11.1.7.1	Functional description.....	98
11.1.7.2	Command parameters and data.....	99
11.1.8	INCREASE.....	100
11.1.8.1	Functional description.....	100
11.1.8.2	Command parameters and data.....	100
11.1.9	VERIFY PIN.....	101
11.1.9.1	Functional description.....	101
11.1.9.1.1	PIN verification.....	101
11.1.9.1.2	PIN retry counter.....	101
11.1.9.2	Void.....	102
11.1.9.3	Command parameters.....	102
11.1.10	CHANGE PIN.....	102
11.1.10.1	Functional description.....	102
11.1.10.2	Command parameters.....	103
11.1.11	DISABLE PIN.....	103
11.1.11.1	Functional description.....	103
11.1.11.2	Command parameters.....	104
11.1.12	ENABLE PIN.....	104
11.1.12.1	Functional description.....	104
11.1.12.2	Command parameters.....	105
11.1.13	UNBLOCK PIN.....	105
11.1.13.1	Functional description.....	105
11.1.13.1.1	PIN unblocking.....	105
11.1.13.1.2	UNBLOCK PIN retry counter.....	106
11.1.13.2	Void.....	106
11.1.13.3	Command parameters.....	106
11.1.14	DEACTIVATE FILE.....	106
11.1.14.1	Functional description.....	106
11.1.14.2	Command parameters.....	107
11.1.15	ACTIVATE FILE.....	107
11.1.15.1	Functional description.....	107
11.1.15.2	Command parameters.....	107
11.1.16	AUTHENTICATE.....	108
11.1.16.1	Functional description.....	108
11.1.16.2	Command parameters and data.....	109

11.1.17	MANAGE CHANNEL.....	110
11.1.17.1	Functional description.....	110
11.1.17.2	Command parameters and data .....	111
11.1.18	GET CHALLENGE.....	111
11.1.18.1	Functional description.....	111
11.1.18.2	Command parameters and data .....	112
11.1.19	TERMINAL CAPABILITY .....	112
11.1.19.1	Functional description.....	112
11.1.19.2	Command parameters and data .....	112
11.1.19.2.0	Base coding .....	112
11.1.19.2.1	Terminal power supply.....	113
11.1.19.2.2	Extended logical channels terminal support.....	113
11.1.19.2.3	Additional interfaces support.....	113
11.1.19.2.4	Additional Terminal capability indications related to eUICC .....	114
11.1.20	MANAGE SECURE CHANNEL.....	114
11.1.20.1	General functional description .....	114
11.1.20.2	Retrieve UICC Endpoints .....	115
11.1.20.2.0	Introduction .....	115
11.1.20.2.1	Functional description .....	115
11.1.20.2.2	Command parameters and data.....	116
11.1.20.3	Establish SA - Master SA .....	117
11.1.20.3.0	Introduction .....	117
11.1.20.3.1	Functional description .....	118
11.1.20.3.2	Command parameters and data.....	118
11.1.20.4	Establish SA - Connection SA .....	120
11.1.20.4.0	Introduction .....	120
11.1.20.4.1	Functional description .....	120
11.1.20.4.2	Command parameters and data.....	120
11.1.20.5	Establish SA - Start Secure Channel.....	122
11.1.20.5.0	Introduction .....	122
11.1.20.5.1	Functional description.....	122
11.1.20.5.2	Command parameters and data.....	122
11.1.20.6	Terminate Secure Channel SA .....	123
11.1.20.6.0	Introduction .....	123
11.1.20.6.1	Functional description .....	124
11.1.20.6.2	Command parameters and data.....	124
11.1.21	TRANSACT DATA .....	125
11.1.21.1	General functional description .....	125
11.1.21.2	Command parameters and data .....	126
11.1.22	SUSPEND UICC .....	128
11.1.22.1	Functional description.....	128
11.1.22.2	UICC suspension.....	128
11.1.22.2.1	Introduction .....	128
11.1.22.2.2	Functional description .....	128
11.1.22.2.3	Command parameters and data.....	129
11.1.22.3	UICC resume.....	129
11.1.22.3.1	Introduction .....	129
11.1.22.3.2	Functional description .....	130
11.1.22.3.3	Command parameters and data.....	130
11.2	CAT commands.....	131
11.2.1	TERMINAL PROFILE.....	131
11.2.1.1	Functional description.....	131
11.2.1.2	Command parameters and data .....	131
11.2.2	ENVELOPE.....	131
11.2.2.1	Functional description.....	131
11.2.2.2	Command parameters and data .....	131
11.2.3	FETCH.....	132
11.2.3.1	Functional description.....	132
11.2.3.2	Command parameters and data .....	132
11.2.4	TERMINAL RESPONSE.....	132
11.2.4.1	Functional description.....	132
11.2.4.2	Command parameters and data .....	132

11.3	Data Oriented commands .....	133
11.3.0	Overview and generic mechanism .....	133
11.3.1	RETRIEVE DATA .....	134
11.3.1.1	Functional description .....	134
11.3.1.2	Command parameters and data .....	135
11.3.2	SET DATA .....	135
11.3.2.1	Functional description .....	135
11.3.2.2	Command parameters and data .....	136
12	Transmission oriented commands .....	137
12.1	T = 0 specific commands .....	137
12.1.1	GET RESPONSE .....	137
12.1.1.1	Functional description .....	137
12.1.1.2	Command parameters .....	137
13	Application independent files .....	138
13.1	EF <sub>DIR</sub> .....	138
13.2	EF <sub>ICCID</sub> (ICC Identification) .....	139
13.3	EF <sub>PL</sub> (Preferred Languages) .....	140
13.4	EF <sub>ARR</sub> (Access Rule Reference) .....	140
13.5	DF <sub>CD</sub> (Configuration Data) .....	140
13.5.0	Introduction .....	140
13.5.1	EF <sub>LAUNCH PAD</sub> .....	141
13.5.2	EF <sub>ICON</sub> .....	144
13.6	EF <sub>UMPC</sub> (UICC Maximum Power Consumption) .....	145
14	Application independent protocol .....	146
14.1	File related procedures .....	146
14.1.1	Reading an EF .....	146
14.1.2	Updating an EF .....	146
14.1.3	Increasing an EF .....	146
14.2	PIN related procedures .....	147
14.2.0	Overview .....	147
14.2.1	PIN verification .....	147
14.2.2	PIN value substitution .....	147
14.2.3	PIN disabling .....	148
14.2.4	PIN enabling .....	148
14.2.5	PIN unblocking .....	148
14.3	Application selection procedures .....	148
14.3.1	Application selection by use of the EF <sub>DIR</sub> file .....	148
14.3.2	Direct application selection .....	149
14.3.3	Direct application selection with partial AID .....	149
14.4	General application related procedures .....	149
14.4.1	Application session activation .....	149
14.4.2	UICC application interrogation .....	149
14.4.3	UICC application session termination .....	149
14.5	Miscellaneous procedures .....	149
14.5.1	UICC activation .....	149
14.5.2	UICC presence detection .....	149
14.5.3	UICC preferred language request .....	150
14.5.4	UICC logical channels .....	150
14.5.5	Power negotiation .....	150
14.5.6	UICC suspension .....	150
14.6	CAT related procedures .....	150
14.6.0	Scope of CAT related procedures in ETSI TS 102 221 .....	150
14.6.1	CAT Initialization procedure .....	150
14.6.2	Proactive polling .....	151
14.6.3	Support of commands .....	151
14.6.4	Support of response codes .....	151
14.6.5	Independence of applications and CAT tasks .....	151
14.6.6	Use of BUSY status response .....	151
14.6.7	Additional processing time .....	151

15	Support of APDU-based UICC applications over USB .....	151
<b>Annex A (normative):</b>	<b>UCS2 coding of Alpha fields for files residing on the UICC .....</b>	<b>153</b>
<b>Annex B (informative):</b>	<b>Main states of a UICC .....</b>	<b>155</b>
<b>Annex C (informative):</b>	<b>APDU protocol transmission examples.....</b>	<b>156</b>
C.1	Exchanges Using T = 0 .....	156
C.1.0	Overview .....	156
C.1.1	Case 1 command .....	156
C.1.2	Case 2 command .....	156
C.1.3	Case 3 command .....	157
C.1.4	Case 4 command .....	157
C.1.5	Case 2 commands Using the '61' and '6C' procedure bytes .....	157
C.1.6	Case 4 command Using the '61' procedure byte .....	158
C.1.7	Case 4 command with warning condition .....	158
<b>Annex D (informative):</b>	<b>ATR examples .....</b>	<b>159</b>
<b>Annex E (informative):</b>	<b>Security attributes mechanisms and examples.....</b>	<b>161</b>
E.1	Coding .....	161
E.2	Compact format .....	161
E.2.0	Coding .....	161
E.2.1	AM byte .....	161
E.2.2	SC byte .....	161
E.2.3	Examples .....	162
E.3	Expanded format .....	162
E.3.0	Coding .....	162
E.3.1	AM_DO .....	162
E.3.2	SC_DO .....	162
E.3.3	Access rule referencing .....	163
E.3.4	Examples .....	163
<b>Annex F (informative):</b>	<b>Example of contents of EF<sub>ARR</sub> '2F06' .....</b>	<b>164</b>
F.1	Sample content of the EF <sub>ARR</sub> .....	164
<b>Annex G (informative):</b>	<b>Access Rules Referencing (ARR).....</b>	<b>165</b>
G.1	Sample content of EF <sub>ARR</sub> .....	165
G.2	Example of access rule referencing with SE ID .....	168
<b>Annex H (normative):</b>	<b>List of SFI Values assigned in ETSI TS 102 221 .....</b>	<b>169</b>
H.1	List of SFI Values at the MF Level .....	169
<b>Annex I (informative):</b>	<b>Resets and modes of operation .....</b>	<b>170</b>
<b>Annex J (informative):</b>	<b>Example of the use of PINs .....</b>	<b>171</b>
J.1	Application having several ADFs .....	171
J.2	Two applications with two different security contexts.....	171
<b>Annex K (informative):</b>	<b>Examples of the PIN state transition on multi verification capable UICC .....</b>	<b>172</b>
K.0	Context .....	172
K.1	PIN state transition on the single logical channel .....	172
K.2	PIN state transition between logical channels .....	174

**Annex L (informative): Examples of SET DATA and RETRIEVE DATA usage.....178**  
L.1 Examples of SET DATA and RETRIEVE DATA usage .....178  
L.2 Examples of RETRIEVE DATA usage with transport protocol T = 0 .....179

**Annex M (informative): Examples of ODD AUTHENTICATE instruction code usage .....182**  
M.1 Examples of ODD AUTHENTICATE instruction code usage at applicative level.....182  
M.2 Examples of ODD AUTHENTICATE instruction code usage with transport protocol T = 0.....183

**Annex N (informative): Change history .....186**  
History .....190

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/eb67512b-ec1f-4882-ab78-11017a0bd26e/etsi-ts-102-221-v14.0.0-2017-02>

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Smart Card Platform (SCP).

It is based on work originally done in the 3GPP in TSG-terminals WG3.

The contents of the present document are subject to continuing work within TC SCP and may change following formal TC SCP approval. If TC SCP modifies the contents of the present document, it will then be republished by ETSI with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 0 early working draft;
  - 1 presented to TC SCP for information;
  - 2 presented to TC SCP for approval;
  - 3 or greater indicates TC SCP approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

# Introduction

The present document defines a generic Terminal/Integrated Circuit Card (ICC) interface.

The aim of the present document is to ensure interoperability between an ICC and a terminal independently of the respective manufacturer, card issuer or operator. The present document does not define any aspects related to the administrative management phase of the ICC. Any internal technical realization of either the ICC or the terminal is only specified where these are reflected over the interface.

Application specific details for applications residing on an ICC are specified in the respective application specific documents. The Universal Subscriber Identity Module (USIM)-application for 3G telecommunication networks is specified in ETSI TS 131 102 [2].

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/eb67512b-ec1f-4882-ab78-11017a0bd26e/etsi-ts-102-221-v14.0.0-2017-02>