



**Speech and multimedia Transmission Quality (STQ);
Transmission requirements for wideband
VoIP terminals (handset and headset)
from a QoS perspective as perceived by the user**

Full Standard
iTech Standards
(standards.iteh.ai)
Full Standard
https://standards.iteh.ai/catalog/standards/sis/6612357-74c7-4da9-86d2-96e8d8b686b6/etsi-202-739-v1-7-1-2017-09

ReferenceRES/STQ-258

Keywordsquality, speech, telephony, terminal, VoIP,
wideband

ETSI650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	5
Introduction	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	7
3 Definitions and abbreviations.....	8
3.1 Definitions.....	8
3.2 Abbreviations	8
4 General considerations	9
4.1 Coding algorithm.....	9
4.2 End-to-end considerations	9
5 Test equipment	10
5.1 IP half channel measurement adaptor.....	10
5.2 Environmental conditions for tests	10
5.3 Accuracy of measurements and test signal generation.....	10
5.4 Network impairment simulation.....	11
5.5 Acoustic environment.....	12
5.6 Influence of terminal delay on measurements.....	12
6 Requirements and associated measurement methodologies.....	12
6.1 Notes	12
6.2 Test setup.....	13
6.2.1 General.....	13
6.2.2 Setup for handsets and headsets.....	13
6.2.3 Position and calibration of HATS.....	14
6.2.4 Test signal levels.....	14
6.2.5 Setup of background noise simulation.....	14
6.2.6 Setup of variable echo path.....	14
6.3 Coding independent parameters	15
6.3.1 Send frequency response	15
6.3.2 Send Loudness Rating (SLR).....	16
6.3.3 Mic mute.....	17
6.3.4 Linearity range for SLR.....	17
6.3.5 Send distortion	18
6.3.6 Out-of-band signals in send direction	19
6.3.7 Send noise.....	19
6.3.8 SideTone Masking Rating STMR (mouth to ear)	20
6.3.9 Sidetone delay.....	20
6.3.10 Terminal Coupling Loss (TCL)	21
6.3.11 Stability loss.....	22
6.3.12 Receive frequency response.....	23
6.3.13 Receive Loudness Rating (RLR)	25
6.3.14 Receive distortion	26
6.3.15 Out-of-band signals in receive direction	27
6.3.16 Minimum activation level and sensitivity in receive direction	27
6.3.17 Receive noise	27
6.3.18 Automatic level control in receive	28
6.3.19 Double talk performance	28
6.3.19.1 General	28
6.3.19.2 Attenuation range in send direction during double talk $A_{H,S,dt}$	28

6.3.19.3	Attenuation range in receive direction during double talk $A_{H,R,dt}$	29
6.3.19.4	Detection of echo components during double talk	30
6.3.19.5	Minimum activation level and sensitivity of double talk detection.....	31
6.3.20	Switching characteristics	31
6.3.20.1	Note.....	31
6.3.20.2	Activation in send direction	32
6.3.20.3	Silence suppression and comfort noise generation.....	32
6.3.21	Background noise performance	32
6.3.21.1	Performance in send in the presence of background noise.....	32
6.3.21.2	Speech quality in the presence of background noise.....	33
6.3.21.3	Quality of background noise transmission (with far end speech).....	34
6.3.22	Quality of echo cancellation	34
6.3.22.1	Temporal echo effects.....	34
6.3.22.2	Spectral echo attenuation	35
6.3.22.3	Occurrence of artefacts	36
6.3.22.4	Variable echo path.....	36
6.3.23	Variant impairments; network dependant	36
6.3.23.1	Clock accuracy send.....	36
6.3.23.2	Clock accuracy receive	36
6.3.23.3	Send packet delay variation.....	37
6.3.24	Send and receive delay - round trip delay	37
6.4	Codec specific requirements.....	40
6.4.1	Objective listening speech quality MOS-LQO in send direction.....	40
6.4.2	Objective listening quality MOS-LQO in receive direction	41
6.4.3	Quality of jitter buffer adjustment	43
Annex A (informative):	Processing delays in VoIP terminals.....	45
Annex B (informative):	Optimum frequency responses for wideband transmission in receive direction - underlying subjective experiments	48
Annex C (informative):	Bibliography.....	50
History		51

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This ETSI Standard (ES) has been produced by ETSI Technical Committee Speech and multimedia Transmission Quality (STQ).

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

Traditionally, the analogue and digital telephones were interfacing switched-circuit 64 kbit/s PCM networks. With the fast growth of IP networks, wideband terminals providing higher audio-bandwidth and directly interfacing packet-switched networks (VoIP) are being rapidly introduced. Such IP network edge devices may include gateways, specifically designed IP phones, soft phones or other devices connected to the IP based networks and providing telephony service. Since the IP networks will be in many cases interworking with the traditional PSTN and private networks, many of the basic transmission requirements have to be harmonised with specifications for traditional digital terminals. However, due to the unique characteristics of the IP networks including packet loss, delay, etc. New performance specification, as well as appropriate measuring methods, will have to be developed. Terminals are getting increasingly complex, advanced signal processing is used to address the IP specific issues.

The advanced signal processing of terminals is targeted to speech signals. Therefore, wherever possible speech signals are used for testing in order to achieve mostly realistic test conditions and meaningful results.

The present document provides speech transmission performance requirements for wideband VoIP handset and headset terminals.

NOTE: Requirement limits are given in tables, the associated curve when provided is given for illustration.

1 Scope

The present document provides speech transmission performance requirements for 8 kHz wideband VoIP handset and headset terminals; it addresses all types of IP based terminals, including wireless and soft phones.

In contrast to other standards which define minimum performance requirements it is the intention of the present document to specify terminal equipment requirements which enable manufacturers and service providers to enable good quality end-to-end speech performance as perceived by the user.

In addition to basic testing procedures, the present document describes advanced testing procedures taking into account further quality parameters as perceived by the user.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Recommendation ITU-T G.107: "The E-model, a computational model for use in transmission planning".
- [2] Recommendation ITU-T G.108: "Application of the E-model: A planning guide".
- [3] Recommendation ITU-T G.109: "Definition of categories of speech transmission quality".
- [4] Void.
- [5] Recommendation ITU-T G.722: "7 kHz audio-coding within 64 kbit/s".
- [6] Recommendation ITU-T G.722.1: "Low-complexity coding at 24 and 32 kbit/s for hands-free operation in systems with low frame loss".
- [7] Recommendation ITU-T G.729.1: "G.729 based Embedded Variable bit-rate coder: An 8-32 kbit/s scalable wideband coder bitstream interoperable with G.729".
- [8] Recommendation ITU-T P.56: "Objective measurement of active speech level".
- [9] Recommendation ITU-T P.57: "Artificial ears".
- [10] Recommendation ITU-T P.58: "Head and torso simulator for telephonometry".
- [11] Recommendation ITU-T P.64: "Determination of sensitivity/frequency characteristics of local telephone systems".
- [12] Recommendation ITU-T P.79: "Calculation of loudness ratings for telephone sets".
- [13] Recommendation ITU-T P.340: "Transmission characteristics and speech quality parameters of hands-free terminals".
- [14] Recommendation ITU-T P.380: "Electro-acoustic measurements on headsets".
- [15] Recommendation ITU-T P.501: "Test signals for use in telephonometry".

- [16] Recommendation ITU-T P.502: "Objective test methods for speech communication systems using complex test signals".
- [17] Recommendation ITU-T P.581: "Use of head and torso simulator (HATS) for hands-free terminal testing".
- [18] IEC 61260-1: "Electroacoustics - Octave-band and fractional-octave-band filters - Part 1: Specifications".
- [19] TIA-920.130-A: "Telecommunications Telephone Terminal Equipment Transmission Requirements for Wideband Digital Wireline Telephones with Headset".
- [20] ETSI TS 103 224: "Speech and multimedia Transmission Quality (STQ); A sound field reproduction method for terminal testing including a background noise database".
- [21] Recommendation ITU-T P.863: "Perceptual objective listening quality assessment".
- [22] Recommendation ITU-T P.863.1: "Application Guide for Recommendation ITU-T P.863".
- [23] ETSI ES 202 737: "Speech and multimedia Transmission Quality (STQ); Transmission requirements for narrowband VoIP terminals (handset and headset) from a QoS perspective as perceived by the user".
- [24] Recommendation ITU-T P.1010: "Fundamental voice transmission objectives for VoIP terminals and gateways".
- [25] Recommendation ITU-T G.722.2: "Wideband coding of speech at around 16 kbit/s using Adaptive Multi-Rate Wideband (AMR-WB)".
- [26] IETF RFC 3550: "RTP: A Transport Protocol for Real-Time Applications".
- [27] Recommendation ITU-T G.122: "Influence of national systems on stability and talker echo in international connections".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EG 201 377-1: "Speech and multimedia Transmission Quality (STQ); Specification and measurement of speech transmission quality; Part 1: Introduction to objective comparison measurement methods for one-way speech quality across networks".
- [i.2] ETSI EG 202 425: "Speech Processing, Transmission and Quality Aspects (STQ); Definition and implementation of VoIP reference point".
- [i.3] ETSI EG 202 396-3: "Speech and multimedia Transmission Quality (STQ); Speech Quality performance in the presence of background noise; Part 3: Background noise transmission - Objective test methods".
- [i.4] Recommendation ITU-T P.800.1: "Mean Opinion Score (MOS) Terminology".
- [i.5] NIST Net™.

NOTE: Available at <https://www-x.antd.nist.gov/itg/nistnet/>.

[i.6] Netem™.

NOTE: Available at <http://www.linuxfoundation.org/en/Net:Netem>.

[i.7] DAGA 2008: "Testing Wideband Terminals", March 10-13, Dresden, Proceedings. Poschen S., Kettler F., Raake A., Spors S.

[i.8] Trace Control for Netem (TCN): A. Keller, "Trace Control for Netem", Semester Thesis SA-2006-15, ETH Zürich, 2006.

[i.9] ETSI ES 202 739 (V1.2.1): "Speech and multimedia Transmission Quality (STQ); Transmission requirements for wideband VoIP terminals (handset and headset) from a QoS perspective as perceived by the user".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

artificial ear: device for the calibration of earphones incorporating an acoustic coupler and a calibrated microphone for the measurement of the sound pressure and having an overall acoustic impedance similar to that of the median adult human ear over a given frequency band

codec: combination of an analogue-to-digital encoder and a digital-to-analogue decoder operating in opposite directions of transmission in the same equipment

diffuse field equalization: equalization of the HATS sound pick-up, equalization of the difference, in dB, between the spectrum level of the acoustic pressure at the ear Drum Reference Point (DRP) and the spectrum level of the acoustic pressure at the HATS Reference Point (HRP) in a diffuse sound field with the HATS absent using the reverse nominal curve given in table 3 of Recommendation ITU-T P.58 [10].

ear-Drum Reference Point (DRP): point located at the end of the ear canal, corresponding to the ear-drum position

freefield reference point: point located in the free sound field, at least in 1,5 m distance from a sound source radiating in free air (in case of a head and torso simulator (HATS) in the centre of the artificial head with no artificial head present)

Head And Torso Simulator (HATS) for telephonometry: manikin extending downward from the top of the head to the waist, designed to simulate the sound pick-up characteristics and the acoustic diffraction produced by a median human adult and to reproduce the acoustic field generated by the human mouth

Mouth Reference Point (MRP): point located on axis and 25 mm in front of the lip plane of a mouth simulator

nominal setting of the volume control: when a receive volume control is provided, the setting which is closest to the nominal RLR of 2 dB

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AM-FM	Amplitude Modulation-Frequency Modulation
AMR-WB	Adaptive Multi Rate - Wideband
CS	Composite Source
CSS	Composite Source Signal
DRP	ear Drum Reference Point
EC	Echo Canceller
ELR	Echo Loudness Rating
ERP	Ears Reference Point
ETH	Eidgenössische Technische Hochschule
FFT	Fast Fourier Transform

G-MOS-LQOw	Overall transmission quality wideband
GSM	Global System for Mobile communications
HATS	Head And Torso Simulator
HRP	HATS Reference Point
IEC	International Electrotechnical Commission
IP	Internet Protocol
IPDV	IP Packet Delay Variation
ITU-T	International Telecommunication Union -Telecommunication standardization sector
MOS	Mean Opinion Score
MOS-LQOy	Mean Opinion Score - Listening Quality Objective

NOTE: y being N for narrow-band, M for mixed and S for superwideband. See Recommendation ITU-T P.800.1 [i.4].

MRP	Mouth Reference Point
NIST	National Institute of Standards and Technology
NLP	Non Linear Processor
N-MOS-LQOw	Transmission quality of the background noise wideband
PBX	Private Branch eXchange
PC	Personal Computer
PCM	Pulse Code Modulation
POI	Point Of Interconnect
PSTN	Public Switched Telephone Network
QoS	Quality of Service
RLR	Receive Loudness Rating
RMS	Root Mean Square
RTP	Real Time Protocol
SLR	Send Loudness Rating
S-MOS-LQOw	Transmission quality of the speech wideband
STMR	SideTone Masking Rating
TCL	Terminal Coupling Loss
TCN	Trace Control for Netem
TDM	Time Division Multiplex
TOSQA	Telecommunication Objective Speech Quality Assessment
VAD	Voice Activity Detection
VoIP	Voice over IP

4 General considerations

4.1 Coding algorithm

The assumed coding algorithm is according to Recommendation ITU-T G.722 [5]. VoIP terminals may support other coding algorithms.

NOTE: Associated Packet Loss Concealment, e.g. as defined in Recommendation ITU-T G.722 [5], Appendixes 3 and 4 should be used.

4.2 End-to-end considerations

In order to achieve a desired end-to-end speech transmission performance (mouth-to-ear) it is recommended that the general rules of transmission planning are carried out with the E-model of Recommendation ITU-T G.107 [1] taking into account that the E-model does not yet address wideband transmission planning; this includes the a-priori determination of the desired category of speech transmission quality as defined in Recommendation ITU-T G.109 [3].

While, in general, the transmission characteristics of single circuit-oriented network elements, such as switches or terminals can be assumed to have a single input value for the planning tasks of Recommendation ITU-T G.108 [2], this approach is not applicable in packet based systems and thus there is a need for the transmission planner's specific attention.

In particular the decision as to which delay measured according to the present document should be acceptable or representative for the specific configuration is the responsibility of the individual transmission planner.

Recommendation ITU-T G.108 [2] with its amendments provides further guidance on this important issue.

The following optimum terminal parameters from a user's perspective need to be considered:

- minimized delay in send and receive direction;
- optimum loudness Rating (RLR, SLR);
- compensation for network delay variation;
- packet loss recovery performance;
- maximized terminal coupling loss.

5 Test equipment

5.1 IP half channel measurement adaptor

The IP half channel measurement adaptor is described in ETSI EG 202 425 [i.2].

5.2 Environmental conditions for tests

The following conditions shall apply for the testing environment:

- a) ambient temperature: 15 °C to 35 °C (inclusive);
- b) relative humidity: 5 % to 85 %;
- c) air pressure: 86 kPa to 106 kPa (860 mbar to 1 060 mbar).

5.3 Accuracy of measurements and test signal generation

Unless specified otherwise, the accuracy of measurements made by test equipment shall be equal to or better than:

Table 1: Measurement accuracy

Item	Accuracy
Electrical signal level	±0,2 dB for levels ≥ -50 dBV ±0,4 dB for levels < -50 dBV
Sound pressure	±0,7 dB
Frequency	±0,2 %
Time	±0,2 %
Application force	±2 N
Measured maximum frequency	20 kHz

NOTE: The measured maximum frequency is due to Recommendation ITU-T P.58 limitations [10].

Unless specified otherwise, the accuracy of the signals generated by the test equipment shall be better than:

Table 2: Accuracy of test signal generation

Quantity	Accuracy
Sound pressure level at Mouth Reference Point (MRP)	±3 dB for frequencies from 100 Hz to 200 Hz ±1 dB for frequencies from 200 Hz to 4 000 Hz ±3 dB for frequencies from 4 000 Hz to 14 000 Hz
Electrical excitation levels	±0,4 dB across the whole frequency range
Frequency generation	±2 % (see note)
Time	±0,2 %
Specified component values	±1 %
NOTE: This tolerance may be used to avoid measurements at critical frequencies, e.g. those due to sampling operations within the terminal under test.	

For terminal equipment which is directly powered from the mains supply, all tests shall be carried out within ±5 % of the rated voltage of that supply. If the equipment is powered by other means and those means are not supplied as part of the apparatus, all tests shall be carried out within the power supply limit declared by the supplier. If the power supply is a.c., the test shall be conducted within ±4 % of the rated frequency.

5.4 Network impairment simulation

At least one set of requirements is based on the assumption of an error free packet network, and at least one other set of requirements is based on a defined simulated malperformance of the packet network.

An appropriate network simulator has to be used, for example NIST Net™ [i.5] (<https://www-x.antd.nist.gov/itg/nistnet/>) or Netem [i.6].

Based on the positive experience STQ have made during the ETSI Speech Quality Test Events with "NIST Net™" this will be taken as a basis to express and describe the variations of packet network parameters for the appropriate tests.

Here is a brief blurb about NIST Net™:

- The NIST Net™ network emulator is a general-purpose tool for emulating performance dynamics in IP networks. The tool is designed to allow controlled, reproducible experiments with network performance sensitive/adaptive applications and control protocols in a simple laboratory setting. By operating at the IP level, NIST Net can emulate the critical end-to-end performance characteristics imposed by various wide area network situations (e.g. congestion loss) or by various underlying subnetwork technologies (e.g. asymmetric bandwidth situations of xDSL and cable modems).
- NIST Net™ is implemented as a kernel module extension to the Linux™ operating system and an X Window System-based user interface application. In use, the tool allows an inexpensive PC-based router to emulate numerous complex performance scenarios, including: tunable packet delay distributions, congestion and background loss, bandwidth limitation, and packet reordering/duplication. The X interface allows the user to select and monitor specific traffic streams passing through the router and to apply selected performance "effects" to the IP packets of the stream. In addition to the interactive interface, NIST Net™ can be driven by traces produced from measurements of actual network conditions. NIST Net also provides support for user defined packet handlers to be added to the system. Examples of the use of such packet handlers include: time stamping/data collection, interception and diversion of selected flows, generation of protocol responses from emulated clients.

The key points of Netem™ can be summarized as follows:

- Netem™ is nowadays part of most Linux™ distributions, it only has to be switched on, when compiling a kernel. With Netem, there are the same possibilities as with NIST Net™, there can be generated loss, duplication, delay and jitter (and the distribution can be chosen during runtime). Netem can be run on a Linux™-PC running as a bridge or a router (NIST Net™ only runs on routers).

- With an amendment of Netem™, Trace Control for Netem (TCN) [i.8] which was developed by ETH Zurich, it is even possible, to control the behaviour of single packets via a trace file. So it is for example possible to generate a single packet loss, or a specific delay pattern. This amendment is planned to be included in new Linux™ kernels, nowadays it is available as a patch to a specific kernel and to the iproute2 tool (iproute2 contains Netem™).
- It is not advised to define specific distortion patterns for testing in standards, because it will be easy to adapt devices to these patterns (as it is already done for test signals). But if a pattern is unknown to a manufacturer, the same pattern can be used by a test lab for different devices and gives comparable results. It is also possible to take a trace of NIST Net distortions, generate a file out of this and playback exact the same distortions with Netem.

NOTE: NIST Net™, Netem™, Linux™ and X Window System™ are examples of suitable products available commercially. This information is given for the convenience of users of the present document and does not constitute an endorsement by ETSI of these product(s).

5.5 Acoustic environment

Unless stated otherwise measurements shall be conducted under quiet and "anechoic" conditions. Depending on the distance of the transducers from mouth and ear a quiet office room may be sufficient e.g. for handsets where artificial mouth and artificial ear are located close to the acoustical transducers.

However, for some headsets or handset terminals with smaller dimension an anechoic room will be required.

In cases where real or simulated background noise is used as part of the testing environment, the original background noise shall not be noticeably influenced by the acoustical properties of the room.

In all cases where the performance of acoustic echo cancellers shall be tested a realistic room which represents the typical user environment for the terminal shall be used.

Standardized measurement methods for measurements with variable echo paths are for further study.

5.6 Influence of terminal delay on measurements

As delay is introduced by the terminal, care shall be taken for all measurements where exact position of the analysis window is required. It shall be checked that the test is performed on the test signal and not on any other signal.

6 Requirements and associated measurement methodologies

6.1 Notes

NOTE 1: In general the test methods as described in the present document apply. If alternative methods exist they may be used if they have been proven to give the same result as the method described in the present document. This will be indicated in the test report.

NOTE 2: Due to the time variant nature of IP connections delay variation may impair the measurements. In such cases the measurement has to be repeated until a valid measurement result is achieved.

6.2 Test setup

6.2.1 General

The preferred acoustical access to terminals is the most realistic simulation of the "average" subscriber. This can be made by using Head And Torso Simulator (HATS) with appropriate ear simulation and appropriate means to fix handset and headset terminals in a realistic and reproducible way to the HATS. HATS is described in Recommendation ITU-T P.58 [10], appropriate ears are described in Recommendation ITU-T P.57 [9] (type 3.3 and type 3.4 ear), a proper positioning of handsets under realistic conditions is to be found in Recommendation ITU-T P.64 [11].

The preferred way of testing a terminal is to connect it to a network simulator with exact defined settings and access points. The test sequences are fed in either electrically, using a reference codec or using the direct signal processing approach or acoustically using ITU-T specified devices.




Figure 1: Half channel terminal measurement

6.2.2 Setup for handsets and headsets

When using a handset telephone the handset is placed in the HATS position as described in Recommendation ITU-T P.64 [11]. The artificial mouth shall conform with Recommendation ITU-T P.58 [10]. The artificial ear shall conform with Recommendation ITU-T P.57 [9], type 3.3 or type 3.4 ears shall be used.

Recommendations for positioning headsets are given in Recommendation ITU-T P.380 [14]. If not stated otherwise headsets shall be placed in their recommended wearing position. Further information about setup and the use of HATS can be found in Recommendation ITU-T P.380 [14].

Unless stated otherwise if a volume control is provided the setting is chosen such that the nominal RLR is met as close as possible.

Unless stated otherwise the application force of 8 N is used for handset testing. No application force is used for headsets.