



SLOVENSKI STANDARD
SIST EN 301 502 V12.5.2:2017
01-maj-2017

**Globalni sistem mobilnih komunikacij (GSM) - Oprema bazne postaje -
Harmonizirani standard, ki zajema bistvene zahteve člena 3.2 direktive 2014/53/EU**

Global System for Mobile communications (GSM) - Base Station (BS) equipment -
Harmonised Standard covering the essential requirements of article 3.2 of Directive
2014/53/EU

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 502 V12.5.2:2017](https://standards.iteh.ai/catalog/standards/sist/4fd2ff3e-a01f-4d38-9f3d-5da56a590574/sist-en-301-502-v12-5-2-2017)

Ta slovenski standard je istoveten z: **ETSI EN 301 502 V12.5.2 (2017-03)**

ICS:

33.070.50	Globalni sistem za mobilno telekomunikacijo (GSM)	Global System for Mobile Communication (GSM)
-----------	--	---

SIST EN 301 502 V12.5.2:2017 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 502 V12.5.2:2017](https://standards.iteh.ai/catalog/standards/sist/4fd2ff3e-a01f-4d38-9f3d-3da3ba3903f4/sist-en-301-502-v12-5-2-2017)

<https://standards.iteh.ai/catalog/standards/sist/4fd2ff3e-a01f-4d38-9f3d-3da3ba3903f4/sist-en-301-502-v12-5-2-2017>

ETSI EN 301 502 V12.5.2 (2017-03)



**Global System for Mobile communications (GSM);
Base Station (BS) equipment;
Harmonised Standard covering the essential requirements
of article 3.2 of Directive 2014/53/EU**

SIST EN 301 502 V12.5.2:2017
<https://standards.iteh.ai/catalog/standards/sist/4fd2ff3e-a01f-4d38-9f3d-3da3ba3903f4/sist-en-301-502-v12-5-2-2017>

Reference

REN/MSG-0019-RED-C1

Keywords

base station, cellular, ER-GSM, GSM, R-GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 502 V12.5.2:2017

<https://standards.iteh.ai/catalog/standards/sist/4fd2f3e-a01f-4d38-9f3d-3da3ba3904e4/etsi-en-301-502-v12-5-2-2017>

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	7
Introduction	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	10
3 Definitions, symbols and abbreviations	11
3.1 Definitions	11
3.2 Symbols.....	13
3.3 Abbreviations	13
4 Technical requirements specifications	15
4.1 Environmental profile.....	15
4.2 Conformance requirements	15
4.2.0 General.....	15
4.2.1 Introduction.....	15
4.2.2 Mean transmitted RF carrier power	16
4.2.2.1 Definition	16
4.2.2.2 Limit.....	16
4.2.2.3 Conformance.....	17
4.2.3 Void	17
4.2.4 Adjacent channel power.....	17
4.2.4.0 General	17
4.2.4.1 Spectrum <small>due to modulation and wideband noise</small>	17
4.2.4.1.1 Definition.....	17
4.2.4.1.2 Limit	17
4.2.4.1.3 Conformance	19
4.2.4.2 Switching transients spectrum.....	20
4.2.4.2.1 Definition.....	20
4.2.4.2.2 Limit	20
4.2.4.2.3 Conformance	20
4.2.5 Spurious emissions from the transmitter antenna connector.....	20
4.2.5.0 General	20
4.2.5.1 Conducted spurious emissions from the transmitter antenna connector, inside the BTS transmit band.....	20
4.2.5.1.1 Definition.....	20
4.2.5.1.2 Limit	20
4.2.5.1.3 Conformance	20
4.2.5.2 Conducted spurious emissions from the transmitter antenna connector, outside the BTS transmit band.....	21
4.2.5.2.0 General	21
4.2.5.2.1 Definition.....	21
4.2.5.2.2 Limit	21
4.2.5.2.3 Conformance	22
4.2.5.3 Conducted spurious emissions from the transmitter antenna connector, in 3G bands outside the BTS transmit band	22
4.2.5.3.0 General	22
4.2.5.3.1 Definition.....	22
4.2.5.3.2 Limit	22
4.2.5.3.3 Conformance	22
4.2.6 Intermodulation attenuation	22
4.2.6.1 Definition	22
4.2.6.2 Limit.....	23

4.2.6.2.1	For BTS not belonging to a multicarrier BTS class.....	23
4.2.6.2.2	For BTS belonging to a multicarrier BTS class.....	23
4.2.6.3	Conformance.....	23
4.2.7	Intra Base Station System intermodulation attenuation	24
4.2.7.1	Definition	24
4.2.7.2	Limit.....	24
4.2.7.2.1	For BTS not belonging to a multicarrier BTS class.....	24
4.2.7.2.2	For BTS belonging to a multicarrier BTS class.....	24
4.2.7.3	Conformance.....	24
4.2.8	Wideband noise and intra BSS intermodulation attenuation in multicarrier operation.....	24
4.2.8.1	Definition	24
4.2.8.2	Limit.....	24
4.2.9	Static Reference Sensitivity Level	26
4.2.9.1	Definition	26
4.2.9.2	Limit.....	26
4.2.9.3	Conformance.....	27
4.2.10	Void	27
4.2.11	Reference Interference Level.....	27
4.2.11.1	Definition	27
4.2.11.2	Limit.....	28
4.2.11.3	Conformance.....	34
4.2.12	Blocking Characteristics	34
4.2.12.0	General	34
4.2.12.1	Definition	35
4.2.12.2	Limit.....	35
4.2.12.2.1	Blocking	35
4.2.12.2.2	Spurious response	36
4.2.12.3	Conformance.....	36
4.2.13	Intermodulation characteristics.....	36
4.2.13.1	Definition	36
4.2.13.2	Limit.....	36
4.2.13.3	Conformance.....	36
4.2.14	AM suppression.....	36
4.2.14.1	Definition	36
4.2.14.2	Limit.....	36
4.2.14.3	Conformance.....	37
4.2.15	Spurious emissions from the receiver antenna connector	37
4.2.15.0	General	37
4.2.15.1	Definition	37
4.2.15.2	Limit.....	37
4.2.15.3	Conformance.....	37
4.2.16	Radiated spurious emissions	37
4.2.16.0	General	37
4.2.16.1	Definition	37
4.2.16.2	Limit.....	37
4.2.16.3	Conformance.....	37
5	Testing for compliance with technical requirements.....	38
5.1	Environmental conditions for testing	38
5.2	Interpretation of the measurement results	38
5.3	Essential radio test suites.....	39
5.3.0	General.....	39
5.3.1	Void	39
5.3.2	Mean transmitted RF carrier power	39
5.3.2.1	Test case.....	39
5.3.2.2	Test Environment.....	40
5.3.3	Void	41
5.3.4	Adjacent channel power.....	41
5.3.4.1	Spectrum due to modulation and wideband noise	41
5.3.4.1.1	Test case	41
5.3.4.1.2	Test Environment	41
5.3.4.2	Switching transients spectrum.....	42

5.3.4.2.1	Test case	42
5.3.4.2.2	Test Environment	43
5.3.5	Spurious emissions from the transmitter antenna connector.....	43
5.3.5.1	Conducted spurious emissions from the transmitter antenna connector, inside the BTS transmit band.....	43
5.3.5.1.1	Test case	43
5.3.5.1.2	Test Environment	43
5.3.5.2	Conducted spurious emissions from the transmitter antenna connector, outside the BTS transmit band.....	44
5.3.5.2.0	General	44
5.3.5.2.1	For BTS not belonging to a multicarrier BTS class.....	44
5.3.5.2.2	For BTS belonging to a multicarrier BTS class.....	45
5.3.5.3	Conducted spurious emissions from the transmitter antenna connector, in 3G bands outside the BTS transmit band	47
5.3.5.3.0	General	47
5.3.5.3.1	Test case	47
5.3.5.3.2	Test Environment	47
5.3.6	Intermodulation attenuation	47
5.3.6.1	Test case.....	47
5.3.6.2	Test Environment.....	49
5.3.7	Intra Base Station System intermodulation attenuation	49
5.3.7.1	Test case.....	49
5.3.7.2	Test Environment.....	50
5.3.8	Wideband noise and intra BSS intermodulation attenuation in multicarrier operation.....	50
5.3.8.1	Test case.....	50
5.3.8.2	Test Environment.....	53
5.3.9	Static reference sensitivity level	53
5.3.9.1	Test case.....	53
5.3.9.2	Test Environment.....	54
5.3.10	Void.....	54
5.3.11	Reference Interference Level.....	54
5.3.11.1	Test case.....	54
5.3.11.2	Test Environment.....	63
5.3.12	Blocking Characteristics.....	63
5.3.12.0	General	63
5.3.12.1	Test case.....	63
5.3.12.2	Test Environment.....	69
5.3.13	Intermodulation characteristics.....	69
5.3.13.1	Test case.....	69
5.3.13.2	Test Environment.....	70
5.3.14	AM suppression	70
5.3.14.1	Test case.....	70
5.3.14.2	Test Environment.....	72
5.3.15	Spurious emissions from the receiver antenna connector	72
5.3.15.0	General	72
5.3.15.1	Test case.....	72
5.3.15.2	Test Environment.....	72
5.3.16	Radiated spurious emissions	73
5.3.16.0	General	73
5.3.16.1	Test case.....	74
5.3.16.2	Test Environment.....	75

Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	76
-------------------------------	---	-----------

Annex B (normative):	General test conditions and declarations.....	78
-----------------------------	--	-----------

B.1	Declaration by manufacturer	78
B.1.0	General	78
B.1.1	Output power and determination of power class	78
B.1.2	Specified frequency range	79
B.1.3	Frequency hopping	79

B.1.4	Void.....	79
B.1.5	Downlink discontinuous transmission (DTX).....	79
B.2	BTS Configurations.....	80
B.2.0	General	80
B.2.1	Receiver diversity.....	80
B.2.2	Duplexers	80
B.2.3	Power supply options	81
B.2.4	Ancillary RF amplifiers.....	81
B.2.5	BSS using antenna arrays	82
B.2.6	BTS supporting 8-PSK modulation.....	83
B.2.7	BTS supporting additional modulations in EGPRS2.....	83
B.2.8	Supported Symbol Rate.....	83
B.2.9	Support of RTTI and/or FANR	83
B.2.10	Multicarrier BTS	84
B.2.11	BTS supporting VAMOS	85
B.2.12	BTS supporting ER-GSM	85
Annex C (normative): Test environments.....		86
C.0	General	86
C.1	Normal test environment.....	86
C.2	Extreme test environment.....	86
C.2.0	General	86
C.2.1	Extreme temperature	86
C.3	Void.....	87
C.4	Power supply	87
Annex D (informative): Void.....		88
Annex E (informative): Change History.....		89
History		90

iTech STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 502 V12.5.2:2017
<https://standards.iteh.ai/catalog/standards/sist/4fd2ff5e-a01f-4d58-9f5d-3da3ba3903f4/sist-en-301-502-v12-5-2-2017>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG).

For non EU countries the present document may be used for regulatory (Type Approval) purposes.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.10] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

SIST EN 301 502 V12.5.2:2017

<https://standards.etsi.org/standards-search/461237-cc01f-4d38-9f3d-3da2ba3903f/sist-en-301-502-v12-5-2-2017>

National transition dates

Date of latest announcement of this EN (doa):	30 June 2017
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 December 2017
Date of withdrawal of any conflicting National Standard (dow):	31 December 2017

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document is part of a set of standards developed by ETSI that are designed to fit in a modular structure to cover radio equipment within the scope of the Radio Equipment Directive [i.1]. The present document is produced following the guidance in ETSI EG 203 336 [i.2] as applicable.

1 Scope

The present document applies to the following radio equipment type:

- 1) GSM base stations.

Table 1-1: GSM Base Station System frequency bands

GSM band	Direction of transmission	GSM Base Station System relevant frequency bands
P-GSM 900	Transmit	935 MHz to 960 MHz
	Receive	890 MHz to 915 MHz
E-GSM 900	Transmit	925 MHz to 960 MHz
	Receive	880 MHz to 915 MHz
R-GSM 900	Transmit	921 MHz to 960 MHz
	Receive	876 MHz to 915 MHz
ER-GSM 900	Transmit	918 MHz to 960 MHz
	Receive	873 MHz to 915 MHz
DCS 1 800	Transmit	1 805 MHz to 1 880 MHz
	Receive	1 710 MHz to 1 785 MHz
GSM 450	Transmit	460,4 MHz to 467,6 MHz
	Receive	450,4 MHz to 457,6 MHz
GSM 480	Transmit	488,8 MHz to 496 MHz
	Receive	478,8 MHz to 486 MHz

The present document contains requirements aiming to demonstrate that that radio equipment both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference.

In regards to interference to systems operating in adjacent bands guidance for single carrier BTS and multicarrier BTS is provided in ECC Report 146 [i.3].

SIST EN 301 502 V12.5.2:2017

<https://standards.etsi.org/catalog/standards/sist/461283e-a01f-4d38-99d1-3da3ba3903f4/sist-en-301-502-v12-5-2-2017>

2 References

2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 301 908-18 (V11.1.1) (07-2016): "IMT cellular networks; Harmonised Standard covering the essential requirements of article 3.2 of the Radio Equipment Directive 2014/53/EU; Part 18: E-UTRA, UTRA and GSM/EDGE Multi-Standard Radio (MSR) Base Station (BS)".
- [2] ETSI TS 151 021 (V12.3.0) (01-2015): "Digital cellular telecommunications system (Phase 2+); Base Station System (BSS) equipment specification; Radio aspects (3GPP TS 51.021 version 12.3.0 Release 12)".
- [3] ETSI TS 145 002 (V12.4.0) (04-2015): "Digital cellular telecommunications system (Phase 2+); Multiplexing and multiple access on the radio path (3GPP TS 45.002 version 12.4.0 Release 12)".
- [4] ETSI TS 145 004 (V12.0.0) (10-2014): "Digital cellular telecommunications system (Phase 2+); Modulation (3GPP TS 45.004 version 12.0.0 Release 12)".

- [5] ETSI TS 145 005 (V12.5.0) (04-2015): "Digital cellular telecommunications system (Phase 2+); Radio Transmission and reception (3GPP TS 45.005 version 12.5.0 Release 12)".
- [6] ETSI TS 145 010 (V12.0.0) (10-2014): "Digital cellular telecommunications system (Phase 2+); Radio subsystem synchronization (3GPP TS 45.010 version 12.0.0 Release 12)".
- [7] ETSI EN 300 019-1-0 (V2.1.2) (09-2003): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-0: Classification of environmental conditions; Introduction".
- [8] ETSI EN 300 019-1-3 (V2.4.1) (04-2014): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-3: Classification of environmental conditions; Stationary use at weather protected locations".
- [9] ETSI EN 300 019-1-4 (V2.2.1) (04-2014): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-4: Classification of environmental conditions; Stationary use at non-weather protected locations".
- [10] ETSI TS 124 022 (V12.0.0) (10-2014): "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); Radio Link Protocol (RLP) for circuit switched bearer and teleservices (3GPP TS 24.022 version 12.0.0 Release 12)".
- [11] ETSI TS 148 020 (V12.0.0) (10-2014): "Digital cellular telecommunications system (Phase 2+); Rate adaption on the Base Station System - Mobile-services Switching Centre (BSS-MSC) interface (3GPP TS 48.020 version 12.0.0 Release 12)".
- [12] Recommendation ITU-T O.153 (10-1992): "Basic Parameters for the measurement of error performance at bit rates below the primary rate".
- [13] Recommendation ITU-R SM.329-12 (09-2012): "Unwanted emissions in the spurious domain".
- [14] ETSI EN 300 019-2-3 (V2.3.1) (04-2013): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-3: Specification of environmental tests; Stationary use at weather protected locations".
<https://standards.iteh.ai/catalog/standards/sist/4fd2f3e-a01f-4d38-9f3d-3a7609231d3c/en-300-019-2-3-v12-3-1>
- [15] ETSI EN 300 019-2-4 (V2.3.1) (08-2013): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-4: Specification of environmental tests; Stationary use at non-weather protected locations".
- [16] IEC EN 60721-1 (ed.2.2, 10-2002): "Classification of environmental conditions: Part 1: Environmental parameters and their severities".
- [17] IEC EN 60721-2-1 (ed.2.0, 06-2013): "Classification of environmental conditions - Part 2-1: Environmental conditions appearing in nature - Temperature and humidity".
- [18] IEC EN 60721-2-4 (ed.1.1, 10-2002): "Classification of environmental conditions - Part 2-4: Environmental conditions appearing in nature - Solar radiation and temperature".
- [19] IEC EN 60721-3-0 (ed.1.1, 10-2002): "Classification of environmental conditions - Part 3: Classification of groups of environmental parameters and their severities - Introduction".
- [20] ETSI EN 301 908-1 (V11.1.1) (07-2016): "IMT cellular networks; Harmonised Standard covering the essential requirements of article 3.2 of the Radio Equipment Directive 2014/53/EU; Part 1: Introduction and common requirements".
- [21] ETSI TS 145 008 (V12.4.0) (01-2015): "Digital cellular telecommunications system (Phase 2+); Radio subsystem link control (3GPP TS 45.008 version 12.4.0 Release 12)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European parliament and of the council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] ETSI EG 203 336: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.3] ECC Report 146, 6th July 2010: "Compatibility between GSM MCBTS and other services (TRR, RSBN/PRMG, HC-SDMA, GSM-R, DME, MIDS, DECT) operating in the 900 and 1800 MHz frequency bands".
- [i.4] ETSI TS 144 060 (V12.5.0) (07-2015): "Digital cellular telecommunications system (Phase 2+); General Packet Radio Service (GPRS); Mobile Station (MS) - Base Station System (BSS) interface; Radio Link Control / Medium Access Control (RLC/MAC) protocol (3GPP TS 44.060 version 12.5.0 Release 12)".
- [i.5] CEPT/ERC/Recommendation 74-01E (01-2011): "Unwanted emissions in the spurious domain".
- [i.6] ETSI TR 100 028 (all parts) (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
<https://standards.iteh.ai/catalog/standards/sist/4fd2f3e-a01f-4d38-9f3d-3da3ba3903ff/sist-en-301-502-v12-5-2-2017>
- [i.7] ETSI TS 145 001 (V12.1.0) (01-2015): "Digital cellular telecommunications system (Phase 2+); Physical layer on the radio path; General description (3GPP TS 45.001 version 12.1.0 Release 12)".
- [i.8] ETSI TR 145 050 (V12.2.0) (04-2015): "Digital cellular telecommunications system (Phase 2+); Background for Radio Frequency (RF) requirements (3GPP TR 45.050 version 12.2.0 Release 12)".
- [i.9] ETSI TR 121 905 (V12.0.0) (10-2014): "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Vocabulary for 3GPP Specifications (3GPP TR 21.905 version 12.0.0 Release 12)".
- [i.10] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.11] ETSI TR 100 028-2: "ElectroMagnetic Compatibility and Radio Spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics Part 2".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ETSI TR 121 905 [i.9] and the following apply:

8-PSK: Modulation type as defined in ETSI TS 145 004 [4], clause 3.

16-QAM: Modulation type as defined in ETSI TS 145 004 [4], clause 4 for EGPRS2-A and clause 5 for EGRPS2-B.

32-QAM: Modulation type as defined in ETSI TS 145 004 [4], clause 4 for EGPRS2-A and clause 5 for EGRPS2-B.

ancillary RF amplifier: piece of equipment, which when connected by RF coaxial cables to the BTS, has the primary function to provide amplification between the transmit and/or receive antenna connector of a BTS and an antenna without requiring any control signal to fulfil its amplifying function

AQPSK: Modulation type as defined in ETSI TS 145 004 [4], clause 6.

base station RF bandwidth: instantaneous bandwidth in which a BTS belonging to a multicarrier BTS class transmits or transmits and receives multiple carriers simultaneously

Base Station System Test Equipment (BSSTE): See annex B in ETSI TS 151 021 [2].

BSS: BTS or integrated BSS

NOTE: If a separate BSC is required to perform tests on a BTS, the BSC may be regarded as test equipment and the environmental conditions of the BSC need not be controlled.

carrier frequency: centre of the ARFCN under test

circuit switched logical channels: all the standard GSM logical channels, including traffic channels (TCH), common control channels (RACH) and dedicated control channels (SDCCH, SACCH)

E-GSM: extended GSM 900 band (includes P-GSM band)

ECSD: any subset of the E-TCH traffic channels and related control channels

EGPRS: any subset of the packet traffic channels PDTCH/MCS-1 to MCS-9 and related control channels

EGPRS2: any of EGPRS2-A and EGPRS2-B

EGPRS2-A: packet traffic channels utilizing any subset of the packet traffic channels MCS-1 to 6 and PDTCH/UAS-7 to UAS-11 in uplink, together with MCS-1 to 4 and PDTCH/DAS-5 to DAS-12 in downlink, and related control channels

NOTE: In addition, MCS-7 and MCS-8 may be used in downlink when either the USF or the PAN or both are addressed to one or more EGPRS mobile stations.

EGPRS2-B: packet traffic channels utilizing any subset of the packet traffic channels MCS-1 to 4 and PDTCH/UBS-5 to UBS-12 in uplink, together with MCS-1 to 4 and PDTCH/DBS-5 to DBS-12 in downlink, and related control channels

NOTE: In addition, MCS-6 to MCS-9, DAS-5, DAS-6, DAS-8, DAS-9, DAS-10 pad, DAS-11, and DAS-12pad may be used in downlink under the conditions specified in ETSI TS 144 060 [i.4].

enclosure port: physical boundary of the apparatus through which electromagnetic fields may radiate or impinge

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

ER-GSM 900: extended Railway GSM 900 band (includes R-GSM band)

GMSK: Modulation type as defined by ETSI TS 145 004 [4], clause 2.

GPRS: any subset of the packet traffic channels PDTCH/CS-1 to CS-4 and related control channels

GSM: unless otherwise specified, references to GSM include GSM 400, GSM 900, ER-GSM 900 and DCS 1 800

GSM 400: unless otherwise specified, references to GSM 400 include GSM 450 and GSM 480 band

GSM 900: unless otherwise specified, references to GSM 900 include P-GSM, E-GSM and R-GSM band

GSM-R: GSM Railway communication, operated in the R-GSM or ER-GSM band, respectively

Local Area (LA) multicarrier BTS: class of multicarrier BTS with both multicarrier transmitter and multicarrier receiver, characterized by requirements derived from pico cell scenarios

manufacturer: in the present document, a reference to a manufacturer also applies to an agent of the manufacturer

maximum base station RF bandwidth: maximum bandwidth in which a BTS belonging to a multicarrier BTS class transmits or transmits and receives multiple carriers simultaneously

maximum transmit filter bandwidth: maximum bandwidth of the duplexer or the transmit filter used in a BTS belonging to a multicarrier BTS class transmitting carriers simultaneously

Medium Range (MR) multicarrier BTS: class of multicarrier BTS with both multicarrier transmitter and multicarrier receiver, characterized by requirements derived from micro cell scenarios

micro-BTS: low-power BTS with performance requirements defined in ETSI TS 145 005 [5]

NOTE: In the present document, this also includes a BSS which incorporates a micro-BTS.

minimum carrier frequency spacing: minimum spacing between the centre frequencies of simultaneously transmitted or received GSM carriers of a BTS belonging to a multicarrier BTS class

NOTE: The minimum carrier frequency spacing is 600 kHz.

multicarrier BTS: BTS, characterized by the ability to, in addition to single carrier operation, process two or more carriers in common active components simultaneously

multicarrier BTS equipped with multicarrier receiver: subgroup of multicarrier BTS, characterized by the ability to, in addition to single carrier operation, process two or more carriers in common active components simultaneously, in both multicarrier transmitter and multicarrier receiver

normal BTS: any BTS or BSS as defined by ETSI TS 145 005 [5] which is not a micro-BTS, pico-BTS or multicarrier BTS

operating band: transmit and receive operating bands together comprise the frequency band supported by the BSS

NOTE: As defined in clause B.1.2.

P-GSM: primary GSM 900 band

packet switched logical channels: all the General Packet Radio Services (GPRS) packet data logical channels, including packet traffic channels (PDTCH and PACCH) and packet common control channels (PRACH)

pico-BTS: low-power BTs with performance requirements defined in ETSI TS 145 005 [5]

NOTE: In the present document, this also includes a BSS which incorporates a pico-BTS.

port: particular interface, of the specified equipment (apparatus), with the electromagnetic environment

QPSK: Modulation type as defined ETSI TS 145 004 clause 5 [4], used in EGPRS2-B.

R-GSM: railways GSM 900 band (includes P-GSM band and E-GSM band)

radio digital unit: equipment which contains base band and functionality for controlling radio unit

radio equipment: equipment which contains radio digital unit and radio unit

radio unit: equipment which contains transmitter and receiver

relevant RX band (or relevant receive band): receive band for the frequency band of BTS declared by the manufacturer

NOTE: As defined in clause 1.

relevant TX band (or relevant transmit band): transmit band for the frequency band of BTS declared by the manufacturer

NOTE: As defined in clause 1.

SCPIR_UL: As defined in ETSI TS 145 005 [5], clause 1.3.

sub-block: contiguous allocated block of spectrum for use by the same Base Station

NOTE: There may be multiple instances of sub-blocks within an RF bandwidth.

sub-block bandwidth: bandwidth of one sub-block

sub-block gap: frequency gap between two consecutive sub-blocks within an RF bandwidth, where the RF requirements in the gap are based on co-existence for un-coordinated operation

VAMOS mode: As defined in ETSI TS 145 001 [i.7], clause 13.1.

VAMOS sub-channel: As defined in ETSI TS 145 001 [i.7], clause 13.1.

Wide Area (WA) multicarrier BTS: class of multicarrier BTS with either multicarrier transmitter only, or both multicarrier transmitter and receiver, characterized by requirements derived from macro cell scenarios

3.2 Symbols STANDARD PREVIEW

For the purposes of the present document, the following symbols apply:

Δf	frequency offset from the edge of the relevant TX band when measuring spurious emissions
f_o	frequency of wanted signal
$RF_{BW Max}$	maximum Base Station RF bandwidth

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI TR 121 905 [i.9] and the following apply:

AM	Amplitude Modulation
AMR	Adaptive Multi-Rate
AFS	AMR Full-rate Speech
AHS	AMR Half-rate Speech
AQPSK	Adaptive Quadrature Phase Shift Keying
ARFCN	Absolute Radio Frequency Channel Number
B	Bottom
BCCH	BroadCast Control CHannel
BER	Bit Error Ratio
BLER	Block Error Ratio
BS	Base Station
BSC	Base Station Controller
BSS	Base Station System
BSSTE	Base Station System Test Equipment
BTS	Base Transceiver Station
BTTI	Basic Transmission Time Interval
BW	BandWidth
DAS	EGPRS2 Downlink Level A modulation and coding Scheme
DBS	EGPRS2 Downlink Level B modulation and coding Scheme
DC	Direct Current
DCS	Digital Cellular System
DTX	Discontinuous Transmission